

# Introduction to the R Language

## Data Types and Basic Operations

Biostatistics 140.776

R has five basic or “atomic” classes of objects:

- character
- numeric (real numbers)
- integer
- complex
- logical (True/False)

The most basic object is a vector

- A vector can only contain objects of the same class
- BUT: The one exception is a *list*, which is represented as a vector but can contain objects of different classes (indeed, that’s usually why we use them)

Empty vectors can be created with the `vector()` function.

- Numbers in R are generally treated as numeric objects (i.e. double precision real numbers)
- If you explicitly want an integer, you need to specify the L suffix
- Ex: Entering 1 gives you a numeric object; entering 1L explicitly gives you an integer.
- There is also a special number `Inf` which represents infinity; e.g.  $1 / 0$ ; `Inf` can be used in ordinary calculations; e.g.  $1 / \text{Inf}$  is 0
- The value `NaN` represents an undefined value (“not a number”); e.g.  $0 / 0$ ; `NaN` can also be thought of as a missing value (more on that later)

R objects can have attributes

- names, dimnames
- dimensions (e.g. matrices, arrays)
- class
- length
- other user-defined attributes/metadata

Attributes of an object can be accessed using the `attributes()` function.

# Entering Input

At the R prompt we type *expressions*. The `<-` symbol is the assignment operator.

```
> x <- 1
> print(x)
[1] 1
> x
[1] 1
> msg <- "hello"
```

The grammar of the language determines whether an expression is complete or not.

```
> x <- ## Incomplete expression
```

The `#` character indicates a *comment*. Anything to the right of the `#` (including the `#` itself) is ignored.

When a complete expression is entered at the prompt, it is *evaluated* and the result of the evaluated expression is returned. The result may be *auto-printed*.

```
> x <- 5  ## nothing printed
> x        ## auto-printing occurs
[1] 5
> print(x) ## explicit printing
[1] 5
```

The [1] indicates that x is a vector and 5 is the first element.

```
> x <- 1:20  
> x  
[1]  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15  
[16] 16 17 18 19 20
```

The `:` operator is used to create integer sequences.

# Creating Vectors

The `c()` function can be used to create vectors of objects.

```
> x <- c(0.5, 0.6)      ## numeric
> x <- c(TRUE, FALSE)   ## logical
> x <- c(T, F)           ## logical
> x <- c("a", "b", "c") ## character
> x <- 9:29              ## integer
> x <- c(1+0i, 2+4i)     ## complex
```

Using the `vector()` function

```
> x <- vector("numeric", length = 10)
> x
[1] 0 0 0 0 0 0 0 0 0 0
```



What about the following?

```
> y <- c(1.7, "a")    ## character  
> y <- c(TRUE, 2)     ## numeric  
> y <- c("a", TRUE)   ## character
```

When different objects are mixed in a vector, *coercion* occurs so that every element in the vector is of the same class.

# Explicit Coercion

Objects can be explicitly coerced from one class to another using the `as.*` functions, if available.

```
> x <- 0:6
> class(x)
[1] "integer"
> as.numeric(x)
[1] 0 1 2 3 4 5 6
> as.logical(x)
[1] FALSE TRUE TRUE TRUE TRUE TRUE TRUE
> as.character(x)
[1] "0" "1" "2" "3" "4" "5" "6"
> as.complex(x)
[1] 0+0i 1+0i 2+0i 3+0i 4+0i 5+0i 6+0i
```

Nonsensical coercion results in NAs.

```
> x <- c("a", "b", "c")
```

```
> as.numeric(x)
```

```
[1] NA NA NA
```

Warning message:

NAs introduced by coercion

```
> as.logical(x)
```

```
[1] NA NA NA
```

Matrices are vectors with a *dimension* attribute. The dimension attribute is itself an integer vector of length 2 (nrow, ncol)

```
> m <- matrix(nrow = 2, ncol = 3)
```

```
> m
```

```
      [,1] [,2] [,3]  
[1,]   NA   NA   NA  
[2,]   NA   NA   NA
```

```
> dim(m)
```

```
[1] 2 3
```

```
> attributes(m)
```

```
$dim
```

```
[1] 2 3
```

## Matrices (cont'd)

Matrices are constructed *column-wise*, so entries can be thought of starting in the “upper left” corner and running down the columns.

```
> m <- matrix(1:6, nrow = 2, ncol = 3)
```

```
> m
```

	[,1]	[,2]	[,3]
[1,]	1	3	5
[2,]	2	4	6

## Matrices (cont'd)

Matrices can also be created directly from vectors by adding a dimension attribute.

```
> m <- 1:10
> m
 [1]  1  2  3  4  5  6  7  8  9 10
> dim(m) <- c(2, 5)
> m
      [,1] [,2] [,3] [,4] [,5]
[1,]    1    3    5    7    9
[2,]    2    4    6    8   10
```

## cbind-ing and rbind-ing

Matrices can be created by *column-binding* or *row-binding* with `cbind()` and `rbind()`.

```
> x <- 1:3
> y <- 10:12
> cbind(x, y)
      x  y
[1,] 1 10
[2,] 2 11
[3,] 3 12
> rbind(x, y)
      [,1] [,2] [,3]
x         1     2     3
y        10    11    12
```

Lists are a special type of vector that can contain elements of different classes. Lists are a very important data type in R and you should get to know them well.

```
> x <- list(1, "a", TRUE, 1 + 4i)
```

```
> x
```

```
[[1]]
```

```
[1] 1
```

```
[[2]]
```

```
[1] "a"
```

```
[[3]]
```

```
[1] TRUE
```

```
[[4]]
```

```
[1] 1+4i
```



Factors are used to represent categorical data. Factors can be unordered or ordered. One can think of a factor as an integer vector where each integer has a *label*.

- Factors are treated specially by modelling functions like `lm()` and `glm()`
- Using factors with labels is *better* than using integers because factors are self-describing; having a variable that has values “Male” and “Female” is better than a variable that has values 1 and 2.

```
> x <- factor(c("yes", "yes", "no", "yes", "no"))
> x
[1] yes yes no  yes no
Levels: no yes
> table(x)
x
no yes
 2  3
> unclass(x)
[1] 2 2 1 2 1
attr("levels")
[1] "no" "yes"
```

The order of the levels can be set using the `levels` argument to `factor()`. This can be important in linear modelling because the first level is used as the baseline level.

```
> x <- factor(c("yes", "yes", "no", "yes", "no"),  
              levels = c("yes", "no"))  
  
> x  
[1] yes yes no  yes no  
Levels: yes no
```

Missing values are denoted by NA or NaN for undefined mathematical operations.

- `is.na()` is used to test objects if they are NA
- `is.nan()` is used to test for NaN
- NA values have a class also, so there are integer NA, character NA, etc.
- A NaN value is also NA but the converse is not true

# Missing Values

```
> x <- c(1, 2, NA, 10, 3)
> is.na(x)
[1] FALSE FALSE  TRUE FALSE FALSE
> is.nan(x)
[1] FALSE FALSE FALSE FALSE FALSE
> x <- c(1, 2, NaN, NA, 4)
> is.na(x)
[1] FALSE FALSE  TRUE  TRUE FALSE
> is.nan(x)
[1] FALSE FALSE  TRUE FALSE FALSE
```

Data frames are used to store tabular data

- They are represented as a special type of list where every element of the list has to have the same length
- Each element of the list can be thought of as a column and the length of each element of the list is the number of rows
- Unlike matrices, data frames can store different classes of objects in each column (just like lists); matrices must have every element be the same class
- Data frames also have a special attribute called `row.names`
- Data frames are usually created by calling `read.table()` or `read.csv()`
- Can be converted to a matrix by calling `data.matrix()`

```
> x <- data.frame(foo = 1:4, bar = c(T, T, F, F))
> x
  foo  bar
1   1 TRUE
2   2 TRUE
3   3 FALSE
4   4 FALSE
> nrow(x)
[1] 4
> ncol(x)
[1] 2
```

R objects can also have names, which is very useful for writing readable code and self-describing objects.

```
> x <- 1:3
> names(x)
NULL
> names(x) <- c("foo", "bar", "norf")
> x
  foo  bar norf
   1    2    3
> names(x)
[1] "foo"  "bar"  "norf"
```



Lists can also have names.

```
> x <- list(a = 1, b = 2, c = 3)
```

```
> x
```

```
$a
```

```
[1] 1
```

```
$b
```

```
[1] 2
```

```
$c
```

```
[1] 3
```

And matrices.

```
> m <- matrix(1:4, nrow = 2, ncol = 2)
> dimnames(m) <- list(c("a", "b"), c("c", "d"))
> m
  c d
a 1 3
b 2 4
```

## Data Types

- atomic classes: numeric, logical, character, integer, complex
- vectors, lists
- factors
- missing values
- data frames
- names

There are a number of operators that can be used to extract subsets of R objects.

- `[]` always returns an object of the same class as the original; can be used to select more than one element (there is one exception)
- `[[` is used to extract elements of a list or a data frame; it can only be used to extract a single element and the class of the returned object will not necessarily be a list or data frame
- `$` is used to extract elements of a list or data frame by name; semantics are similar to hat of `[]`.

```
> x <- c("a", "b", "c", "c", "d", "a")
> x[1]
[1] "a"
> x[2]
[1] "b"
> x[1:4]
[1] "a" "b" "c" "c"
> x[x > "a"]
[1] "b" "c" "c" "d"
> u <- x > "a"
> u
[1] FALSE TRUE TRUE TRUE TRUE FALSE
> x[u]
[1] "b" "c" "c" "d"
```

# Subsetting a Matrix

Matrices can be subsetting in the usual way with  $(i,j)$  type indices.

```
> x <- matrix(1:6, 2, 3)
> x[1, 2]
[1] 3
> x[2, 1]
[1] 2
```

Indices can also be missing.

```
> x[1, ]
[1] 1 3 5
> x[, 2]
[1] 3 4
```

# Subsetting a Matrix

By default, when a single element of a matrix is retrieved, it is returned as a vector of length 1 rather than a  $1 \times 1$  matrix. This behavior can be turned off by setting `drop = FALSE`.

```
> x <- matrix(1:6, 2, 3)
```

```
> x[1, 2]
```

```
[1] 3
```

```
> x[1, 2, drop = FALSE]
```

```
      [,1]
```

```
[1,]      3
```

# Subsetting a Matrix

Similarly, subsetting a single column or a single row will give you a vector, not a matrix (by default).

```
> x <- matrix(1:6, 2, 3)
> x[1, ]
[1] 1 3 5
> x[1, , drop = FALSE]
      [,1] [,2] [,3]
[1,]    1    3    5
```



# Subsetting Lists

```
> x <- list(foo = 1:4, bar = 0.6)
```

```
> x[1]
```

```
$foo
```

```
[1] 1 2 3 4
```

```
> x[[1]]
```

```
[1] 1 2 3 4
```

```
> x$bar
```

```
[1] 0.6
```

```
> x[["bar"]]
```

```
[1] 0.6
```

```
> x["bar"]
```

```
$bar
```

```
[1] 0.6
```

# Subsetting Lists

Extracting multiple elements of a list.

```
> x <- list(foo = 1:4, bar = 0.6, baz = "hello")
```

```
> x[c(1, 3)]
```

```
$foo
```

```
[1] 1 2 3 4
```

```
$baz
```

```
[1] "hello"
```

# Subsetting Lists

The `[[` operator can be used with *computed* indices; `$` can only be used with literal names.

```
> x <- list(foo = 1:4, bar = 0.6, baz = "hello")
> name <- "foo"
> x[[name]] ## computed index for 'foo'
[1] 1 2 3 4
> x$name     ## element 'name' doesn't exist!
NULL
> x$foo
[1] 1 2 3 4 ## element 'foo' does exist
```

# Subsetting Nested Elements of a List

The `[[` can take an integer sequence.

```
> x <- list(a = list(10, 12, 14), b = c(3.14, 2.81))
```

```
> x[[c(1, 3)]]
```

```
[1] 14
```

```
> x[[1]][[3]]
```

```
[1] 14
```

```
> x[[c(2, 1)]]
```

```
[1] 3.14
```

# Partial Matching

Partial matching of names is allowed with `[[` and `$`.

```
> x <- list(aardvark = 1:5)
> x$a
[1] 1 2 3 4 5
> x[["a"]]
NULL
> x[["a", exact = FALSE]]
[1] 1 2 3 4 5
```

# Removing NA Values

A common task is to remove missing values (NAs).

```
> x <- c(1, 2, NA, 4, NA, 5)
> bad <- is.na(x)
> x[!bad]
[1] 1 2 4 5
```

# Removing NA Values

What if there are multiple things and you want to take the subset with no missing values?

```
> x <- c(1, 2, NA, 4, NA, 5)
> y <- c("a", "b", NA, "d", NA, "f")
> good <- complete.cases(x, y)
> good
[1] TRUE TRUE FALSE TRUE FALSE TRUE
> x[good]
[1] 1 2 4 5
> y[good]
[1] "a" "b" "d" "f"
```

# Removing NA Values

```
> airquality[1:6, ]
  Ozone Solar.R Wind Temp Month Day
1    41     190  7.4   67     5   1
2    36     118  8.0   72     5   2
3    12     149 12.6   74     5   3
4    18     313 11.5   62     5   4
5    NA      NA 14.3   56     5   5
6    28      NA 14.9   66     5   6
> good <- complete.cases(airquality)
> airquality[good, ][1:6, ]
  Ozone Solar.R Wind Temp Month Day
1    41     190  7.4   67     5   1
2    36     118  8.0   72     5   2
3    12     149 12.6   74     5   3
4    18     313 11.5   62     5   4
7    23     299  8.6   65     5   7
```



# Vectorized Operations

Many operations in R are *vectorized* making code more efficient, concise, and easier to read.

```
> x <- 1:4; y <- 6:9
> x + y
[1]  7  9 11 13
> x > 2
[1] FALSE FALSE  TRUE  TRUE
> x >= 2
[1] FALSE  TRUE  TRUE  TRUE
> y == 8
[1] FALSE FALSE  TRUE FALSE
> x * y
[1]  6 14 24 36
> x / y
[1] 0.1666667 0.2857143 0.3750000 0.4444444
```

# Vectorized Matrix Operations

```
> x <- matrix(1:4, 2, 2); y <- matrix(rep(10, 4), 2, 2)
> x * y          ## element-wise multiplication
      [,1] [,2]
[1,]    10    30
[2,]    20    40
> x / y
      [,1] [,2]
[1,]  0.1  0.3
[2,]  0.2  0.4
> x %*% y        ## true matrix multiplication
      [,1] [,2]
[1,]    40    40
[2,]    60    60
```