



PC0

Physical Config Desktop Custom Interface

Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 10.0.0.3

Pinging 10.0.0.3 with 32 bytes of data:
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms

PC>ping 10.0.0.4

Pinging 10.0.0.4 with 32 bytes of data:
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms
```

Cluster

Move Object

Laptop0

Physical Config Desktop Custom Interface

Command Prompt

```
Packet Tracer PC Command Line 1.0
Laptop>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms

Laptop>ping 10.0.0.3

Pinging 10.0.0.3 with 32 bytes of data:
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128
Reply from 10.0.0.3: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms
```

PC1

Physical Config Desktop Custom Interface

Command Prompt

```
Packet Tracer PC Command Line 1.0
PC1>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128
Reply from 10.0.0.1: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms

PC1>ping 10.0.0.4

Pinging 10.0.0.4 with 32 bytes of data:
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128
Reply from 10.0.0.4: bytes=32 time=16ms TTL=128

Ping statistics for 10.0.0.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 16ms, Average = 16ms
```

Time: 00:29:54 Power Cycle Devices Fast Forward Time

Connections

Scenario 0

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete

Toggle PDU List Window

29°C Mostly cloudy

ENG IN 1010 18-06-2023

Cisco Packet Tracer Student

File Edit Options View Tools Extensions Help

PC1

Physical Config Desktop Custom Interface

Wireless0

Port Status: 54 Mbps

Bandwidth: 54 Mbps

MAC Address: 0002.4A0A.827E

SSID: WLAN

Authentication:

- ☐ Disabled
- ☒ WEP WEP Key: 1234567890
- ☐ WPA-PSK
- ☐ WPA2-PSK PSK Pass Phrase
- ☐ WPA
- ☐ WPA2 User ID: Password

Encryption Type: 40/64-Bits (10 Hex digits)

IP Configuration:

- ☐ DHCP
- ☒ Static IP Address: 10.0.0.3 Subnet Mask: 255.0.0.0

IPv6 Configuration:

- ☐ DHCP
- ☐ Auto Config
- ☒ Static

Cluster

Move Object

Laptop0

Physical Config Desktop Custom Interface

Wireless0

Port Status: 48 Mbps

Bandwidth: 48 Mbps

MAC Address: 0000.BAAB.0ADC

SSID: WLAN

Authentication:

- ☐ Disabled
- ☒ WEP WEP Key: 1234567890
- ☐ WPA-PSK
- ☐ WPA2-PSK PSK Pass Phrase
- ☐ WPA
- ☐ WPA2 User ID: Password

Encryption Type: 40/64-Bits (10 Hex digits)

IP Configuration:

- ☐ DHCP
- ☒ Static IP Address: 10.0.0.4 Subnet Mask: 255.0.0.0

IPv6 Configuration:

- ☐ DHCP
- ☐ Auto Config
- ☒ Static

Printer0

Physical Config

Wireless0

Port Status: 24 Mbps

Bandwidth: 24 Mbps

MAC Address: 00E0.A3C5.C12C

SSID: WLAN

Authentication:

- ☐ Disabled
- ☒ WEP WEP Key: 1234567890
- ☐ WPA-PSK
- ☐ WPA2-PSK PSK Pass Phrase
- ☐ WPA
- ☐ WPA2 User ID: Password

Encryption Type: 40/64-Bits (10 Hex digits)

IP Configuration:

- ☐ DHCP
- ☒ Static IP Address: 10.0.0.5 Subnet Mask: 255.0.0.0

IPv6 Configuration:

- ☐ DHCP
- ☐ Auto Config
- ☒ Static

Time: 00:31:21 Power Cycle Devices Fast Forward Time

Connections

Scenario 0

New Delete

Toggle PDU List Window

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete

29°C Mostly cloudy

ENG IN 10:11 18-06-2023