

CPS 510 - Assignment 4

Shayaan Kirubakaran (Section 5)

Kirusanth Palakanthan (Section 10)

Ahmed Hasan (Section 5)

menu.sh

```
GNU nano 6.2
#!/bin/sh
MainMenu() {
  while [ "$CHOICE" != "E" ]
  do
    clear
    echo "=====
    echo "|           Ride & Pickup DBMS – Oracle Tool           |"
    echo "-----"
    echo " 1) Drop Tables"
    echo " 2) Create Tables"
    echo " 3) Populate Tables"
    echo " 4) Run Advanced Queries"
    echo " E) Exit"
    echo "-----"
    echo -n "Choose: "
    read CHOICE

    case $CHOICE in
      1) bash drop_table.sh; read -p "Press Enter to continue..." ;;
      2) bash create_tables.sh; read -p "Press Enter to continue..." ;;
      3) bash populate_tables.sh; read -p "Press Enter to continue..." ;;
      4) bash queries.sh; read -p "Press Enter to continue..." ;;
      E) exit ;;
      *) echo "Invalid option."; sleep 1 ;;
    esac
  done
}

ProgramStart() {
  echo "Starting Ride & Pickup DBMS Menu..."
  sleep 1
  MainMenu
}

ProgramStart
```

create_tables.sh

```
GNU nano 6.2
#!/bin/sh
echo -n "Enter Oracle password: "
read -s PASSWORD
echo
sqlplus64 "skirubak/$PASSWORD@(DESCRIPTION=
(ADDRESS=(PROTOCOL=TCP)(Host=oracle.scs.ryerson.ca)(Port=1521))
(CONNECT_DATA=(SID=orcl)))" <<EOF

-- Create all project tables
CREATE TABLE Customer (
  customerID    NUMBER PRIMARY KEY,
  name          VARCHAR2(50),
  age           NUMBER,
  address       VARCHAR2(100),
  balance       NUMBER(10,2)
);

CREATE TABLE Driver (
  driverID      NUMBER PRIMARY KEY,
  name          VARCHAR2(50),
  licenseNo     VARCHAR2(30),
  rating        NUMBER(2,1)
);

CREATE TABLE Vehicle (
  vehicleID     NUMBER PRIMARY KEY,
  driverID      NUMBER REFERENCES Driver(driverID),
  make          VARCHAR2(30),
  model         VARCHAR2(30),
  licensePlate  VARCHAR2(15)
);

CREATE TABLE Merchant (
  merchantID    NUMBER PRIMARY KEY,
  name          VARCHAR2(50),
  location      VARCHAR2(100)
);

CREATE TABLE Location (
  locationID    NUMBER PRIMARY KEY,
  address       VARCHAR2(100),
  latitude      NUMBER(8,5),
  longitude     NUMBER(8,5)
);

CREATE TABLE ServiceOrder (
  orderID       NUMBER PRIMARY KEY,
  customerID    NUMBER REFERENCES Customer(customerID),
  driverID      NUMBER REFERENCES Driver(driverID),
  merchantID    NUMBER REFERENCES Merchant(merchantID),
  pickupID     NUMBER REFERENCES Location(locationID),
  dropoffID     NUMBER REFERENCES Location(locationID),
  fare          NUMBER(10,2),
  orderType     VARCHAR2(20),
  status        VARCHAR2(20)
);
```

```
CREATE TABLE Payment (  
  paymentID    NUMBER PRIMARY KEY,  
  orderID      NUMBER REFERENCES ServiceOrder(orderID),  
  amount       NUMBER(10,2),  
  method       VARCHAR2(20),  
  status       VARCHAR2(20)  
);  
  
CREATE TABLE Rating (  
  ratingID     NUMBER PRIMARY KEY,  
  orderID      NUMBER REFERENCES ServiceOrder(orderID),  
  customerRating NUMBER(2,1),  
  driverRating  NUMBER(2,1),  
  comments     VARCHAR2(200)  
);  
  
EXIT;  
EOF
```

drop_table.sh

```
GNU nano 6.2
#!/bin/sh
echo -n "Enter Oracle password: "
read -s PASSWORD
echo
sqlplus64 "skirubak/$PASSWORD@(DESCRIPTION=
(ADDRESS=(PROTOCOL=TCP)(Host=oracle.scs.ryerson.ca)(Port=1521))
(CONNECT_DATA=(SID=orcl)))" <<EOF

-- Drop all tables in reverse dependency order
DROP TABLE Rating CASCADE CONSTRAINTS;
DROP TABLE Payment CASCADE CONSTRAINTS;
DROP TABLE ServiceOrder CASCADE CONSTRAINTS;
DROP TABLE Vehicle CASCADE CONSTRAINTS;
DROP TABLE Driver CASCADE CONSTRAINTS;
DROP TABLE Customer CASCADE CONSTRAINTS;
DROP TABLE Merchant CASCADE CONSTRAINTS;
DROP TABLE Location CASCADE CONSTRAINTS;

EXIT;
EOF
```

populate_tables.sh

```
GNU nano 6.2
#!/bin/sh
echo -n "Enter Oracle password: "
read -s PASSWORD
echo
sqlplus64 "skirubak/$PASSWORD@(DESCRIPTION=
(ADDRESS=(PROTOCOL=TCP)(Host=oracle.scs.ryerson.ca)(Port=1521))
(CONNECT_DATA=(SID=orcl)))" <<EOF

-- Clear any existing data before inserting new records
DELETE FROM Rating;
DELETE FROM Payment;
DELETE FROM ServiceOrder;
DELETE FROM Vehicle;
DELETE FROM Driver;
DELETE FROM Customer;
DELETE FROM Merchant;
DELETE FROM Location;

-- Customers
INSERT INTO Customer VALUES (1, 'Alice', 25, 'Toronto', 100.00);
INSERT INTO Customer VALUES (2, 'Bob', 31, 'Mississauga', 50.00);
INSERT INTO Customer VALUES (3, 'Cathy', 40, 'Scarborough', 200.00);
INSERT INTO Customer VALUES (4, 'David', 28, 'North York', 75.00);
INSERT INTO Customer VALUES (5, 'Evelyn', 33, 'Brampton', 60.00);

-- Drivers
INSERT INTO Driver VALUES (1, 'John Doe', 'ON12345', 4.8);
INSERT INTO Driver VALUES (2, 'Mary P', 'ON67890', 4.9);
INSERT INTO Driver VALUES (3, 'Kevin L', 'ON24680', 4.2);
INSERT INTO Driver VALUES (4, 'Rita Z', 'ON13579', 4.6);

-- Vehicles
INSERT INTO Vehicle VALUES (1, 1, 'Toyota', 'Camry', 'AB1234');
INSERT INTO Vehicle VALUES (2, 2, 'Honda', 'Civic', 'XY5678');
INSERT INTO Vehicle VALUES (3, 3, 'Nissan', 'Altima', 'RT4321');
INSERT INTO Vehicle VALUES (4, 4, 'Ford', 'Escape', 'QP9988');

-- Merchants
INSERT INTO Merchant VALUES (1, 'Pizza Palace', 'Toronto');
INSERT INTO Merchant VALUES (2, 'Burger Barn', 'Mississauga');
INSERT INTO Merchant VALUES (3, 'Taco Town', 'Scarborough');

-- Locations
INSERT INTO Location VALUES (1, '123 King St', 43.6532, -79.3832);
INSERT INTO Location VALUES (2, '456 Queen St', 43.6530, -79.3800);
INSERT INTO Location VALUES (3, '789 Bloor St', 43.6600, -79.4000);
INSERT INTO Location VALUES (4, '321 Dundas St', 43.6500, -79.3800);
INSERT INTO Location VALUES (5, '555 Bay St', 43.6550, -79.3805);
```

```

-- Service Orders
INSERT INTO ServiceOrder VALUES (1, 1, 1, 1, 1, 2, 18.50, 'Delivery', 'Completed');
INSERT INTO ServiceOrder VALUES (2, 2, 2, 2, 3, 4, 25.00, 'Delivery', 'Completed');
INSERT INTO ServiceOrder VALUES (3, 3, 3, 3, 2, 5, 32.75, 'Ride', 'Completed');
INSERT INTO ServiceOrder VALUES (4, 4, 4, 1, 4, 1, 20.00, 'Ride', 'Cancelled');
INSERT INTO ServiceOrder VALUES (5, 5, 1, 2, 5, 3, 15.50, 'Delivery', 'Completed');
INSERT INTO ServiceOrder VALUES (6, 3, 2, 1, 3, 1, 40.00, 'Ride', 'Completed');
INSERT INTO ServiceOrder VALUES (7, 2, 4, 3, 5, 4, 12.25, 'Delivery', 'Pending');
INSERT INTO ServiceOrder VALUES (8, 1, 3, 2, 2, 3, 21.50, 'Ride', 'Completed');

-- Payments
INSERT INTO Payment VALUES (1, 1, 18.50, 'Credit', 'Success');
INSERT INTO Payment VALUES (2, 2, 25.00, 'Credit', 'Success');
INSERT INTO Payment VALUES (3, 3, 32.75, 'Debit', 'Success');
INSERT INTO Payment VALUES (4, 4, 20.00, 'Credit', 'Failed');
INSERT INTO Payment VALUES (5, 5, 15.50, 'Debit', 'Success');
INSERT INTO Payment VALUES (6, 6, 40.00, 'Credit', 'Success');
INSERT INTO Payment VALUES (7, 7, 12.25, 'Credit', 'Pending');
INSERT INTO Payment VALUES (8, 8, 21.50, 'Credit', 'Success');

-- Ratings (customers who rated)
INSERT INTO Rating VALUES (1, 1, 5, 4.8, 'Fast delivery!');
INSERT INTO Rating VALUES (2, 2, 4, 4.9, 'Great driver!');
INSERT INTO Rating VALUES (3, 3, 5, 4.2, 'Comfortable ride');
INSERT INTO Rating VALUES (4, 5, 3, 4.7, 'Late pickup');
INSERT INTO Rating VALUES (5, 6, 5, 4.9, 'Excellent service');
-- Note: Orders 4, 7, and 8 are missing ratings to make Query #3 work

COMMIT;
EXIT;
EOF

```

queries.sh

```
GNU nano 6.2
#!/bin/sh
echo -n "Enter Oracle password: "
read -s PASSWORD
echo
sqlplus64 "skirubak/$PASSWORD@(DESCRIPTION=
(ADDRESS=(PROTOCOL=TCP)(Host=oracle.scs.ryerson.ca)(Port=1521))
(CONNECT_DATA=(SID=orcl)))" <<EOF

-- Formatting for cleaner query outputs
SET PAGESIZE 200
SET LINESIZE 200
COLUMN Customer FORMAT A20
COLUMN Driver   FORMAT A20
COLUMN address  FORMAT A30

PROMPT
PROMPT === 1) Join: List all completed orders with customer and driver names ===
SELECT s.orderID,
       c.name AS Customer,
       d.name AS Driver,
       s.status,
       s.fare
FROM   ServiceOrder s
       JOIN Customer c ON s.customerID = c.customerID
       JOIN Driver d   ON s.driverID   = d.driverID
WHERE  s.status = 'Completed';

PROMPT
PROMPT === 2) Aggregation: Average rating per driver ===
SELECT d.name,
       ROUND(AVG(r.driverRating),2) AS AvgRating
FROM   Driver d
       JOIN ServiceOrder s ON d.driverID = s.driverID
       JOIN Rating r      ON s.orderID  = r.orderID
GROUP BY d.name;

PROMPT
PROMPT === 3) Set Operation: Customers who paid but have not rated ===
SELECT customerID
FROM   ServiceOrder
MINUS
SELECT s.customerID
FROM   ServiceOrder s
       JOIN Rating r ON s.orderID = r.orderID;
```



```
PROMPT
PROMPT === 4) Nested Query: Drivers with earnings above average ===
SELECT name
FROM Driver
WHERE driverID IN (
    SELECT driverID
    FROM ServiceOrder
    GROUP BY driverID
    HAVING SUM(fare) > (SELECT AVG(fare) FROM ServiceOrder)
);

PROMPT
PROMPT === 5) Statistical Query: Total earnings by drop-off address ===
SELECT l.address,
       SUM(s.fare) AS TotalEarnings
FROM ServiceOrder s
JOIN Location l ON s.dropoffID = l.locationID
GROUP BY l.address
ORDER BY TotalEarnings DESC;

EXIT;
EOF
█
```

User interface output:

```
=====
|           Ride & Pickup DBMS – Oracle Tool           |
|-----|
1) Drop Tables
2) Create Tables
3) Populate Tables
4) Run Advanced Queries
E) Exit
|-----|
Choose: █
```

```
=====
|           Ride & Pickup DBMS – Oracle Tool           |
|-----|
1) Drop Tables
2) Create Tables
3) Populate Tables
4) Run Advanced Queries
E) Exit
|-----|
Choose: 1
Enter Oracle password:

SQL*Plus: Release 12.1.0.2.0 Production on Fri Oct 24 22:23:54 2025

Copyright (c) 1982, 2014, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SQL> SQL> SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL>
Table dropped.

SQL> SQL> Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
Press Enter to continue...█
```

```

=====
| Ride & Pickup DBMS - Oracle Tool |
=====
1) Drop Tables
2) Create Tables
3) Populate Tables
4) Run Advanced Queries
E) Exit
=====
Choose: 2
Enter Oracle password:

SQL*Plus: Release 12.1.0.2.0 Production on Fri Oct 24 22:24:26 2025

Copyright (c) 1982, 2014, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SQL> SQL> SQL> 2 3 4 5 6 7
Table created.

SQL> SQL> 2 3 4 5 6
Table created.

SQL> SQL> 2 3 4 5 6 7
Table created.

SQL> SQL> 2 3 4 5
Table created.

SQL> SQL> 2 3 4 5 6
Table created.

SQL> SQL> 2 3 4 5 6 7 8 9 10 11
Table created.

SQL> SQL> 2 3 4 5 6 7
Table created.

SQL> SQL> 2 3 4 5 6 7
Table created.

SQL> SQL> Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
Press Enter to continue...

```

```
=====
| Ride & Pickup DBMS – Oracle Tool |
-----
1) Drop Tables
2) Create Tables
3) Populate Tables
4) Run Advanced Queries
E) Exit
-----
Choose: 3
Enter Oracle password:

SQL*Plus: Release 12.1.0.2.0 Production on Fri Oct 24 22:24:49 2025

Copyright (c) 1982, 2014, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SQL> SQL> SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL>
0 rows deleted.

SQL> SQL> SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.
```

```
SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL> SQL> SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL> SQL> SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL>
1 row created.

SQL> SQL> SQL>
Commit complete.

SQL> Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
Press Enter to continue...
```

```

=====
| Ride & Pickup DBMS - Oracle Tool |
=====
1) Drop Tables
2) Create Tables
3) Populate Tables
4) Run Advanced Queries
E) Exit
-----
Choose: 4
Enter Oracle password:

SQL*Plus: Release 12.1.0.2.0 Production on Fri Oct 24 22:26:17 2025

Copyright (c) 1982, 2014, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SQL> SQL> SQL> SQL> SQL> SQL> SQL> SQL>
SQL> === 1) Join: List all completed orders with customer and driver names ===
SQL> 2 3 4 5 6 7 8 9
ORDERID CUSTOMER DRIVER STATUS FARE
-----
8 Alice Kevin L Completed 21.5
1 Alice John Doe Completed 18.5
2 Bob Mary P Completed 25
6 Cathy Mary P Completed 40
3 Cathy Kevin L Completed 32.75
5 Evelyn John Doe Completed 15.5

6 rows selected.

SQL> SQL>
SQL> === 2) Aggregation: Average rating per driver ===
SQL> 2 3 4 5 6
NAME AVGRATING
-----
Kevin L 4.2
Mary P 4.9
John Doe 4.75

SQL> SQL>
SQL> === 3) Set Operation: Customers who paid but have not rated ===
SQL> 2 3 4 5 6
CUSTOMERID
-----
4

```

```

SQL> SQL>
SQL> === 4) Nested Query: Drivers with earnings above average ===
SQL> 2 3 4 5 6 7 8
NAME
-----
John Doe
Mary P
Rita Z
Kevin L

SQL> SQL>
SQL> === 5) Statistical Query: Total earnings by drop-off address ===
SQL> 2 3 4 5 6
ADDRESS TOTAL EARNINGS
-----
123 King St 60
321 Dundas St 37.25
789 Bloor St 37
555 Bay St 32.75
456 Queen St 18.5

SQL> SQL> Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
Press Enter to continue...

```