Connect, communicate and extend your agents

Attendee guide. Build Atlas, a map agent, one step at a time on your own laptop: an agent, tools, MCP, MCP auth, A2A and skills.

Speaker: Kiruthika Subramani

Built with the Google Agent Development Kit and Gemini on Google Cloud

Written for complete beginners: it starts from an empty laptop

Every screenshot and every terminal block in this guide comes from a real run.

Long terminal output is shortened

Contents

1 What you will build

2 Before you start

3 Install three programs

4 Set up Google Cloud

5 Get the code and check your setup

6 Open the lessons

7 Step 1: an agent with nothing but confidence

8 Step 2: tools

9 Step 3: MCP

10 Step 4: MCP auth

11 Step 5: A2A

12 Step 6: skills

13 The map app: everything together

14 Test every part

15 No Google Cloud? Run it on your own laptop with Gemma

16 When something goes wrong

17 Small glossary

1 What you will build

Atlas is a map agent. You tell it where you are and what you are after, and it shows you three places worth the walk, with a description you can check and the walking route to each one.

You will not build it in one go. You will ask the same question six times, and each time the agent gets exactly one new thing. That way you can see what each idea is for.

THE QUESTION YOU ASK AT EVERY STEP

I'm at Grand Central Market in Los Angeles. Where should I eat?

STEP	THE ONE NEW IDEA	WHAT CHANGES IN THE ANSWER
1	An agent is a model with a job	Confident, and not checked against anything
2	A tool is a Python function	Real places with real distances
3	MCP serves those tools to any agent	Same answer, and the agent has no map code left
4	MCP auth decides who may call the tools	Without a login, the tools are refused
5	A2A lets one agent ask another	Each place gets a description with facts
6	A skill is a new job in one file	The agent can plan a walking tour

At the end, the same pieces run behind a map:

```
your browser ── web app ── recommendation agent ──MCP──▶ places server
                                    │                      geocode · nearby_places · walking_route
                                    │
                                    ├──A2A──▶ description agent ── Google Search
                                    │
                                    └──skill── walking-tour (one file of instructions)
```

MCP: an agent calling tools | A2A: an agent asking another agent | Skill: instructions loaded on demand

2 Before you start

You do not need to have built an agent before, or to have used Google Cloud. This guide starts from an empty laptop.

YOU WILL NEED	DETAILS
A laptop	Windows, macOS or Linux, with permission to install programs
A Google account	Any Gmail address works
A bank card	Google Cloud asks for one to open a billing account, even for small use
About 45 minutes	For sections 3 to 5, which you only ever do once
About an hour	For the steps themselves

What it costs. Each question you ask an agent is a handful of model calls, and in the later steps three Google Search lookups as well. Following this whole guide once is small change, but it is not free. Section 13 ends with how to stop everything.

2.1 How to open a terminal

A terminal is a window where you type commands. You will use it throughout.

ON	DO THIS
Windows	Press the Windows key, type **PowerShell**, press Enter
macOS	Press Cmd+Space, type **Terminal**, press Enter
Linux	Press Ctrl+Alt+T

2.2 How to read the dark boxes

Dark boxes show a terminal. A bright line after the green **>** is something **you type**, followed by Enter. Do not type the **>** itself. Grey lines are what the computer answers; yours may differ slightly.

```
> python --version
Python 3.13.0
```

Type one line at a time and wait for it to finish before typing the next.

3 Install three programs

Python runs the code. Git downloads it. The Google Cloud CLI signs you in. If you already have one of them, run its check and skip ahead.

3.1 Python

1. Go to **python.org/downloads** and press the yellow **Download Python** button.
2. Open the file that downloads.
3. **Windows only:** on the first screen, tick **Add python.exe to PATH** at the bottom. Then press **Install Now**.
4. **macOS:** press Continue through the installer and accept the defaults.
5. Close your terminal and open a new one. A terminal only notices new programs when it starts.

Check it:

```
> python --version
Python 3.13.0
```

Any version from 3.11 up is fine. On macOS and Linux the command may be `python3`. If `python` is not found, try `python3 --version`, and use `python3` wherever this guide says `python` until section 5.2.

Windows says "Python was not found" and opens the Store? The PATH box was not ticked. Run the installer again, choose **Modify**, and tick it.

3.2 Git

1. **Windows:** go to **git-scm.com/downloads**, download the Windows installer, open it, and press Next on every screen. The defaults are fine.

2. **macOS:** type `git --version` in the terminal. If Git is missing, a window offers to install the developer tools. Press Install.
3. Close your terminal and open a new one.

Check it:

```
> git --version
git version 2.54.0.windows.1
```

3.3 The Google Cloud CLI

This gives you the `gcloud` command. It is how your laptop proves to Google who you are, so that the code never needs a secret key.

1. Go to **cloud.google.com/sdk/docs/install** and choose your operating system.
2. **Windows:** download **GoogleCloudSDKInstaller.exe**, open it, and accept the defaults. On the last screen you can untick the boxes that offer to start a shell; you will sign in from your own terminal in section 4.
3. **macOS and Linux:** follow the steps on that page for your system. They end with running an install script that adds `gcloud` to your terminal.
4. Close your terminal and open a new one.

Check it:

```
> gcloud --version
Google Cloud SDK 571.0.0
```

Your number will be different. If the terminal says `gcloud` is not recognised, close every terminal window and open a fresh one. If it still fails, run the installer once more.

4 Set up Google Cloud

The agents use Google's Gemini model. Google runs it for you, and to use it you need four things: a project, a billing account, the service switched on, and your laptop signed in.

4.1 Create a project

A project is a labelled box that holds everything you use on Google Cloud and the bill for it.

1. Open **console.cloud.google.com/projectcreate** and sign in with your Google account. The first time, accept the terms of service.
2. Type a project name, for example **my-atlas**.
3. Under the name box there is a line that begins **Project ID**. Write it down. It looks like `my-atlas-123456`, and you will type it twice later. The ID is what matters, not the name.
4. Press **Create** and wait for the bell at the top right to show it is done.

4.2 Open a billing account and connect it

1. Open **console.cloud.google.com/billing**.
2. If you have no billing account, press **Create account** (it may say **Add billing account**). Choose your country, enter your card, and confirm. New accounts are often offered free trial credit on this screen; accept it if you see it.
3. Now connect it to your project. On the same Billing page, open the **My projects** tab, find your project, press the three dots at the end of its row, choose **Change billing**, and pick your billing account.

You know it worked when your project's row shows the billing account's name instead of *Billing is disabled*.

4.3 Sign in from your terminal

Type these two lines. Replace `YOUR_PROJECT_ID` with the ID you wrote down.

```
> gcloud auth login
> gcloud config set project YOUR_PROJECT_ID
```

LINE 1 Opens your browser. Choose your Google account and press Allow. The terminal then says you are logged in.

LINE 2 Tells `gcloud` which project to work in. It answers with a line that starts *Updated property*.

4.4 Switch on Gemini

On Google Cloud, Gemini is reached through a service called **Vertex AI**. Every service is off until you switch it on for your project. One line does it:

```
> gcloud services enable aiplatform.googleapis.com
```

It thinks for up to a minute and then reports that the operation finished. If it complains about billing, go back to 4.2: the project is not connected to a billing account yet.

4.5 Sign in the programs on your laptop

```
> gcloud auth application-default login
```

The browser opens again. Choose the same account and press Allow.

This looks like a repeat of 4.3, but it is a different login. The first one signed *you* in to the `gcloud` tool. This one signs in *programs running on your laptop*, which is what the agents are. It is the reason there is no API key anywhere in the code.

5 Get the code and check your setup

5.1 Download the code

In your terminal, go to a folder where you keep projects (your Documents folder is fine), then copy the repository and step into the folder for this session:

```
> cd Documents
> git clone https://github.com/Kiruthika162003/atlas-agents-workshop.git
> cd atlas-agents-workshop/demo1-build
```

`cd` means "change directory": it moves the terminal into a folder. **Everything from here on is typed inside `demo1-build`.** To see that you are in the right place, list what is there:

```
WINDOWS: dir    ·    MACOS AND LINUX: ls
> ls
GUIDE.md   Modelfile   README.md   atlas/   check.py   description_agent/
learn/     mcp_server/ requirements.txt   skills/   start.py
```

FOLDER OR FILE	WHAT IT IS	RUNS ON
`learn/`	The step by step agents, one small folder each	port 8000
`mcp_server/`	The places server: three map tools served over MCP	port 8001
`description_agent/`	The second agent, reached over A2A	port 8002
`skills/`	The walking tour skill, one file	
`atlas/`	The map app and the recommendation agent behind it	port 5000
`check.py`	Tests your setup and tells you what to fix	
`start.py`	Starts the whole map app with one command	

No Git? Open the repository page in your browser, press the green **Code** button, choose **Download ZIP**, unzip it, and `cd` into the `demo1-build` folder inside.

Opened a new terminal later? You have to come back here first: `cd Documents/atlas-agents-workshop/demo1-build`, then switch the virtual environment on again (5.2).

5.2 Make a private Python environment

A virtual environment keeps this project's packages separate from the rest of your computer. Create it once, then switch it on. **You must switch it on again in every new terminal you open.**

```
WINDOWS (POWERSHELL)
> python -m venv .venv
> .venv\Scripts\activate
```

```
MACOS AND LINUX
> python3 -m venv .venv
> source .venv/bin/activate
```

When it is on, the start of your prompt shows `(.venv)`. From now on, plain `python` works on every system.

> **PowerShell says running scripts is disabled?** Run `Set-ExecutionPolicy -Scope CurrentUser RemoteSigned` once, answer Y, and try the activate line again.

5.3 Install the packages

```
> pip install -r requirements.txt
```

This downloads the Agent Development Kit, the MCP library and the small web framework the map uses. It takes a few minutes and prints a lot. It is finished when your prompt comes back and one of the last lines starts with *Successfully installed*.

5.4 Tell the code which project to use

Copy the example settings file:

```
WINDOWS
> copy .env.example .env
```

```
MACOS AND LINUX
> cp .env.example .env
```

Open the new `.env` file in a text editor. On Windows, `notepad .env` opens it; on macOS, `open -e .env`. Find the line `GOOGLE_CLOUD_PROJECT=your-project-id` and replace `your-project-id` with your own Project ID. Save and close. The lines that matter should read:

```
GOOGLE_GENAI_USE_VERTEXAI=TRUE
GOOGLE_CLOUD_PROJECT=my-atlas-123456
GOOGLE_CLOUD_LOCATION=global
ATLAS_MODEL=gemini-3.8-flash
```

5.5 Check that everything works

One command tests the whole setup, including a real question to Gemini:

```
> python check.py

Checking your setup

  [ ok ]  Python 3.13
  [ ok ]  The packages are installed
  [ ok ]  The settings file points at project my-atlas-123456
  [ ok ]  gcloud is installed
  [ ok ]  Programs on this computer are signed in
  [ ok ]  Gemini answered: ready   (model gemini-3.8-flash)
  [ ok ]  The map service answered: Eiffel Tower is at 48.8583, 2.2945

Everything works. You are ready for step 1.
```

If a line says **[FIX]**, the check stops there and the line under it tells you what to do. Fix that one thing and run `python check.py` again.

THE LINE THAT FAILS	WHAT IT MEANS	GO TO
A package is missing	The virtual environment is off, or the install did not finish	5.2, then 5.3
There is no .env file, or it has the placeholder	The settings file was not copied or not edited	5.4
The gcloud command was not found	The Google Cloud CLI is not installed, or this terminal is older than the install	3.3, then open a new terminal
Programs are not signed in	The second login is missing	4.5
Gemini refused: billing is off	The project has no billing account	4.2
Gemini refused: Vertex AI is not switched on	The service is still off	4.4
Gemini is busy (429)	Nothing is wrong on your side	Wait a minute and try again

Do not go further until the last line says **Everything works**. Every later step depends on it.

6 Open the lessons

The Agent Development Kit comes with a small website for trying agents. Start it and leave it running.

```
> adk web learn
INFO:     Started server process [20588]
INFO:     Waiting for application startup.
+-----------------------------------------------------------------------------+
| ADK Web Server started                                                      |
|                                                                             |
| For local testing, access at http://127.0.0.1:8000.                        |
+-----------------------------------------------------------------------------+
INFO:     Uvicorn running on http://127.0.0.1:8000 (Press CTRL+C to quit)
```

Open **http://127.0.0.1:8000** in your browser. The dropdown at the top left lists the agents. You will pick them one after another.

You will need more than one terminal. From step 3 on, some programs have to keep running while you start others. Open a new terminal window for each, go to the `demo1-build` folder, and switch the virtual environment on again (section 5.2). To stop a running program, click its terminal and press **Ctrl+C**.

7 Step 1: an agent with nothing but confidence

In the dropdown, pick `agent_1_simple`. Type the question and press Enter.

ASK

I'm at Grand Central Market in Los Angeles. Where should I eat?




FIG 1. Three names and tempting descriptions, straight from the model's memory. Read its last line: it says itself that it cannot check any of this.

YOU WILL SEE A fluent answer in a second or two, with no tool calls on the screen.

IT MEANS The model is recalling, not looking. A stall that closed last year sounds exactly as confident as one that is open.

BEHIND IT The whole agent is a name, a model and an instruction. Open `learn/agent_1_simple/agent.py`; it is about twenty lines.

```
root_agent = Agent(
    name="agent_1_simple",
    model=os.getenv("ATLAS_MODEL", "gemini-3.8-flash"),
    description="A local guide with no tools.",
    instruction=("You are Atlas, a local guide. ... You have NO tools and NO map ..."),
)
```

8 Step 2: tools

Pick `agent_2_tools` and ask the same question.




FIG 2. The lightning bolts are the agent asking for a tool; the ticks are the answers coming back. First `geocode`, then `nearby_places`, then the reply. On the left, the three tools this agent owns.

YOU WILL SEE Real places with real distances: a bakery 13 metres away, a pasta restaurant at 81 metres.

IT MEANS The answer now comes from data. And nobody wrote "first find the location, then search": the agent chose that order itself.

BEHIND IT A tool is a normal Python function. The model never sees the code inside. It reads the name, the arguments and the description in quotes, which is why that description is written for a reader.

```
def geocode(place: str) -> dict:
    """Turn a place name or address into coordinates.

    Args:
        place: a name and its city, e.g. "Grand Central Market, Los Angeles".
    """
    ...

root_agent = Agent(
    ...
    tools=[geocode, nearby_places, walking_route],
)
```

Click any row in the conversation to see exactly what was sent and what came back.

9 Step 3: MCP

The three functions work, but they live inside one agent's file. The next agent would have to copy them. MCP, the Model Context Protocol, is an agreed way to serve tools so that any agent can use them.

Open a **second terminal**, switch on the virtual environment, and start the places server. Leave it running.

```
> python mcp_server/server.py
Open. Anyone who can reach this address may call the tools.
INFO:     Uvicorn running on http://localhost:8001 (Press CTRL+C to quit)
```

Back in the browser, pick `agent_3_mcp` and ask the same question.




FIG 3. The same two calls and the same kind of answer. The difference is where the tools live.

YOU WILL SEE The same answer as step 2, and new lines appearing in the server's terminal each time a tool is called.

IT MEANS The tools moved out of the agent. Write them once, and any program that speaks MCP can use them.

BEHIND IT In `mcp_server/server.py` the functions are the same, with `@mcp.tool()` on top. In `learn/agent_3_mcp/agent.py` there is no map code left: the agent points at an address and asks the server what it offers.

```
places = McpToolset(
    connection_params=StreamableHTTPConnectionParams(url="http://localhost:8001/mcp",
timeout=60),
)

root_agent = Agent(..., tools=[places])
```

10 Step 4: MCP auth

Look again at what the server printed when it started: *Anyone who can reach this address may call the tools.* On your laptop that is only you. On the internet it is everybody.

10.1 Walk in without a login

Open a **third terminal**, switch on the virtual environment, and knock on the server the way a stranger would:

```
> python mcp_server/knock.py
Let in. Tools on offer: geocode, nearby_places, walking_route
Called geocode('Eiffel Tower, Paris') -> { "found": true, "name": "Eiffel Tower", "address":
"Eiffel Tower, 5, Avenue Anatole France, ...", "lat": 48.85826, "lon": 2.2945 }
```

No name, no password, and it listed your tools and ran one.

10.2 Lock the door

Go to the terminal running the server and press **Ctrl+C**. Start it again, this time naming the Google account that is allowed in. Use the address you signed in with in section 4.

```
> python mcp_server/server.py --allow you@gmail.com
Locked. Only these accounts may call the tools: you@gmail.com
INFO:     Uvicorn running on http://localhost:8001 (Press CTRL+C to quit)
```

Knock again, first as a stranger, then with your login:

```
> python mcp_server/knock.py
Refused. The server wants a login it accepts (HTTP 401).
> python mcp_server/knock.py --login
Let in. Tools on offer: geocode, nearby_places, walking_route
Called geocode('Eiffel Tower, Paris') -> { "found": true, "name": "Eiffel Tower", "address":
"Eiffel Tower, 5, Avenue Anatole France, ...", "lat": 48.85826, "lon": 2.2945 }
```

The server's own terminal shows both attempts:

```
INFO:     ::1:51588 - "POST /mcp HTTP/1.1" 401 Unauthorized
INFO:     ::1:59898 - "POST /mcp HTTP/1.1" 200 OK
```

10.3 Let the agent in

In the browser, pick `agent_4_mcp_auth` and ask the same question. It works, because this agent shows your Google login to the server.




FIG 4. The agent with a login, answering through the locked server. `agent_3_mcp` has no login, so against the locked server its tools are refused.

IT MEANS The lock is in the server's code, not in a polite instruction to a model. A request with no valid login never reaches a tool.

BEHIND IT MCP auth is built on OAuth, the same family of standards behind "Sign in with Google". Three parties are involved. **GOOGLE** issues a signed token that says who you are. The **AGENT** carries that token with every request. The **SERVER** checks Google's signature, checks the expiry, and checks that the account is on its list. The server never sees a password.

```
class GoogleSignIn:
    """Lets a caller in only if Google vouches for them and they are on the list."""

    async def verify_token(self, token: str) -> AccessToken | None:
        try:
            who = id_token.verify_oauth2_token(token, google_transport.Request())
        except ValueError:
            return None                          # forged or expired
        if who.get("email") not in ALLOWED:
            return None                          # a real account, but not invited
        return AccessToken(token=token, client_id=who["email"], scopes=[],
expires_at=who["exp"])
```

Before you go on, unlock the server. The next steps use agents that send no login. Go to the server's terminal, press Ctrl+C, and start it the plain way: `python mcp_server/server.py`. You can close the third terminal.

About `agent_5_remote_mcp`. You will see it in the dropdown. It is the same agent pointed at a places server running in the cloud, and it is shown live in the session. It needs a deployed server, so this guide skips it.

11 Step 5: A2A

Finding places and describing them well are different jobs. Describing needs a web search and a strict rule about not inventing things. So that becomes a second agent, running as its own program.

In the third terminal (or a new one, with the virtual environment on), start the description agent and leave it running:

```
> python description_agent/agent.py
INFO:     Uvicorn running on http://localhost:8002 (Press CTRL+C to quit)
```

Every A2A agent publishes a card that says who it is and what it does. Open **http://localhost:8002/.well-known/agent-card.json** in your browser to read it:

```
{
  "name": "description_agent",
  "description": "Describes one real place in a few checked sentences.",
  "supportedInterfaces": [
    { "url": "http://localhost:8002", "protocolBinding": "JSONRPC", "protocolVersion": "1.0" }
  ],
  "capabilities": { "streaming": true }
}
```

Now pick `agent_6_a2a` in the lessons and ask the same question.




FIG 5. Three requests go out to `description_agent` at the same moment, three answers come back, and the reply carries real detail. The diagram on the left shows the agent's two helpers: the MCP tools and the other agent.

YOU WILL SEE Descriptions with facts in them: who founded the bakery, what the trattoria is known for, that one place takes no walk-ins.

IT MEANS MCP gives an agent hands. A2A gives it colleagues. The first agent does not know how the second one works, only what its card promises.

BEHIND IT The description agent searches Google for each place and is told to write only what the search confirms. In `learn/agent_6_a2a/agent.py`, two lines connect them:

```
description_agent = RemoteA2aAgent(
    name="description_agent",
    description="Describes one real place in a few checked sentences. Send one place per
request.",
    agent_card="http://localhost:8002" + AGENT_CARD_WELL_KNOWN_PATH,
)

root_agent = Agent(..., tools=[places, AgentTool(description_agent)])
```

12 Step 6: skills

Suppose you want the agent to plan walking tours. You could make its instruction longer, and longer again for the next idea. A skill is the alternative: a folder with one file of instructions that the agent only reads when a request needs it.

Pick `agent_7_skills` and ask for a tour:

ASK

I'm at Grand Central Market in Los Angeles. Plan me a walking tour of fun things.




FIG 6. The agent finds the skill, loads it, then follows it: one route per leg, and totals that add up.

YOU WILL SEE Calls named `list_skills` and `load_skill`, then the usual map tools, then a tour with times.

IT MEANS The agent learned a new job from a text file. Ask it the eating question instead and it never opens that file.

BEHIND IT Open `skills/walking-tour/SKILL.md`. The two lines at the top are all the agent sees until it decides it needs the rest.

```
---
name: walking-tour
description: Turn a few nearby places into a walking tour with an order, timings
  and a total. Use when someone asks for a tour, an itinerary, ...
---

# Planning a walking tour

Work only from what the tools returned. Never add a place, a time or a fact of your own.
...
```

Try changing a number in that file, for example the minutes to allow at a museum. Stop `adk web learn` with Ctrl+C, start it again, and ask once more. You changed what the agent does without touching any Python.

13 The map app: everything together

The lessons showed one idea at a time. The map app runs all of them behind one page.

First stop everything you started: press **Ctrl+C** in each terminal. Then, in one terminal with the virtual environment on:

```
> python start.py
Model: gemini (Google Cloud) or gemma (this laptop)? [gemini]
Atlas is starting on http://localhost:5000 with gemini-3.8-flash. Ctrl+C stops everything.
Open. Anyone who can reach this address may call the tools.
INFO:     Uvicorn running on http://localhost:8001 (Press CTRL+C to quit)
INFO:     Uvicorn running on http://localhost:8002 (Press CTRL+C to quit)
 * Serving Flask app 'app'
```

Press Enter to accept `gemini`. That one command starts the places server, the description agent and the web app. Open **http://localhost:5000**.




FIG 7. The opening screen. Type a place, press one of the three examples, or use the round button to share your real location.

13.1 Ask for food

ASK

I'm at Grand Central Market, Los Angeles. Find me food.




FIG 8. Every step the agent takes appears as a row. Blue rows tagged MCP are calls to the places server. Green rows tagged A2A are requests to the description agent.




FIG 9. Three picks, three colours. Each pick has a card, a numbered pin and a walking route in the same colour, labelled with its distance and time.

Look closely at the first card in FIG 9. The description agent found that this stall had closed, and said so. It did not copy the cheerful version.

ON THE CARD	WHERE IT COMES FROM
Name, type, address, opening hours, website	The map listing, exactly as it is
Distance, minutes and the route line	The `walking_route` tool
The Directions button	A Google Maps link built from two coordinates
The description	The description agent, checked with Google Search
"Checked against" links	The pages that search used

The model writes one paragraph. Everything else on the card is data.




FIG 10. Click a card and the map goes to that place.

13.2 Ask a follow-up question

Ask about one of the places by name. The question goes back to the description agent, and the answer arrives in the chat with its sources.




FIG 11. A follow-up about vegetarian food. Ask about an allergy and it reports what it found, then tells you to confirm with the staff.

13.3 Add a place of your own

The grey dots are the other places the agent could have chosen. Hover over one to see what it is. Click it, then **Add to my picks**, and the agent describes it and draws its route like the others.




FIG 12. Hovering and clicking cost nothing. The description is only requested when you press the button.




FIG 13. The added place becomes pick number four, with its own colour.

13.4 Other kinds of places

Under every answer there are buttons for what to try next. **More** opens four more kinds. After a search you also get buttons that narrow it, such as **Only museums**.




FIG 14. Seven kinds in all: food, coffee, fun, shopping, outdoors, schools and essentials.

KIND	WHAT IT FINDS
Food	restaurants, cafes, bakeries
Coffee	cafes
Fun	museums, attractions, theatres, cinemas
Shopping	markets, bookshops, malls, gift shops
Outdoors	parks, gardens, viewpoints, beaches
Schools	schools, universities, libraries
Essentials	pharmacies, cash machines, toilets, stations

Essentials get a pin and a route but no description. There is nothing to say about a cash machine, so the agent does not ask.




FIG 15. The box in the top corner changes the look of the map: Street, Light, Satellite or Terrain.

13.5 Ask for a walking tour

ASK

Plan me a walking tour of fun things.




FIG 16. Purple rows tagged **SKILL**: the agent loads the walking tour instructions, plans three legs, and the map draws them in order.

13.6 Try anywhere

Nothing in the code is tied to Los Angeles. Try *I'm near the Eiffel Tower, Paris. Show me fun things*, or your own street. Big cities have many places on the map; a small town may have only a few.

When you are done, press **Ctrl+C** in the terminal. That stops all three programs.

14 Test every part

A checklist for when you want to be sure each piece works on its own. Work down it in order. Each line says what to do and what you should see.

14.1 Your setup

#	DO THIS	YOU SHOULD SEE
1	`python check.py`	Seven lines that say ok, ending with *Everything works*
2	`adk web learn`, then open http://127.0.0.1:8000	The lesson page, with seven agents in the dropdown at the top left

14.2 The agent and its tools

#	DO THIS	YOU SHOULD SEE
3	Pick `agent_1_simple`, ask the eating question	An answer with no lightning bolt rows: it used no tools
4	Pick `agent_2_tools`, ask the same	Rows for `geocode` and `nearby_places`, then places with distances in metres
5	Click the `nearby_places` row with the tick	On the left, the list of places the tool returned

14.3 The places server (MCP)

#	DO THIS	YOU SHOULD SEE
6	In a second terminal: `python mcp_server/server.py`	A first line that begins *Open.* and a line ending in *localhost:8001*
7	Pick `agent_3_mcp`, ask the eating question	The same kind of answer as test 4, and new lines in the server's terminal
8	In a third terminal: `python mcp_server/knock.py`	*Let in*, the three tool names, and coordinates for the Eiffel Tower

14.4 The lock (MCP auth)

#	DO THIS	YOU SHOULD SEE
9	Stop the server with Ctrl+C. Start it with `python mcp_server/server.py --allow you@gmail.com`, using your own address	A first line that begins *Locked.* and shows your address
10	`python mcp_server/knock.py`	*Refused*, and a line with *401 Unauthorized* in the server's terminal
11	`python mcp_server/knock.py --login`	*Let in* again
12	Pick `agent_4_mcp_auth`, ask the eating question	A normal answer, through the locked server
13	Stop the server and start it the plain way again: `python mcp_server/server.py`	*Open.* You need this for everything that follows

14.5 The second agent (A2A)

#	DO THIS	YOU SHOULD SEE
14	`python description_agent/agent.py`	A line ending in *localhost:8002*
15	Open http://localhost:8002/.well-known/agent-card.json in the browser	A small page of text that includes *"name": "description_agent"*
16	Pick `agent_6_a2a`, ask the eating question	Three `description_agent` rows, and descriptions with specific facts

14.6 The skill

#	DO THIS	YOU SHOULD SEE
17	Pick `agent_7_skills`, ask for a walking tour of fun things	Rows for `list_skills` and `load_skill`, then a numbered tour with minutes and metres
18	Add up the minutes in the tour yourself	They match the total in its first line

14.7 The map app

Stop everything with Ctrl+C in each terminal, then run `python start.py`, press Enter, and open http://localhost:5000.

#	DO THIS	YOU SHOULD SEE
19	Type *I'm at Grand Central Market, Los Angeles. Find me food.*	The map flies there. Three cards, three pins and three routes, each set in its own colour
20	Read the rows above the cards	Blue **MCP** rows and green **A2A** rows
21	Read one card to the bottom	A line that starts *Checked against* with links, and a **Directions** button
22	Click a card	The map moves to that place and opens its popup
23	Ask *What does* (a name from a card) *serve for vegetarians?*	An answer in the chat, with its own *Checked against* links
24	Hover over a grey dot, then click it and press **Add to my picks**	A fourth card, pin and route in a new colour
25	Press **More**, then **Essentials**	Three pins with routes and no description
26	Press one of the **Only …** buttons after a search	Results of just that type
27	In the box at the top right of the map, choose **Satellite**	The map changes to aerial photos; pins and routes stay
28	Type *Plan me a walking tour of fun things.*	Purple **SKILL** rows, a tour in the chat, and purple numbered legs on the map
29	Type a place in another country, for example *I'm near the Eiffel Tower, Paris. Show me fun things.*	The same behaviour, somewhere else
30	Press Ctrl+C in the terminal	All three programs stop, and the page no longer answers

15 No Google Cloud? Run it on your own laptop with Gemma

Gemma is Google's open model. With a recent graphics card you can run it yourself, and then nothing in this guide needs a cloud project or costs anything.

1. Install Ollama from **ollama.com**.
2. Download the model. It is about 6 GB.
3. Build the copy this project uses, which has more room to read tool results.

```
> ollama pull gemma4:e4b-it-qat
> ollama create atlas-gemma -f Modelfile
```

Then start the app and type `gemma` when it asks:

```
> python start.py
Model: gemini (Google Cloud) or gemma (this laptop)? [gemini] > gemma
```

For the lessons, change the last line of `.env` to `ATLAS_MODEL=ollama_chat/atlas-gemma` before you run `adk web learn`.

What is different on Gemma. It is slower, about a minute for a question on a laptop graphics card. And it has no Google Search, so the description agent reads Wikipedia instead. Famous places get real history; a small cafe gets an honest "little is published about it".

16 When something goes wrong

WHAT YOU SEE	WHY	WHAT TO DO
`python` or `adk` is not recognised	The virtual environment is off in this terminal	Run the activate line from section 5.2 again
This API method requires billing to be enabled	Billing is off for the project	Section 4.2
Permission denied or *API has not been used in project*	Vertex AI is not switched on, or the wrong project is set	Sections 4.3 and 4.4
Your default credentials were not found	Programs on your laptop are not signed in	Section 4.5
`429 RESOURCE_EXHAUSTED`, or a card that says the description agent was rate limited	Gemini is busy. It happens in bursts	Wait a few seconds and ask again
A row ends *failed: The map service refused the request*	The free map service allows about one request a second	Wait a few seconds and ask again
An agent says it cannot find a location, or has no tools	The places server is not running, or it is still locked from step 4	Start it the plain way: `python mcp_server/server.py`
`agent_6_a2a` fails	The description agent is not running	`python description_agent/agent.py`
Address already in use	An earlier copy is still running	Find its terminal and press Ctrl+C, or close that terminal
The page looks old after a change	The browser kept the previous version	Hard refresh: Ctrl+F5, or Cmd+Shift+R on a Mac

17 Small glossary

WORD	IN PLAIN WORDS
Agent	A model in a loop that decides its own next step: think, use a tool, read the result, repeat
Tool	A function the agent can ask your program to run
MCP	Model Context Protocol. A shared way to serve tools so any agent can use them
MCP server	The program that offers the tools. Here, the places server
OAuth	The standard behind "Sign in with Google". Someone you trust issues a token that proves who the caller is
Token	A short-lived, signed proof of identity. Here it lasts an hour
401	The web's code for "I do not know who you are". What the locked server answers to a stranger
A2A	Agent to Agent. A shared way for one agent to hand a task to another
Agent card	A small public file where an A2A agent says who it is and what it does
Skill	A folder with a `SKILL.md` file: instructions the agent loads only when it needs them
Grounding	Making the model answer from a search or a document, not from memory
Virtual environment	A private set of Python packages for one project
Port	A numbered door on your computer. Each program in this guide listens on its own
localhost	Your own computer, as seen from itself