



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 01

Objective & Lecture Mapping: Recall that an intelligent agent acts within a continuous loop: Sensors generate percept sequences, and Actuators execute actions to maximize a Performance measure. Use this sheet to execute practical modifications and incrementally evaluate your design against Lecture 01 and 02 theory (from basic recall to analytical classification).

Part 1: Code Analysis & PEAS Evaluation

Task 0 : Setting up and getting the starter Code

1. Go to the [Git Hub Repo](#). Create a Fork of this Git Repo to your Personal Github Profile. Open it using your favourite IDE and follow the below instruction to complete the practical. The base code is in the "master" branch of the repo.

Task 1.1: The Environment State (`__init__`)

1. (Remember) List the four components of the PEAS framework discussed in Lecture 01.

Environment
Actuators
Sensors

2. (Understand) Look at the `VisualGridHuntGame.__init__` method. Which specific variables in this code represent the physical "Environment (E)" state?

`self.width, self.height, self.walls, self.food_positions, self.agent_pos, self.opponents`

3. (Analyze) Based on the variables initialized (specifically `self.opponents`), classify this baseline environment as "Single-Agent" or "Multi-Agent". Briefly justify your choice.

Multi Agent - `self.opponents` represents other agents that move in the same environment and can collide with the main agent.

Task 1.2: The Perception Subsystem (`get_percept`)

4. (Remember) Define what a "percept sequence" is according to Lecture 01.

The complete history of all percepts the agent has perceived up to the current moment

5. (Understand) Which component of the PEAS framework does the `get_percept()` method represent in our code?

Sensors component of the PEAS framework does the `get_percept()` method represent in our code.

6. (Evaluate) Based on the exact dictionary returned by `get_percept()`, is this environment "Fully Observable" or "Partially Observable"? Explain why based on what the agent can and cannot see.

Fully Observable - Because `get_percept()` returns a dictionary containing the exact state of the entire map without hiding anything, therefore the environment is fully observable.

Task 1.3: Action Execution (`execute_action`)

7. (Understand) When `execute_action()` deducts points for hitting a wall, which PEAS component is being actively updated?

Performance Measure

8. (Evaluate) Why is it structurally important that this metric evaluates changes in the external environment state (hitting a wall) rather than the agent's internal processing effort?

It is structurally important that the performance measure evaluates the external environment state rather than internal processing effort because it aligns the agent's incentives with the actual goals of the system

Part 2: Guided Modification & Deep Theory Mapping

Follow the implementation instructions to inject a new hazard, then answer the questions to map your code changes back to the theoretical nature of the environment.

Step 2.1: Extending the Environment Initialization (`__init__`)

1. **Implementation Instructions:** Declare a new trap collection attribute (e.g., `self.toxic_traps = set()`) inside `__init__`. Populate it with coordinate tuples safely avoiding position `(0, 0)`, walls, and food.

9. (Understand) If you successfully add `self.toxic_traps` to the environment but intentionally **hide** this data from the agent's sensors, how does this specifically alter the environment's "Observability" classification?

If you add `self.toxic_traps` to the environment but intentionally omit this data from the `get_percept()` dictionary, the environment remains decisively classified as partially Observable.

Step 2.2: Updating the Perception Subsystem (`get_percept`)

1. **Implementation Instructions:** Locate `get_percept(self)` and add a new boolean sensor key (e.g., `'smells_toxin': tuple(self.agent_pos) in self.toxic_traps`) to the dictionary returned to the agent loop.

10. (Analyze) By adding `'smells_toxin'`, you expand the agent's percept sequence. Explain how this specific sensor helps the agent act with "Rationality" (maximizing expected utility).

By introducing the smell_toxin sensor into the `get_percept()` dictionary, you directly enhance the agent's ability to act rationally. In artificial Intelligence a rational agent is the one who selects actions to maximize it's expected utility based on it's percept

Step 2.3: Modifying Action Execution & Visual Rendering (`execute_action` & `draw_grid`)

1. **Implementation Instructions:** In `execute_action`, check if the updated `self.agent_pos` intersects with `self.toxic_traps` to decrement `self.score` by 15 points. In `draw_grid`, iterate through traps to render custom purple shapes on the canvas.

11. (Remember) You programmed a severe score penalty for stepping on a trap to avoid metric exploitation. What was the classic "Vacuum World Exploit" example discussed in Lecture 01 that illustrated the danger of faulty metrics?

Here if the human designer creates a performance measure that rewards the vacuum agent for the action of cleaning up the dirt rather than clean floor, a rational agent will find a loophole.

Finalize and Lock Lab 01 Analytical Evaluation

Lab 01 code analysis and theoretical evaluation complete and verified!



FACULTY OF COMPUTING

