



Sky Cool

MANUFACTURING OF
ALL COOLING SOLUTIONS



An ISO 9001-2015 Certified Company





ABOUT COMPANY

We, Rapid Air Solution are an ISO 9001:2015 Certified Company. We, Rapid Air Solution are a newly formed company, started our journey from Ahmedabad, Gujarat (India) with an aim to succeed in this domain by earning the support of the customers from every region of the country.

Our Employees work sincerely with an aim to make a huge name for our brand in the market by providing our clients with exceptional sales and after sales services. In order to store our stock in an safe and organized manner we have maintained a spacious warehousing unit.



VISION

We Envision Provide Quality Products For Every Application And Providing Efficient And Round The Clock Services To The Satisfaction Of Our Customers At The Economically Affordable Price.



MISSION

We Aim To Satisfy Our Customers To The Maximum Extent Because Customer Satisfaction Is The Key To Our Growth. Their Feedback Invariably Serves As The Most Potential Support For Continuous Improvement In Our People,



REFRIGERATED AIR DRYER



FEATURES

- Copper "TUBE & TUBE and SHELL & TUBE" Non Corrosive Heat Exchanger, Designed To Have Lower Pressure Drop And Higher Efficiency contains In Built Centrifugal Moisture Separator Having Dead zone To Avoid Carry Over Of Condensate.
- PUF Insulation For Heat Exchanger Assembly.
- Electronic (Digital) Timer Operated Auto Drain Valve.
- Universally Available Refrigeration Components Like Condenser, Compressor, Fan Motor, Filter, Expansion Valve Etc.
- Non Cyclic Refrigeration Systems, With Help Of Hot Gas By Pass Solenoid Valve, For Varying Load Condition And Seasonal Adjustments.
- Our All Model Of Dryers Are Filled With "OZONE FRIENDLY" R134a, R22, R410A & R407C Refrigerant.



Correction Factor of Air Dryer



SIZING OF REFRIGERATION AIR DRYERS

Boundary Conditions

Operating Parameters	ideal	Minimum	Maximum
Inlet Air Temperature, °C	45	10	60
Ambient Temperature. °C	40	-5	50
Inlet Air Pressure, bar g	7	2	16
Pressure Dew Point, °C	3	3	10



Correction Factor for Conditions differing from the ideal one...

Inlet Air Temperature, L1							
Inlet Air Temperature, °C	30	35	40	45	50	55	60
Correction Factor L1	1.61	1.38	1.22	1.00	0.76	0.60	0.49

Ambient Temperature, L2							
Inlet Air Temperature, °C	25	30	35	40	45	50	55
Correction Factor L2	1.21	1.14	1.07	1.00	0.93	0.85	0.74

Inlet AirPressure, L3											
Inlet Air Pressure, bar g	3	4	5	6	7	8	9	10	12	14	16
Correction Factor L3	0.54	0.66	0.76	0.87	1	1.02	1.17	1.26	1.38	1.51	1.65

Pressure Dew Point, L4				
Pressure Dew Point, °C	3	5	7	10
Conversion Factor °C	1.00	1.14	1.24	1.39



TECHNICAL SPECIFICATION

Model	Air Flow	Power	Power Supply	Length	Width	Height	Approx Weight	Air Connection
	CFM	KW	V/Ph 50Hz					BSP
SC-S20	20	0.6	1 Phase	400	400	700	38	1/2"
SC-S40	40	0.6	1 Phase	400	400	700	40	1/2"
SC-S60	60	0.8	1 Phase	440	440	700	43	1/2"
SC-S80	80	0.9	1 Phase	440	440	700	50	1/2"
SC-S100	100	1.3	1 Phase	530	600	880	60	1
SC-S125	125	1.3	1 Phase	530	600	880	80	1
SC-S150	150	1.4	1 Phase	530	600	880	80	1 1/2"
SC-S200	200	1.5	1 Phase	700	700	1100	100	1 1/2"
SC-S250	250	2	3 Phase	700	700	1100	100	1 1/2"
SC-S300	300	2	3 Phase	700	700	1100	100	1 1/2"
SC-S350	350	3	3 Phase	800	800	1300	120	2"
SC-S400	400	3	3 Phase	800	800	1300	120	2"
SC-S500	500	3	3 Phase	800	800	1300	120	2"



INDUSTRIES WE SERVES

- CERAMIC INDUSTRY
- OFFSET PRINTING
- TEXTILE PRINTING
- VMC / CNC MACHINES SHOP
- ELECTRONICS INDUSTRY
- PHARMACEUTICAL INDUSTRY
- FOUNDRY
- WOODEN FACTORY
- PNEUMATIC OPERATED MACHINERY
- CEMENT PLANTS
- AUTOMOBILE INDUSTRY
- HEALTHCARE/HOSPITAL
- PET BOTTLE INDUSTRY
- GLASS INDUSTRY
- CHEMICAL INDUSTRY
- FOOD AND BEVERAGE PLANT
- TOOL ROOM & MORE....



SKY COOL SYSTEM

SHED NO 40, Parishikhar Industrial Estate 2,
S P RING ROAD, NR RAMOL TOLL PLAZA, Ramol,
Ahmedabad, Ahmedabad, Gujarat, 382449
M.: +91 90333 75597