

Slip 8

Program 1: LRU Page Replacement Algorithm

```
#include <stdio.h>

#define MAX 20

int frames[MAX], ref[MAX], mem[MAX][MAX], time[MAX], faults = 0, m, n, counter = 0;

void accept() {
    printf("Enter number of frames: ");
    scanf("%d", &n);
    printf("Enter number of references: ");
    scanf("%d", &m);
    printf("Enter reference string:\n");
    for (int i = 0; i < m; i++) {
        printf("[%d] = ", i);
        scanf("%d", &ref[i]);
    }
}

int search(int pno) {
    for (int i = 0; i < n; i++) {
        if (frames[i] == pno) return i;
    }
    return -1;
}

int get_lru() {
    int min = 9999, min_i = 0;
    for (int i = 0; i < n; i++) {
        if (time[i] < min) {
            min = time[i];
            min_i = i;
        }
    }
}
```

```
    return min_i;
}
```

```
void lru() {
    for (int i = 0; i < m; i++) {
        int k = search(ref[i]);
        if (k == -1) {
            if (counter < n) {
                frames[counter] = ref[i];
                time[counter] = i;
                counter++;
            } else {
                int pos = get_lru();
                frames[pos] = ref[i];
                time[pos] = i;
            }
            faults++;
        } else {
            time[k] = i;
        }
        for (int j = 0; j < n; j++) {
            mem[j][i] = frames[j];
        }
    }
}
```

```
void disp() {
    printf("\nReference String:\n");
    for (int i = 0; i < m; i++) {
        printf("%3d", ref[i]);
    }
    printf("\n\nFrame Allocation:\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            if (mem[i][j]) {
```

```

        printf("%3d", mem[i][j]);

    } else {

        printf(" ");

    }

}

printf("\n");

}

printf("\nTotal Page Faults: %d\n", faults);

}

```

```

int main() {

    accept();

    lru();

    disp();

    return 0;

}

```

Program 2: Shell with search Command

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
void search_file(char *option, char *filename, char *pattern) {
```

```
    FILE *file = fopen(filename, "r");
```

```
    if (file == NULL) {
```

```
        printf("File %s not found.\n", filename);
```

```
        return;
```

```
    }
```

```
    char line[256];
```

```
    int count = 0, line_num = 0;
```

```
    while (fgets(line, sizeof(line), file)) {
```

```
        line_num++;
```

```
        if (strstr(line, pattern) != NULL) {
```

```
            if (strcmp(option, "a") == 0) {
```

```

        printf("Line %d: %s", line_num, line);
    }

    count++;
}
}

if (strcmp(option, "c") == 0) {

    printf("Pattern '%s' occurred %d times in file %s.\n", pattern, count, filename);

}

fclose(file);
}

```

```

int main() {

    char command[100], *args[10];

    while (1) {

        printf("\nmysHELL$ ");

        fgets(command, 100, stdin);

        command[strlen(command) - 1] = '\0'; // Remove newline

        char *token = strtok(command, " ");

        int i = 0;

        while (token != NULL) {

            args[i++] = token;

            token = strtok(NULL, " ");

        }

        args[i] = NULL;

        if (strcmp(args[0], "search") == 0) {

            search_file(args[1], args[2], args[3]);

        } else if (strcmp(args[0], "exit") == 0) {

            exit(0);

        } else {

            int pid = fork();

            if (pid == 0) {

```

```
    execvp(args[0], args);  
    exit(0);  
} else {  
    wait(NULL);  
}  
}  
}  
return 0;  
}
```