Script-Controlled ACL – Restrict Record Access

Milestone 5: Deployment & Conclusion
Activity 1: Make Update Set → Complete State → Conclusion

Purpose

This guide gives a practical step-by-step flow for completing the final project activity shown in the uploaded project dashboard. It covers the three requested actions: (1) create/configure the script-controlled ACL, (2) test and verify record access, and (3) make the Update Set complete and finish the deployment/conclusion stage.

Project Type

Item	Value
Project / Feature	Script-Controlled ACL
Security goal	Restrict record access based on a scripted condition
Milestone	Milestone 5 – Deployment & Conclusion
Activity	Activity 1 – Make Update Set to Complete State / Conclusion
Main actions	Action 1: ACL → Action 2: Test → Action 3: Update Set & Conclusion

ACTION 1 — Create / Configure the Script-Controlled ACL

1. Open the application navigator and go to System Security → Access Control (ACL).

2. Select New to create a new ACL, or open the existing ACL for the project table/record.

3. Choose the correct Type (for example, record/table ACL) and select the target Table and operation such as Read, Write, Create, or Delete according to the project requirement.

4. Add the required Role or roles if role-based access is part of the requirement.

5. Enable/use the Script condition when the access decision must be controlled by a scripted rule.

6. Enter the project-specific logic. The script should return true only when the current user is allowed to access the record.

Example ACL Script Pattern

Use this only as a pattern. Replace the field/role names with the exact fields and roles in your project.

```
// Example pattern
answer = false;
if (gs.hasRole('your_project_role')) {
  answer = true;
} else if (current.u_owner == gs.getUserID()) {
  answer = true;
}
```

Save the ACL and make sure the ACL name, table, operation, roles, and script match the project requirement.

ACTION 2 — Test and Verify Record Access

1. Create or identify at least two test users: an authorized user and an unauthorized user.

2. Give the authorized user the required project role/condition.

3. Log in or impersonate the authorized user and open the target record. Confirm the user can perform the intended operation.

4. Test the same record with the unauthorized user. Confirm that the ACL blocks the operation when the script condition is false.

5. Test edge cases such as a different owner, missing role, or a record that should not be accessible.

6. If the result is wrong, review the ACL operation, table, role requirements, script condition, and ACL evaluation order. Correct the rule and test again.

Verification Checklist

Test	Expected result
Authorized user	Access is allowed when the script condition is true.
Unauthorized user	Access is denied when the condition is false.
Correct record/operation	ACL applies to the intended table and operation.
Edge case	Access follows the project rule.

ACTION 3 — Make the Update Set Complete and Finish Conclusion

1. Open System Update Sets → Local Update Sets.

2. Open the Update Set used for this ACL project. Verify that the required ACL and related configuration changes are captured.

3. Review the Customer Updates / captured changes. Remove or correct unwanted changes before completion.

4. Make sure the ACL has been tested successfully and the project changes are ready to move forward.

5. Change the Update Set State from In Progress to Complete.

6. Save/update the record. The completed Update Set can then be prepared for transfer/deployment according to the project's target instance/process.

7. For deployment, retrieve/preview the Update Set on the target instance and resolve any preview errors before committing it.

8. After deployment, run the final ACL tests again on the target environment and record the result.

9. Update the project conclusion: ACL implemented, access verified, Update Set completed, and deployment validated.

Milestone 5 – Completion Checklist

Activity	Done when...
ACL implementation	Script-controlled record access works as required.
Testing	Authorized and unauthorized cases have been verified.
Update Set review	Only required project changes are included.
Update Set state	State is changed to Complete.
Deployment	Target instance receives and validates the changes.
Conclusion	Project result and verification are documented.

Project Editing / Submission Place

Use your project workspace shown in the uploaded screenshot to edit the milestone/activity and record completion. The screenshot shows Project Progress 90%, View Demo, View Repo, and Milestone-1: Creation of Users and Roles. For Milestone 5, update the corresponding activity in the same project workspace when that milestone is available.

Project PDF / Link

A real project URL was not visible in the uploaded screenshot, so no project link has been invented here. After opening the project, copy its browser URL and paste it into the submission/project document. You can use the following placeholder in your final submission:

Project Link: _____

Demo Link: _____
Repository Link: _____

Final answer: Action 1 = configure the Script-Controlled ACL; Action 2 = test authorized/unauthorized record access; Action 3 = review the Update Set, change its State to Complete, deploy/validate, and document the conclusion.

Note: Exact table names, ACL operations, roles, fields, and script logic must match your actual project requirements. The uploaded screenshot does not expose those implementation-specific values.