Script-Controlled ACL – Restrict Record Access

Milestone 6: Creation of Access Control List – Delete

Objective: Create a Delete Access Control (ACL) that restricts who can delete records from the selected table by using a script-controlled condition.

Prerequisites

• ServiceNow instance access with permission to create ACLs.

• The target table should already exist.

• A user role should be available for testing the ACL.

• Use a non-production/development instance for testing.

Action 1 – Open Access Control (ACL)

Step 1: Log in to the ServiceNow instance.

Step 2: In the left-side Application Navigator, search for **Access Control (ACL)**.

Step 3: Open **System Security** → **Access Control (ACL)**.

Step 4: Click **New** to create a new Access Control.

Action 2 – Configure the Delete ACL

Field	Value / Action
Type	Record
Operation	Delete
Name	Select the target table, or the required table.*
Requires role	Select the role(s) allowed to delete records.
Condition	Add any required condition for the records.
Advanced	Enable Advanced/script option if required.
Script	Enter the server-side script that returns true for authorized deletion.

***Important:** Replace the target table and role with the values required by your project. Do not use a delete ACL on a production table until it has been fully tested.

Action 3 – Add the Script-Controlled Rule

Step 1: In the ACL form, select the **Advanced** option when available.

Step 2: Enter the project-specific server-side script in the Script field.

Step 3: The script must evaluate the current user and/or record and return **true** only when deletion is permitted.

Step 4: Save or submit the ACL.

Example Script Pattern

Use this only as a pattern; replace the role/condition with the rule defined in your project:

```
answer = gs.hasRole('your_required_role');
```

Action 4 – Test the Delete ACL

Step 1: Impersonate or log in as a user who does **not** satisfy the ACL rule.

Step 2: Open a record from the target table and verify that deletion is denied.

Step 3: Test again with a user who satisfies the ACL rule.

Step 4: Verify that the authorized user can delete the record.

Step 5: Check the system logs or ACL evaluation details if the result is unexpected.

Expected Result

The Delete ACL successfully restricts record deletion. Unauthorized users are prevented from deleting records, while users who satisfy the configured role/condition/script are allowed to delete them.

Milestone 6 – Completion Checklist

■ Delete ACL created

■ Correct target table selected

■ Delete operation selected

■ Required role/condition configured

■ Script-controlled rule added

■ ACL saved successfully

■ Unauthorized deletion tested and blocked

■ Authorized deletion tested successfully

Conclusion: Milestone 6 is complete when the Delete ACL is created, script-controlled access is configured, and both authorized and unauthorized deletion scenarios have been tested successfully.