Code test before the run ->

```
(jupyter-env) ➜  Lab-7 git:(main) ✗ python3 income_tax_parser.py
==== Running clean_pan ====
Enter a PAN (e.g. abcde 1234f): abcde
Cleaned PAN: ABCDE

==== Running parse_amount ====
Enter an amount (e.g. Rs 12,50,000): 125000
Amount in rupees: 125000

==== Running parse_tax_slab ====
Enter a tax slab as LOW-HIGH:RATE (e.g. 250000-500000:5): 250000-50000:3
Tax slab (low, high, rate): (250000, 50000, 3)
(jupyter-env) ➜  Lab-7 git:(main) ✗
```

Test Cases Failing ->

```
(jupyter-env) ➜  Lab-7 git:(main) ✗ pytest test_income_tax_parser.py
============================= test session starts ==============
platform linux -- Python 3.14.7, pytest-9.2.0, pluggy-1.7.0
rootdir: /home/hecker/Documents/SE/Lab-7
plugins: platformdirs-4.12.4, anyio-4.15.1, hypothesis-6.170.15
collected 3 items

test_income_tax_parser.py FFF

=================================== FAILURES ===================================
_____________________________ test_clean_pan_no_crash _____________________________

s = None

    @given(st.text() | st.none())
    def test_clean_pan_no_crash(s):
        try:
>           result = clean_pan(s)
                     ^^^^^^^^^^^^

test_income_tax_parser.py:8:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -

pan = None

    def clean_pan(pan):
        """
        Removes spaces from a PAN and upper-cases it.
        Assumes pan is a non-empty string.
        """
>       return pan.strip().replace(' ', '').upper()
               ^^^^^^^^^
E       AttributeError: 'NoneType' object has no attribute 'strip'

income_tax_parser.py:6: AttributeError

During handling of the above exception, another exception occurred:

    @given(st.text() | st.none())
>   def test_clean_pan_no_crash(s):
                ^^^

test_income_tax_parser.py:6:
- - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - - -
```

```
s = None

    @given(st.text() | st.none())
    def test_clean_pan_no_crash(s):
        try:
            result = clean_pan(s)
            assert result is None or isinstance(result, str)
        except Exception as e:
>           raise AssertionError(f"clean_pan crashed on {s!r}: {type(e).__name__}: {e}")
E           AssertionError: clean_pan crashed on None: AttributeError: 'NoneType' object has no attribute 'strip'
E           Failing test case: test_clean_pan_no_crash(
E               s=None,
E           )

test_income_tax_parser.py:11: AssertionError
```

Summary of the test cases ->

```
=========================== short test summary info ============================
FAILED test_income_tax_parser.py::test_clean_pan_no_crash - AssertionError: clean_pan crashed on None: AttributeError: 'NoneType' object has no attribute 'strip'
FAILED test_income_tax_parser.py::test_parse_amount_no_crash - ExceptionGroup: Hypothesis found 2 distinct failures. (2 sub-exceptions)
FAILED test_income_tax_parser.py::test_parse_tax_slab_no_crash - ExceptionGroup: Hypothesis found 3 distinct failures. (3 sub-exceptions)
============================== 3 failed in 0.16s ===============================
```

Code Run after the Fix ->

```
(jupyter-env) ➜  Lab-7 git:(main) ✗ python3 income_tax_parser.py
==== Running clean_pan ====
Enter a PAN (e.g. abcde 1234f): 1234f
Cleaned PAN: 1234F

==== Running parse_amount ====
Enter an amount (e.g. Rs 12,50,000): 12500
Amount in rupees: 12500

==== Running parse_tax_slab ====
Enter a tax slab as LOW-HIGH:RATE (e.g. 250000-500000:5): 1000 - 2000:4
Tax slab (low, high, rate): (1000, 2000, 4)
(jupyter-env) ➜  Lab-7 git:(main) ✗
```

Test Cases after the fixes ->

```
(jupyter-env) ➜  Lab-7 git:(main) ✗ pytest test_income_tax_parser.py
============================= test session starts ==============================
platform linux -- Python 3.14.7, pytest-9.2.0, pluggy-1.7.0
rootdir: /home/hecker/Documents/SE/Lab-7
plugins: platformdirs-4.12.4, anyio-4.15.1, hypothesis-6.170.15
collected 3 items

test_income_tax_parser.py ...

============================== 3 passed in 0.19s ===============================
```