Experiment: 8 Develop a program to create reverse shell using Tcp socket

Date: 17/09/26

AIM:

To develop a Tcp socket based client-server program that establishes a connection btw the client & server enables message communication.

PROCEDURE:

1. Verify Python Installation
2. Create a python file as server.py & client.py
3. Write the python program in server.py & client.py
4. Start the Tcp server and bind it to the specified Ip
5. Make the client connect to the server using the same Ip address & post
6. Send the message to the server and recieve the server response using recvc).
7. Display the recieved response on the client.

RESULT:

Thus, the Tcp socket client-server communication program was successfully implemented in python.

```
PS D:\server.py> python client.py
Connected to server
Enter message: Hello Server
Server: Message received
Enter message: Hello
Server: Message received
Enter message: TCP
Server: Message received
Enter message: Python Networking
Server: Message received
Enter message:
```

```
PS D:\server.py> python server.py
Waiting for connection...
Connected from: ('127.0.0.1', 50275)
Client: Hello Server
Client: Hello
Client: TCP
Client: Python Networking
```

client.py

```python
import socket
SERVER_IP = "127.0.0.1"
PORT = 5000
client = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
client.connect((SERVER_IP, PORT))
print("Connected to server")
while True:
    message = input("Enter message: ")
    if message.lower() == "exit":
        break
    client.send(message.encode())
    response = client.recv(1024).decode()
    print("Server:", response)
client.close()
```

server.py

```python
import socket
HOST = "0.0.0.0"
PORT = 5000
server = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
server.bind((HOST, PORT))
server.listen(1)
print("Waiting for connection...")
conn, addr = server.accept()
print("Connected from:", addr)
while True:
    message = conn.recv(1024).decode()
    if not message:
        break
    print("Client:", message)
    reply = "Message received"
    conn.send(reply.encode())
conn.close()
server.close()
```