

Table of Contents

SuperNet.Netcode.Compress

CompressorDeflate

CompressorLZF

ICompressor

SuperNet.Netcode.Crypto

CryptoAES

CryptoECDH

CryptoRandom

CryptoRSA

Curve25519

ICryptoAuthenticator

ICryptoEncryptor

ICryptoExchanger

ICryptoRandom

SuperNet.Netcode.Transport

ConnectionRequest

DisconnectReason

Host

HostConfig

HostEvents

HostStatistics

HostTimespan

HostTimestamp

IHostListener

IMessage

IMessageListener

IPeerListener

MessageEvents

MessageReceived

MessageSent

Peer

PeerConfig

PeerEvents

- PeerStatistics
- SuperNet.Netcode.Util
 - Allocator
 - ArrayPool<T>
 - CRC32
 - IPComparer
 - IPResolver
 - IWritable
 - ObjectPool<T>
 - Reader
 - Serializer
 - Writer
- SuperNet.Unity.Components
 - INetworkAuthoritative
 - INetworkRegisterable
 - INetworkRollbackable
 - NetworkAnimation
 - NetworkAnimator
 - NetworkAuthority
 - NetworkPrefab
 - NetworkRegistrar
 - NetworkSpawner
 - NetworkSyncModeMethod
 - NetworkSyncModeVector2
 - NetworkSyncModeVector3
 - NetworkTransform
- SuperNet.Unity.Core
 - NetworkComponent
 - NetworkHost
 - NetworkIdentity
 - NetworkIdentityExtensions
 - NetworkManager
- SuperNet.Unity.Editor
 - NetworkAuthorityEditor
 - NetworkHostEditor
 - NetworkHostEditor.BandwithUnit
 - NetworkIdentityDrawer

NetworkManagerEditor
NetworkPrefabEditor
NetworkSpawnerEditor

Namespace SuperNet.Netcode.Compress

Classes

[CompressorDeflate](#)

Compression based on the DEFLATE algorithm.

[CompressorLZF](#)

Compression based on the LZF algorithm.

Interfaces

[ICompressor](#)

Defines methods for compressing and decompressing network packets.

Class CompressorDeflate

Compression based on the DEFLATE algorithm.

Inheritance

System.Object
CompressorDeflate

Implements

[ICompressor](#)
IDisposable

Namespace: [SuperNet.Netcode.Compress](#)
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class CompressorDeflate : ICompressor, IDisposable
```

Constructors

CompressorDeflate(Allocator)

Create a new DEFLATE compressor.

Declaration

```
public CompressorDeflate(Allocator allocator)
```

Parameters

TYPE	NAME	DESCRIPTION
Allocator	allocator	Allocator to use for resizing buffers.

Methods

Compress(ArraySegment<Byte>, Byte[], Int32)

Compress data.

Declaration

```
public int Compress(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to compress.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Decompress(ArraySegment<Byte>, ref Byte[], Int32)

Decompress data and resize output if needed.

Declaration

```
public int Decompress(ArraySegment<byte> input, ref byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to decompress.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Dispose()

Instantly dispose of all resources.

Declaration

```
public void Dispose()
```

MaxCompressedLength(Int32)

Compute the maximum compressed length before compressing.

Declaration

```
public int MaxCompressedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the uncompressed input.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible compressed length.

Implements

[ICompressor](#)

IDisposable

Class CompressorLZF

Compression based on the LZF algorithm.

Inheritance

System.Object
CompressorLZF

Implements

[ICompressor](#)
IDisposable

Namespace: [SuperNet.Netcode.Compress](#)
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class CompressorLZF : ICompressor, IDisposable
```

Constructors

CompressorLZF(Allocator)

Create a new LZF compressor.

Declaration

```
public CompressorLZF(Allocator allocator)
```

Parameters

TYPE	NAME	DESCRIPTION
Allocator	allocator	Allocator to use for resizing buffers.

Methods

Compress(ArraySegment<Byte>, Byte[], Int32)

Compress data.

Declaration

```
public int Compress(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to compress.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Decompress(ArraySegment<Byte>, ref Byte[], Int32)

Decompress data and resize output if needed.

Declaration

```
public int Decompress(ArraySegment<byte> input, ref byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to decompress.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Dispose()

Instantly dispose of all resources.

Declaration

```
public void Dispose()
```

MaxCompressedLength(Int32)

Compute the maximum compressed length before compressing.

Declaration

```
public int MaxCompressedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the uncompressed input.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible compressed length.

Implements

[ICompressor](#)

IDisposable

Interface ICompressor

Defines methods for compressing and decompressing network packets.

Namespace: [SuperNet.Netcode.Compress](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface ICompressor : IDisposable
```

Methods

Compress(ArraySegment<Byte>, Byte[], Int32)

Compress data.

Declaration

```
int Compress(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to compress.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Decompress(ArraySegment<Byte>, ref Byte[], Int32)

Decompress data and resize output if needed.

Declaration

```
int Decompress(ArraySegment<byte> input, ref byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to decompress.
System.Byte[]	output	Output buffer to write to.

TYPE	NAME	DESCRIPTION
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

MaxCompressedLength(Int32)

Compute the maximum compressed length before compressing.

Declaration

```
int MaxCompressedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the uncompressed input.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible compressed length.

Namespace SuperNet.Netcode.Crypto

Classes

[CryptoAES](#)

Encryptor based on 256-bit Advanced Encryption Standard (AES).

[CryptoECDH](#)

Implements Elliptic Curve Diffie Hellman key exchange.

[CryptoRandom](#)

Cryptographically secure random number generator.

[CryptoRSA](#)

Authenticator based on 2048-bit RSA (Rivest–Shamir–Adleman).

[Curve25519](#)

Elliptic Curve methods used for Diffie Hellman key exchange.

Interfaces

[ICryptoAuthenticator](#)

Defines methods used for authenticating secure hosts.

[ICryptoEncryptor](#)

Defines methods for encrypting and decrypting network packets.

[ICryptoExchanger](#)

Defines methods used for a key exchange that is able to derive a shared encryptor.

[ICryptoRandom](#)

Defines methods for generating random data.

Class CryptoAES

Encryptor based on 256-bit Advanced Encryption Standard (AES).

Inheritance

System.Object
CryptoAES

Implements

ICryptoEncryptor
IDisposable

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class CryptoAES : ICryptoEncryptor, IDisposable
```

Constructors

CryptoAES(Byte[], Allocator)

Create a new AES encryptor with the provided key.

Declaration

```
public CryptoAES(byte[] key, Allocator allocator)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	key	Encryption key to use.
Allocator	allocator	Allocator to use for allocating keys.

Methods

Decrypt(ArraySegment<Byte>, Byte[], Int32)

Decrypt data.

Declaration

```
public int Decrypt(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to decrypt.
System.Byte[]	output	Output buffer to write to.

TYPE	NAME	DESCRIPTION
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Dispose()

Instantly dispose of all resources.

Declaration

```
public void Dispose()
```

Encrypt(ArraySegment<Byte>, Byte[], Int32)

Encrypt data.

Declaration

```
public int Encrypt(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to encrypt.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

MaxDecryptedLength(Int32)

Compute the maximum decrypted length before decrypting.

Declaration

```
public int MaxDecryptedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the input that is about to be decrypted.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible decrypted length.

MaxEncryptedLength(Int32)

Compute the maximum encrypted length before encrypting.

Declaration

```
public int MaxEncryptedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the input that is about to be encrypted.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible encrypted length.

Implements

- ICryptoEncryptor
- IDisposable

Class CryptoECDH

Implements Elliptic Curve Diffie Hellman key exchange.

Inheritance

System.Object
CryptoECDH

Implements

[ICryptoExchanger](#)
IDisposable

Namespace: [SuperNet.Netcode.Crypto](#)
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class CryptoECDH : ICryptoExchanger, IDisposable
```

Constructors

CryptoECDH(ICryptoRandom, Allocator)

Create a new ECDH key pair for key exchange.

Declaration

```
public CryptoECDH(ICryptoRandom random, Allocator allocator)
```

Parameters

TYPE	NAME	DESCRIPTION
ICryptoRandom	random	Random number generator to use for generating keys.
Allocator	allocator	Allocator to use for allocating keys.

Fields

KeyLength

Size of exchange key in bytes. For ECDH this is 32.

Declaration

```
public const int KeyLength = 32
```

Field Value

TYPE	DESCRIPTION
System.Int32	

Methods

DeriveEncryptor(ArraySegment<Byte>)

Generate a shared encryptor.

Declaration

```
public ICryptoEncryptor DeriveEncryptor(ArraySegment<byte> remoteKey)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	remoteKey	Received remote exchange key.

Returns

TYPE	DESCRIPTION
ICryptoEncryptor	Shared encryptor that is guaranteed to be the same on both peers.

Dispose()

Returns key pair back to the allocator.

Declaration

```
public void Dispose()
```

ExportKey(ArraySegment<Byte>)

Copy exchange key to the output.

Declaration

```
public void ExportKey(ArraySegment<byte> output)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	output	Output to write to.

Explicit Interface Implementations

ICryptoExchanger.KeyLength

Size of exchange key in bytes. For ECDH this is 32.

Declaration

```
int ICryptoExchanger.KeyLength { get; }
```

Returns

TYPE	DESCRIPTION
System.Int32	

Implements

[ICryptoExchanger](#)

IDisposable

Class CryptoRandom

Cryptographically secure random number generator.

Inheritance

System.Object
CryptoRandom

Implements

ICryptoRandom
IDisposable

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class CryptoRandom : ICryptoRandom, IDisposable
```

Constructors

CryptoRandom()

Create random number generator.

Declaration

```
public CryptoRandom()
```

Methods

Dispose()

Instantly dispose of all resources.

Declaration

```
public void Dispose()
```

GetBytes(Byte[], Int32, Int32)

Generate cryptographically secure random data.

This method is thread safe.

Declaration

```
public void GetBytes(byte[] output, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

TYPE	NAME	DESCRIPTION
System.Int32	count	Number of bytes to write.

Implements

[ICryptoRandom](#)

IDisposable

Class CryptoRSA

Authenticator based on 2048-bit RSA (Rivest–Shamir–Adleman).

Inheritance

System.Object
CryptoRSA

Implements

[ICryptoAuthenticator](#)
IDisposable

Namespace: [SuperNet.Netcode.Crypto](#)
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class CryptoRSA : ICryptoAuthenticator, IDisposable
```

Constructors

CryptoRSA(Allocator)

Create a new RSA authenticator.

Declaration

```
public CryptoRSA(Allocator allocator = null)
```

Parameters

TYPE	NAME	DESCRIPTION
Allocator	allocator	Allocator to use for keys or null for none.

Properties

SignatureLength

Number of bytes in the signature. For RSA this is 256.

Declaration

```
public int SignatureLength { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Methods

Dispose()

Instantly dispose of all resources.

Declaration

```
public void Dispose()
```

ExportPrivateKey()

Export all RSA parameters as a Base64 string.

Declaration

```
public string ExportPrivateKey()
```

Returns

TYPE	DESCRIPTION
System.String	Base64 encoded parameters.

ExportPublicKey()

Export RSA modulus as a Base64 string.

Declaration

```
public string ExportPublicKey()
```

Returns

TYPE	DESCRIPTION
System.String	Base64 encoded RSA modulus.

ImportPrivateKey(String)

Import previously exported private key.

Declaration

```
public void ImportPrivateKey(string privateKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	privateKey	Private key to import.

Sign(ArraySegment<Byte>, ArraySegment<Byte>)

Generate a signature of that can then be verified by the public key.

Declaration

```
public void Sign(ArraySegment<byte> data, ArraySegment<byte> output)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	data	Data to sign.

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	output	Output to write signature to.

Verify(ArraySegment<Byte>, ArraySegment<Byte>, String)

Verify that signature has been signed by someone with the private key.

Declaration

```
public bool Verify(ArraySegment<byte> data, ArraySegment<byte> signature, string remotePublicKey)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	data	Data that has been signed.
ArraySegment<System.Byte>	signature	Signature that has been generated.
System.String	remotePublicKey	Public key corresponding to the private key that signed the data.

Returns

TYPE	DESCRIPTION
System.Boolean	True if verified, false if not.

Implements

[ICryptoAuthenticator](#)

IDisposable

Class Curve25519

Elliptic Curve methods used for Diffie Hellman key exchange.

Inheritance

System.Object
Curve25519

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public static class Curve25519
```

Fields

KeySize

Key size in bytes.

Declaration

```
public const int KeySize = 32
```

Field Value

TYPE	DESCRIPTION
System.Int32	

Methods

ClampPrivateKey(Byte[])

Private key clamping.

Declaration

```
public static byte[] ClampPrivateKey(byte[] rawKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	rawKey	[in] Random 32 bytes

Returns

TYPE	DESCRIPTION
System.Byte[]	Clamped private key.

ClampPrivateKeyInline(Byte[])

Private key clamping (inline, for performance).

Declaration

```
public static void ClampPrivateKeyInline(byte[] key)
```


Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	key	[out] Random 32 bytes.

CreateRandomPrivateKey()

Create a random clamped private key.

Declaration

```
public static byte[] CreateRandomPrivateKey()
```

Returns

TYPE	DESCRIPTION
System.Byte[]	Random 32 bytes that are clamped to a suitable private key.

GetPublicKey(Byte[])

Generate the public key out of the clamped private key.

Declaration

```
public static byte[] GetPublicKey(byte[] privateKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	privateKey	[in] Private key (must be clamped).

Returns

TYPE	DESCRIPTION
System.Byte[]	Public key.

GetPublicKeyInline(Byte[], Byte[])

Generate the public key out of the clamped private key (inline, for performance).

Declaration

```
public static void GetPublicKeyInline(byte[] privateKey, byte[] publicKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	privateKey	[in] Private key (must be clamped).

TYPE	NAME	DESCRIPTION
System.Byte[]	publicKey	[out] Public key.

GetSharedSecret(Byte[], Byte[])

Key agreement.

Declaration

```
public static byte[] GetSharedSecret(byte[] privateKey, byte[] peerPublicKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	privateKey	[in] Your private key for key agreement.
System.Byte[]	peerPublicKey	[in] Peer's public key.

Returns

TYPE	DESCRIPTION
System.Byte[]	Shared secret (needs hashing before use).

GetSharedSecretInline(Byte[], Byte[], Byte[])

Key agreement.

Declaration

```
public static void GetSharedSecretInline(byte[] privateKey, byte[] peerPublicKey, byte[] sharedSecret)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	privateKey	[in] Your private key for key agreement.
System.Byte[]	peerPublicKey	[in] Peer's public key.
System.Byte[]	sharedSecret	[out] Shared secret (needs hashing before use).

GetSigningKey(Byte[])

Generate signing key out of the clamped private key.

Declaration

```
public static byte[] GetSigningKey(byte[] privateKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	privateKey	[in] Private key (must be clamped).

Returns

TYPE	DESCRIPTION
System.Byte[]	Signing key.

KeyGenInline(Byte[], Byte[], Byte[])

Generate key-pair (inline, for performance).

Declaration

```
public static void KeyGenInline(byte[] publicKey, byte[] signingKey, byte[] privateKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	publicKey	[out] Public key.
System.Byte[]	signingKey	[out] Signing key (ignored if NULL).
System.Byte[]	privateKey	[out] Private key.

Remarks

WARNING: if signingKey is not NULL, this function has data-dependent timing.

Interface ICryptoAuthenticator

Defines methods used for authenticating secure hosts.

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface ICryptoAuthenticator : IDisposable
```

Properties

SignatureLength

Number of bytes in the signature.

Declaration

```
int SignatureLength { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Methods

ExportPrivateKey()

Export the current private key to a human readable format.

Declaration

```
string ExportPrivateKey()
```

Returns

TYPE	DESCRIPTION
System.String	Human readable private key

ExportPublicKey()

Export the current public key to a human readable format.

Declaration

```
string ExportPublicKey()
```

Returns

TYPE	DESCRIPTION
System.String	Human readable public key.

ImportPrivateKey(String)

Import private key.

Declaration

```
void ImportPrivateKey(string privateKey)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	privateKey	Private key to import.

Sign(ArraySegment<Byte>, ArraySegment<Byte>)

Generate a signature that can be verified by the public key.

Declaration

```
void Sign(ArraySegment<byte> data, ArraySegment<byte> output)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	data	Data to sign.
ArraySegment<System.Byte>	output	Output to write signature to.

Verify(ArraySegment<Byte>, ArraySegment<Byte>, String)

Verify signature.

Declaration

```
bool Verify(ArraySegment<byte> data, ArraySegment<byte> signature, string remotePublicKey)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	data	Data that has been signed.
ArraySegment<System.Byte>	signature	Signature that has been generated.
System.String	remotePublicKey	Public key corresponding to the private key that signed the data.

Returns

TYPE	DESCRIPTION
System.Boolean	True if verified, false if not.

Interface ICryptoEncryptor

Defines methods for encrypting and decrypting network packets.

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface ICryptoEncryptor : IDisposable
```

Methods

Decrypt(ArraySegment<Byte>, Byte[], Int32)

Decrypt data.

Declaration

```
int Decrypt(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to decrypt.
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

Encrypt(ArraySegment<Byte>, Byte[], Int32)

Encrypt data.

Declaration

```
int Encrypt(ArraySegment<byte> input, byte[] output, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	input	Array segment to encrypt.
System.Byte[]	output	Output buffer to write to.

TYPE	NAME	DESCRIPTION
System.Int32	offset	Output offset to write to.

Returns

TYPE	DESCRIPTION
System.Int32	Total number of bytes written to the output.

MaxDecryptedLength(Int32)

Compute the maximum decrypted length before decrypting.

Declaration

```
int MaxDecryptedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the input that is about to be decrypted.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible decrypted length.

MaxEncryptedLength(Int32)

Compute the maximum encrypted length before encrypting.

Declaration

```
int MaxEncryptedLength(int inputLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	inputLength	Length of the input that is about to be encrypted.

Returns

TYPE	DESCRIPTION
System.Int32	Maximum possible encrypted length.

Interface ICryptoExchanger

Defines methods used for a key exchange that is able to derive a shared encryptor.

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface ICryptoExchanger : IDisposable
```

Properties

KeyLength

Size of exchange key in bytes.

Declaration

```
int KeyLength { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Methods

DeriveEncryptor(ArraySegment<Byte>)

Generate a shared encryptor.

Declaration

```
ICryptoEncryptor DeriveEncryptor(ArraySegment<byte> remoteKey)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	remoteKey	Received remote exchange key.

Returns

TYPE	DESCRIPTION
ICryptoEncryptor	Shared encryptor that is guaranteed to be the same on both peers.

ExportKey(ArraySegment<Byte>)

Copy exchange key to the output.

Declaration

```
void ExportKey(ArraySegment<byte> output)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	output	Output to write to.

Interface ICryptoRandom

Defines methods for generating random data.

Namespace: [SuperNet.Netcode.Crypto](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface ICryptoRandom : IDisposable
```

Methods

GetBytes(Byte[], Int32, Int32)

Generate cryptographically secure random data.

This method is thread safe.

Declaration

```
void GetBytes(byte[] output, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	output	Output buffer to write to.
System.Int32	offset	Output offset to write to.
System.Int32	count	Number of bytes to write.

Namespace SuperNet.Netcode.Transport

Classes

[ConnectionRequest](#)

A connection request received by an active host.

[Host](#)

Manages a network socket and all network communication between peers.

[HostConfig](#)

Holds configuration values for hosts.

[HostEvents](#)

Event based implementation of a host listener.

[HostStatistics](#)

Stores packet statistics for hosts.

[MessageEvents](#)

Event based implementation of a message listener.

[MessageReceived](#)

Extra information for a network message that has been received by a connected peer.

[MessageSent](#)

Network message that has been sent to a connected peer.

[Peer](#)

Manages an active network connection.

[PeerConfig](#)

Holds configuration values for peers.

[PeerEvents](#)

Event based implementation of a peer listener.

[PeerStatistics](#)

Stores packet statistics for peers.

Structs

[HostTimespan](#)

Stores a difference between two timestamps as a duration.

[HostTimestamp](#)

Stores a local timestamp of an event.

Interfaces

[IHostListener](#)

Implements a host listener.

[IMessage](#)

Implements a message that can be sent by the netcode to a connected peer.

[IMessageListener](#)

Implements a sent message listener.

[IPeerListener](#)

Implements a peer listener.

Enums

[DisconnectReason](#)

Reason provided when a connection ends.

Class ConnectionRequest

A connection request received by an active host.

Inheritance

System.Object

ConnectionRequest

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class ConnectionRequest : IDisposable
```

Fields

Host

The host that received this request.

Declaration

```
public readonly Host Host
```

Field Value

TYPE	DESCRIPTION
Host	

Remote

Remote address that the request was received from.

Declaration

```
public readonly IPEndPoint Remote
```

Field Value

TYPE	DESCRIPTION
IPEndPoint	

Properties

Accepted

True if the request has been accepted.

Declaration

```
public bool Accepted { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Authenticate

True if remote peer requires us to authenticate.

Declaration

```
public bool Authenticate { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Disposed

True if the underlying buffers for the request have been repurposed for something else.

Declaration

```
public bool Disposed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Encrypted

True if remote peer requires encryption.

Declaration

```
public bool Encrypted { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Peer

Peer accepted or null if none.

Declaration

```
public Peer Peer { get; }
```

Property Value

TYPE	DESCRIPTION
Peer	

Rejected

True if the request has been rejected.

Declaration

```
public bool Rejected { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

Accept(PeerConfig, IPeerListener)

Accept the request, create a new peer and establish a connection.

Declaration

```
public Peer Accept(PeerConfig config = null, IPeerListener listener = null)
```

Parameters

TYPE	NAME	DESCRIPTION
PeerConfig	config	Peer configuration values. If null, default is used.
IPeerListener	listener	Peer listener. If null, event based listener is created.

Returns

TYPE	DESCRIPTION
Peer	The created peer.

Dispose()

Used internally by the netcode to invalidate the request, making it unable to be accepted.

This is called when the underlying buffers have been repurposed for something else.

Declaration

```
public void Dispose()
```

Reject(IWritable)

Reject the request by sending a reject message.

Declaration

```
public void Reject(IWritable message = null)
```

Parameters

TYPE	NAME	DESCRIPTION
IWritable	message	Message to reject with.

Enum DisconnectReason

Reason provided when a connection ends.

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public enum DisconnectReason : byte
```

Fields

NAME	DESCRIPTION
BadSignature	Remote host failed to authenticate.
Disconnected	Graceful disconnect after requested.
Disposed	Peer or host has been disposed.
Exception	An exception has caused the peer to be disconnected. Always includes the actual exception.
Rejected	Connection request has been rejected by the remote peer.
Terminated	Graceful disconnect after the remote peer has requested it.
Timeout	Remote host has stopped responding to messages.

Class Host

Manages a network socket and all network communication between peers.

Inheritance

System.Object

Host

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class Host : IDisposable
```

Constructors

Host(HostConfig, IHostListener)

Create a new UDP socket and start listening for packets.

Declaration

```
public Host(HostConfig config, IHostListener listener)
```

Parameters

TYPE	NAME	DESCRIPTION
HostConfig	config	Host configuration values. If null, defaults are used.
IHostListener	listener	Host listener to use. If null, event based listener is created.

Fields

Allocator

Allocator used to manage internal buffers.

Declaration

```
public readonly Allocator Allocator
```

Field Value

TYPE	DESCRIPTION
Allocator	

Config

Configuration values for this host.

Declaration

```
public readonly HostConfig Config
```

Field Value

TYPE	DESCRIPTION
HostConfig	

Frequency

Tick frequency of the host in ticks per second.

Declaration

```
public const long Frequency = 1000L
```

Field Value

TYPE	DESCRIPTION
System.Int64	

Statistics

Packet statistics.

Declaration

```
public readonly HostStatistics Statistics
```

Field Value

TYPE	DESCRIPTION
HostStatistics	

Properties

BindAddress

Address this host is listening on.

Declaration

```
public IPEndPoint BindAddress { get; }
```

Property Value

TYPE	DESCRIPTION
IPEndPoint	

Disposed

True if host is disposed and cannot be used anymore.

Declaration

```
public bool Disposed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Listener

Listener used by this host.

Declaration

```
public IHostListener Listener { get; }
```

Property Value

TYPE	DESCRIPTION
IHostListener	

Now

Create a new timestamp at the current host time.

Declaration

```
public static HostTimestamp Now { get; }
```

Property Value

TYPE	DESCRIPTION
HostTimestamp	

SupportsIPv6

Platform dependant IPv6 support check. True if IPv6 is supported, false if not.

Declaration

```
public static bool SupportsIPv6 { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Ticks

Number of milliseconds that have elapsed since the host was created.

Declaration

```
public static long Ticks { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

Methods

Accept(ConnectionRequest, PeerConfig, IPeerListener)

Accept a connection request and return a connected local peer.

Declaration

```
public Peer Accept(ConnectionRequest request, PeerConfig config, IPeerListener listener)
```

Parameters

TYPE	NAME	DESCRIPTION
ConnectionRequest	request	Connection request to accept.
PeerConfig	config	Peer configuration values. If null, default is used.
IPeerListener	listener	Peer listener to use. If null, event based listener is created.

Returns

TYPE	DESCRIPTION
Peer	Connected local peer.

Connect(IPEndPoint, PeerConfig, IPeerListener, IWritable)

Create a local peer and start connecting to an active remote host.

Declaration

```
public Peer Connect(IPEndPoint remote, PeerConfig config, IPeerListener listener, IWritable message = null)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address to connect to.
PeerConfig	config	Peer configuration values. If null, default is used.
IPeerListener	listener	Peer listener to use. If null, PeerEvents is used.
IWritable	message	Connect message to use.

Returns

TYPE	DESCRIPTION
Peer	Local peer that attempts to connect.

Dispose()

Instantly dispose all resources held by this host and connected peers.

Declaration

```
public void Dispose()
```

FindPeer(IPEndPoint)

Attempt to find an existing peer based on remote address.

Declaration

```
public Peer FindPeer(IPEndPoint remote)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address of the peer.

Returns

TYPE	DESCRIPTION
Peer	An existing peer or null if not found.

IsLocal(IPEndPoint)

Check if address is connected locally.

Declaration

```
public static bool IsLocal(IPEndPoint remote)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Address to check.

Returns

TYPE	DESCRIPTION
System.Boolean	True if address is local, false if not.

IsPortUsed(Int32)

Check if port is used by any active host.

Declaration

```
public static bool IsPortUsed(int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Port to check.

Returns

TYPE	DESCRIPTION
System.Boolean	True if port is used, false if not.

Reject(ConnectionRequest, IWritable)

Reject a connection request.

Declaration

```
public void Reject(ConnectionRequest request, IWritable message = null)
```

Parameters

TYPE	NAME	DESCRIPTION
ConnectionRequest	request	Connection request to reject.
IWritable	message	Rejection message.

SendAll(IMessage, Peer[])

Send a message to all connected peers.

Declaration

```
public void SendAll(IMessage message, params Peer[] exclude)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
Peer[]	exclude	Peers to exclude.

SendBroadcast(Int32, IWritable)

Send an unconnected message to all machines on the local network.

Declaration

```
public void SendBroadcast(int port, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Network port to send to.
IWritable	message	Message to send.

SendBroadcastAsync(Int32, IWritable)

Send an unconnected message to all machines on the local network.

Declaration

```
public Task<int> SendBroadcastAsync(int port, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Network port to send to.
IWritable	message	Message to send.

Returns

TYPE	DESCRIPTION
Task<System.Int32>	Task that returns number of bytes sent.

SendUnconnected(IPEndPoint, IWritable)

Send an unconnected message to a remote host.

Declaration

```
public void SendUnconnected(IPEndPoint remote, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address to send to.

TYPE	NAME	DESCRIPTION
IWritable	message	Message to send.

SendUnconnectedAsync(IPEndPoint, IWritable)

Send an unconnected message to a remote host.

Declaration

```
public Task<int> SendUnconnectedAsync(IPEndPoint remote, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address to send to.
IWritable	message	Message to send.

Returns

TYPE	DESCRIPTION
Task<System.Int32>	Task that returns number of bytes sent.

SetListener(IHostListener)

Replace the current listener with a new one.

Declaration

```
public IHostListener SetListener(IHostListener listener)
```

Parameters

TYPE	NAME	DESCRIPTION
IHostListener	listener	Listener to replace with.

Returns

TYPE	DESCRIPTION
IHostListener	The old HostListener.

Shutdown()

Gracefully disconnect all peers and perform a shutdown.

Declaration


```
public void Shutdown()
```

ShutdownAsync()

Gracefully disconnect all peers and perform a shutdown.

Declaration

```
public Task ShutdownAsync()
```

Returns

TYPE	DESCRIPTION
Task	Task that completes when shutdown is completed.

Class HostConfig

Holds configuration values for hosts.

Inheritance

System.Object

HostConfig

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class HostConfig
```

Fields

AllocatorCount

Number of pooled arrays.

Declaration

```
public int AllocatorCount
```

Field Value

TYPE	DESCRIPTION
System.Int32	

AllocatorExpandLength

Number of bytes to add when a non-pooled array becomes too small

Declaration

```
public int AllocatorExpandLength
```

Field Value

TYPE	DESCRIPTION
System.Int32	

AllocatorMaxLength

Maximum length of allocated arrays.

Declaration

```
public int AllocatorMaxLength
```

Field Value

TYPE	DESCRIPTION
System.Int32	

AllocatorPooledExpandLength

Number of bytes to add when a pooled array becomes too small.

Declaration

```
public int AllocatorPooledExpandLength
```

Field Value

TYPE	DESCRIPTION
System.Int32	

AllocatorPooledLength

Maximum length an array can still be to be pooled.

Declaration

```
public int AllocatorPooledLength
```

Field Value

TYPE	DESCRIPTION
System.Int32	

BindAddress

Bind socket to a specific address or null for any.

Declaration

```
public IPAddress BindAddress
```

Field Value

TYPE	DESCRIPTION
IPAddress	

Broadcast

Set `Socket.EnableBroadcast` when creating a socket.

If true, allow broadcast messages to be sent.

Declaration

```
public bool Broadcast
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Compression

Enable compression of outgoing network packets.

If false and a compressed packet is received, it is still decompressed.

Declaration

```
public bool Compression
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

CRC32

Enable CRC32 error checking to make sure packets don't get corrupted in transit.

If false and a CRC32 code is received, it is ignored.

Declaration

```
public bool CRC32
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

DualMode

Set `Socket.DualMode` when creating a socket.

If true, accept both IPv6 and IPv4 connections.

Declaration

```
public bool DualMode
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Encryption

Enable end to end encryption between peers.

A connection request without encryption can still be accepted.

Declaration

```
public bool Encryption
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Port

UDP port to listen on or zero for random.

Must be between 0 and 65536.

Declaration

```
public int Port
```

Field Value

TYPE	DESCRIPTION
System.Int32	

PrivateKey

Private key to use when authenticating this host.

If null, this host cannot be authenticated.

Declaration

```
public string PrivateKey
```

Field Value

TYPE	DESCRIPTION
System.String	

ReceiveBufferSize

Set `Socket.ReceiveBufferSize` when creating a socket.

Maximum socket receive buffer in bytes.

Declaration

```
public int ReceiveBufferSize
```

Field Value

TYPE	DESCRIPTION
System.Int32	

ReceiveCount

Maximum number of possible concurrent read operations.

Declaration

```
public int ReceiveCount
```

Field Value

TYPE	DESCRIPTION
System.Int32	

ReceiveMTU

Maximum number of bytes in a single received UDP packet.

This is used to allocate appropriately sized receive buffers.

Declaration

```
public int ReceiveMTU
```

Field Value

TYPE	DESCRIPTION
System.Int32	

SendBufferSize

Set `Socket.SendBufferSize` when creating a socket.

Maximum socket send buffer in bytes.

Declaration

```
public int SendBufferSize
```

Field Value

TYPE	DESCRIPTION
System.Int32	

SimulatorEnabled

Enable latency and packet loss simulation.

Declaration

```
public bool SimulatorEnabled
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

SimulatorIncomingJitter

Randomly added delay in milliseconds when receiving packets.

Making this non-zero can scramble the order of packets.

Declaration

```
public float SimulatorIncomingJitter
```

Field Value

TYPE	DESCRIPTION
System.Single	

SimulatorIncomingLatency

Simulated delay in milliseconds when receiving packets.

Declaration

```
public float SimulatorIncomingLatency
```

Field Value

TYPE	DESCRIPTION
System.Single	

SimulatorIncomingLoss

Simulated packet loss % when receiving. Must be between 0 and 1.

Value of 0 means no packet loss, value of 1 means all packets are dropped.

Declaration

```
public float SimulatorIncomingLoss
```

Field Value

TYPE	DESCRIPTION
System.Single	

SimulatorOutgoingJitter

Randomly added delay in milliseconds when sending packets.

Making this non-zero can scramble the order of packets.

Declaration

```
public float SimulatorOutgoingJitter
```

Field Value

TYPE	DESCRIPTION
System.Single	

SimulatorOutgoingLatency

Simulated delay in milliseconds when sending packets.

Declaration

```
public float SimulatorOutgoingLatency
```

Field Value

TYPE	DESCRIPTION
System.Single	

SimulatorOutgoingLoss

Simulated packet loss % when sending. Must be between 0 and 1.

Value of 0 means no packet loss, value of 1 means all packets are dropped.

Declaration

```
public float SimulatorOutgoingLoss
```

Field Value

TYPE	DESCRIPTION
System.Single	

TTL

Set `Socket.Ttl` when creating a socket.

Maximum number of hops packets can take before being dropped.

Declaration

```
public short TTL
```

Field Value

TYPE	DESCRIPTION
System.Int16	

Class HostEvents

Event based implementation of a host listener.

Inheritance

System.Object
HostEvents

Implements

IHostListener

Namespace: SuperNet.Netcode.Transport

Assembly: cs.temp.dll.dll

Syntax

```
public class HostEvents : IHostListener
```

Events

OnException

Called when an exception occurs internally. Can be ignored.

Declaration

```
public event HostEvents.OnExceptionHandler OnException
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnExceptionHandler	

OnReceiveBroadcast

Called for every broadcast message the host receives.

Declaration

```
public event HostEvents.OnReceiveBroadcastHandler OnReceiveBroadcast
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnReceiveBroadcastHandler	

OnReceiveRequest

Called when a connection request is received.

Declaration

```
public event HostEvents.OnReceiveRequestHandler OnReceiveRequest
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnReceiveRequestHandler	

OnReceiveSocket

Called for every raw packet the host receives.

Declaration

```
public event HostEvents.OnReceiveSocketHandler OnReceiveSocket
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnReceiveSocketHandler	

OnReceiveUnconnected

Called for every unconnected message the host receives.

Declaration

```
public event HostEvents.OnReceiveUnconnectedHandler OnReceiveUnconnected
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnReceiveUnconnectedHandler	

OnShutdown

Called when the host shuts down.

Declaration

```
public event HostEvents.OnShutdownHandler OnShutdown
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.HostEvents.OnShutdownHandler	

Explicit Interface Implementations

IHostListener.OnHostException(IPEndPoint, Exception)

Declaration

```
void IHostListener.OnHostException(IPEndPoint remote, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Exception	exception	

IHostListener.OnHostReceiveBroadcast(IPEndPoint, Reader)

Declaration

```
void IHostListener.OnHostReceiveBroadcast(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Reader	message	

IHostListener.OnHostReceiveRequest(ConnectionRequest, Reader)

Declaration

```
void IHostListener.OnHostReceiveRequest(ConnectionRequest request, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
ConnectionRequest	request	
Reader	message	

IHostListener.OnHostReceiveSocket(IPEndPoint, Byte[], Int32)

Declaration

```
void IHostListener.OnHostReceiveSocket(IPEndPoint remote, byte[] buffer, int length)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
System.Byte[]	buffer	
System.Int32	length	

IHostListener.OnHostReceiveUnconnected(IPEndPoint, Reader)

Declaration

```
void IHostListener.OnHostReceiveUnconnected(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Reader	message	

IHostListener.OnHostShutdown()

Declaration

```
void IHostListener.OnHostShutdown()
```

Implements

[IHostListener](#)

Class HostStatistics

Stores packet statistics for hosts.

Inheritance

System.Object

HostStatistics

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class HostStatistics
```

Properties

SocketReceiveBytes

Total number of bytes received.

Declaration

```
public long SocketReceiveBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

SocketReceiveCount

Total number of packets received.

Declaration

```
public long SocketReceiveCount { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

SocketReceiveTicks

Host ticks at the moment of the last socket receive operation.

Declaration

```
public long SocketReceiveTicks { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

SocketSendBytes

Total number of bytes sent.

Declaration

```
public long SocketSendBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

SocketSendCount

Total number of packets sent.

Declaration

```
public long SocketSendCount { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

SocketSendTicks

Host ticks at the moment of the last socket send operation.

Declaration

```
public long SocketSendTicks { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

Methods

Reset()

Reset all statistics back to zero.

Declaration

```
public void Reset()
```

Struct HostTimespan

Stores a difference between two timestamps as a duration.

Implements

Comparable

Comparable<HostTimespan>

IComparable<HostTimespan>

IFormattable

Namespace: SuperNet.Netcode.Transport

Assembly: cs.temp.dll.dll

Syntax

```
public struct HostTimespan : Comparable, Comparable<HostTimespan>, IComparable<HostTimespan>, IFormattable
```

Fields

Zero

Timespan representing zero time.

Declaration

```
public static readonly HostTimespan Zero
```

Field Value

TYPE	DESCRIPTION
HostTimespan	

Properties

Days

Duration in number of days.

Declaration

```
public double Days { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

Hours

Duration in number of hours.

Declaration

```
public double Hours { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

Milliseconds

Duration in number of milliseconds.

Declaration

```
public double Milliseconds { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

Minutes

Duration in number of minutes.

Declaration

```
public double Minutes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

Seconds

Duration in number of seconds.

Declaration

```
public double Seconds { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

Methods

Abs(HostTimespan)

Returns the absolute value of a timespan.

Declaration

```
public static HostTimespan Abs(HostTimespan timespan)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	timespan	Timespan to use.

Returns

TYPE	DESCRIPTION
HostTimespan	The absolute value.

Clamp([HostTimespan](#), [HostTimespan](#), [HostTimespan](#))

Returns a clamped value of a timespan.

Declaration

```
public static HostTimespan Clamp(HostTimespan value, HostTimespan min, HostTimespan max)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	value	Value to clamp.
HostTimespan	min	Lower bound.
HostTimespan	max	Upper bound.

Returns

TYPE	DESCRIPTION
HostTimespan	Clamped value.

CompareTo([HostTimespan](#))

Declaration

```
public int CompareTo(HostTimespan other)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	other	

Returns

TYPE	DESCRIPTION
System.Int32	

CompareTo(Object)

Declaration

```
public int CompareTo(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Int32	

Equals(HostTimespan)

Declaration

```
public bool Equals(HostTimespan other)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	other	

Returns

TYPE	DESCRIPTION
System.Boolean	

Equals(Object)

Declaration

```
public override bool Equals(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

System.ValueType.Equals(System.Object)

FromDays(Double)

Create a timespan from days.

Declaration

```
public static HostTimespan FromDays(double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Double	value	Number of days.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromHours(Double)

Create a timespan from hours.

Declaration

```
public static HostTimespan FromHours(double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Double	value	Number of hours.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromMilliseconds(Double)

Create a timespan from milliseconds.

Declaration

```
public static HostTimespan FromMilliseconds(double value)
```

Parameters

TYPE	NAME	DESCRIPTION

TYPE	NAME	DESCRIPTION
System.Double	value	Number of milliseconds.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromMinutes(Double)

Create a timespan from minutes.

Declaration

```
public static HostTimespan FromMinutes(double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Double	value	Number of minutes.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromSeconds(Double)

Create a timespan from seconds.

Declaration

```
public static HostTimespan FromSeconds(double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Double	value	Number of seconds.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromStopwatchTicks(Int64)

Create a timespan with the provided ticks at stopwatch frequency.

Declaration

```
public static HostTimespan FromStopwatchTicks(long ticks)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	ticks	Raw ticks.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromTicks(Int64, Int64)

Create a timespan from raw ticks with provided frequency.

Declaration

```
public static HostTimespan FromTicks(long ticks, long frequency)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	ticks	Raw ticks.
System.Int64	frequency	Ticks per second.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

FromTimeSpan(TimeSpan)

Create a timespan from the TimeSpan object.

Declaration

```
public static HostTimespan FromTimeSpan(TimeSpan value)
```

Parameters

TYPE	NAME	DESCRIPTION

TYPE	NAME	DESCRIPTION
TimeSpan	value	The TimeSpan object.

Returns

TYPE	DESCRIPTION
HostTimespan	A new timespan.

GetHashCode()

Declaration

```
public override int GetHashCode()
```

Returns

TYPE	DESCRIPTION
System.Int32	

Overrides

System.ValueType.GetHashCode()

GetStopwatchTicks()

Get raw ticks with stopwatch frequency.

Declaration

```
public long GetStopwatchTicks()
```

Returns

TYPE	DESCRIPTION
System.Int64	Raw stopwatch ticks.

GetTicks(Int64)

Get raw ticks with provided frequency.

Declaration

```
public long GetTicks(long frequency)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	frequency	Ticks per second.

Returns

TYPE	DESCRIPTION
System.Int64	Raw ticks.

Max(HostTimespan, HostTimespan)

Returns the larger of the two timespans.

Declaration

```
public static HostTimespan Max(HostTimespan a, HostTimespan b)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	a	First value.
HostTimespan	b	Second value.

Returns

TYPE	DESCRIPTION
HostTimespan	The larger of the two values.

Min(HostTimespan, HostTimespan)

Returns the smaller of the two timespans.

Declaration

```
public static HostTimespan Min(HostTimespan a, HostTimespan b)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	a	First value.
HostTimespan	b	Second value.

Returns

TYPE	DESCRIPTION
HostTimespan	The smaller of the two values.

ToString()

Declaration

```
public override string ToString()
```

Returns

TYPE	DESCRIPTION
System.String	

Overrides

System.ValueType.ToString()

ToString(String, IFormatProvider)

Declaration

```
public string ToString(string format, IFormatProvider formatProvider)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	format	
IFormatProvider	formatProvider	

Returns

TYPE	DESCRIPTION
System.String	

(TimeSpan)

Get the TimeSpan equivalent.

Declaration

```
public TimeSpan ToTimeSpan()
```

Returns

TYPE	DESCRIPTION
TimeSpan	

Operators

Addition(HostTimespan, HostTimespan)

Declaration

```
public static HostTimespan operator +(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	

TYPE	NAME	DESCRIPTION
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
HostTimespan	

Division([HostTimespan](#), [HostTimespan](#))

Declaration

```
public static double operator /(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Double	

Equality([HostTimespan](#), [HostTimespan](#))

Declaration

```
public static bool operator ==(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

GreaterThan([HostTimespan](#), [HostTimespan](#))

Declaration

```
public static bool operator >(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

GreaterThanOrEqual(HostTimespan, HostTimespan)

Declaration

```
public static bool operator >=(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Inequality(HostTimespan, HostTimespan)

Declaration

```
public static bool operator !=(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

LessThan(HostTimespan, HostTimespan)

Declaration

```
public static bool operator <(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

LessThanOrEqual(HostTimespan, HostTimespan)

Declaration

```
public static bool operator <=(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Subtraction(HostTimespan, HostTimespan)

Declaration

```
public static HostTimespan operator -(HostTimespan lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
HostTimespan	

UnaryNegation(HostTimespan)

Declaration

```
public static HostTimespan operator -(HostTimespan time)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	time	

Returns

TYPE	DESCRIPTION
HostTimespan	

Implements

- Comparable
- Comparable<>
- IComparable<>
- IFormattable

Struct HostTimestamp

Stores a local timestamp of an event.

Implements

Comparable

Comparable<HostTimestamp>

IComparable<HostTimestamp>

IFormattable

Namespace: SuperNet.Netcode.Transport

Assembly: cs.temp.dll.dll

Syntax

```
public struct HostTimestamp : Comparable, Comparable<HostTimestamp>, IComparable<HostTimestamp>, IFormattable
```

Fields

MaxValue

Biggest possible timestamp.

Declaration

```
public static readonly HostTimestamp MaxValue
```

Field Value

TYPE	DESCRIPTION
HostTimestamp	

MinValue

Smallest possible timestamp.

Declaration

```
public static readonly HostTimestamp MinValue
```

Field Value

TYPE	DESCRIPTION
HostTimestamp	

Start

Timestamp at the time the system started.

Declaration

```
public static readonly HostTimestamp Start
```

Field Value

TYPE	DESCRIPTION
HostTimestamp	

Properties

Elapsed

Get elapsed time since the creation of this timestamp.

Declaration

```
public HostTimespan Elapsed { get; }
```

Property Value

TYPE	DESCRIPTION
HostTimespan	

Now

Create a new timestamp at the current time.

Declaration

```
public static HostTimestamp Now { get; }
```

Property Value

TYPE	DESCRIPTION
HostTimestamp	

Methods

CompareTo(HostTimestamp)

Declaration

```
public int CompareTo(HostTimestamp other)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	other	

Returns

TYPE	DESCRIPTION
System.Int32	

CompareTo(Object)

Declaration

```
public int CompareTo(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Int32	

Equals(HostTimestamp)

Declaration

```
public bool Equals(HostTimestamp other)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	other	

Returns

TYPE	DESCRIPTION
System.Boolean	

Equals(Object)

Declaration

```
public override bool Equals(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

System.ValueType.Equals(System.Object)

FromDateTimeOffset(DateTimeOffset)

Create a timestamp from the DateTimeOffset object.

Declaration

```
public static HostTimestamp FromDateTimeOffset(DateTimeOffset time)
```

Parameters

TYPE	NAME	DESCRIPTION
DateTimeOffset	time	The DateTimeOffset object.

Returns

TYPE	DESCRIPTION
HostTimestamp	A new timestamp.

FromStopwatchTicks(Int64)

Create a timestamp with the provided ticks at stopwatch frequency.

Declaration

```
public static HostTimestamp FromStopwatchTicks(long ticks)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	ticks	Raw ticks.

Returns

TYPE	DESCRIPTION
HostTimestamp	A new timestamp.

FromTicks(Int64, Int64)

Create a timestamp from raw ticks with provided frequency.

Declaration

```
public static HostTimestamp FromTicks(long ticks, long frequency)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	ticks	Raw ticks.
System.Int64	frequency	Ticks per second.

Returns

TYPE	DESCRIPTION
HostTimestamp	A new timestamp.

GetHashCode()

Declaration

```
public override int GetHashCode()
```


Returns

TYPE	DESCRIPTION
System.Int32	

Overrides

System.ValueType.GetHashCode()

GetStopwatchTicks()

Get raw ticks with stopwatch frequency.

Declaration

```
public long GetStopwatchTicks()
```

Returns

TYPE	DESCRIPTION
System.Int64	Raw stopwatch ticks.

GetTicks(Int64)

Get raw ticks with provided frequency.

Declaration

```
public long GetTicks(long frequency)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	frequency	Ticks per second.

Returns

TYPE	DESCRIPTION
System.Int64	Raw ticks.

ToDateTimeOffset(TimeSpan)

Convert timestamp to a DateTimeOffset object.

Declaration

```
public DateTimeOffset ToDateTimeOffset(TimeSpan offset)
```

Parameters

TYPE	NAME	DESCRIPTION

TYPE	NAME	DESCRIPTION
TimeSpan	offset	UTC offset to use.

Returns

TYPE	DESCRIPTION
DateTimeOffset	The DateTimeOffset equivalent.

ToString()

Declaration

```
public override string ToString()
```

Returns

TYPE	DESCRIPTION
System.String	

Overrides

System.ValueType.ToString()

ToString(String, IFormatProvider)

Declaration

```
public string ToString(string format, IFormatProvider formatProvider)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	format	
IFormatProvider	formatProvider	

Returns

TYPE	DESCRIPTION
System.String	

Operators

Addition(HostTimespan, HostTimestamp)

Declaration

```
public static HostTimestamp operator +(HostTimespan lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimespan	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
HostTimestamp	

Addition([HostTimestamp](#), [HostTimespan](#))

Declaration

```
public static HostTimestamp operator +(HostTimestamp lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
HostTimestamp	

Equality([HostTimestamp](#), [HostTimestamp](#))

Declaration

```
public static bool operator ==(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

GreaterThan([HostTimestamp](#), [HostTimestamp](#))

Declaration

```
public static bool operator > (HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

GreaterThanOrEqualTo(HostTimestamp, HostTimestamp)

Declaration

```
public static bool operator >=(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Inequality(HostTimestamp, HostTimestamp)

Declaration

```
public static bool operator !=(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

LessThan(HostTimestamp, HostTimestamp)

Declaration

```
public static bool operator <(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

LessThanOrEqual(HostTimestamp, HostTimestamp)

Declaration

```
public static bool operator <=(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Subtraction(HostTimestamp, HostTimespan)

Declaration

```
public static HostTimestamp operator -(HostTimestamp lhs, HostTimespan rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimespan	rhs	

Returns

TYPE	DESCRIPTION
HostTimestamp	

Subtraction(HostTimestamp, HostTimestamp)

Declaration

```
public static HostTimespan operator -(HostTimestamp lhs, HostTimestamp rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	lhs	
HostTimestamp	rhs	

Returns

TYPE	DESCRIPTION
HostTimespan	

Implements

Comparable

Comparable<>

IEquatable<>

IFormattable

Interface IHostListener

Implements a host listener.

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface IHostListener
```

Methods

OnHostException(IPEndPoint, Exception)

Called when an exception occurs internally.

This does not usually indicate any fatal errors and can be ignored.

Declaration

```
void OnHostException(IPEndPoint remote, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address associated with this exception or null.
Exception	exception	Exception that was thrown.

OnHostReceiveBroadcast(IPEndPoint, Reader)

Called for every broadcast message the host receives.

Declaration

```
void OnHostReceiveBroadcast(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address message was received from.
Reader	message	Message that was received.

OnHostReceiveRequest(ConnectionRequest, Reader)

Called when a connection request is received.

The request can only be accepted during this call.

Declaration

```
void OnHostReceiveRequest(ConnectionRequest request, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
ConnectionRequest	request	Connection request received.
Reader	message	Message sent with the connection request.

OnHostReceiveSocket(IPEndPoint, Byte[], Int32)

Called for every raw packet the host receives.

Declaration

```
void OnHostReceiveSocket(IPEndPoint remote, byte[] buffer, int length)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address packet was received from.
System.Byte[]	buffer	Receive buffer the packet is written on.
System.Int32	length	Number of bytes in the packet.

OnHostReceiveUnconnected(IPEndPoint, Reader)

Called for every unconnected message the host receives.

Declaration

```
void OnHostReceiveUnconnected(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address message was received from.
Reader	message	Message that was received.

OnHostShutdown()

Called when the host shuts down.

Declaration

```
void OnHostShutdown()
```


Interface IMessage

Implements a message that can be sent by the netcode to a connected peer.

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface IMessage : IWritable
```

Properties

Channel

Which data channel to send the message on.

Declaration

```
byte Channel { get; }
```

Property Value

TYPE	DESCRIPTION
System.Byte	

Ordered

Message must be delivered in order within the channel.

Any unreliable messages that arrive out of order are dropped.

Any reliable messages that arrive out of order are reordered automatically.

Declaration

```
bool Ordered { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Reliable

Message requires an acknowledgment and needs to be resent until acknowledged.

This makes sure the message will never be lost.

Declaration

```
bool Reliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Timed

Message includes a timestamp of the moment of creation.

If false, received timestamp might be innacurate due to message delays.

Declaration

```
bool Timed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Timestamp

Timestamp of this message.

If message is not timed, this is ignored.

Declaration

```
HostTimestamp Timestamp { get; }
```

Property Value

TYPE	DESCRIPTION
HostTimestamp	

Unique

Message is guaranteed not to be duplicated.

Declaration

```
bool Unique { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Interface IMessageListener

Implements a sent message listener.

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface IMessageListener
```

Methods

OnMessageAcknowledge(Peer, MessageSent)

Called when a reliable message gets acknowledged.

Declaration

```
void OnMessageAcknowledge(Peer peer, MessageSent message)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer that received the acknowledgment.
MessageSent	message	Message that was acknowledged.

OnMessageSend(Peer, MessageSent)

Called after the message gets sent to the socket.

Declaration

```
void OnMessageSend(Peer peer, MessageSent message)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer that sent the message.
MessageSent	message	Message that was sent.

Interface IPeerListener

Implements a peer listener.

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface IPeerListener
```

Methods

OnPeerConnect(Peer)

Called when a peer successfully connects.

Declaration

```
void OnPeerConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Connected peer.

OnPeerDisconnect(Peer, Reader, DisconnectReason, Exception)

Called when a peer disconnects.

Declaration

```
void OnPeerDisconnect(Peer peer, Reader reader, DisconnectReason reason, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Disconnected peer.
Reader	reader	Disconnect message or null if not included.
DisconnectReason	reason	Disconnect reason.
Exception	exception	Exception associated with the disconnect or null if none.

OnPeerException(Peer, Exception)

Called when an exception occurs internally. Can be ignored.

Declaration

```
void OnPeerException(Peer peer, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer involved.
Exception	exception	Exception that was thrown.

OnPeerReceive(Peer, Reader, MessageReceived)

Called when a peer receives a connected message.

Declaration

void OnPeerReceive(Peer peer, Reader reader, MessageReceived info)

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Receiver of the message.
Reader	reader	Message that was received.
MessageReceived	info	Extra message information.

OnPeerUpdateRTT(Peer, UInt16)

Called when round trip time (ping) is updated.

Declaration

void OnPeerUpdateRTT(Peer peer, ushort rtt)

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Updated peer.
System.UInt16	rtt	New RTT value.

Class MessageEvents

Event based implementation of a message listener.

Inheritance

System.Object
MessageEvents

Implements

[IMessageListener](#)

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class MessageEvents : IMessageListener
```

Events

OnAcknowledge

Called when a reliable message gets acknowledged.

Declaration

```
public event MessageEvents.OnAcknowledgeHandler OnAcknowledge
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.MessageEvents.OnAcknowledgeHandler	

OnSend

Called after the message gets sent to the socket.

Declaration

```
public event MessageEvents.OnSendHandler OnSend
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.MessageEvents.OnSendHandler	

Explicit Interface Implementations

IMessageListener.OnMessageAcknowledge(Peer, MessageSent)

Declaration

```
void IMessageListener.OnMessageAcknowledge(Peer peer, MessageSent message)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

TYPE	NAME	DESCRIPTION
MessageSent	message	

IMessageListener.OnMessageSend(Peer, MessageSent)

Declaration

```
void IMessageListener.OnMessageSend(Peer peer, MessageSent message)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
MessageSent	message	

Implements

[IMessageListener](#)

Class MessageReceived

Extra information for a network message that has been received by a connected peer.

Inheritance

System.Object

MessageReceived

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class MessageReceived
```

Fields

Attempt

How many times the message was previously sent before.

Declaration

```
public readonly byte Attempt
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Channel

Data channel the message was sent over.

Declaration

```
public readonly byte Channel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Timestamp

Timestamp included in the message.

If message was not timed, this is approximated using round trip time.

Declaration

```
public readonly HostTimestamp Timestamp
```

Field Value

TYPE	DESCRIPTION
HostTimestamp	

Properties

Ordered

Received message is ordered.

Declaration

```
public bool Ordered { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Reliable

Received message is reliable.

Declaration

```
public bool Reliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Timed

Received message is timed.

Declaration

```
public bool Timed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Unique

Received message is unique.

Declaration

```
public bool Unique { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Class MessageSent

Network message that has been sent to a connected peer.

Inheritance

System.Object

MessageSent

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class MessageSent
```

Fields

Channel

Data channel this message is sent over.

Declaration

```
public readonly byte Channel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Listener

Listener used for this message or null if not provided.

Declaration

```
public readonly IMessageListener Listener
```

Field Value

TYPE	DESCRIPTION
IMessageListener	

Payload

Message payload that is used to write to internal buffers.

Declaration

```
public readonly IWritable Payload
```

Field Value

TYPE	DESCRIPTION
IWritable	

Sequence

Internal sequence number of the message.

Declaration

```
public readonly ushort Sequence
```

Field Value

TYPE	DESCRIPTION
System.UInt16	

Timestamp

Timestamp included in the message.

Declaration

```
public readonly HostTimestamp Timestamp
```

Field Value

TYPE	DESCRIPTION
HostTimestamp	

Properties

Ordered

Sent message is ordered.

Declaration

```
public bool Ordered { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Reliable

Sent message is reliable.

Declaration

```
public bool Reliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Timed

Sent message is timed.

Declaration

```
public bool Timed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Unique

Sent message is unique.

Declaration

```
public bool Unique { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

StopResending()

Stop resending this message if reliable. May cause the message to be lost.

Declaration

```
public void StopResending()
```

Class Peer

Manages an active network connection.

Inheritance

System.Object

Peer

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class Peer : IDisposable
```

Fields

Config

Configuration values for this peer.

Declaration

```
public readonly PeerConfig Config
```

Field Value

TYPE	DESCRIPTION
PeerConfig	

Host

Host used to manage this peer.

Declaration

```
public readonly Host Host
```

Field Value

TYPE	DESCRIPTION
Host	

Remote

Address this peer is connected to.

Declaration

```
public readonly IPEndPoint Remote
```

Field Value

TYPE	DESCRIPTION
IPEndPoint	

Statistics

Packet statistics.

Declaration

```
public readonly PeerStatistics Statistics
```

Field Value

TYPE	DESCRIPTION
PeerStatistics	

Properties

Connected

True if messages can be sent.

Declaration

```
public bool Connected { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Connecting

True if peer is in the process of connecting.

Declaration

```
public bool Connecting { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

DeltaAverage

Average clock difference in last 16 bits of ticks between peers.

Declaration

```
public double DeltaAverage { get; }
```

Property Value

TYPE	DESCRIPTION
System.Double	

DeltaLast

Last clock difference in last 16 bits of ticks between peers.

Declaration

```
public ushort DeltaLast { get; }
```

Property Value

TYPE	DESCRIPTION
System.UInt16	

Disposed

True if peer has been disposed.

Declaration

```
public bool Disposed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Listener

Listener used by this peer.

Declaration

```
public IPeerListener Listener { get; }
```

Property Value

TYPE	DESCRIPTION
IPeerListener	

RTT

Current round trip time (ping) in milliseconds.

Declaration

```
public ushort RTT { get; }
```

Property Value

TYPE	DESCRIPTION
System.UInt16	

Methods

Disconnect(IWritable)

Disconnect by sending a disconnect message.

Declaration

```
public void Disconnect(IWritable message = null)
```

Parameters

TYPE	NAME	DESCRIPTION
IWritable	message	Disconnect message to include or null if none.

DisconnectAsync(IWritable)

Disconnect by sending a disconnect message.

Declaration

```
public Task DisconnectAsync(IWritable message = null)
```

Parameters

TYPE	NAME	DESCRIPTION
IWritable	message	Disconnect message to include or null if none.

Returns

TYPE	DESCRIPTION
Task	

Dispose()

Instantly dispose of all resources held by this peer.

Declaration

```
public void Dispose()
```

Send(IMessage, IMessageListener)

Queue a message for sending and return a sent message handle.

Declaration

```
public MessageSent Send(IMessage message, IMessageListener listener = null)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
IMessageListener	listener	Message listener to use or null if not used.

Returns

TYPE	DESCRIPTION
MessageSent	Sent message handle.

SetListener(IPeerListener)

Replace the current listener with a new one.

Declaration

```
public IPeerListener SetListener(IPeerListener listener)
```

Parameters

TYPE	NAME	DESCRIPTION
IPeerListener	listener	Listener to replace with.

Returns

TYPE	DESCRIPTION
IPeerListener	The old PeerListener.

Class PeerConfig

Holds configuration values for peers.

Inheritance

System.Object

PeerConfig

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: [cs.temp.dll.dll](#)

Syntax

```
public class PeerConfig
```

Fields

ConnectAttempts

Number of connection requests to send before giving up. This is a high number to allow enough time for UDP hole punching.

Declaration

```
public int ConnectAttempts
```

Field Value

TYPE	DESCRIPTION
System.Int32	

ConnectDelay

Delay in milliseconds between connection requests.

Declaration

```
public int ConnectDelay
```

Field Value

TYPE	DESCRIPTION
System.Int32	

DisconnectDelay

Number of milliseconds to delay closing the connection when a disconnect request is received.

This is useful in cases where both peers disconnect at the same time. It is also useful for when a disconnect acknowledge gets lost. Set to zero to disable this delay.

Declaration

```
public int DisconnectDelay
```

Field Value

TYPE	DESCRIPTION
System.Int32	

DuplicateTimeout

How long in milliseconds to keep received reliable messages for. If the same reliable message is received during this timeout, it is ignored.

Declaration

```
public int DuplicateTimeout
```

Field Value

TYPE	DESCRIPTION
System.Int32	

FragmentTimeout

Timeout in milliseconds until a received incompleated fragmented packet times out.

Declaration

```
public int FragmentTimeout
```

Field Value

TYPE	DESCRIPTION
System.Int32	

MTU

Maximum bytes to send in one UDP packet.

MTU on ethernet is 1500 bytes - 20 bytes for IP header - 8 bytes for UDP header.

Declaration

```
public int MTU
```

Field Value

TYPE	DESCRIPTION
System.Int32	

OrderedDelayMax

Maximum number of messages to wait for before processing a reliable ordered message that came out of order.

If an ordered reliable message comes late, it is delayed until all missing messages are received. This value controls maximum number of missing messages to wait for. If this is zero, delaying is disabled.

Declaration

```
public int OrderedDelayMax
```

Field Value

TYPE	DESCRIPTION
System.Int32	

OrderedDelayTimeout

Maximum number of milliseconds to wait for before processing a reliable ordered message that came out of order.

If an ordered reliable message comes late, it is delayed until all missing messages are received. This controls maximum number of milliseconds to wait for. If this is zero, delaying is disabled.

Declaration

```
public int OrderedDelayTimeout
```

Field Value

TYPE	DESCRIPTION
System.Int32	

PingDelay

Delay in milliseconds between ping messages.

Declaration

```
public int PingDelay
```

Field Value

TYPE	DESCRIPTION
System.Int32	

RemotePublicKey

Remote public key to verify authentication signature against.

If provided and remote peer has authentication disabled, they will ignore connection requests.

Declaration

```
public string RemotePublicKey
```

Field Value

TYPE	DESCRIPTION
System.String	

ResendCount

Maximum number of times a reliable message is resent without being acknowledged before the connection times out.

Declaration

```
public byte ResendCount
```

Field Value

TYPE	DESCRIPTION
System.Byte	

ResendDelayJitter

Maximum number of milliseconds to wait before declaring a reliable message as lost.

When a reliable message is sent, peer waits RTT + ResendDelayJitter milliseconds for an acknowledgment. If no acknowledgment is received within that time, the message is resent. A small value can result in unnecessary duplicated messages wasting networking bandwidth.

Declaration

```
public int ResendDelayJitter
```

Field Value

TYPE	DESCRIPTION
System.Int32	

ResendDelayMax

Maximum delay in milliseconds before resending unacknowledged reliable messages.

Declaration

```
public int ResendDelayMax
```

Field Value

TYPE	DESCRIPTION
System.Int32	

ResendDelayMin

Minimum delay in milliseconds before resending unacknowledged reliable messages.

Declaration

```
public int ResendDelayMin
```

Field Value

TYPE	DESCRIPTION
System.Int32	

SendDelay

Delay in milliseconds before combining and sending messages to the socket.

Declaration

```
public int SendDelay
```

Field Value

TYPE	DESCRIPTION
System.Int32	

TimeStability

How fast the clock tick difference can change. Must be between 0 and 1.

Clock tick difference is an exponential moving average. If this value is 1, clock drifting is completely ignored once calculated. if this value is 0, latest calculated value is always used.

Declaration

```
public float TimeStability
```

Field Value

TYPE	DESCRIPTION
System.Single	

UnsequencedMax

Maximum number of consecutive unsequenced messages to send.

All reliable messages include a sequence number. Unreliable messages don't need a sequence number but can include it. This value controls how often to include a sequence number. Sending a sequence number every so often is important to check for lost messages.

Declaration

```
public int UnsequencedMax
```

Field Value

TYPE	DESCRIPTION
System.Int32	

Class PeerEvents

Event based implementation of a peer listener.

Inheritance

System.Object
PeerEvents

Implements

[IPeerListener](#)

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class PeerEvents : IPeerListener
```

Events

OnConnect

Called when a peer successfully connects.

Declaration

```
public event PeerEvents.OnConnectHandler OnConnect
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.PeerEvents.OnConnectHandler	

OnDisconnect

Called when a peer disconnects.

Declaration

```
public event PeerEvents.OnDisconnectHandler OnDisconnect
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.PeerEvents.OnDisconnectHandler	

OnException

Called when an exception occurs internally. Can be ignored.

Declaration

```
public event PeerEvents.OnExceptionHandler OnException
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.PeerEvents.OnExceptionHandler	

OnReceive

Called when a peer receives a connected message.

Declaration

```
public event PeerEvents.OnReceiveHandler OnReceive
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.PeerEvents.OnReceiveHandler	

OnUpdateRTT

Called when round trip time (ping) is updated.

Declaration

```
public event PeerEvents.OnUpdateRTTHandler OnUpdateRTT
```

Event Type

TYPE	DESCRIPTION
SuperNet.Netcode.Transport.PeerEvents.OnUpdateRTTHandler	

Explicit Interface Implementations

IPeerListener.OnPeerConnect(Peer)

Declaration

```
void IPeerListener.OnPeerConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

IPeerListener.OnPeerDisconnect(Peer, Reader, DisconnectReason, Exception)

Declaration

```
void IPeerListener.OnPeerDisconnect(Peer peer, Reader reader, DisconnectReason reason, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
DisconnectReason	reason	
Exception	exception	

IPeerListener.OnPeerException(Peer, Exception)

Declaration

```
void IPeerListener.OnPeerException(Peer peer, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Exception	exception	

IPeerListener.OnPeerReceive(Peer, Reader, MessageReceived)

Declaration

```
void IPeerListener.OnPeerReceive(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

IPeerListener.OnPeerUpdateRTT(Peer, UInt16)

Declaration

```
void IPeerListener.OnPeerUpdateRTT(Peer peer, ushort rtt)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
System.UInt16	rtt	

Implements

[IPeerListener](#)

Class PeerStatistics

Stores packet statistics for peers.

Inheritance

System.Object

PeerStatistics

Namespace: [SuperNet.Netcode.Transport](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class PeerStatistics
```

Properties

MessageReceiveAcknowledge

Total number of received acknowledgements.

Declaration

```
public long MessageReceiveAcknowledge { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveBytes

Total number of bytes recieved in messages after decryption and decompression.

Declaration

```
public long MessageReceiveBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveDuplicated

Total number of received duplicated messages.

Declaration

```
public long MessageReceiveDuplicated { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveLost

Total number of lost messages.

Declaration

```
public long MessageReceiveLost { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceivePing

Total number of received pings.

Declaration

```
public long MessageReceivePing { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveReliable

Total number of received reliable messages.

Declaration

```
public long MessageReceiveReliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveTotal

Total number of received messages.

Declaration

```
public long MessageReceiveTotal { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageReceiveUnreliable

Total number of received unreliable messages.

Declaration

```
public long MessageReceiveUnreliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendAcknowledge

Total number of sent acknowledgements.

Declaration

```
public long MessageSendAcknowledge { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendBytes

Total number of sent bytes in messages before compression and encryption.

Declaration

```
public long MessageSendBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendDuplicated

Total number of sent duplicated messages.

Declaration

```
public long MessageSendDuplicated { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendPing

Total number of sent pings.

Declaration

```
public long MessageSendPing { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendReliable

Total number of sent reliable messages.

Declaration

```
public long MessageSendReliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendTotal

Total number of sent messages.

Declaration

```
public long MessageSendTotal { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

MessageSendUnreliable

Total number of sent unreliable messages.

Declaration

```
public long MessageSendUnreliable { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketReceiveBytes

Total number of bytes received.

Declaration

```
public long PacketReceiveBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketReceiveCount

Total number of packets received.

Declaration

```
public long PacketReceiveCount { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketReceiveTicks

Host ticks at the moment of the last receive operation.

Declaration

```
public long PacketReceiveTicks { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketSendBytes

Total number of bytes sent.

Declaration

```
public long PacketSendBytes { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketSendCount

Total number of sent packets.

Declaration

```
public long PacketSendCount { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

PacketSendTicks

Host ticks at the moment of the last send operation.

Declaration

```
public long PacketSendTicks { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int64	

Methods

Reset()

Reset all statistics to zero.

Declaration

```
public void Reset()
```

Namespace SuperNet.Netcode.Util

Classes

[Allocator](#)

[ArrayPool<T>](#)

Array pool for reusing arrays to avoid too many allocations.

[CRC32](#)

Fast CRC32 error-checking code calculation for network packets.

[IPComparer](#)

Equality comparer used by the netcode to distinguish between peers.

[IPResolver](#)

Helper methods that convert a connection string to an `IPEndPoint` used by the netcode.

[ObjectPool<T>](#)

Object pool for reusing objects to avoid too many allocations.

[Reader](#)

Fast deserializer for network messages.

[Serializer](#)

Platform independent serialization of values in Big-endian (network byte order).

[Writer](#)

Fast serializer for network messages.

Interfaces

[IWritable](#)

Defines a serializable network payload.

Class Allocator

Inheritance

System.Object

Allocator

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class Allocator
```

Constructors

Allocator()

Create a new allocator without any pooling.

Declaration

```
public Allocator()
```

Allocator(HostConfig)

Create a new allocator for a host.

Declaration

```
public Allocator(HostConfig config)
```

Parameters

TYPE	NAME	DESCRIPTION
HostConfig	config	Configuration to use.

Methods

CreateIV(Int32)

Allocate a new IV array for crypto.

Declaration

```
public byte[] CreateIV(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Length of the array.

Returns

TYPE	DESCRIPTION
System.Byte[]	A new unused array.

CreateKey(Int32)

Allocate a new key array for crypto.

Declaration

```
public byte[] CreateKey(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Length of the array.

Returns

TYPE	DESCRIPTION
System.Byte[]	A new unused array.

CreateMessage(Int32)

Allocate a new resizable array to store a single message.

Declaration

```
public byte[] CreateMessage(int minLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	minLength	Minimum length of the returned array.

Returns

TYPE	DESCRIPTION
System.Byte[]	A new unused array.

CreatePacket(Int32)

Allocate a new short array to store a single packet.

Declaration

```
public byte[] CreatePacket(int minLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	minLength	Minimum length of the returned array.

Returns

TYPE	DESCRIPTION
System.Byte[]	A new unused array.

CreateSent()

Allocate a new sent message storage used by peers.

Declaration

```
public Dictionary<Tuple<byte, ushort>, MessageSent> CreateSent()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.Dictionary<Tuple<System.Byte, System.UInt16>, MessageSent>	A new unused sent message storage.

CreateSet()

Allocate a new HashSet used by peers.

Declaration

```
public HashSet<Tuple<byte, ushort>> CreateSet()
```

Returns

TYPE	DESCRIPTION
HashSet<Tuple<System.Byte, System.UInt16>>	A new unused HashSet.

CreateSocketArgs(EventHandler<SocketAsyncEventArgs>)

Declaration

```
public SocketAsyncEventArgs CreateSocketArgs(EventHandler<SocketAsyncEventArgs> callback)
```

Parameters

TYPE	NAME	DESCRIPTION
EventHandler<SocketAsyncEventArgs>	callback	

Returns

TYPE	DESCRIPTION
SocketAsyncEventArgs	

ExpandMessage(Byte[], Int32, Int32)

Resize a message array to a larger size.

Declaration

```
public byte[] ExpandMessage(byte[] array, int offset, int length = 1)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to resize.
System.Int32	offset	Current array offset.
System.Int32	length	Length beyond the array offset to add.

Returns

TYPE	DESCRIPTION
System.Byte[]	A new resized array with copied data.

HashTableCreate(Int32)

Allocate a new hash table array for the LZF compressor.

Declaration

```
public long[] HashTableCreate(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Length of the array.

Returns

TYPE	DESCRIPTION
System.Int64[]	A new unused array.

HashTableReturn(Int64[])

Return a hash table array back to the pool.

Declaration

```
public void HashTableReturn(long[] array)
```

Parameters

TYPE	NAME	DESCRIPTION

TYPE	NAME	DESCRIPTION
System.Int64[]	array	Array to return.

ReturnIV(ref Byte[])

Return an IV array back to the pool.

Declaration

```
public void ReturnIV(ref byte[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to return.

ReturnKey(ref Byte[])

Return a key array back to the pool.

Declaration

```
public void ReturnKey(ref byte[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to return.

ReturnMessage(ref Byte[])

Return a message array back to the pool.

Declaration

```
public void ReturnMessage(ref byte[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to return.

ReturnPacket(ref Byte[])

Return a packet array back to the pool.

Declaration

```
public void ReturnPacket(ref byte[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to return.

ReturnSent(ref Dictionary<Tuple<Byte, UInt16>, MessageSent>)

Return a sent message storage back to the pool.

Declaration

```
public void ReturnSent(ref Dictionary<Tuple<byte, ushort>, MessageSent> set)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Collections.Generic.Dictionary<Tuple<System.Byte, System.UInt16>, MessageSent>	set	Sent message storage to return.

ReturnSet(ref HashSet<Tuple<Byte, UInt16>>)

Return a HashSet back to the pool.

Declaration

```
public void ReturnSet(ref HashSet<Tuple<byte, ushort>> set)
```

Parameters

TYPE	NAME	DESCRIPTION
HashSet<Tuple<System.Byte, System.UInt16>>	set	HashSet to return.

ReturnSocketArgs(ref SocketAsyncEventArgs)

Declaration

```
public void ReturnSocketArgs(ref SocketAsyncEventArgs args)
```

Parameters

TYPE	NAME	DESCRIPTION
SocketAsyncEventArgs	args	

SequenceNew(Int32)

Allocate a new array to store message sequence for each channel.

Declaration

```
public int[] SequenceNew(int channels)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	channels	Number of channels.

Returns

TYPE	DESCRIPTION
System.Int32[]	A new unused array.

SequenceReturn(ref Int32[])

Return a sequence array back to the pool.

Declaration

```
public void SequenceReturn(ref int[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32[]	array	Array to return.

TokensNew(Int32)

Allocate a new cancellation token array for each channel.

Declaration

```
public CancellationTokenSource[] TokensNew(int channels)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	channels	Number of channels.

Returns

TYPE	DESCRIPTION
CancellationTokenSource[]	A new unused array.

TokensReturn(ref CancellationTokenSource[])

Return a cancellation token array back to the pool.

Declaration

```
public void TokensReturn(ref CancellationTokenSource[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
CancellationTokenSource[]	array	Array to return.

Class ArrayPool<T>

Array pool for reusing arrays to avoid too many allocations.

Inheritance

System.Object

ArrayPool<T>

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class ArrayPool<T>
```

Type Parameters

NAME	DESCRIPTION
T	Underlying array type.

Constructors

ArrayPool(Int32, Int32)

Create a new array pool.

Declaration

```
public ArrayPool(int count, int maxLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	count	Number of arrays this pool can hold.
System.Int32	maxLength	Maximum length arrays can be saved at.

Methods

Expand(T[], Int32, Int32, Int32)

Resize an array created by this pool.

Declaration

```
public T[] Expand(T[] array, int copyLength, int addLength, int expandLength)
```

Parameters

TYPE	NAME	DESCRIPTION
T[]	array	Array to resize.

TYPE	NAME	DESCRIPTION
System.Int32	copyLength	Number of bytes to copy to the new array.
System.Int32	addLength	Number of bytes to add after the copy length.
System.Int32	expandLength	Array length multiplier.

Returns

TYPE	DESCRIPTION
T[]	A new resized array.

Rent(Int32)

Extract an array from this pool or allocate a new one.

Declaration

```
public T[] Rent(int minimumLength)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	minimumLength	Minimum length that the returned array has to be.

Returns

TYPE	DESCRIPTION
T[]	An unused array.

Return(T[])

Return an array back to this pool.

Declaration

```
public void Return(T[] array)
```

Parameters

TYPE	NAME	DESCRIPTION
T[]	array	Array to return.

Class CRC32

Fast CRC32 error-checking code calculation for network packets.

Inheritance

System.Object

CRC32

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public static class CRC32
```

Methods

Compute(Byte[], Int32, Int32)

Compute a CRC32 code for the input array segment.

Declaration

```
public static uint Compute(byte[] array, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to read from.
System.Int32	offset	Offset in the array to start reading from.
System.Int32	count	Number of bytes to read.

Returns

TYPE	DESCRIPTION
System.UInt32	CRC32 code of the input.

Class IPComparer

Equality comparer used by the netcode to distinguish between peers.

Inheritance

System.Object
IPComparer

Implements

System.Collections.Generic.IEqualityComparer<IPEndPoint>

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class IPComparer : IEqualityComparer<IPEndPoint>
```

Methods

Equals(IPEndPoint, IPEndPoint)

Check if both address and port match.

Declaration

```
public bool Equals(IPEndPoint x, IPEndPoint y)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	x	First IP
IPEndPoint	y	Second IP

Returns

TYPE	DESCRIPTION
System.Boolean	True if they match, false if not.

GetHashCode(IPEndPoint)

Construct a hash code based on address and port.

Declaration

```
public int GetHashCode(IPEndPoint obj)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	obj	Object to construct the hash code from.

Returns

TYPE	DESCRIPTION
System.Int32	Constructed hash code.

Implements

System.Collections.Generic.IEqualityComparer<T>

Class IPResolver

Helper methods that convert a connection string to an `IPEndPoint` used by the netcode.

Inheritance

System.Object

IPResolver

Namespace: `SuperNet.Netcode.Util`

Assembly: `cs.temp.dll.dll`

Syntax

```
public static class IPResolver
```

Methods

GetLocalAddress()

Get local IPv4 address other machines on the same network can use to connect to us. This can be used to create LAN connections.

Declaration

```
public static IPAddress GetLocalAddress()
```

Returns

TYPE	DESCRIPTION
IPAddress	Local IPv4 address or 127.0.0.1 if none found.

GetLocalAddress(Int32)

Get local IPv4 address other machines on the same network can use to connect to us. This can be used to create LAN connections.

Declaration

```
public static IPEndPoint GetLocalAddress(int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Port to use.

Returns

TYPE	DESCRIPTION
IPEndPoint	Local IPv4 address or 127.0.0.1 if none found.

GetLocalAddressIPv6()

Get local IPv6 address other machines on the same network can use to connect to us. This can be used to create LAN connections.

Declaration

```
public static IPAddress GetLocalAddressIPv6()
```

Returns

TYPE	DESCRIPTION
IPAddress	Local IPv6 address or ::1 if none found.

GetLocalAddressIPv6(Int32)

Get local IPv6 address other machines on the same network can use to connect to us. This can be used to create LAN connections.

Declaration

```
public static IPEndPoint GetLocalAddressIPv6(int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Port to use.

Returns

TYPE	DESCRIPTION
IPEndPoint	Local IPv6 address or ::1 if none found.

Resolve(String)

Perform a synchronous DNS lookup if needed and create an IPEndPoint.

Host must be a valid IP address, followed by a colon and a port such as 192.168.12.43:80 or 127.0.0.1:44015.

Declaration

```
public static IPEndPoint Resolve(string host)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname with port to resolve.

Returns

TYPE	DESCRIPTION
IPEndPoint	Resolved address.

Resolve(String, Action<IPEndPoint, Exception>)

Perform an asynchronous DNS lookup if needed and create an IPEndPoint. All exceptions are thrown via the callback.

Host must be a valid IP address, followed by a colon and a port such as 192.168.12.43:80 or 127.0.0.1:44015.

Declaration

```
public static void Resolve(string host, Action<IPEndPoint, Exception> callback)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname with port to resolve.
Action<IPEndPoint, Exception>	callback	Callback to invoke after DNS lookup completes.

Resolve(String, Int32)

Perform a synchronous DNS lookup if needed and create an IPEndPoint.

Host must be a valid hostname without a port such as 192.168.12.43 or superversus.com.

Declaration

```
public static IPEndPoint Resolve(string host, int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname to resolve.
System.Int32	port	Port to use.

Returns

TYPE	DESCRIPTION
IPEndPoint	Resolved address.

Resolve(String, Int32, Action<IPEndPoint, Exception>)

Perform an asynchronous DNS lookup if needed and create an IPEndPoint. All exceptions are thrown via the callback.

Host must be a valid hostname without a port such as 192.168.12.43 or superversus.com.

Declaration

```
public static void Resolve(string host, int port, Action<IPEndPoint, Exception> callback)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname to resolve.

TYPE	NAME	DESCRIPTION
System.Int32	port	Port to use.
Action<IPEndPoint, Exception>	callback	Callback to invoke after DNS lookup completes.

ResolveAsync(String)

Perform an asynchronous DNS lookup if needed and create an `IPEndPoint`.

Host must be a valid hostname, followed by a colon and a port such as `192.168.12.43:80` or `superversus.com:44015`.

Declaration

```
public static Task<IPEndPoint> ResolveAsync(string host)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname with port to resolve.

Returns

TYPE	DESCRIPTION
Task<IPEndPoint>	A valid <code>IPEndPoint</code> with the provided IP address and port.

ResolveAsync(String, CancellationToken)

Perform an asynchronous DNS lookup if needed and create an `IPEndPoint`.

Host must be a valid hostname, followed by a colon and a port such as `192.168.12.43:80` or `superversus.com:44015`.

Declaration

```
public static Task<IPEndPoint> ResolveAsync(string host, CancellationToken token)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname with port to resolve.
CancellationToken	token	Cancellation token that can stop the DNS lookup before it is completed.

Returns

TYPE	DESCRIPTION

TYPE	DESCRIPTION
Task<IPEndPoint>	A valid <code>IPEndPoint</code> with the provided IP address and port.

ResolveAsync(String, Int32)

Perform an asynchronous DNS lookup if needed and create an `IPEndPoint`.

Host must be a valid hostname without a port such as `192.168.12.43` or `superversus.com`.

Declaration

```
public static Task<IPEndPoint> ResolveAsync(string host, int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname to resolve.
System.Int32	port	Port to use.

Returns

TYPE	DESCRIPTION
Task<IPEndPoint>	A valid <code>IPEndPoint</code> with the provided IP address and port.

ResolveAsync(String, Int32, CancellationToken)

Perform an asynchronous DNS lookup if needed and create an `IPEndPoint`.

Host must be a valid hostname without a port such as `192.168.12.43` or `superversus.com`.

Declaration

```
public static Task<IPEndPoint> ResolveAsync(string host, int port, CancellationToken token)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	Hostname to resolve.
System.Int32	port	Port to use.
CancellationToken	token	Cancellation token that can stop the DNS lookup before it is completed.

Returns

TYPE	DESCRIPTION
Task<IPEndPoint>	A valid <code>IPEndPoint</code> with the provided IP address and port.

TryParse(String)

Try to parse the host as an IP address followed by a colon and a part. This method never throws any exceptions and returns immediately.

Host must be a valid IP address, followed by a colon and a port such as `192.168.12.43:80` or `127.0.0.1:44015`.

Declaration

```
public static IPEndPoint TryParse(string host)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	IP address with port to parse.

Returns

TYPE	DESCRIPTION
IPEndPoint	Parsed <code>IPEndPoint</code> or null if invalid.

TryParse(String, Int32)

Try to parse the host as an IP address. This method never throws any exceptions and returns immediately.

Host must contain a valid IP address such as `192.168.12.43` or `127.0.0.1`.

Declaration

```
public static IPEndPoint TryParse(string host, int port)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	host	IP address to parse.
System.Int32	port	Port to use.

Returns

TYPE	DESCRIPTION
IPEndPoint	Parsed <code>IPEndPoint</code> or null if invalid.

Interface IWritable

Defines a serializable network payload.

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface IWritable
```

Methods

Write(Writer)

Serialize payload into the provided writer.

Declaration

```
void Write(Writer writer)
```

Parameters

TYPE	NAME	DESCRIPTION
Writer	writer	Writer to write to.

Class ObjectPool<T>

Object pool for reusing objects to avoid too many allocations.

Inheritance

System.Object

ObjectPool<T>

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class ObjectPool<T>
    where T : class
```

Type Parameters

NAME	DESCRIPTION
T	Object type.

Constructors

ObjectPool(Int32)

Create a new object pool.

Declaration

```
public ObjectPool(int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	count	Number of objects this pool can hold.

Methods

Rent()

Extract an object from this pool or return null.

Declaration

```
public T Rent()
```

Returns

TYPE	DESCRIPTION
T	Extracted object or null if none available.

Return(T)

Return an object back to this pool.

Declaration

```
public void Return(T obj)
```

Parameters

TYPE	NAME	DESCRIPTION
T	obj	Object to return.

Class Reader

Fast deserializer for network messages.

Inheritance

System.Object

Reader

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class Reader : IDisposable
```

Constructors

Reader(ArraySegment<Byte>)

Create a new reader from the provided array segment.

Declaration

```
public Reader(ArraySegment<byte> segment)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	segment	Array segment to read from.

Reader(Byte[], Int32, Int32)

Create a new reader from the provided array segment.

Declaration

```
public Reader(byte[] array, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to read from.
System.Int32	offset	Offset in the array to start reading from.
System.Int32	count	Number of bytes to read.

Fields

First

Index of the first byte that is included in the message.

Declaration

```
public readonly int First
```

Field Value

TYPE	DESCRIPTION
System.Int32	

Last

Index of the last byte that is not included in the message.

Declaration

```
public readonly int Last
```

Field Value

TYPE	DESCRIPTION
System.Int32	

Properties

Available

Number of bytes still available to be read or 0 if the reader has been disposed.

Declaration

```
public int Available { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Buffer

Internal buffer that contains the serialized message or null if the reader has been disposed.

Declaration

```
public byte[] Buffer { get; }
```

Property Value

TYPE	DESCRIPTION
System.Byte[]	

Disposed

True if reader has been disposed.

Declaration

```
public bool Disposed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Position

Current position in the internal buffer or 0 if the reader has been disposed.

Declaration

```
public int Position { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Methods

CheckAvailableSpace(Int32)

Check if message has enough bytes left, throw exception if not.

Declaration

```
public void CheckAvailableSpace(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Length to check for.

Dispose()

Invalidate the underlying buffer when it gets used for something else. Calling this causes all future read operation to fail.

Declaration

```
public void Dispose()
```

ReadBoolean()

Read a single boolean (1 byte).

Declaration

```
public bool ReadBoolean()
```

Returns

TYPE	DESCRIPTION
System.Boolean	Boolean value.

ReadBoolean(out Boolean, out Boolean, out Boolean, out Boolean, out Boolean, out Boolean, out Boolean, out Boolean)

Read 8 booleans (1 byte).

Declaration

```
public void ReadBoolean(out bool v0, out bool v1, out bool v2, out bool v3, out bool v4, out bool v5, out bool v6, out bool v7)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	v0	First boolean value.
System.Boolean	v1	Second boolean value.
System.Boolean	v2	Third boolean value.
System.Boolean	v3	Fourth boolean value.
System.Boolean	v4	Fifth boolean value.
System.Boolean	v5	Sixth boolean value.
System.Boolean	v6	Seventh boolean value.
System.Boolean	v7	Eighth boolean value.

ReadByte()

Read byte (1 byte).

Declaration

```
public byte ReadByte()
```

Returns

TYPE	DESCRIPTION
System.Byte	Byte value.

ReadBytes(Byte[], Int32, Int32)

Read into an array segment.

Declaration

```
public void ReadBytes(byte[] array, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	array	Array to read to.
System.Int32	offset	Array offset to read to.
System.Int32	count	Number of bytes to read.

ReadChar()

Read a single character (2 bytes).

Declaration

```
public char ReadChar()
```

Returns

TYPE	DESCRIPTION
System.Char	Character value.

ReadDecimal()

Read decimal (16 bytes).

Declaration

```
public decimal ReadDecimal()
```

Returns

TYPE	DESCRIPTION
System.Decimal	Decimal value.

ReadDouble()

Read double (8 bytes).

Declaration

```
public double ReadDouble()
```

Returns

TYPE	DESCRIPTION

TYPE	DESCRIPTION
System.Double	Double value.

ReadEnum<T>()

Read enum (1, 2 or 4 bytes).

Number of bytes read is dependant on the underlying type the enum is backed by.

Declaration

```
public T ReadEnum<T>()  
    where T : struct, IConvertible
```

Returns

TYPE	DESCRIPTION
T	Enum value.

Type Parameters

NAME	DESCRIPTION
T	Enum type.

ReadInt16()

Read short (2 bytes).

Declaration

```
public short ReadInt16()
```

Returns

TYPE	DESCRIPTION
System.Int16	Short value.

ReadInt32()

Read integer (4 bytes).

Declaration

```
public int ReadInt32()
```

Returns

TYPE	DESCRIPTION

TYPE	DESCRIPTION
System.Int32	Integer value.

ReadInt64()

Read long integer (8 bytes).

Declaration

```
public long ReadInt64()
```

Returns

TYPE	DESCRIPTION
System.Int64	Long integer value.

ReadSByte()

Read signed byte (1 byte).

Declaration

```
public sbyte ReadSByte()
```

Returns

TYPE	DESCRIPTION
System.SByte	Signed byte value.

ReadSingle()

Read float (4 bytes).

Declaration

```
public float ReadSingle()
```

Returns

TYPE	DESCRIPTION
System.Single	Float value.

ReadString()

Read 4 bytes length, then UTF8 encoded string.

Declaration

```
public string ReadString()
```

Returns

TYPE	DESCRIPTION
System.String	String value or null if length is negative.

ReadUInt16()

Read unsigned short (2 bytes).

Declaration

```
public ushort ReadUInt16()
```

Returns

TYPE	DESCRIPTION
System.UInt16	Unsigned short value.

ReadUInt32()

Read unsigned integer (4 bytes).

Declaration

```
public uint ReadUInt32()
```

Returns

TYPE	DESCRIPTION
System.UInt32	Unsigned integer value.

ReadUInt64()

Read unsigned long integer (8 bytes).

Declaration

```
public ulong ReadUInt64()
```

Returns

TYPE	DESCRIPTION
System.UInt64	Unsigned long integer value.

Reset(Int32)

Manually set the read position.

Declaration

```
public void Reset(int position)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	position	Position to set.

Skip(Int32)

Advance the read position without reading anything.

Declaration

```
public void Skip(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Number of bytes to skip for.

Class Serializer

Platform independent serialization of values in Big-endian (network byte order).

Inheritance

System.Object
Serializer

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public static class Serializer
```

Properties

Encoding

Character encoding to use when serializing strings.

Declaration

```
public static Encoding Encoding { get; }
```

Property Value

TYPE	DESCRIPTION
Encoding	

Methods

ReadDouble(Byte[], Int32)

Deserialize double (8 bytes) from the buffer.

Declaration

```
public static double ReadDouble(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.Double	Deserialized value.

ReadInt16(Byte[], Int32)

Deserialize short (2 bytes) from the buffer.

Declaration

```
public static short ReadInt16(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.Int16	Deserialized value.

ReadInt32(Byte[], Int32)

Deserialize int (4 bytes) from the buffer.

Declaration

```
public static int ReadInt32(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.Int32	Deserialized value.

ReadInt64(Byte[], Int32)

Deserialize long (8 bytes) from the buffer.

Declaration

```
public static long ReadInt64(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.Int64	Deserialized value.

ReadSingle(Byte[], Int32)

Deserialize float (4 bytes) from the buffer.

Declaration

```
public static float ReadSingle(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.Single	Deserialized value.

ReadUInt16(Byte[], Int32)

Deserialize ushort (2 bytes) from the buffer.

Declaration

```
public static ushort ReadUInt16(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.

TYPE	NAME	DESCRIPTION
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.UInt16	Deserialized value.

ReadUInt32(Byte[], Int32)

Deserialize uint (4 bytes) from the buffer.

Declaration

```
public static uint ReadUInt32(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.UInt32	Deserialized value.

ReadUInt64(Byte[], Int32)

Deserialize ulong (8 bytes) from the buffer.

Declaration

```
public static ulong ReadUInt64(byte[] buffer, int offset)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to read from.
System.Int32	offset	Buffer offset to read from.

Returns

TYPE	DESCRIPTION
System.UInt64	Deserialized value.

Write16(Byte[], Int32, Int16)

Serialize short (2 bytes) to the buffer.

Declaration

```
public static void Write16(byte[] buffer, int offset, short value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.Int16	value	Value to write.

Write16(Byte[], Int32, UInt16)

Serialize ushort (2 bytes) to the buffer.

Declaration

```
public static void Write16(byte[] buffer, int offset, ushort value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.UInt16	value	Value to write.

Write32(Byte[], Int32, Int32)

Serialize int (4 bytes) to the buffer.

Declaration

```
public static void Write32(byte[] buffer, int offset, int value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.Int32	value	Value to write.

Write32(Byte[], Int32, UInt32)

Serialize uint (4 bytes) to the buffer.

Declaration

```
public static void Write32(byte[] buffer, int offset, uint value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.UInt32	value	Value to write.

Write64(Byte[], Int32, Int64)

Serialize long (8 bytes) to the buffer.

Declaration

```
public static void Write64(byte[] buffer, int offset, long value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.Int64	value	Value to write.

Write64(Byte[], Int32, UInt64)

Serialize ulong (8 bytes) to the buffer.

Declaration

```
public static void Write64(byte[] buffer, int offset, ulong value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.UInt64	value	Value to write.

WriteDouble(Byte[], Int32, Double)

Serialize double (8 bytes) to the buffer.

Declaration

```
public static void WriteDouble(byte[] buffer, int offset, double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.
System.Double	value	Value to write.

WriteSingle(Byte[], Int32, Single)

Serialize float (4 bytes) to the buffer.

Declaration

```
public static void WriteSingle(byte[] buffer, int offset, float value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to write to.
System.Int32	offset	Buffer offset to write to.

TYPE	NAME	DESCRIPTION
System.Single	value	Value to write.

Class Writer

Fast serializer for network messages.

Inheritance

System.Object

Writer

Namespace: [SuperNet.Netcode.Util](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class Writer : IDisposable
```

Constructors

Writer(Allocator, Int32)

Allocate a new buffer and create a writer for it. The buffer is automatically resized by the allocator.

Declaration

```
public Writer(Allocator allocator, int position)
```

Parameters

TYPE	NAME	DESCRIPTION
Allocator	allocator	Allocator to use for the internal buffer.
System.Int32	position	Initial position in the internal buffer.

Properties

Buffer

Internal buffer to write to or null if the writer has been disposed.

Declaration

```
public byte[] Buffer { get; }
```

Property Value

TYPE	DESCRIPTION
System.Byte[]	

Disposed

True if writer has been disposed.

Declaration

```
public bool Disposed { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Position

Current write position within the internal buffer or 0 if the writer has been disposed.

Declaration

```
public int Position { get; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

Methods

Dispose()

Invalidate the underlying buffer when it gets used for something else. Calling this causes all future write operation to fail.

Declaration

```
public void Dispose()
```

Skip(Int32)

Advance the write position without writing anything.

Declaration

```
public void Skip(int length)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	length	Number of bytes to skip for.

Write(Boolean)

Write a single boolean value (1 byte) to the writer.

Declaration

```
public void Write(bool value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	value	Boolean to write.

Write(Boolean, Boolean, Boolean, Boolean, Boolean, Boolean, Boolean, Boolean)

Write 8 boolean values (1 byte) to the writer

Write 8 boolean values (1 byte) to the writer.

Declaration

```
public void Write(bool v0, bool v1, bool v2, bool v3, bool v4, bool v5, bool v6, bool v7)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	v0	First boolean value.
System.Boolean	v1	Second boolean value.
System.Boolean	v2	Third boolean value.
System.Boolean	v3	Fourth boolean value.
System.Boolean	v4	Fifth boolean value.
System.Boolean	v5	Sixth boolean value.
System.Boolean	v6	Seventh boolean value.
System.Boolean	v7	Eighth boolean value.

Write(Byte)

Write a single byte (1 byte) to the writer.

Declaration

```
public void Write(byte value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte	value	Byte to write.

Write(Char)

Write a single character (2 bytes) to the writer.

Declaration

```
public void Write(char value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Char	value	Character to write.

Write(Decimal)

Write a decimal (16 bytes) to the writer.

Declaration

```
public void Write(decimal value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Decimal	value	Decimal to write.

Write(Double)

Write a double (8 bytes) to the writer.

Declaration

```
public void Write(double value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Double	value	Double to write.

Write(Int16)

Write a short (2 bytes) to the writer.

Declaration

```
public void Write(short value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int16	value	Short to write.

Write(Int32)

Write an integer (4 bytes) to the writer.

Declaration

```
public void Write(int value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	value	Integer to write.

Write(Int64)

Write a long (8 bytes) to the writer.

Declaration

```
public void Write(long value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int64	value	Long to write.

Write(SByte)

Write a signed byte (1 byte) to the writer.

Declaration

```
public void Write(sbyte value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.SByte	value	Signed byte to write.

Write(Single)

Write a float (4 bytes) to the writer.

Declaration

```
public void Write(float value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Single	value	Float to write.

Write(String)

Write 4 bytes for length, then UTF8 encoded string.

Declaration

```
public void Write(string value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	value	String to write.

Write(UInt16)

Write an unsigned short (2 bytes) to the writer.

Declaration

```
public void Write(ushort value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt16	value	Unsigned short to write.

Write(UInt32)

Write an unsigned integer (4 bytes) to the writer.

Declaration

```
public void Write(uint value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt32	value	Unsigned integer to write.

Write(UInt64)

Write an unsigned long (8 bytes) to the writer.

Declaration

```
public void Write(ulong value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt64	value	Unsigned long to write.

WriteBytes(ArraySegment<Byte>)

Copy a segment of bytes to the writer.

Declaration

```
public void WriteBytes(ArraySegment<byte> segment)
```

Parameters

TYPE	NAME	DESCRIPTION
ArraySegment<System.Byte>	segment	Segment to copy

WriteBytes(Byte[])

Copy an entire buffer to the writer.

Declaration

```
public void WriteBytes(byte[] buffer)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to copy.

WriteBytes(Byte[], Int32, Int32)

Copy a segment of bytes to the writer.

Declaration

```
public void WriteBytes(byte[] buffer, int offset, int count)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Byte[]	buffer	Buffer to copy from.
System.Int32	offset	Offset within the provided buffer.
System.Int32	count	Number of bytes to copy.

WriteEnum<T>(T)

Write an enum (1, 2 or 4 bytes) to the writer.

Number of bytes written is dependant on the underlying type enum is backed by.

Declaration

```
public void WriteEnum<T>(T value)
    where T : struct, IConvertible
```

Parameters

TYPE	NAME	DESCRIPTION

TYPE	NAME	DESCRIPTION
T	value	Enum value.

Type Parameters

NAME	DESCRIPTION
T	Enum type.

Namespace SuperNet.Unity.Components

Classes

[NetworkAnimation](#)

Synchronizes legacy animation over the network.

[NetworkAnimator](#)

Synchronizes an animator over the network.

[NetworkAuthority](#)

Manages authority over child authoritative components.

[NetworkPrefab](#)

Spawnable prefab with network components.

[NetworkRegistrar](#)

Singleton used to notify network components about register and unregister events.

[NetworkSpawner](#)

Manages spawnable network prefabs.

[NetworkTransform](#)

Synchronizes a transform over the network.

Interfaces

[INetworkAuthoritative](#)

Allows network components to be controlled by a single authority on the network.

[INetworkRegisterable](#)

Allows network components to listen for register events.

[INetworkRollbackable](#)

Allows network components to be temporarily rolled back in time.

Enums

[NetworkSyncModeMethod](#)

Synchronization method to use.

[NetworkSyncModeVector2](#)

Synchronization mode for Vector2 values.

[NetworkSyncModeVector3](#)

Synchronization mode for Vector3 values.

Interface INetworkAuthoritative

Allows network components to be controlled by a single authority on the network.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface INetworkAuthoritative
```

Methods

OnNetworkAuthorityUpdate(Boolean, HostTimestamp)

Called when authority of this component changes.

Declaration

```
void OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	True if component has local authority, false if not.
HostTimestamp	timestamp	Timestamp when authority changed.

Interface INetworkRegisterable

Allows network components to listen for register events.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface INetworkRegisterable
```

Methods

OnNetworkRegister(Peer)

Called when this component is registered on a peer.

Declaration

```
void OnNetworkRegister(Peer remote)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	remote	Peer the component is registered on.

OnNetworkUnregister(Peer)

Called when this component is unregistered from a peer.

Declaration

```
void OnNetworkUnregister(Peer remote)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	remote	Peer the component is unregistered from.

Interface INetworkRollbackable

Allows network components to be temporarily rolled back in time.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public interface INetworkRollbackable
```

Methods

OnNetworkRollbackBegin(HostTimestamp, Peer)

Update the state of the component to be the same as in the past.

Declaration

```
void OnNetworkRollbackBegin(HostTimestamp time, Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	time	Which timestamp in the past to rollback to.
Peer	peer	Peer that we're performing the rollback for.

OnNetworkRollbackEnd()

Revert any rollbacks.

Declaration

```
void OnNetworkRollbackEnd()
```

Class NetworkAnimation

Synchronizes legacy animation over the network.

Inheritance

System.Object

NetworkComponent

NetworkAnimation

Implements

INetworkAuthoritative

Inherited Members

- NetworkComponent.NetworkID
- NetworkComponent.IsRegisteredOnNetwork
- NetworkComponent.Start()
- NetworkComponent.OnDestroy()
- NetworkComponent.ResetNetworkID()
- NetworkComponent.GetNetworkPeers()
- NetworkComponent.Run(Action)
- NetworkComponent.Run(Action, Single)
- NetworkComponent.RunAsync(Action)
- NetworkComponent.SendNetworkMessage(IMessage)
- NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, Peer[])
- NetworkComponent.OnNetworkUnregister()
- NetworkComponent.OnNetworkRegister(NetworkComponent)
- NetworkComponent.OnNetworkUnregister(NetworkComponent)

Namespace: SuperNet.Unity.Components

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkAnimation : NetworkComponent, INetworkAuthoritative
```

Fields

Animation

Animation component to synchronize. Required.

Declaration

```
public Animation Animation
```

Field Value

TYPE	DESCRIPTION
Animation	

ReceiveDelay

Declaration

```
public float ReceiveDelay
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendIntervalMin

Declaration

```
public float SendIntervalMin
```

Field Value

TYPE	DESCRIPTION
System.Single	

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

SyncMethod

Which method to synchronize in.

Declaration

```
public NetworkSyncModeMethod SyncMethod
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeMethod	

Properties

IsAuthority

Send updates to remote peers.

Declaration

```
public bool IsAuthority { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkConnect\(Peer\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

[NetworkComponent.OnNetworkMessage\(Peer, Reader, MessageReceived\)](#)

OnNetworkRegister()

Declaration

```
public override void OnNetworkRegister()
```

Overrides

[NetworkComponent.OnNetworkRegister\(\)](#)

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

SetAuthority(Boolean)

Update authority on this component.

Declaration

```
public void SetAuthority(bool authority)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	Authority to set.

Explicit Interface Implementations

[INetworkAuthoritative.OnNetworkAuthorityUpdate\(Boolean, HostTimestamp\)](#)

Declaration

```
void INetworkAuthoritative.OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	
HostTimestamp	timestamp	

Implements

[INetworkAuthoritative](#)

Class NetworkAnimator

Synchronizes an animator over the network.

Inheritance

System.Object
NetworkComponent
NetworkAnimator

Implements

INetworkAuthoritative

Inherited Members

NetworkComponent.NetworkID
NetworkComponent.IsRegisteredOnNetwork
NetworkComponent.Start()
NetworkComponent.OnDestroy()
NetworkComponent.ResetNetworkID()
NetworkComponent.GetNetworkPeers()
NetworkComponent.Run(Action)
NetworkComponent.Run(Action, Single)
NetworkComponent.RunAsync(Action)
NetworkComponent.SendNetworkMessage(IMessage)
NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, Peer[])
NetworkComponent.OnNetworkUnregister()
NetworkComponent.OnNetworkRegister(NetworkComponent)
NetworkComponent.OnNetworkUnregister(NetworkComponent)

Namespace: SuperNet.Unity.Components

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkAnimator : NetworkComponent, INetworkAuthoritative
```

Fields

Animator

Animator component to synchronize. Required.

Declaration

```
public Animator Animator
```

Field Value

TYPE	DESCRIPTION
Animator	

ReceiveDelay

Declaration

```
public float ReceiveDelay
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendIntervalMin

Declaration

```
public float SendIntervalMin
```

Field Value

TYPE	DESCRIPTION
System.Single	

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

SyncMethod

Which method to synchronize in.

Declaration

```
public NetworkSyncModeMethod SyncMethod
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeMethod	

SyncParameters

Synchronize animator parameters.

Declaration

```
public bool SyncParameters
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

SyncStates

Synchronize animator states

Synchronize animator states.

Declaration

```
public bool SyncStates
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Properties

IsAuthority

Send updates to remote peers.

Declaration

```
public bool IsAuthority { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkConnect\(Peer\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

[NetworkComponent.OnNetworkMessage\(Peer, Reader, MessageReceived\)](#)

OnNetworkRegister()

Declaration

```
public override void OnNetworkRegister()
```

Overrides

[NetworkComponent.OnNetworkRegister\(\)](#)

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

SetAuthority(Boolean)

Update authority on this component.

Declaration

```
public void SetAuthority(bool authority)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	Authority to set.

SetTrigger(Int32)

Sets a trigger locally and sends it to everybody on the network regardless of authority.

Declaration

```
public void SetTrigger(int id)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	id	Trigger hash ID.

SetTrigger(String)

Sets a trigger locally and sends it to everybody on the network regardless of authority.

Declaration

```
public void SetTrigger(string triggerName)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	triggerName	Trigger name.

Events

OnNetworkTrigger

Called when trigger parameter is set remotely.

Declaration

```
public event NetworkAnimator.OnNetworkTriggerHandler OnNetworkTrigger
```

Event Type

TYPE	DESCRIPTION
SuperNet.Unity.Components.NetworkAnimator.OnNetworkTriggerHandler	

Explicit Interface Implementations

INetworkAuthoritative.OnNetworkAuthorityUpdate(Boolean, HostTimestamp)

Declaration

```
void INetworkAuthoritative.OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	
HostTimestamp	timestamp	

Implements

[INetworkAuthoritative](#)

Class NetworkAuthority

Manages authority over child authoritative components.

Inheritance

System.Object
NetworkComponent
NetworkAuthority

Implements

INetworkAuthoritative

Inherited Members

- NetworkComponent.NetworkID
- NetworkComponent.IsRegisteredOnNetwork
- NetworkComponent.OnDestroy()
- NetworkComponent.ResetNetworkID()
- NetworkComponent.GetNetworkPeers()
- NetworkComponent.Run(Action)
- NetworkComponent.Run(Action, Single)
- NetworkComponent.RunAsync(Action)
- NetworkComponent.SendNetworkMessage(IMessage)
- NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, Peer[])
- NetworkComponent.OnNetworkUnregister()
- NetworkComponent.OnNetworkRegister(NetworkComponent)
- NetworkComponent.OnNetworkUnregister(NetworkComponent)

Namespace: SuperNet.Unity.Components
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkAuthority : NetworkComponent, INetworkAuthoritative
```

Fields

Locked

True if only authority can claim access. Set to false to let anybody claim.

Declaration

```
public bool Locked
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Properties

IsAuthority

True if we can grant and revoke ownership to peers.

Declaration

```
public bool IsAuthority { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

IsOwner

True if we have local ownership over child authoritative components.

Declaration

```
public bool IsOwner { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Owner

Current owner of the components or null if unknown.

Declaration

```
public Peer Owner { get; }
```

Property Value

TYPE	DESCRIPTION
Peer	

Timestamp

Timestamp when the ownership was last changed.

Declaration

```
public HostTimestamp Timestamp { get; }
```

Property Value

TYPE	DESCRIPTION
HostTimestamp	

Methods

Claim(UInt32)

Claim local ownership access.

Declaration

```
public void Claim(uint priority = 1U)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt32	priority	Claim priority. Higher values have more claim.

GetAuthoritativeComponents()

Return all authoritative components managed by this authority.

Declaration

```
public IReadOnlyList<INetworkAuthoritative> GetAuthoritativeComponents()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< INetworkAuthoritative >	All authoritative components.

Grant(Peer)

Grant ownership access to a specific peer.

Declaration

```
public void Grant(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	New owner.

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkConnect\(Peer\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

[NetworkComponent.OnNetworkMessage\(Peer, Reader, MessageReceived\)](#)

OnNetworkRegister()

Declaration

```
public override void OnNetworkRegister()
```

Overrides

[NetworkComponent.OnNetworkRegister\(\)](#)

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

Rebind()

Force an update to the list of child components this authority has control over.

Declaration

```
public void Rebind()
```

SetAuthority(Boolean)

Update authority on this component.

Declaration

```
public void SetAuthority(bool authority)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	Authority to set.

Start()

Declaration

```
protected override void Start()
```

Overrides

[NetworkComponent.Start\(\)](#)

Explicit Interface Implementations

INetworkAuthoritative.OnNetworkAuthorityUpdate(Boolean, HostTimestamp)

Declaration

```
void INetworkAuthoritative.OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	
HostTimestamp	timestamp	

Implements

[INetworkAuthoritative](#)

Class NetworkPrefab

Spawnable prefab with network components.

Inheritance

System.Object
NetworkComponent
NetworkPrefab

Inherited Members

NetworkComponent.NetworkID
NetworkComponent.IsRegisteredOnNetwork
NetworkComponent.ResetNetworkID()
NetworkComponent.GetNetworkPeers()
NetworkComponent.Run(Action)
NetworkComponent.Run(Action, Single)
NetworkComponent.RunAsync(Action)
NetworkComponent.SendNetworkMessage(IMessage)
NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, Peer[])
NetworkComponent.OnNetworkMessage(Peer, Reader, MessageReceived)
NetworkComponent.OnNetworkResend(Peer, Peer, Reader, MessageReceived)
NetworkComponent.OnNetworkRegister()
NetworkComponent.OnNetworkUnregister()
NetworkComponent.OnNetworkRegister(NetworkComponent)
NetworkComponent.OnNetworkUnregister(NetworkComponent)
NetworkComponent.OnNetworkConnect(Peer)

Namespace: SuperNet.Unity.Components
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkPrefab : NetworkComponent
```

Fields

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Properties

Spawnee

The peer that spawned this prefab or null if none.

Declaration

```
public Peer Spawnee { get; }
```

Property Value

TYPE	DESCRIPTION
Peer	

Spawner

Network spawner responsible for this prefab or null if not spawned.

Declaration

```
public NetworkSpawner Spawner { get; }
```

Property Value

TYPE	DESCRIPTION
NetworkSpawner	

Methods

GetNetworkComponents()

Return all components managed by this prefab.

Declaration

```
public IReadOnlyList<NetworkComponent> GetNetworkComponents()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< NetworkComponent >	All prefab components.

OnDestroy()

Declaration

```
protected override void OnDestroy()
```

Overrides

[NetworkComponent.OnDestroy\(\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

Start()

Declaration

```
protected override void Start()
```

Overrides

[NetworkComponent.Start\(\)](#)

Class NetworkRegistrar

Singleton used to notify network components about register and unregister events.

Inheritance

System.Object
NetworkComponent
NetworkRegistrar

Inherited Members

NetworkComponent.NetworkID
NetworkComponent.IsRegisteredOnNetwork
NetworkComponent.Start()
NetworkComponent.ResetNetworkID()
NetworkComponent.GetNetworkPeers()
NetworkComponent.Run(Action)
NetworkComponent.Run(Action, Single)
NetworkComponent.RunAsync(Action)
NetworkComponent.SendNetworkMessage(IMessage)
NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, Peer[])
NetworkComponent.OnNetworkRegister()
NetworkComponent.OnNetworkUnregister()

Namespace: SuperNet.Unity.Components
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkRegistrar : NetworkComponent
```

Fields

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

Methods

OnDestroy()

Declaration

```
protected override void OnDestroy()
```

Overrides

NetworkComponent.OnDestroy()

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkConnect\(Peer\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

[NetworkComponent.OnNetworkMessage\(Peer, Reader, MessageReceived\)](#)

OnNetworkRegister(NetworkComponent)

Declaration

```
public override void OnNetworkRegister(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	

Overrides

[NetworkComponent.OnNetworkRegister\(NetworkComponent\)](#)

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

OnNetworkUnregister(NetworkComponent)

Declaration

```
public override void OnNetworkUnregister(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	

Overrides

[NetworkComponent.OnNetworkUnregister\(NetworkComponent\)](#)

Class NetworkSpawner

Manages spawnable network prefabs.

Inheritance

System.Object
NetworkComponent
NetworkSpawner

Implements

INetworkAuthoritative

Inherited Members

- NetworkComponent.NetworkID
- NetworkComponent.IsRegisteredOnNetwork
- NetworkComponent.OnDestroy()
- NetworkComponent.ResetNetworkID()
- NetworkComponent.GetNetworkPeers()
- NetworkComponent.Run(Action)
- NetworkComponent.Run(Action, Single)
- NetworkComponent.RunAsync(Action)
- NetworkComponent.SendNetworkMessage(IMessage)
- NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
- NetworkComponent.SendNetworkMessage(IMessage, Peer[])
- NetworkComponent.OnNetworkUnregister()
- NetworkComponent.OnNetworkRegister(NetworkComponent)
- NetworkComponent.OnNetworkUnregister(NetworkComponent)

Namespace: SuperNet.Unity.Components
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkSpawner : NetworkComponent, INetworkAuthoritative
```

Fields

Locked

True if only authority can spawn. Set to false to let anybody spawn.

Declaration

```
public bool Locked
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Parent

The parent transform to spawn under.

Declaration

```
public Transform Parent
```

Field Value

TYPE	DESCRIPTION
Transform	

Prefab

The prefab to clone when spawning.

Declaration

<code>public NetworkPrefab Prefab</code>
--

Field Value

TYPE	DESCRIPTION
NetworkPrefab	

SyncChannel

Network channel to use.

Declaration

<code>public byte SyncChannel</code>

Field Value

TYPE	DESCRIPTION
System.Byte	

Properties

IsAuthority

True if we can spawn and despawn.

Declaration

<code>public bool IsAuthority { get; }</code>

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

Despawn(NetworkPrefab, Boolean)

Despawn an instantiated instance and optionally destroy it.

Declaration

<code>public bool Despawn(NetworkPrefab instance, bool destroy = true)</code>

Parameters

TYPE	NAME	DESCRIPTION
NetworkPrefab	instance	Instance to despawn.
System.Boolean	destroy	True to also destroy the instance.

Returns

TYPE	DESCRIPTION
System.Boolean	True if despawned, false if not.

DespawnAll(Boolean)

Despawn all instantiated instances and optionally destroy them.

Declaration

```
public void DespawnAll(bool destroy = true)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	destroy	True to also destroy the instances.

GetSpawnedPrefabs()

Get all spawned instances as a list.

Declaration

```
public IReadOnlyList<NetworkPrefab> GetSpawnedPrefabs()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< NetworkPrefab >	All spawned instances.

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

NetworkComponent.OnNetworkConnect(Peer)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

NetworkComponent.OnNetworkDisconnect(Peer)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

NetworkComponent.OnNetworkMessage(Peer, Reader, MessageReceived)

OnNetworkRegister()

Declaration

```
public override void OnNetworkRegister()
```

Overrides

NetworkComponent.OnNetworkRegister()

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	

TYPE	NAME	DESCRIPTION
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

SetAuthority(Boolean)

Update authority on this component.

Declaration

```
public void SetAuthority(bool authority)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	Authority to set.

Spawn(NetworkPrefab)

Spawn an already instantiated prefab.

Declaration

```
public void Spawn(NetworkPrefab instance)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkPrefab	instance	Instantiated prefab.

Spawn(Boolean)

Spawn a network instance and notify the network.

Declaration

```
public NetworkPrefab Spawn(bool relativeToSpawner = true)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	relativeToSpawner	True to position the new object relative to the spawner.

Returns

TYPE	DESCRIPTION
NetworkPrefab	The instantiated clone.

Spawn(Vector3, Quaternion, Boolean)

Spawn a network instance and notify the network.

Declaration

```
public NetworkPrefab Spawn(Vector3 position, Quaternion rotation, bool relativeToParent = false)
```

Parameters

TYPE	NAME	DESCRIPTION
Vector3	position	Position for the new object.
Quaternion	rotation	Orientation of the new object.
System.Boolean	relativeToParent	True to position the new object relative to spawn parent.

Returns

TYPE	DESCRIPTION
NetworkPrefab	The instantiated clone.

Start()

Declaration

```
protected override void Start()
```

Overrides

[NetworkComponent.Start\(\)](#)

Explicit Interface Implementations

INetworkAuthoritative.OnNetworkAuthorityUpdate(Boolean, HostTimestamp)

Declaration

```
void INetworkAuthoritative.OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	
HostTimestamp	timestamp	

Implements

[INetworkAuthoritative](#)

Enum NetworkSyncModeMethod

Synchronization method to use.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public enum NetworkSyncModeMethod : byte
```

Fields

NAME	DESCRIPTION
FixedUpdate	
LateUpdate	
Update	

Enum NetworkSyncModeVector2

Synchronization mode for Vector2 values.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public enum NetworkSyncModeVector2 : byte
```

Fields

NAME	DESCRIPTION
None	
X	
XY	
Y	

Enum NetworkSyncModeVector3

Synchronization mode for Vector3 values.

Namespace: [SuperNet.Unity.Components](#)

Assembly: cs.temp.dll.dll

Syntax

```
public enum NetworkSyncModeVector3 : byte
```

Fields

NAME	DESCRIPTION
None	
X	
XY	
XYZ	
XZ	
Y	
YZ	
Z	

Class NetworkTransform

Synchronizes a transform over the network.

Inheritance

System.Object
NetworkComponent
NetworkTransform

Implements

INetworkAuthoritative
INetworkRollbackable

Inherited Members

NetworkComponent.NetworkID
NetworkComponent.IsRegisteredOnNetwork
NetworkComponent.Start()
NetworkComponent.OnDestroy()
NetworkComponent.ResetNetworkID()
NetworkComponent.GetNetworkPeers()
NetworkComponent.Run(Action)
NetworkComponent.Run(Action, Single)
NetworkComponent.RunAsync(Action)
NetworkComponent.SendNetworkMessage(IMessage)
NetworkComponent.SendNetworkMessage(IMessage, Predicate<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, IEnumerable<Peer>)
NetworkComponent.SendNetworkMessage(IMessage, Peer[])
NetworkComponent.OnNetworkUnregister()
NetworkComponent.OnNetworkRegister(NetworkComponent)
NetworkComponent.OnNetworkUnregister(NetworkComponent)

Namespace: SuperNet.Unity.Components
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkTransform : NetworkComponent, INetworkAuthoritative, INetworkRollbackable
```

Fields

ReceiveAuthorityDelay

How many seconds to delay authority transfer for to allow smooth transitions.

Declaration

```
public float ReceiveAuthorityDelay
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveDelay

Declaration

```
public float ReceiveDelay
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveDuration

How many seconds to keep received values for.

Declaration

public float ReceiveDuration

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveExtrapolate

Seconds after the last update is received to extrapolate for. Bigger values make the transform less likely to jitter during lag spikes but can introduce rubber banding.

Declaration

public float ReceiveExtrapolate
--

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapAngularVelocity

Maximum angular velocity difference allowed to interpolate before snapping. Zero to disable.

Declaration

public float ReceiveSnapAngularVelocity
--

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapDuration

Maximum seconds between two updates still allowed to interpolate before snapping. Zero to disable.

Declaration

public float ReceiveSnapDuration

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapPosition

Maximum distance allowed to interpolate before teleporting. Zero to disable.

Declaration

```
public float ReceiveSnapPosition
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapRectAnchors

Maximum RectTransform anchor difference allowed to interpolate before snapping. Zero to disable.

Declaration

```
public float ReceiveSnapRectAnchors
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapRectPivot

Maximum RectTransform pivot difference allowed to interpolate before snapping. Zero to disable.

Declaration

```
public float ReceiveSnapRectPivot
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapRectSizeDelta

Maximum RectTransform size difference allowed to interpolate before snapping. Zero to disable.

Declaration

```
public float ReceiveSnapRectSizeDelta
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapRotation

Maximum rotation angle allowed to interpolate before teleporting. Zero to disable.

Declaration

```
public float ReceiveSnapRotation
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapScale

Maximum scale difference allowed to interpolate before snapping. Zero to disable.

Declaration

```
public float ReceiveSnapScale
```

Field Value

TYPE	DESCRIPTION
System.Single	

ReceiveSnapVelocity

Maximum velocity difference allowed to interpolate before snapping. Zero to disable.

Declaration

```
public float ReceiveSnapVelocity
```

Field Value

TYPE	DESCRIPTION
System.Single	

RectTransform

RectTransform component to synchronize. Optional.

Declaration

```
public RectTransform RectTransform
```

Field Value

TYPE	DESCRIPTION
RectTransform	

Rigidbody

Rigidbody component to synchronize. Optional.

Declaration

```
public Rigidbody Rigidbody
```

Field Value

TYPE	DESCRIPTION
Rigidbody	

Rigidbody2D

Rigidbody2D component to synchronize. Required.

Declaration

```
public Rigidbody2D Rigidbody2D
```

Field Value

TYPE	DESCRIPTION
Rigidbody2D	

SendIntervalMax

Maximum number of seconds to wait before sending an update.

Declaration

```
public float SendIntervalMax
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendIntervalMin

Declaration

```
public float SendIntervalMin
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdAngularVelocity

Minimum amount angular velocity is able to change before an update is sent.

Declaration

```
public float SendThresholdAngularVelocity
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdExtrapolate

Should remote peer extrapolation be taken into account when checking for thresholds.

Declaration

```
public bool SendThresholdExtrapolate
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

SendThresholdPosition

Minimum distance transform is able to move before an update is sent.

Declaration

```
public float SendThresholdPosition
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdRectAnchors

Minimum RectTransform anchor is able to change before an update is sent.

Declaration

```
public float SendThresholdRectAnchors
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdRectPivot

Minimum amount RectTransform pivot is able to change before an update is sent.

Declaration

```
public float SendThresholdRectPivot
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdRectSizeDelta

Minimum amount RectTransform size is able to change before an update is sent.

Declaration

```
public float SendThresholdRectSizeDelta
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdRotation

Minimum amount rotation angle (in radians) is able to change before an update is sent.

Declaration

```
public float SendThresholdRotation
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdScale

Minimum amount transform is able to scale before an update is sent.

Declaration

```
public float SendThresholdScale
```

Field Value

TYPE	DESCRIPTION
System.Single	

SendThresholdVelocity

Minimum amount velocity is able to change before an update is sent.

Declaration

```
public float SendThresholdVelocity
```

Field Value

TYPE	DESCRIPTION
System.Single	

SyncAngularVelocity

Which angular velocity components to synchronize.

Declaration

```
public NetworkSyncModeVector3 SyncAngularVelocity
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector3	

SyncChannel

Network channel to use.

Declaration

```
public byte SyncChannel
```

Field Value

TYPE	DESCRIPTION
System.Byte	

SyncLocalTransform

Synchronize position and rotation in local space.

Declaration

```
public bool SyncLocalTransform
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

SyncMethod

Which method to synchronize in.

Declaration

```
public NetworkSyncModeMethod SyncMethod
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeMethod	

SyncPosition

Which position components to synchronize.

Declaration

```
public NetworkSyncModeVector3 SyncPosition
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector3	

SyncRectAnchorMax

Should RectTransform anchorMax be synchronized.

Declaration

```
public NetworkSyncModeVector2 SyncRectAnchorMax
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector2	

SyncRectAnchorMin

Should RectTransform anchorMin be synchronized.

Declaration

```
public NetworkSyncModeVector2 SyncRectAnchorMin
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector2	

SyncRectPivot

Should RectTransform pivot be synchronized.

Declaration

```
public NetworkSyncModeVector2 SyncRectPivot
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector2	

SyncRectSizeDelta

Should RectTransform sizeDelta be synchronized.

Declaration

```
public NetworkSyncModeVector2 SyncRectSizeDelta
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector2	

SyncRotation

Which rotation components to synchronize.

Declaration

```
public NetworkSyncModeVector3 SyncRotation
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector3	

SyncScale

Which scale components to synchronize.

Declaration

```
public NetworkSyncModeVector3 SyncScale
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector3	

SyncVelocity

Which velocity components to synchronize.

Declaration

```
public NetworkSyncModeVector3 SyncVelocity
```

Field Value

TYPE	DESCRIPTION
NetworkSyncModeVector3	

Transform

Transform component to synchronize. Required.

Declaration

```
public Transform Transform
```

Field Value

TYPE	DESCRIPTION
Transform	

Properties

HasRectTransform

True if a RectTransform is attached.

Declaration

```
public bool HasRectTransform { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

HasRigidbody

True if a rigidbody is attached.

Declaration

```
public bool HasRigidbody { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

IsAuthority

Send updates to remote peers.

Declaration

```
public bool IsAuthority { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

OnNetworkConnect(Peer)

Declaration

```
public override void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkConnect\(Peer\)](#)

OnNetworkDisconnect(Peer)

Declaration

```
public override void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

Overrides

[NetworkComponent.OnNetworkDisconnect\(Peer\)](#)

OnNetworkMessage(Peer, Reader, MessageReceived)

Declaration

```
public override void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

Overrides

[NetworkComponent.OnNetworkMessage\(Peer, Reader, MessageReceived\)](#)

OnNetworkRegister()

Declaration

```
public override void OnNetworkRegister()
```

Overrides

[NetworkComponent.OnNetworkRegister\(\)](#)

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Declaration

```
public override bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	
Peer	peer	
Reader	reader	
MessageReceived	info	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

[NetworkComponent.OnNetworkResend\(Peer, Peer, Reader, MessageReceived\)](#)

SetAuthority(Boolean)

Update authority on this component.

Declaration

```
public void SetAuthority(bool authority)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	Authority to set.

Explicit Interface Implementations

[INetworkAuthoritative.OnNetworkAuthorityUpdate\(Boolean, HostTimestamp\)](#)

Declaration

```
void INetworkAuthoritative.OnNetworkAuthorityUpdate(bool authority, HostTimestamp timestamp)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	authority	
HostTimestamp	timestamp	

[INetworkRollbackable.OnNetworkRollbackBegin\(HostTimestamp, Peer\)](#)

Declaration

```
void INetworkRollbackable.OnNetworkRollbackBegin(HostTimestamp time, Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	time	
Peer	peer	

[INetworkRollbackable.OnNetworkRollbackEnd\(\)](#)

Declaration

```
void INetworkRollbackable.OnNetworkRollbackEnd()
```

Implements

[INetworkAuthoritative](#)

[INetworkRollbackable](#)

Namespace SuperNet.Unity.Core

Classes

[NetworkComponent](#)

Base class for synchronized network components.

[NetworkHost](#)

Manages a network socket and all network communication between peers.

[NetworkIdentityExtensions](#)

Network ID Extensions.

[NetworkManager](#)

Provides API access to static network methods.

Structs

[NetworkIdentity](#)

ID used to synchronize components over network.

Class NetworkComponent

Base class for synchronized network components.

Inheritance

- System.Object
- NetworkComponent
- [NetworkAnimation](#)
- [NetworkAnimator](#)
- [NetworkAuthority](#)
- [NetworkPrefab](#)
- [NetworkRegistrar](#)
- [NetworkSpawner](#)
- [NetworkTransform](#)

Namespace: [SuperNet.Unity.Core](#)
Assembly: cs.temp.dll.dll

Syntax

```
public abstract class NetworkComponent : MonoBehaviour
```

Properties

IsRegisteredOnNetwork

True if this component is registered on the network.

Declaration

```
public bool IsRegisteredOnNetwork { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

NetworkID

Registered network ID or serialized ID if not registered.

Declaration

```
public NetworkIdentity NetworkID { get; }
```

Property Value

TYPE	DESCRIPTION
NetworkIdentity	

Methods

GetNetworkPeers()

Return all registered peers.

Declaration

```
public IReadOnlyList<Peer> GetNetworkPeers()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< Peer >	All registered peers.

OnDestroy()

Automatically unregisters the component. Do not override.

Declaration

```
protected virtual void OnDestroy()
```

OnNetworkConnect(Peer)

Called when any peer connects to the network.

Declaration

```
public virtual void OnNetworkConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer that connected.

OnNetworkDisconnect(Peer)

Called when any peer disconnects from the network.

Declaration

```
public virtual void OnNetworkDisconnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer that disconnected.

OnNetworkMessage(Peer, Reader, MessageReceived)

Called when a message is received from a peer.

Declaration

```
public virtual void OnNetworkMessage(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer that received the message.

TYPE	NAME	DESCRIPTION
Reader	reader	Message received.
MessageReceived	info	Message information.

OnNetworkRegister()

Called when this component is registered locally.

Declaration

```
public virtual void OnNetworkRegister()
```

OnNetworkRegister(NetworkComponent)

Called when any component is registered locally.

Declaration

```
public virtual void OnNetworkRegister(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Registered component.

OnNetworkResend(Peer, Peer, Reader, MessageReceived)

Called when a received message is about to be resent to a peer.

Declaration

```
public virtual bool OnNetworkResend(Peer origin, Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	origin	Original sender of the message.
Peer	peer	Peer message is being resent to.
Reader	reader	Message being resent.
MessageReceived	info	Message information.

Returns

TYPE	DESCRIPTION
System.Boolean	True to resend, false to block resending.

OnNetworkUnregister()

Called when this component is unregistered locally.

Declaration

```
public virtual void OnNetworkUnregister()
```

OnNetworkUnregister(NetworkComponent)

Called when any component is unregistered locally.

Declaration

```
public virtual void OnNetworkUnregister(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Unregistered component.

ResetNetworkID()

Reset serialized network ID to default. Editor only.

Declaration

```
protected void ResetNetworkID()
```

Run(Action)

Queue action to be ran on the main unity thread.

Declaration

```
public void Run(Action action)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.

Run(Action, Single)

Queue action to be ran on the main unity thread after a delay.

Declaration

```
public void Run(Action action, float seconds)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.
System.Single	seconds	Delay in seconds.

RunAsync(Action)

Queue action to be ran on a separate thread.

Declaration

```
public void RunAsync(Action action)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.

SendNetworkMessage(IMessage)

Send a component message to all registered peers.

Declaration

```
public void SendNetworkMessage(IMessage message)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.

SendNetworkMessage(IMessage, Predicate<Peer>)

Send a component message to all registered peers.

Declaration

```
public void SendNetworkMessage(IMessage message, Predicate<Peer> filter)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
Predicate<Peer>	filter	Predicate to filter peers.

SendNetworkMessage(IMessage, Peer[])

Send a component message to specific peers.

Declaration

```
public void SendNetworkMessage(IMessage message, params Peer[] peers)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
Peer[]	peers	Peers to send to.

SendNetworkMessage(IMessage, IEnumerable<Peer>)

Send a component message to specific peers.

Declaration

```
public void SendNetworkMessage(IMessage message, IEnumerable<Peer> peers)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
System.Collections.Generic.IEnumerable< Peer >	peers	Peers to send to.

Start()

Automatically registers the component. Do not override.

Declaration

```
protected virtual void Start()
```

Class NetworkHost

Manages a network socket and all network communication between peers.

Inheritance

System.Object
NetworkHost

Implements

IHostListener
IPeerListener

Namespace: [SuperNet.Unity.Core](#)
Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkHost : MonoBehaviour, IHostListener, IPeerListener
```

Constructors

NetworkHost()

Declaration

```
public NetworkHost()
```

Fields

AutoConnect

Remote address to connect to on startup or empty to disable.

Declaration

```
public string AutoConnect
```

Field Value

TYPE	DESCRIPTION
System.String	

AutoRegister

Automatically register all peers to the network.

Declaration

```
public bool AutoRegister
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

AutoStartup

Should the host start listening on startup.

Declaration


```
public bool AutoStartup
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

HostConfiguration

Host configuration values.

Declaration

```
public HostConfig HostConfiguration
```

Field Value

TYPE	DESCRIPTION
HostConfig	

MaxConnections

The maximum number of concurrent network connections to support.

Declaration

```
public int MaxConnections
```

Field Value

TYPE	DESCRIPTION
System.Int32	

PeerConfiguration

Peer configuration values.

Declaration

```
public PeerConfig PeerConfiguration
```

Field Value

TYPE	DESCRIPTION
PeerConfig	

PersistAcrossScenes

Do not destroy the host when loading a new Scene.

Declaration

```
public bool PersistAcrossScenes
```

Field Value

TYPE	DESCRIPTION
System.Boolean	

Properties

Allocator

Host allocator or an empty allocator if not listening.

Declaration

```
public Allocator Allocator { get; }
```

Property Value

TYPE	DESCRIPTION
Allocator	

HostEvents

Host events for this host.

Declaration

```
public HostEvents HostEvents { get; }
```

Property Value

TYPE	DESCRIPTION
HostEvents	

Listening

True if host is active and listening.

Declaration

```
public bool Listening { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

PeerEvents

Peer events for all peers.

Declaration

```
public PeerEvents PeerEvents { get; }
```

Property Value

TYPE	DESCRIPTION
PeerEvents	

Methods

Connect(IPEndPoint, IPeerListener, IWritable, Boolean)

Create a local peer and start connecting to an active remote host.

Declaration

```
public Peer Connect(IPEndPoint remote, IPeerListener listener = null, IWritable message = null, bool rethrow = false)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address to connect to.
IPeerListener	listener	Peer listener to use or null for none.
IWritable	message	Connect message to use.
System.Boolean	rethrow	Rethrow any exceptions on failure.

Returns

TYPE	DESCRIPTION
Peer	Local peer that attempts to connect or null on failure.

Connect(String)

Create a local peer and start connecting to an active remote host.

Declaration

```
public void Connect(string address)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	address	Address to connect to.

Dispose()

Instantly dispose all resources held by this host and connected peers.

Declaration

```
public void Dispose()
```

GetBindAddress()

Get address this host is listening on or loopback if none. This is usually `0.0.0.0` with the listen port.

Declaration

```
public IPEndPoint GetBindAddress()
```

Returns

TYPE	DESCRIPTION
IPEndPoint	A valid address.

GetHost()

Get netcode host or null if not listening.

Declaration

```
public Host GetHost()
```

Returns

TYPE	DESCRIPTION
Host	Netcode host.

GetLocalAddress()

Get LAN address for this host. An example is `192.168.1.10` with the listen port.

Declaration

```
public IPEndPoint GetLocalAddress()
```

Returns

TYPE	DESCRIPTION
IPEndPoint	Local address.

GetLoopbackAddress()

Get loopback address for this host. This is usually `127.0.0.1` with the listen port.

Declaration

```
public IPEndPoint GetLoopbackAddress()
```

Returns

TYPE	DESCRIPTION

TYPE	DESCRIPTION
IPEndPoint	Loopback address.

GetPeers()

Get all peers on this host.

Declaration

```
public IReadOnlyList<Peer> GetPeers()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList<Peer>	Array of all peers on this host.

SendAll(IMessage, Peer[])

Send a global message to all connected peers.

Declaration

```
public void SendAll(IMessage message, params Peer[] exclude)
```

Parameters

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
Peer[]	exclude	Peers to exclude.

SendBroadcast(Int32, IWritable)

Send an unconnected message to all machines on the local network.

Declaration

```
public void SendBroadcast(int port, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Int32	port	Network port to send to.
IWritable	message	Message to send.

SendUnconnected(IPEndPoint, IWritable)

Send an unconnected message to a remote host.

Declaration

```
public void SendUnconnected(IPEndPoint remote, IWritable message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Remote address to send to.
IWritable	message	Message to send.

SetListener(IPEndPoint, IPeerListener)

Set listener for a specific peer.

Declaration

```
public bool SetListener(IPEndPoint remote, IPeerListener listener)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	Peer remote address.
IPeerListener	listener	Listener to replace with.

Returns

TYPE	DESCRIPTION
System.Boolean	True if replaced, false if peer doesn't exist.

Shutdown()

Gracefully disconnect all peers and perform a shutdown.

Declaration

```
public void Shutdown()
```

Startup(Boolean)

Start listening.

Declaration

```
public bool Startup(bool rethrow = false)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Boolean	rethrow	Rethrow any exceptions on failure.

Returns

TYPE	DESCRIPTION
System.Boolean	True on success, false on failure.

Explicit Interface Implementations

IHostListener.OnHostException(IPEndPoint, Exception)

Declaration

```
void IHostListener.OnHostException(IPEndPoint remote, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Exception	exception	

IHostListener.OnHostReceiveBroadcast(IPEndPoint, Reader)

Declaration

```
void IHostListener.OnHostReceiveBroadcast(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Reader	message	

IHostListener.OnHostReceiveRequest(ConnectionRequest, Reader)

Declaration

```
void IHostListener.OnHostReceiveRequest(ConnectionRequest request, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
ConnectionRequest	request	
Reader	message	

IHostListener.OnHostReceiveSocket(IPEndPoint, Byte[], Int32)

Declaration

```
void IHostListener.OnHostReceiveSocket(IPEndPoint remote, byte[] buffer, int length)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
System.Byte[]	buffer	
System.Int32	length	

IHostListener.OnHostReceiveUnconnected(IPEndPoint, Reader)

Declaration

```
void IHostListener.OnHostReceiveUnconnected(IPEndPoint remote, Reader message)
```

Parameters

TYPE	NAME	DESCRIPTION
IPEndPoint	remote	
Reader	message	

IHostListener.OnHostShutdown()

Declaration

```
void IHostListener.OnHostShutdown()
```

IPeerListener.OnPeerConnect(Peer)

Declaration

```
void IPeerListener.OnPeerConnect(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	

IPeerListener.OnPeerDisconnect(Peer, Reader, DisconnectReason, Exception)

Declaration

```
void IPeerListener.OnPeerDisconnect(Peer peer, Reader message, DisconnectReason reason, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	message	
DisconnectReason	reason	

TYPE	NAME	DESCRIPTION
Exception	exception	

IPeerListener.OnPeerException(Peer, Exception)

Declaration

```
void IPeerListener.OnPeerException(Peer peer, Exception exception)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Exception	exception	

IPeerListener.OnPeerReceive(Peer, Reader, MessageReceived)

Declaration

```
void IPeerListener.OnPeerReceive(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
Reader	reader	
MessageReceived	info	

IPeerListener.OnPeerUpdateRTT(Peer, UInt16)

Declaration

```
void IPeerListener.OnPeerUpdateRTT(Peer peer, ushort rtt)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	
System.UInt16	rtt	

Implements

- [IHostListener](#)
- [IPeerListener](#)

Struct NetworkIdentity

ID used to synchronize components over network.

Implements

IComparable

IComparable<[NetworkIdentity](#)>

IEquatable<[NetworkIdentity](#)>

IFormattable

Namespace: [SuperNet.Unity.Core](#)

Assembly: cs.temp.dll.dll

Syntax

```
public struct NetworkIdentity : IComparable, IComparable<NetworkIdentity>, IEquatable<NetworkIdentity>, IFormattable
```

Constructors

NetworkIdentity(UInt32)

Create a new network ID.

Declaration

```
public NetworkIdentity(uint value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt32	value	Raw network ID.

Fields

Value

Raw network ID.

Declaration

```
public uint Value
```

Field Value

TYPE	DESCRIPTION
System.UInt32	

VALUE_INVALID

Invalid value.

Declaration

```
public const uint VALUE_INVALID = 0U
```

Field Value

TYPE	DESCRIPTION
System.UInt32	

Properties

IsValid

This ID is invalid.

Declaration

```
public bool IsValid { get; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

Methods

CompareTo(NetworkIdentity)

Declaration

```
public int CompareTo(NetworkIdentity other)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	other	

Returns

TYPE	DESCRIPTION
System.Int32	

CompareTo(Object)

Declaration

```
public int CompareTo(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Int32	

Equals(NetworkIdentity)

Declaration

```
public bool Equals(NetworkIdentity other)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	other	

Returns

TYPE	DESCRIPTION
System.Boolean	

Equals(Object)

Declaration

```
public override bool Equals(object obj)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Object	obj	

Returns

TYPE	DESCRIPTION
System.Boolean	

Overrides

System.ValueType.Equals(System.Object)

GenerateRandomID(Random)

Generate a new dynamic ID.

Declaration

```
public static NetworkIdentity GenerateRandomID(Random random)
```

Parameters

TYPE	NAME	DESCRIPTION
Random	random	Random generator to use.

Returns

TYPE	DESCRIPTION
NetworkIdentity	A new dynamic ID.

GetHashCode()

Declaration

```
public override int GetHashCode()
```

Returns

TYPE	DESCRIPTION
System.Int32	

Overrides

System.ValueType.GetHashCode()

ToString()

Declaration

```
public override string ToString()
```

Returns

TYPE	DESCRIPTION
System.String	

Overrides

System.ValueType.ToString()

ToString(String, IFormatProvider)

Declaration

```
public string ToString(string format, IFormatProvider provider)
```

Parameters

TYPE	NAME	DESCRIPTION
System.String	format	
IFormatProvider	provider	

Returns

TYPE	DESCRIPTION
System.String	

Operators

Equality(NetworkIdentity, NetworkIdentity)

Declaration

```
public static bool operator ==(NetworkIdentity lhs, NetworkIdentity rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	lhs	

TYPE	NAME	DESCRIPTION
NetworkIdentity	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Explicit(NetworkIdentity to UInt32)

Declaration

```
public static explicit operator uint (NetworkIdentity id)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	id	

Returns

TYPE	DESCRIPTION
System.UInt32	

Implicit(UInt32 to NetworkIdentity)

Declaration

```
public static implicit operator NetworkIdentity(uint value)
```

Parameters

TYPE	NAME	DESCRIPTION
System.UInt32	value	

Returns

TYPE	DESCRIPTION
NetworkIdentity	

Inequality(NetworkIdentity, NetworkIdentity)

Declaration

```
public static bool operator !=(NetworkIdentity lhs, NetworkIdentity rhs)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	lhs	
NetworkIdentity	rhs	

Returns

TYPE	DESCRIPTION
System.Boolean	

Implements

Comparable

Comparable<>

Equatable<>

Formattable

Class NetworkIdentityExtensions

Network ID Extensions.

Inheritance

System.Object

NetworkIdentityExtensions

Namespace: [SuperNet.Unity.Core](#)

Assembly: cs.temp.dll.dll

Syntax

```
public static class NetworkIdentityExtensions
```

Methods

ReadNetworkID(Reader)

Read ID from a network reader.

Declaration

```
public static NetworkIdentity ReadNetworkID(this Reader reader)
```

Parameters

TYPE	NAME	DESCRIPTION
Reader	reader	Reader to read from.

Returns

TYPE	DESCRIPTION
NetworkIdentity	ID that was read.

Write(Writer, NetworkIdentity)

Write ID to a network writer.

Declaration

```
public static void Write(this Writer writer, NetworkIdentity value)
```

Parameters

TYPE	NAME	DESCRIPTION
Writer	writer	Writer to write to.
NetworkIdentity	value	Value to write.

Class NetworkManager

Provides API access to static network methods.

Inheritance

System.Object
NetworkManager

Implements

MonoBehaviour

Namespace: [SuperNet.Unity.Core](#)

Assembly: cs.temp.dll.dll

Syntax

```
public class NetworkManager : MonoBehaviour, MonoBehaviour
```

Properties

DuplicateTimeout

How long in milliseconds to keep received messages for to check for duplicates.

Declaration

```
public static int DuplicateTimeout { get; set; }
```

Property Value

TYPE	DESCRIPTION
System.Int32	

LogEvents

Should events be logged to the debug console.

Declaration

```
public static bool LogEvents { get; set; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

LogExceptions

Should exceptions be logged to the debug console.

Declaration

```
public static bool LogExceptions { get; set; }
```

Property Value

TYPE	DESCRIPTION
System.Boolean	

TTL

Maximum number of hops each message can take before it is dropped.

Declaration

```
public static byte TTL { get; set; }
```

Property Value

TYPE	DESCRIPTION
System.Byte	

Methods

FindComponent(NetworkIdentity)

Find a registered component if it exists.

Declaration

```
public static NetworkComponent FindComponent(NetworkIdentity registerID)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	registerID	Network ID to check for.

Returns

TYPE	DESCRIPTION
NetworkComponent	Registered component or null if not found.

GetComponents()

Return all registered components.

Declaration

```
public static IReadOnlyList<NetworkComponent> GetComponents()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< NetworkComponent >	All registered components.

GetMainThread()

Get main unity thread.

Declaration

```
public static Thread GetMainThread()
```

Returns

TYPE	DESCRIPTION
Thread	Main unity thread.

GetPeers()

Return all registered peers.

Declaration

```
public static IReadOnlyList<Peer> GetPeers()
```

Returns

TYPE	DESCRIPTION
System.Collections.Generic.IReadOnlyList< Peer >	All registered peers.

Initialize()

Initialize network manager.

Declaration

```
public static void Initialize()
```

IsRegistered(Peer)

Check if peer is registered.

Declaration

```
public static bool IsRegistered(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer to check.

Returns

TYPE	DESCRIPTION
System.Boolean	True if registered, false if not.

IsRegistered(NetworkIdentity)

Check if a network ID is registered.

Declaration

```
public static bool IsRegistered(NetworkIdentity registerID)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkIdentity	registerID	Network ID to check for.

Returns

TYPE	DESCRIPTION
System.Boolean	True if registered, false if not.

Receive(Peer, Reader, MessageReceived)

Receive and process a component message.

Declaration

```
public static void Receive(Peer peer, Reader reader, MessageReceived info)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer message was received from.
Reader	reader	Message itself.
MessageReceived	info	Message information.

Register(Peer)

Register a peer to be used for sending and receiving component messages.

Declaration

```
public static void Register(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer to register.

Register(NetworkComponent)

Register a component to be able to start sending and receiving messages.

Declaration

```
public static NetworkIdentity Register(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Component to register.

Returns

TYPE	DESCRIPTION
NetworkIdentity	Registered network ID.

Register(NetworkComponent, NetworkIdentity)

Register a component to be able to start sending and receiving messages.

Declaration

```
public static NetworkIdentity Register(NetworkComponent component, NetworkIdentity registerID)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Component to register.
NetworkIdentity	registerID	Network ID to assign.

Returns

TYPE	DESCRIPTION
NetworkIdentity	Registered network ID.

RollbackBegin(HostTimestamp, Peer, Boolean, Boolean)

Update the state of all components to be the same as in the past.

Declaration

```
public static void RollbackBegin(HostTimestamp time, Peer peer, bool persist = false, bool includeDisabled = false)
```

Parameters

TYPE	NAME	DESCRIPTION
HostTimestamp	time	Which timestamp in the past to rollback to.
Peer	peer	Peer that we're performing the rollback for.

TYPE	NAME	DESCRIPTION
System.Boolean	persist	If true, persist this rollback across multiple frames.
System.Boolean	includeDisabled	If true, include disabled components.

RollbackBegin(IEnumerable<NetworkComponent>, HostTimestamp, Peer, Boolean, Boolean)

Update the state of all provided components to be the same as in the past.

Declaration

```
public static void RollbackBegin(IEnumerable<NetworkComponent> components, HostTimestamp time, Peer peer, bool persist = false, bool includeDisabled = false)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Collections.Generic.IEnumerable<NetworkComponent>	components	Components to update.
HostTimestamp	time	Which timestamp in the past to rollback to.
Peer	peer	Peer that we're performing the rollback for.
System.Boolean	persist	If true, persist this rollback across multiple frames.
System.Boolean	includeDisabled	If true, include disabled components.

RollbackEnd()

Revert all rollbacks.

Declaration

```
public static void RollbackEnd()
```

RollbackEnd(IEnumerable<NetworkComponent>)

Revert any rollbacks.

Declaration

```
public static void RollbackEnd(IEnumerable<NetworkComponent> components)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Collections.Generic.IEnumerable< NetworkComponent >	components	Components to revert for.

Run(Action)

Queue action to be ran on the main unity thread.

Declaration

```
public static void Run(Action action)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.

Run(Action, Single)

Queue action to be ran on the main unity thread after a delay.

Declaration

```
public static void Run(Action action, float seconds)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.
System.Single	seconds	Delay in seconds.

Run(IEnumerator)

Queue a coroutine to be ran on the main unity thread.

Declaration

```
public static Coroutine Run(IEnumerator routine)
```

Parameters

TYPE	NAME	DESCRIPTION
System.Collections.Generic.IEnumerator	routine	Routine to run.

Returns

TYPE	DESCRIPTION
Coroutine	The created coroutine.

RunAsync(Action)

Queue action to be ran on a separate thread.

Declaration

```
public static void RunAsync(Action action)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.

RunAsync(Action, CancellationToken)

Queue action to be ran on a separate thread.

Declaration

```
public static void RunAsync(Action action, CancellationToken token)
```

Parameters

TYPE	NAME	DESCRIPTION
Action	action	Action to run.
CancellationToken	token	Cancellation token to use.

RunAsync(Func<Task>, CancellationToken, Int32)

Queue task to be ran on a separate thread after a delay.

Declaration

```
public static void RunAsync(Func<Task> action, CancellationToken token, int millisecondsDelay = 0)
```

Parameters

TYPE	NAME	DESCRIPTION
Func<Task>	action	Task to run.
CancellationToken	token	Cancellation token to use.

TYPE	NAME	DESCRIPTION
System.Int32	millisecondsDelay	Delay in milliseconds.

RunAsync(Func<Task>, Int32)

Queue task to be ran on a separate thread after a delay.

Declaration

```
public static void RunAsync(Func<Task> action, int millisecondsDelay = 0)
```

Parameters

TYPE	NAME	DESCRIPTION
Func<Task>	action	Task to run.
System.Int32	millisecondsDelay	Delay in milliseconds.

Send(NetworkComponent, IMessage)

Send a component message to all registered peers.

Declaration

```
public static void Send(NetworkComponent component, IMessage message)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Registered component to send through.
IMessage	message	Message to send.

Send(NetworkComponent, IMessage, Predicate<Peer>)

Send a component message to all registered peers.

Declaration

```
public static void Send(NetworkComponent component, IMessage message, Predicate<Peer> filter)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Registered component to send through.

TYPE	NAME	DESCRIPTION
IMessage	message	Message to send.
Predicate< Peer >	filter	Predicate to filter peers.

Send(NetworkComponent, IMessage, Peer[])

Send a component message to specific peers.

Declaration

```
public static void Send(NetworkComponent component, IMessage message, params Peer[] peers)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Registered component to send through.
IMessage	message	Message to send.
Peer []	peers	Peers to send to.

Send(NetworkComponent, IMessage, IEnumerable<Peer>)

Send a component message to specific peers.

Declaration

```
public static void Send(NetworkComponent component, IMessage message, IEnumerable<Peer> peers)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Registered component to send through.
IMessage	message	Message to send.
System.Collections.Generic.IEnumerable< Peer >	peers	Peers to send to.

Unregister(Peer)

Unregister a peer to stop being used for sending component messages.

Declaration

```
public static void Unregister(Peer peer)
```

Parameters

TYPE	NAME	DESCRIPTION
Peer	peer	Peer to unregister.

Unregister(NetworkComponent)

Unregister a component and make it stop receiving messages.

Declaration

```
public static void Unregister(NetworkComponent component)
```

Parameters

TYPE	NAME	DESCRIPTION
NetworkComponent	component	Component to unregister.

Implements

MonoBehaviour

Namespace SuperNet.Unity.Editor

Classes

[NetworkAuthorityEditor](#)

[NetworkHostEditor](#)

[NetworkIdentityDrawer](#)

[NetworkManagerEditor](#)

[NetworkPrefabEditor](#)

[NetworkSpawnerEditor](#)

Enums

[NetworkHostEditor.BandwithUnit](#)

Class NetworkAuthorityEditor

Inheritance

System.Object

NetworkAuthorityEditor

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkAuthorityEditor : UnityEditor.Editor
```

Methods

OnInspectorGUI()

Declaration

```
public override void OnInspectorGUI()
```

Class NetworkHostEditor

Inheritance

System.Object

NetworkHostEditor

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkHostEditor : UnityEditor.Editor
```

Methods

OnInspectorGUI()

Declaration

```
public override void OnInspectorGUI()
```

Enum NetworkHostEditor.BandwidthUnit

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public enum BandwidthUnit
```

Fields

NAME	DESCRIPTION
BitsPerSecond	
BytesPerSecond	
KilobitsPerSecond	
KilobytesPerSecond	
MegabitsPerSecond	
MegabytesPerSecond	

Class NetworkIdentityDrawer

Inheritance

System.Object

NetworkIdentityDrawer

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkIdentityDrawer : PropertyDrawer
```

Methods

GetPropertyHeight(SerializedProperty, GUIContent)

Declaration

```
public override float GetPropertyHeight(SerializedProperty property, GUIContent label)
```

Parameters

TYPE	NAME	DESCRIPTION
SerializedProperty	property	
GUIContent	label	

Returns

TYPE	DESCRIPTION
System.Single	

OnGUI(Rect, SerializedProperty, GUIContent)

Declaration

```
public override void OnGUI(Rect position, SerializedProperty property, GUIContent label)
```

Parameters

TYPE	NAME	DESCRIPTION
Rect	position	
SerializedProperty	property	
GUIContent	label	

Class NetworkManagerEditor

Inheritance

System.Object

NetworkManagerEditor

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkManagerEditor : UnityEditor.Editor
```

Methods

OnInspectorGUI()

Declaration

```
public override void OnInspectorGUI()
```

Class NetworkPrefabEditor

Inheritance

System.Object

NetworkPrefabEditor

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkPrefabEditor : UnityEditor.Editor
```

Methods

OnInspectorGUI()

Declaration

```
public override void OnInspectorGUI()
```

Class NetworkSpawnerEditor

Inheritance

System.Object

NetworkSpawnerEditor

Namespace: [SuperNet.Unity.Editor](#)

Assembly: cs.temp.dll.dll

Syntax

```
public sealed class NetworkSpawnerEditor : UnityEditor.Editor
```

Methods

OnInspectorGUI()

Declaration

```
public override void OnInspectorGUI()
```