

---

# An Introduction of Support Vector Machine

---

Jinwei Gu  
2008/10/16

---

# Review: What We've Learned So Far

- Bayesian Decision Theory
  - Maximum-Likelihood & Bayesian Parameter Estimation
  - Nonparametric Density Estimation
    - Parzen-Window,  $k_n$ -Nearest-Neighbor
  - K-Nearest Neighbor Classifier
  - Decision Tree Classifier
-

# Today: Support Vector Machine (SVM)

- A classifier derived from statistical learning theory by Vapnik, et al. in 1992
- SVM became famous when, using images as input, it gave accuracy comparable to neural-network with hand-designed features in a handwriting recognition task
- Currently, SVM is widely used in object detection & recognition, content-based image retrieval, text recognition, biometrics, speech recognition, etc.
- Also used for regression (will not cover today)
- Chapter 5.1, 5.2, 5.3, 5.11 (5.4\*) in textbook



V. Vapnik

---

# Outline

- Linear Discriminant Function
  - Large Margin Linear Classifier
  - Nonlinear SVM: The Kernel Trick
  - Demo of SVM
-

# Discriminant Function

- Chapter 2.4: the classifier is said to assign a feature vector  $\mathbf{x}$  to class  $w_j$  if

$$g_i(\mathbf{x}) > g_j(\mathbf{x}) \quad \text{for all } j \neq i$$

- For two-category case,  $g(\mathbf{x}) \equiv g_1(\mathbf{x}) - g_2(\mathbf{x})$


Decide  $\omega_1$  if  $g(\mathbf{x}) > 0$ ; otherwise decide  $\omega_2$

- An example we've learned before:
  - Minimum-Error-Rate Classifier


$$g(\mathbf{x}) \equiv p(\omega_1 | \mathbf{x}) - p(\omega_2 | \mathbf{x})$$

# Discriminant Function


- It can be arbitrary functions of  $\mathbf{x}$ , such as:



Nearest  
Neighbor




Decision  
Tree



Linear  
Functions

$$g(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b$$



Nonlinear  
Functions


# Linear Discriminant Function

- $g(\mathbf{x})$  is a linear function:

$$g(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b$$


- A hyper-plane in the feature space
- (Unit-length) normal vector of the hyper-plane:

$$\mathbf{n} = \frac{\mathbf{w}}{\|\mathbf{w}\|}$$



# Linear Discriminant Function


- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!






# Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!




# Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!




# Linear Discriminant Function

- How would you classify these points using a linear discriminant function in order to minimize the error rate?
- Infinite number of answers!
- Which one is the best?



# Large Margin Linear Classifier

- The linear discriminant function (classifier) with the maximum **margin** is the best
- Margin is defined as the width that the boundary could be increased by before hitting a data point
- Why it is the best?
  - Robust to outliers and thus strong generalization ability



# Large Margin Linear Classifier

● denotes +1  
○ denotes -1

- Given a set of data points:  
 $\{(\mathbf{x}_i, y_i)\}$ ,  $i = 1, 2, \dots, n$ , where


For  $y_i = +1$ ,  $\mathbf{w}^T \mathbf{x}_i + b > 0$

For  $y_i = -1$ ,  $\mathbf{w}^T \mathbf{x}_i + b < 0$

- With a scale transformation on both  $\mathbf{w}$  and  $b$ , the above is equivalent to

For  $y_i = +1$ ,  $\mathbf{w}^T \mathbf{x}_i + b \geq 1$

For  $y_i = -1$ ,  $\mathbf{w}^T \mathbf{x}_i + b \leq -1$



# Large Margin Linear Classifier

- We know that


$$\mathbf{w}^T \mathbf{x}^+ + b = 1$$

$$\mathbf{w}^T \mathbf{x}^- + b = -1$$

- The margin width is:

$$M = (\mathbf{x}^+ - \mathbf{x}^-) \cdot \mathbf{n}$$

$$= (\mathbf{x}^+ - \mathbf{x}^-) \cdot \frac{\mathbf{w}}{\|\mathbf{w}\|} = \frac{2}{\|\mathbf{w}\|}$$



# Large Margin Linear Classifier


## ■ Formulation:

$$\text{maximize } \frac{2}{\|\mathbf{w}\|}$$

such that

$$\text{For } y_i = +1, \quad \mathbf{w}^T \mathbf{x}_i + b \geq 1$$

$$\text{For } y_i = -1, \quad \mathbf{w}^T \mathbf{x}_i + b \leq -1$$



# Large Margin Linear Classifier


## ■ Formulation:

$$\text{minimize } \frac{1}{2} \|\mathbf{w}\|^2$$

such that

$$\text{For } y_i = +1, \quad \mathbf{w}^T \mathbf{x}_i + b \geq 1$$

$$\text{For } y_i = -1, \quad \mathbf{w}^T \mathbf{x}_i + b \leq -1$$






# Large Margin Linear Classifier

## ■ Formulation:

$$\text{minimize } \frac{1}{2} \|\mathbf{w}\|^2$$

such that

$$y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1$$




# Solving the Optimization Problem

Quadratic  
programming  
with linear  
constraints

$$\begin{aligned} &\text{minimize} \quad \frac{1}{2} \|\mathbf{w}\|^2 \\ &\text{s.t.} \quad y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1 \end{aligned}$$

Lagrangian  
Function



$$\begin{aligned} &\text{minimize} \quad L_p(\mathbf{w}, b, \alpha_i) = \frac{1}{2} \|\mathbf{w}\|^2 - \sum_{i=1}^n \alpha_i (y_i (\mathbf{w}^T \mathbf{x}_i + b) - 1) \\ &\text{s.t.} \quad \alpha_i \geq 0 \end{aligned}$$

# Solving the Optimization Problem

$$\begin{aligned} \text{minimize } L_p(\mathbf{w}, b, \alpha_i) &= \frac{1}{2} \|\mathbf{w}\|^2 - \sum_{i=1}^n \alpha_i (y_i (\mathbf{w}^T \mathbf{x}_i + b) - 1) \\ \text{s.t. } \alpha_i &\geq 0 \end{aligned}$$


$$\frac{\partial L_p}{\partial \mathbf{w}} = 0 \quad \longrightarrow \quad \mathbf{w} = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i$$

$$\frac{\partial L_p}{\partial b} = 0 \quad \longrightarrow \quad \sum_{i=1}^n \alpha_i y_i = 0$$

# Solving the Optimization Problem

$$\begin{aligned} \text{minimize } L_p(\mathbf{w}, b, \alpha_i) &= \frac{1}{2} \|\mathbf{w}\|^2 - \sum_{i=1}^n \alpha_i (y_i (\mathbf{w}^T \mathbf{x}_i + b) - 1) \\ \text{s.t. } \alpha_i &\geq 0 \end{aligned}$$

Lagrangian Dual  
Problem



$$\begin{aligned} \text{maximize } \sum_{i=1}^n \alpha_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j \\ \text{s.t. } \alpha_i \geq 0, \text{ and } \sum_{i=1}^n \alpha_i y_i = 0 \end{aligned}$$

# Solving the Optimization Problem

- From KKT condition, we know:


$$\alpha_i (y_i (\mathbf{w}^T \mathbf{x}_i + b) - 1) = 0$$

- Thus, only support vectors have  $\alpha_i \neq 0$

- The solution has the form:

$$\mathbf{w} = \sum_{i=1}^n \alpha_i y_i \mathbf{x}_i = \sum_{i \in \text{SV}} \alpha_i y_i \mathbf{x}_i$$

get  $b$  from  $y_i (\mathbf{w}^T \mathbf{x}_i + b) - 1 = 0$ ,  
where  $\mathbf{x}_i$  is support vector



# Solving the Optimization Problem


- The linear discriminant function is:

$$g(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b = \sum_{i \in \text{SV}} \alpha_i \mathbf{x}_i^T \mathbf{x} + b$$

- Notice it relies on a *dot product* between the test point  $\mathbf{x}$  and the support vectors  $\mathbf{x}_i$
- Also keep in mind that solving the optimization problem involved computing the *dot products*  $\mathbf{x}_i^T \mathbf{x}_j$  between all pairs of training points

# Large Margin Linear Classifier

- What if data is not linear separable? (noisy data, outliers, etc.)
- Slack variables  $\xi_i$  can be added to allow misclassification of difficult or noisy data points



# Large Margin Linear Classifier

- Formulation:

$$\text{minimize } \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^n \xi_i$$

such that

$$y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1 - \xi_i$$

$$\xi_i \geq 0$$

- Parameter  $C$  can be viewed as a way to control over-fitting.
-



# Large Margin Linear Classifier

- Formulation: (Lagrangian Dual Problem)

$$\text{maximize } \sum_{i=1}^n \alpha_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$$


such that

$$0 \leq \alpha_i \leq C$$

$$\sum_{i=1}^n \alpha_i y_i = 0$$

# Non-linear SVMs


- Datasets that are linearly separable with noise work out great:



- But what are we going to do if the dataset is just too hard?




- How about... mapping data to a higher-dimensional space:



# Non-linear SVMs: Feature Space

- General idea: the original input space can be mapped to some higher-dimensional feature space where the training set is separable:



# Nonlinear SVMs: The Kernel Trick

- With this mapping, our discriminant function is now:

$$g(\mathbf{x}) = \mathbf{w}^T \phi(\mathbf{x}) + b = \sum_{i \in SV} \alpha_i \boxed{\phi(\mathbf{x}_i)^T \phi(\mathbf{x})} + b$$

- No need to know this mapping explicitly, because we only use the **dot product** of feature vectors in both the training and test.
- A **kernel function** is defined as a function that corresponds to a dot product of two feature vectors in some expanded feature space:

$$K(\mathbf{x}_i, \mathbf{x}_j) \equiv \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$$

# Nonlinear SVMs: The Kernel Trick

- An example:

2-dimensional vectors  $\mathbf{x}=[x_1 \ x_2]$ ;

let  $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^2$ ,

Need to show that  $K(\mathbf{x}_i, \mathbf{x}_j) = \boldsymbol{\varphi}(\mathbf{x}_i)^T \boldsymbol{\varphi}(\mathbf{x}_j)$ :

$$\begin{aligned} K(\mathbf{x}_i, \mathbf{x}_j) &= (1 + \mathbf{x}_i^T \mathbf{x}_j)^2, \\ &= 1 + x_{i1}^2 x_{j1}^2 + 2 x_{i1} x_{j1} x_{i2} x_{j2} + x_{i2}^2 x_{j2}^2 + 2 x_{i1} x_{j1} + 2 x_{i2} x_{j2} \\ &= [1 \ x_{i1}^2 \ \sqrt{2} x_{i1} x_{i2} \ x_{i2}^2 \ \sqrt{2} x_{i1} \ \sqrt{2} x_{i2}]^T [1 \ x_{j1}^2 \ \sqrt{2} x_{j1} x_{j2} \ x_{j2}^2 \ \sqrt{2} x_{j1} \ \sqrt{2} x_{j2}] \\ &= \boldsymbol{\varphi}(\mathbf{x}_i)^T \boldsymbol{\varphi}(\mathbf{x}_j), \quad \text{where } \boldsymbol{\varphi}(\mathbf{x}) = [1 \ x_1^2 \ \sqrt{2} x_1 x_2 \ x_2^2 \ \sqrt{2} x_1 \ \sqrt{2} x_2] \end{aligned}$$

# Nonlinear SVMs: The Kernel Trick

- Examples of commonly-used kernel functions:

- Linear kernel:  $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$

- Polynomial kernel:  $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^p$

- Gaussian (Radial-Basis Function (RBF) ) kernel:

$$K(\mathbf{x}_i, \mathbf{x}_j) = \exp\left(-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right)$$

- Sigmoid:

$$K(\mathbf{x}_i, \mathbf{x}_j) = \tanh(\beta_0 \mathbf{x}_i^T \mathbf{x}_j + \beta_1)$$

- In general, functions that satisfy *Mercer's condition* can be kernel functions.

# Nonlinear SVM: Optimization

- Formulation: (Lagrangian Dual Problem)

$$\text{maximize } \sum_{i=1}^n \alpha_i - \frac{1}{2} \sum_{i=1}^n \sum_{j=1}^n \alpha_i \alpha_j y_i y_j K(\mathbf{x}_i, \mathbf{x}_j)$$

such that

$$0 \leq \alpha_i \leq C$$

$$\sum_{i=1}^n \alpha_i y_i = 0$$

- The solution of the discriminant function is

$$g(\mathbf{x}) = \sum_{i \in \text{SV}} \alpha_i K(\mathbf{x}_i, \mathbf{x}) + b$$

- The optimization technique is the same.

---

# Support Vector Machine: Algorithm

- 1. Choose a kernel function
  - 2. Choose a value for  $C$
  - 3. Solve the quadratic programming problem  
(many software packages available)
  - 4. Construct the discriminant function from the support vectors
-



# Some Issues

- Choice of kernel
  - Gaussian or polynomial kernel is default
  - if ineffective, more elaborate kernels are needed
  - domain experts can give assistance in formulating appropriate similarity measures
- Choice of kernel parameters
  - e.g.  $\sigma$  in Gaussian kernel
  - $\sigma$  is the distance between closest points with different classifications
  - In the absence of reliable criteria, applications rely on the use of a validation set or cross-validation to set such parameters.
- Optimization criterion – Hard margin v.s. Soft margin
  - a lengthy series of experiments in which various parameters are tested

---

# Summary: Support Vector Machine

- 1. Large Margin Classifier
    - Better generalization ability & less over-fitting
  - 2. The Kernel Trick
    - Map data points to higher dimensional space in order to make them linearly separable.
    - Since only dot product is used, we do not need to represent the mapping explicitly.
-

---

# Additional Resource

- <http://www.kernel-machines.org/>

---

# Demo of LibSVM

---

<http://www.csie.ntu.edu.tw/~cjlin/libsvm/>