



Shell commands for process management


Stefano Quer and Pietro Laface

Dipartimento di Automatica e Informatica

Politecnico di Torino


Foreground execution

- ❖ The standard shell commands
 - Allow executing processes **sequentially**
 - Each process is executed in **foreground**, i.e., using the control terminal



Background execution

- ❖ The shell interpret character & as an indication to run the command in **background**
 - The process is executed in concurrency with the shell. It loses the control terminal input
 - The shell outputs immediately a new prompt
 - It is possible to run several processes in parallel



Process status commands

❖ Two main commands

➤ **ps (process status)**

ps <options>

- List active processes and some related information li
- Options
 - -e (or -A) List all processes
 - -f Extended format
 - r (not -r) Shows only the "running" processes
 - -u <user> Shows only the <user> processes

kill command

- ❖ **kill** allows sending signal from the shell
- ❖ **Format**
 - **kill** [**-sig**] **pid**
 - Sends signal **sig** to process with PID=**pid**
 - Option **sig** indicates the signal code
 - **pid** is the process identifier (PID) of the target process
 - The default signal of **kill** is **SIGTERM**, the standard termination command

kill command

- ❖ A signal **sig** can be indicated by means of its name or by its corresponding number
 - The list of the available signals can be obtained using the **-l** option
 - `SIGKILL = KILL = 9`
 - `SIGUSR1 = USR1 = 10`
 - `SIGUSR2 = USR2 = 12`
 - `SIGALRM = ALRM = 14`
 - etc.

kill command

❖ Examples

- `kill -l`
- `kill -9 10234`
- `kill -SIGKILL 10234`
- `kill -KILL 10234`

List available signals

Three commands to terminate process with PID 10234

❖ Shell command `killall` terminates all process with a specified name

- `killall -9 name`

➤ Useful to terminate all processes generated by the same program avoiding to specify their PIDs