

ساختمان داده و الگوریتم ها

مبحث نهم:
صف

سجاد شیرعلی شهرضا

بهار، 1402

شنبه، 6 آبان 1402

اطلاع رسانی

- بخش مرتبط کتاب برای این جلسه: 10
- امتحانک دوم
 - دوشنبه هفته آینده (15 آبان 1402)
 - در ساعت کلاس
 - در محل کلاس

سُورَةُ الصَّافَّاتِ

بِسْمِ اللَّهِ الرَّحْمَنِ الرَّحِيمِ

وَالصَّافَّاتِ صَفًّا ۝

صف

مجموعه ای از اشیاء پشت سر هم قرار گرفته


Idea

Banks'R'Us



(a) A queue (line) of people

Remove
(dequeue)




Insert
(enqueue)

(b) A computer queue

Queue ADT



- Represents an ordered sequence of elements
- Elements can only be added from one end and removed from the other
- First-In, First-Out (FIFO)
- Elements stored in order of insertion



QUEUE ADT


State

Collection of ordered items
Count of items



Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

Operations




Operations




پیاده سازی صف با لیست پیوندی

Linked-list Implementation



(a) Conceptual queue



(b) Physical queue

Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

0

front →

back →

Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

0

add(5)

front →

back →

Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

1

add(5)

front



back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

1

add(5)

add(8)

front



back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior


add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

2

add(5)

add(8)



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0


size =

2

add(5)

add(8)

remove()



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

size =

1

add(5)

add(8)

remove()

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove()

peek()

size()

isEmpty()

add()

add(5)

add(8)

remove()

size =

1

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove() O(1) Constant

peek()

size()

isEmpty()

add()

add(5)

add(8)

remove()

size =

1

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove() O(1) Constant

peek() O(1) Constant

size()

isEmpty()

add()

size =

1

add(5)

add(8)

remove()

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove() O(1) Constant
peek() O(1) Constant
size() O(1) Constant
isEmpty()
add()

add(5)

add(8)

remove()

size =

1

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove()	O(1) Constant
peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	

add(5)

add(8)


remove()

size =

1

front

back



Implementing a Queue with Linked Nodes

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

LinkedList<E>

State

Node front
Node back
size

Behavior

add - add node to back
remove - return and remove
node at front
peek - return node at front
size - return size
isEmpty - return size == 0

Big-Oh Analysis

remove()	O(1) Constant
peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	O(1) Constant

add(5)

add(8)

remove()

size =

1

front

back






سوال؟

پیاده سازی صف با آرایه

Idea

Queue



Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?


ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0



size =

0

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>


State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)



size =

0

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

0	1	2	3	4
5				

size =

1

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

0	1	2	3	4
5				

size =

1

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

0	1	2	3	4
5	8			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

add(9)

0	1	2	3	4
5	8			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

add(9)

0	1	2	3	4
5	8	9		

size =

3

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
5	8	9		

size =

3

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()

size()

isEmpty()

add()

remove()

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant

size()

isEmpty()

add()

remove()

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant

size() O(1) Constant

isEmpty()

add()

remove()

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant
size() O(1) Constant
isEmpty() O(1) Constant
add()
remove()

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant

size() O(1) Constant

isEmpty() O(1) Constant

add() What are different cases?

remove()

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	O(n) Linear: if we need to resize O(1) Constant: otherwise
remove()	

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2

Implementing a Queue with an Array

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV1<E>

State

data[]
size

Behavior

add - data[size] = value,
if out of room grow
remove - return/remove at
0, shift everything
peek - return node at 0
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	O(n) Linear: if we need to resize O(1) Constant: otherwise
remove()	O(n) Linear

add(5)

add(8)

add(9)

remove()

0	1	2	3	4
8	9			

size =

2



سوال؟

Data Structure Invariants

- Invariant: a property of a data structure that is always true between operations
 - True when finishing any operation
 - It can be counted on to be true when starting an operation

Data Structure Invariants

- Invariant: a property of a data structure that is always true between operations
 - True when finishing any operation
 - It can be counted on to be true when starting an operation
- ArrayQueue is basically an ArrayList
- What invariants does ArrayList have for its data array?



Data Structure Invariants

- Invariant: a property of a data structure that is always true between operations
 - True when finishing any operation
 - It can be counted on to be true when starting an operation
- ArrayQueue is basically an ArrayList
- What invariants does ArrayList have for its data array?
 - The i -th item in the list is stored in `data[i]`


Data Structure Invariants

- Invariant: a property of a data structure that is always true between operations
 - True when finishing any operation
 - It can be counted on to be true when starting an operation
- ArrayQueue is basically an ArrayList
- What invariants does ArrayList have for its data array?
 - The i -th item in the list is stored in `data[i]`
- Notice: serving this invariant is what slows down the operation.
- Could we choose a different invariant?

Circular Array




Wrapping Around with “front” and “back” indices




Wrapping Around with “front” and “back” indices

add(7)



Wrapping Around with “front” and “back” indices


add(7)



Wrapping Around with “front” and “back” indices

add(7)


add(4)



Wrapping Around with “front” and “back” indices

add(7)

add(4)




Wrapping Around with “front” and “back” indices

add(7)

add(4)

add(1)



Wrapping Around with “front” and “back” indices

add(7)

add(4)

add(1)

0	1	2	3	4
4	5	9	2	7

numberOfItems =

5


front				back					
0	1	2	3	4	5	6	7	8	9
5	9	2	7	4					

Wrapping Around with “front” and “back” indices

add(7)

add(4)

add(1)




Wrapping Around with “front” and “back” indices

add(7)

add(4)

add(1)

remove()




Wrapping Around with “front” and “back” indices

add(7)

add(4)

add(1)

remove()



Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()
size()
isEmpty()
add()
remove()

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant

size()

isEmpty()

add()

remove()

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek() O(1) Constant

size() O(1) Constant

isEmpty()

add()

remove()

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	
remove()	

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis

peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	O(n) Linear: if we need to resize O(1) Constant: otherwise
remove()	

Implementing a Queue with an Array (v2)

QUEUE ADT

State

Collection of ordered items
Count of items

Behavior

add(item) add item to back
remove() remove and return
item at front
peek() return item at front
size() count of items
isEmpty() count is 0?

ArrayQueueV2<E>

State

data[], front,
size, back

Behavior

add - data[back] = value,
back++, size++, if out of
room grow
remove - return data[front],
size--, front++
peek - return data[front]
size - return size
isEmpty - return size == 0

Big-Oh Analysis


peek()	O(1) Constant
size()	O(1) Constant
isEmpty()	O(1) Constant
add()	O(n) Linear: if we need to resize O(1) Constant: otherwise
remove()	O(1) Constant



سوال؟


ADTs & Data Structures

- ADT can be implemented by multiple data structures




ADTs & Data Structures

- ADT can be implemented by multiple data structures
- Data structure can implement multiple ADTs



ADTs & Data Structures

- ADT can be implemented by multiple data structures
- Data structure can implement multiple ADTs
 - But the ADT decides how it can be used
 - An ArrayList used as a List should support get()
 - An ArrayList used as a Stack should not support get()





سوال؟