

Configuration du switch :

configuration contre accès non autoriser :

Mot de passe enable :

commande : enable secret aurevoir1234

```
switchap2(config-line)#enable secret aurevoir1234
```

Mot de passe configure terminal :

commande : username administrateur secret bonjour1234

```
Switch(config)#username administrateur secret bonjour1234
Switch(config)#line console 0
Switch(config-line)#login local
Switch(config-line)#exit
Switch(config)#
```

administrateur = username
et password = bonjour1234

Vlans :

commande :

vlan « numero »
name »nomchoisie »
exit

Affectation a un port :

commande :

interface (nom du port)
switchport mode access
switchport access vlan(numéro du vlan)
exit

commande pour voir les vlans :

« show running-config »

```
spanning-tree mode pvst
spanning-tree extend system-id
!
interface FastEthernet0/1
 switchport access vlan 2
 switchport mode access
!
interface FastEthernet0/2
 switchport access vlan 3
 switchport mode access
!
interface FastEthernet0/3
 switchport access vlan 4
 switchport mode access
!
interface FastEthernet0/4
 switchport access vlan 5
 switchport mode access
!
interface FastEthernet0/5
 switchport access vlan 6
 switchport mode access
!
interface FastEthernet0/6
 switchport access vlan 7
 switchport mode access
!
interface FastEthernet0/7
 switchport access vlan 8
 switchport mode access
!
interface FastEthernet0/8
 switchport access vlan 9
 switchport mode access
!
interface FastEthernet0/9
 switchport access vlan 10
 switchport mode access
!
interface FastEthernet0/10
 switchport access vlan 11
 switchport mode access
!
interface FastEthernet0/11
 switchport access vlan 12
 switchport mode access
!
interface FastEthernet0/12
 switchport access vlan 13
 switchport mode access
!
```

Montrer les vlans :

commande :

« show vlan »

VLAN	Name	Status	Ports
1	default	active	Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
2	basket	active	Fa0/1
3	volley-ball	active	Fa0/2
4	football	active	Fa0/3
5	curling	active	Fa0/4
6	LoL	active	Fa0/5
7	salle-ressource	active	Fa0/6
8	acces-sans-fil	active	Fa0/7
9	salle-rmba	active	Fa0/8
10	ecran-affichage	active	Fa0/9
11	DMZ	active	Fa0/10
12	serveur-commutateur	active	Fa0/11
13	service-informatique	active	Fa0/12
1002	fddi-default	active	
1003	token-ring-default	active	
1004	fddinet-default	active	
--More--			

j'ai passé les vlans en mode trunk :

commande :

« interface range fa0/1-fa0/12
switchport mode trunk »

Routeur :encapsulation :

commande :

« interface(nomport) numero du vid
encapsulation dot1q vid
ip adress + mask
exit

puis show running-config

pour rentrer sur le routeur :

mot de passe : bonjour1234

pour aller dans enable :

mot de passe = aurevoir123456789

Pour verifier si on a bien le ssh fonctionnel :

commande : show ip ssh

show ip interface brief

(même chose pour le switch)