

EE5176 Programming Assignment 2: Motion Deblurring

Purvam Jain, ee20b101@smail.iitm.ac.in

Note:

1. Please use Moodle discussion threads for posting your doubts and also check it before sending emails to TAs, as the same question might have been asked earlier.
 2. Submit a single zip file named as PA2_Rollno.zip containing a report and folders containing corresponding codes¹.
 3. Read the problem fully to understand the whole procedure.
 4. Late submissions will be evaluated for reduced marks and for each day after the deadline we will reduce the weightage by 10%.
-

1 Motion deblurring with conventional camera

You are given a clean image of a scene having M rows and N columns (fish.png). We capture the scene using a static conventional camera with the aperture kept open for the full exposure time. The exposure time is 52 seconds. For simplicity, consider that the camera captures the scene at times $t = 0, \dots, 51$ (i.e. at 52 instants). At time $t = 0$, the image has zero translation. Then, the whole image as seen by the camera moves at 1 pixel per second to the right (horizontal translation).

- a) Generate the blurred image having M rows and $N + 51$ columns captured by the camera. Generate translated versions of the image for $t = 0, \dots, 51$, and average them. Add Gaussian noise of mean 0 and standard deviation 1 (with respect to the maximum intensity of 255) from gaussNoise.mat. Display the blurred image. [5 marks]

¹ Kindly refrain from using formats like .rar, .7z, etc

- $$RMSE(x, y) = \sqrt{\sum_i \frac{(x_i - y_i)^2}{length(x)}}. \text{ [5 marks]}$$

- e) Using the formula given in part c of Question 1, find the RMSE for the deblurred image compared to the original for both the flutter shutter codes. Comment on your result and explain why there is a difference. [2 marks]
- f) Let the noise be absent in both problems (1) and (2). Compare and comment on the deblurred outputs. [4 marks]

3 Deblurring with motion-invariant photography

You are given images of the top view of a road scene (background.png) and a foreground moving object (redcar.png).

- a) Assuming static camera and the velocity of the car as 1 pixel per second to the right (horizontal translation) relative to a static camera, generate the blurred image captured for an exposure time of 52 seconds. (Hint: First create individual frames for each second, i.e. 52 frames. To create each frame, apply translation corresponding to that frame on the foreground object and merge it with background. Merging: For all pixels with a non-zero values in the foreground image, assign foreground pixel values. or else use background pixel values.) [3 marks]
- b) Consider the same scenario captured using motion invariant photography (i.e. the camera also moves during the exposure). The translational values of the static background due to camera motion at each second are given in CameraT.mat. Generate the blurred image captured in this case with both camera and object motions for an exposure time of 52 seconds. [6 marks]
 - Create individual frames for each second: Apply camera translations to the background image and the relative translations to the moving object separately. Then, merge them to obtain a frame. The relative translations of the moving object with respect to the moving camera can be obtained by *relative translation = static background translation due to camera - object translation*
 - Average all the 52 frames to obtain the blurred image.

- c) Compare and comment on the outputs of (a) and (b). [2 marks]
- d) Find and plot the PSF of the blurred image in (b). If x is the camera translation then PSF weight at x is $\frac{1}{\sqrt{ax}}$. Choose x as $[0.1, 1, 2, \dots, 51]$ and $a = \frac{1}{13}$. Normalize the PSF after assigning these values. [2 marks]
- e) Use the PSF obtained in (d) to form the blur matrix **A**. [2 marks]
- f) Deblur the blurred image in (b) using least squares. [2 marks]