

Galaxy Surfactants Ltd.

C-49/2, TTC Industrial Area, Pawne, Navi Mumbai-400 703, India.

Tel No : +91-22- 65134444/27616666

Fax : +91-22- 27615883/27615886

Email : galaxy@galaxysurfactants.com

Website : www.galaxysurfactants.com

**TECHNICAL DATA SHEET****Product Name****Phenoxyethanol P5****DESCRIPTION**

Chemical Name	: Phenoxyethanol
INCI Name	: Phenoxyethanol
Other names	: Ethylene Glycol Phenyl Ether, Phenyl Cellosolve
CAS Number	: 122-99-6
EC Number	: 204-589-7
Chemical Formula	: $C_6H_5O-CH_2CH_2OH$

TECHNICAL SPECIFICATIONS

Appearance / Nature	: Clear, low viscous liquid
Odour	: Characteristic
Colour	
a) description	: Colourless
b) on Lovibond (5¼" cell, on Y+R), maximum	: 0.5
pH (1% aqueous solution)	: 5.5 - 7.0
Purity, % by GC, minimum	: 99.5
Moisture content, % by mass (by KF), maximum	: 0.2
Phenoxyethoxyethanol, % by GC, maximum	: 0.5
Specific gravity (at 20°C)	: 1.105 - 1.110
Refractive index (at 20°C)	: 1.537 - 1.539
Free Phenol, ppm, maximum	: 5

Phenoxyethanol P5**TECHNICAL DATA SHEET****APPLICATIONS**

Phenoxyethanol P5 is used for a wide range of applications including:

- As a preservative in personal care formulations
- As a latex coalescent in water - based architectural and industrial coatings
- As a solvent and plasticizer for nitrocellulose, cellulose acetate, ethyl cellulose and many vinyl, phenolic, alkyd and ester - type resins in water - based coatings
- As a solvent in printing inks
- As an emulsifier to help lower interfacial tension in oil - water emulsions
- As an ingredient in slurring compounds used to protect metals against corrosion
- As a synergistic component in broad spectrum anti - bacterial agents
- As an additive in paint industry
- As a perfume fixative

PACKING

Phenoxyethanol P5 is available in 235 litres HMHDPE carboys. Total of 80 carboys i.e. 20 MT (250 kg per carboy) can be shipped palletized or non - palletized in 20 ft. full container load. It is available in 35 litres HMHDPE carboys. Total of 480 carboys i.e. 16.8 MT can be shipped palletized or non - palletized in 20 ft. full container load. It is also available in 25 litres HMHDPE carboys. Total of 640 carboys i.e. 16 MT can be shipped palletized or non - palletized in 20 ft. full container load. It can be supplied in IBC of 1 / 1.1 MT capacity. Total of 18 IBC i.e. 18 / 19.8 MT can be shipped in 20 ft. full container load. 20/24 MT of Phenoxyethanol P5 can also be supplied in 24 MT ISO containers

HANDLING AND STORAGE

Store the material in a clean, dry place at 20 - 40°C, away from direct heat and sunlight. Keep the container tightly closed after use. Since product is hygroscopic in nature, moisture content may increase if exposed to atmosphere. In original sealed condition, when stored as

Phenoxyethanol P5**TECHNICAL DATA SHEET**

suggested, shelf life of the product is at least 2.5 years. Once carboy / IBC is opened, consume the product within a week. When taken in ISO container, it is recommended that material be consumed within one month's time, after unloading in storage tank. Product solidifies, if stored below 14°C for prolonged time. If solidifies, it is recommended to heat the jacketed ISO containers with hot water or steam with 1.0 - 1.5 kg / cm² pressure to bring the temperature of product to 30 - 40°C. If the product becomes frozen in IBC / HMHDPE carboys then keep the same in hot room of 30 - 40°C (avoid direct heating). During storage, stacking should be maximum 1+1 for IBC / HMHDPE carboys (palletized as well as non - palletized)

Spill should be contained / collected and disposed off as per the regulations. Avoid ingestion and contact with skin, eyes and clothing. In case of contact with eyes, rinse immediately with plenty of water and seek medical attention, if necessary

Product Name : **Phenoxyethanol P5**
Version : 06
Date of issue : 19th September, 2018
TDS Updated by : MB / AD
Authorised by : BP

The information contained herein is based on the data considered accurate. However, no warranty is expressed, or implied regarding the accuracy of this data or the result to be obtained from the use thereof. Galaxy assumes no responsibility of injury to the user, or third person proximately caused by the material, if reasonable safety procedures are not adhered to, as stipulated in the safety data sheet. Galaxy assumes no responsibility for injury to the user, or third person proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Further, user assumes the risk in his use of the material.