01 / สรุปเอกสารโครงการ · V3

ภาพรวมระบบ UNXO

สรุปพื้นที่สมาชิก เครือข่ายผู้แนะนำ กระเป๋าเงิน และเครื่องมือผู้ดูแลของโปรเจกต์ UNXO

รูปแบบ DEPLOY ปัจจุบันเป็น TESTNET

Polygon Amoy · chain ID 80002 สคริปต์สร้าง tUSDT ทดสอบที่ไม่มีมูลค่าเงินจริง ไม่ใช่ USDT จริงหรือดอลลาร์ ใช้ test POL จ่าย gas

15	52	TH / EN
เลเวล (Level) ที่ซื้อได้	เส้นทาง API	ภาษาหน้าจอ

ความสามารถในโปรเจกต์

ส่วนงาน	สิ่งที่รองรับ
พื้นที่สมาชิก	ภาพรวม ผู้แนะนำ กระเป๋า Explorer, FAQ ตัวอย่าง rank และ analytics
บัญชีผู้ใช้	ลงชื่อเข้าด้วยลายเซ็นกระเป๋า และระบุสมาชิกด้วย ID ตัวเลขที่ไม่ซ้ำ
เครือข่าย	ช่องละ 2 สาขา แมทริกซ์รอบละ 3 ขั้น และยูนิเลเวลต่อเนื่อง 15 ขั้น ค้นหา ID สาธารณะและส่งออกข้อมูล
กระเป๋า EVM	ที่อยู่ที่ผูก ยอด POL/โทเคน ส่งสินทรัพย์ด้วยลายเซ็น และประวัติจาก indexer
ผู้ดูแล	Login ด้วยข้อมูลบัญชี จัดการสถานะสมาชิก ระงับ/คืนสถานะ ตั้งค่า และ audit
หน้าจอ	ไทย/อังกฤษ ธีมสว่าง/มืด มือถือ แป้นพิมพ์ และ reduced motion

องค์ประกอบทำงานร่วมกันอย่างไร

Nuxt / Vue UI → Nitro API → PostgreSQL

API รับรองสายผู้แนะนำและสิทธิ์ กระเป๋าภายนอกลงนามซื้อ ส่วน ReferralDistributor v3 โอนเงินบน Amoy จากนั้น worker ตรวจ receipt ก่อนบันทึกเลเวล (Level) และรายได้ในแอป

แยกอำนาจแต่ละบทบาท

สมาชิกอนุมัติโทเคน ผู้ดูแลจัดการบัญชี Owner ตั้งค่าสัญญา Authority รับรองผัง สิทธิ์ และรอบที่ครบ แล้วส่งอัปเกรดอัตโนมัติ ด้วยวงเงินที่สมาชิกอนุมัติ ต้องมี test POL จ่าย gas

ยอดเงิน 3 แบบมีความหมายต่างกัน

สินทรัพย์บนเชน ประวัติคอมมิชชันที่ยืนยันแล้ว และเครดิตภายในเดิมเป็นคนละส่วน การผูกกระเป๋าไม่ย้ายสินทรัพย์เก่าหรือแปลงเครดิตให้

ตรวจโค้ด 28 ตุลาคม 2026 · revision 614d7cd กติกาเวอร์ชัน 3 ไม่ได้รับรองสถานะ deployment ที่เปิดอยู่

02 / สรุปเอกสารโครงการ · V3

การชำระเงินและเลเวล (Level)

ซื้อเลเวล (Level) ตามลำดับ โดยจ่ายเต็มราคาของแต่ละเลเวล (Level) ค่าเริ่มต้นใช้กระเป๋าภายนอกและ Smart Contract

โหมด	แหล่งเงิน / ผู้ลงนาม
External · ค่าเริ่มต้น	ERC-20 ที่ตั้งค่าในที่อยู่ที่ผูก ให้กระเป๋าอนุมัติ
Embedded + contract	ERC-20 โดยรหัสผ่านปลดล็อก keystore เข้ารหัสฝั่ง server
Embedded + ledger	ต้องเปิดโหมดเดิมชัดเจน ใช้เครดิตภายในที่มีอยู่

ตารางราคา

ราคา(L) = $10 \times 2^{L-1}$ · ซื้อครบ 15 เลเวล (Level): **327,670**

เลเวล (Level)	ราคา	สะสม
1	10	10
2	20	30
3	40	70
4	80	150
5	160	310
6	320	630
7	640	1,270
8	1,280	2,550

เลเวล (Level)	ราคา	สะสม
9	2,560	5,110
10	5,120	10,230
11	10,240	20,470
12	20,480	40,950
13	40,960	81,910
14	81,920	163,830
15	163,840	327,670

จำนวนเงินเป็นหน่วยโทเคนที่ตั้งค่า Deployment ที่ให้มาใช้ tUSDT ทดสอบ ยังไม่รวม gas บัญชีใหม่เริ่มเลเวล (Level) 0 ซื้อเลเวล (Level) 1 แล้วจึงเปิดใช้รหัสแนะนำ

ลำดับซื้อแบบค่าเริ่มต้น


1. **เตรียม**
   ตรวจเลเวล (Level) ถัดไป ยอดโทเคน สายผู้แนะนำ authority และ distributor v3
2. **อนุมัติ**
   เลือกราคาซื้อครั้งนี้ หรือวงเงินจำกัดสำหรับเลเวลที่เหลือเพื่อเปิดอัปเกรดอัตโนมัติ Reset วงเงินเดิมที่ไม่พอก่อน
3. **ซื้อ**
   กระเป๋าลงนาม สัญญารับเงินและโอนทั้ง 19 ส่วนแบบ atomic
4. **ยืนยัน**
   ตรวจ canonical receipt และ events ครบ พร้อม confirmation เริ่มต้น 2 ครั้ง จึงรับรองเลเวล (Level) ในแอป

สถานะ: awaiting_signature → pending → confirmed / failed Quote ภายนอกอายุ 10 นาที Retry ใช้ request key เดิม การ timeout ไม่ใช่หลักฐานว่าจ่ายล้มเหลว

03 / สรุปเอกสารโครงการ · V3

การแบ่งจ่ายค่าคอมมิชชัน

การซื้อที่เข้าเงื่อนไขจะแบ่งเงินครบ 100% เป็น 19 ส่วน และโอนพร้อมกันในธุรกรรมเดียว



ส่วนแบ่ง	อัตรา	เมื่อซื้อ 10 โทเคน
แมทริกซ์ · ขั้น 1 / 2 / 3	10% / 20% / 50%	1.00 / 2.00 / 5.00
ยูนิเลเวล · parent ถึงขั้น 15	ขั้นละ 1% · รวม 15%	ขั้นละ 0.10 · รวม 1.50
ส่วนแพลตฟอร์มพื้นฐาน	5%	0.50

สองผังอาจจ่ายคนละคน ตัวอย่างด้านล่างสมมติสมาชิกและสิทธิ์ตรงกันทุกขั้น หากรับทั้งสองแผน ขั้น 1/2/3 จึงรวมเป็น 11% / 21% / 51%

ใครมีสิทธิ์รับส่วนของผู้แนะนำ

ต้องซื้อเลเวลเดียวกับรายการซื้อแล้ว บัญชี active และมีกระเป๋าตามโหมดที่ใช้งาน Server บันทึกสิทธิ์ตอนเตรียม quote ช่องที่ยังล็อกไม่รับส่วนของเลเวลนั้น

กรณีไม่มีผู้รับหรือช่องยังล็อก

- ส่วน**จ่ายตรง**ที่ไม่มีผู้มีสิทธิ์ไปแพลตฟอร์ม ไม่เลื่อนคนอื่นขึ้นมาแทนช่องนั้น
- ยูนิเลเวลที่ขาดผู้รับหรือยังล็อกไปแพลตฟอร์มทุกขั้น ไม่รวมส่วนที่เหลือให้ผู้แนะนำคนอื่น
- ถ้าไม่มีผู้มีสิทธิ์เลย แพลตฟอร์มรับทั้งหมด ยอดที่แพลตฟอร์มรับจริงจึงอาจมากกว่าส่วนพื้นฐาน 5%

ตัวอย่าง · ซื้อราคา 10

ผู้มีสิทธิ์	ผลในหน่วยโทเคน
เฉพาะชั้น 1	ผู้แนะนำ **1.10**; แพลตฟอร์ม **8.90**
ชั้น 1–5	ชั้น 1/2/3/4/5: 1.10 / 2.10 / 5.10 / 0.10 / 0.10; แพลตฟอร์ม 1.50
มี 1,3,4,5 แต่ชั้น 2 ไม่มีสิทธิ์	ชั้น 1/3/4/5: 1.10 / 5.10 / 0.10 / 0.10; แพลตฟอร์ม 3.60
ไม่มีเลย	แพลตฟอร์ม **10.00**

แมทริกซ์ชำระครบ 2/4/8 เปิดช่องเลเวลเดิมใหม่และเข้าคิวหักราคาเลเวลถัดไปเต็มจากกระเป๋า เงินหรือวงเงินไม่พอให้รอ วงเงินรวมเริ่มต้นสูงสุด 327,670 โทเคน แต่หักเฉพาะรายการปัจจุบันก่อน เลเวล 15 เปิดรอบใหม่ได้โดยไม่มีเลเวล 16

04 / สรุปเอกสารโครงการ · V3

การดูแลระบบและเงื่อนไขสำคัญ

สิทธิ์ควบคุม พฤติกรรมระบบเดิม และข้อจำกัดที่ควรเข้าใจก่อนติดตั้งหรือทำธุรกรรม

บัญชี สิทธิ์ และสวิตช์ควบคุม

- Member wallet login ใช้ข้อความครั้งเดียวอายุ 5 นาที Session 7 วัน ปิด member password login โดยเริ่มต้น ผู้ดูแลใช้ /admin/login
- Sponsor ต้อง active และเปิดสิทธิ์ ผูกได้ครั้งเดียว ห้ามตนเอง/วงจร ตำแหน่งละ 2 สาขา ผู้เชิญเพิ่มลงช่องว่างต่อใต้สมาชิกเดิม
- ปิดสมัครหยุดบัญชีใหม่ ปิด funding หยุดเฉพาะขอเติมเครดิตเดิม Pause สัญญาใช้ owner การระงับบัญชีไม่อายัดกระเป๋าภายนอก

การตรวจรับเงินเดิมแยกจาก on-chain

คำขอเติมเป็น pending และยังไม่เพิ่มเครดิต ผู้ดูแลตรวจรับจริง พร้อม reference ไม่ซ้ำก่อนอนุมัติ/เพิ่มเครดิตแบบ atomic โอนภายในต้องมีรหัสผู้ส่ง ส่วน platform payable เดิมคือบัญชีค้างจ่าย ไม่ใช่โทเคนที่จ่ายบนเชนแล้ว

เปิดระบบ ดูแล และกู้สถานะ

ใช้ Node 24+ และ PostgreSQL 17+ ติดตั้ง dependencies ตั้ง .env/DATABASE_URL ทำ migration สร้างผู้ดูแล แล้วเปิด Nuxt Production ต้องใช้ Node server; static hosting รัน API ไม่ได้

Worker ตรวจทุก 15 วินาที ค้นหา purchase ที่ถูกแทนจาก signed ID ได้ แต่ Send ทั่วไปยังไม่มี replacement discovery เก็บ ID/hash และตรวจ pending ก่อนจ่ายใหม่ สำรอง PostgreSQL config ส่วนตัว และ contract artifacts

ขอบเขตคู่มือ API

12	18	9	13
auth / สาธารณะ	สมาชิก / กระเป๋า	embedded / เดิม	ผู้ดูแล

ค่า gas และนโยบายที่ต้องแยกให้ชัด

Approve ซื้อ และส่งต้องมี POL gas รวมกรณี revert หาก purchase ล้มเหลวจะย้อนการจ่ายโทเคนทั้งหมด แต่ approve/gas แยกอาจคงอยู่ ยังไม่มีชำระ/ถอนเงินสด คืนเงิน แปลงเครดิตเป็นโทเคน MFA กู้รหัสผ่าน หรือเปลี่ยนกระเป๋าที่ผูก โค้ดไม่ได้กำหนดสิทธิ์คืนเงิน ค่าถอน หรือการรับประกันเชิงพาณิชย์

เอกสารฉบับเต็ม

อ่านรายละเอียดใน repository ซึ่งเก็บคู่มือไว้ควบคู่กับไฟล์สรุปนี้:

คู่มือระบบ
docs/th/system-guide.md

การจ่ายเงินและเงื่อนไข
docs/th/payments-and-conditions.md

ติดตั้ง ดูแล และกู้สถานะ
docs/th/operations.md

API ทั้ง 52 เส้นทาง
docs/th/api-reference.md

ตรวจโค้ด 28 ตุลาคม 2026 · revision 614d7cd กติกาเวอร์ชัน 3 ไม่ได้รับรองสถานะ deployment ที่เปิดอยู่

01 / PROJECT SUMMARY · V3

The system at a glance

A concise guide to UNXO's member workspace, referral network, wallets and administrator tools.

CURRENT DEPLOYMENT WORKFLOW: TESTNET

Polygon Amoy · chain ID 80002. The supplied deployment creates valueless tUSDT, not real USDT or dollars. Test POL pays network gas.

15	52	TH / EN
paid levels	API routes	interface languages

What the project includes

Area	Implemented behavior
Member workspace	Overview, referrals, wallet, explorer, FAQ, rank examples and analytics.
Accounts	Wallet-message sign-in and identification by unique numeric member ID.
Referral network	Binary matrix (3 steps), continuous unilevel (15 steps), two branches, ID search and exports.
EVM wallet	Linked address, POL/token reads, signed sends and indexed transaction history.
Administrator	Credential login, member status management, suspend/reactivate, settings and audit.
Presentation	Thai/English, light/dark themes, mobile layouts, keyboard controls and reduced motion.

How the components work together

Nuxt / Vue UI → Nitro API → PostgreSQL

The API attests eligibility; the wallet signs. ReferralDistributor v3 pays recipients on Amoy. A worker verifies receipts before recording activation and earnings.

Separate authorities

Members approve tokens. Owners configure contracts. The authority attests placement, eligibility and cycles, and relays approved upgrades using its test POL.

Three balances with different meanings

Token holdings, confirmed commission history and legacy credits are separate. Linking does not move assets or convert credits.

Source review: 28 October 2026 · revision 614d7cd. Version-3 rules; this does not certify a live deployment.

02 / PROJECT SUMMARY · V3

Payments & fifteen levels

Buy levels sequentially at their full price. The default flow uses a connected wallet and a smart contract.

Mode	Payment source / signer
External · default	Configured ERC-20 at the linked address; wallet approval.
Embedded + contract	Configured ERC-20; password unlocks the encrypted server keystore.
Embedded + ledger	Explicit legacy mode; spends existing internal credits.

Price schedule

$\text{Price}(L) = 10 \times 2^{L-1}$ · Total through level 15: **327,670**

Level	Price	Cumulative
1	10	10
2	20	30
3	40	70
4	80	150
5	160	310
6	320	630
7	640	1,270
8	1,280	2,550

Level	Price	Cumulative
9	2,560	5,110
10	5,120	10,230
11	10,240	20,470
12	20,480	40,950
13	40,960	81,910
14	81,920	163,830
15	163,840	327,670

All amounts are configured token units; the supplied deployment uses test tUSDT. Gas is additional. A new account begins at level 0; buying level 1 activates its invite code.

Default purchase flow


1. **Prepare**
   Check next level, token balance, ancestry, authority and distributor v3.
2. **Approve**
   Approve this price or a finite ceiling for remaining levels. Reset a nonzero insufficient allowance first.
3. **Purchase**
   Wallet signs; the contract collects and distributes all nineteen shares atomically.
4. **Confirm**
   A verified receipt, nineteen share events and two confirmations by default activate the paid level.

Tracking: awaiting_signature → pending → confirmed / failed. External purchase quotes last ten minutes. Reuse the operation's request key on retries; a timeout does not prove failure.

03 / PROJECT SUMMARY · V3

How commissions are paid

Every qualifying purchase allocates 100% of its token price across nineteen shares in one transaction.



Allocation	Rate	At a 10-token purchase
Matrix · steps 1 / 2 / 3	10% / 20% / 50%	1.00 / 2.00 / 5.00
Unilevel · parent through step 15	1% each · 15% total	0.10 each · 1.50 total
Base platform share	5%	0.50

The trees can have different recipients. Examples below assume the same members and eligibility at matching depths; combined first-three shares are then 11% / 21% / 51%.

Who can receive an upline payment?

Purchased matching level + active account + wallet for the selected mode. Eligibility is snapshotted in the quote.

Missing or locked recipients

- Missing/ineligible **direct** shares go to the platform; ancestors do not move into those gaps.
- Every missing or locked unilevel depth pays the platform. No shares combine into another member's payout.
- With no eligible ancestor, the platform receives the full price. Its actual receipt can exceed the base 5%.

Examples · price 10

Eligible uplines	Result in token units
Only depth 1	Upline: **1.10**; platform: **8.90**.
Depths 1–5	Depths 1/2/3/4/5: 1.10 / 2.10 / 5.10 / 0.10 / 0.10; platform: 1.50.
Depth 2 gap; 1,3,4,5 eligible	Depths 1/3/4/5: 1.10 / 5.10 / 0.10 / 0.10; platform: 3.60.
None	Platform: **10.00**.

A paid 2/4/8 matrix opens a new same-level slot and queues a full-price next level from the member's wallet. Low balance/approval keeps it queued. Initial all-level approval caps at 327,670 tokens; the current purchase alone is charged now. Level 15 recycles without level 16.

04 / PROJECT SUMMARY · V3

Operations & key conditions

The controls, legacy behavior and operational limits to understand before running or using the platform.

Accounts, permissions and controls

- Member wallet sign-in uses a single-use five-minute message. Sessions last seven days; passwords are disabled for members by default. Admins use /admin/login.
- A sponsor must be active and activated. Attach once; no self-link or cycle. Each placement has two branches; extra invitations spill over below existing members.
- Closing registration blocks new accounts. Closing funding blocks legacy deposit requests only. Contract pause requires the owner. Suspension does not freeze an external wallet.

Legacy settlement stays separate

A funding request is pending and adds no credit. An admin verifies receipt and records a unique reference before atomic approval/credit. Internal transfers require the sender's password. Legacy platform payables are records awaiting settlement, not completed on-chain payouts.

Run, maintain and recover

Node 24+ and PostgreSQL 17+. Install dependencies, configure .env and DATABASE_URL, migrate, create an admin, then run Nuxt. Production requires the Node server; static hosting cannot run the APIs.

The worker reconciles every 15 seconds. Purchase replacements can be found by signed ID; ordinary send replacement discovery is absent. Preserve IDs/hashes and investigate pending receipts before another payment. Back up PostgreSQL, private configuration and contract artifacts.

API documentation coverage

12	18	9	13
auth / public	member / wallet	embedded / legacy	admin management

Gas and policies to keep clear

Approvals, purchases and sends need POL gas, including reverted attempts. A failed purchase reverts its token payouts, while separate approvals/gas can remain. No fiat checkout/cash-out, refund workflow, credit-to-token redemption, MFA, password recovery or linked-wallet replacement is implemented. Refund entitlements, withdrawal fees and commercial guarantees are not defined by the code.

Full documentation

The complete guides are in the repository, alongside this summary:

System guide
docs/en/system-guide.md

Payments and conditions
docs/en/payments-and-conditions.md

Operations and recovery
docs/en/operations.md

All 52 API routes
docs/en/api-reference.md

Source review: 28 October 2026 · revision 614d7cd. Version-3 rules; this does not certify a live deployment.