01 / PROJECT SUMMARY · V3

The system at a glance

A concise guide to UNXO's member workspace, referral network, wallets and administrator tools.

CURRENT DEPLOYMENT WORKFLOW: TESTNET

Polygon Amoy · chain ID 80002. The supplied deployment creates valueless tUSDT, not real USDT or dollars. Test POL pays network gas.

15	52	TH / EN
paid levels	API routes	interface languages

What the project includes

Area	Implemented behavior
Member workspace	Overview, referrals, wallet, explorer, FAQ, rank examples and analytics.
Accounts	Wallet-message sign-in and identification by unique numeric member ID.
Referral network	Binary matrix (3 steps), continuous unilevel (15 steps), two branches, ID search and exports.
EVM wallet	Linked address, POL/token reads, signed sends and indexed transaction history.
Administrator	Credential login, member status management, suspend/reactivate, settings and audit.
Presentation	Thai/English, light/dark themes, mobile layouts, keyboard controls and reduced motion.

How the components work together

Nuxt / Vue UI → Nitro API → PostgreSQL

The API attests eligibility; the wallet signs. ReferralDistributor v3 pays recipients on Amoy. A worker verifies receipts before recording activation and earnings.

Separate authorities

Members approve tokens. Owners configure contracts. The authority attests placement, eligibility and cycles, and relays approved upgrades using its test POL.

Three balances with different meanings

Token holdings, confirmed commission history and legacy credits are separate. Linking does not move assets or convert credits.

Source review: 28 October 2026 · revision 614d7cd. Version-3 rules; this does not certify a live deployment.

02 / PROJECT SUMMARY · V3

Payments & fifteen levels

Buy levels sequentially at their full price. The default flow uses a connected wallet and a smart contract.

Mode	Payment source / signer
External · default	Configured ERC-20 at the linked address; wallet approval.
Embedded + contract	Configured ERC-20; password unlocks the encrypted server keystore.
Embedded + ledger	Explicit legacy mode; spends existing internal credits.

Price schedule

$\text{Price}(L) = 10 \times 2^{L-1}$ · Total through level 15: **327,670**

Level	Price	Cumulative
1	10	10
2	20	30
3	40	70
4	80	150
5	160	310
6	320	630
7	640	1,270
8	1,280	2,550

Level	Price	Cumulative
9	2,560	5,110
10	5,120	10,230
11	10,240	20,470
12	20,480	40,950
13	40,960	81,910
14	81,920	163,830
15	163,840	327,670

All amounts are configured token units; the supplied deployment uses test tUSDT. Gas is additional. A new account begins at level 0; buying level 1 activates its invite code.

Default purchase flow


1. **Prepare**
   Check next level, token balance, ancestry, authority and distributor v3.
2. **Approve**
   Approve this price or a finite ceiling for remaining levels. Reset a nonzero insufficient allowance first.
3. **Purchase**
   Wallet signs; the contract collects and distributes all nineteen shares atomically.
4. **Confirm**
   A verified receipt, nineteen share events and two confirmations by default activate the paid level.

Tracking: awaiting_signature → pending → confirmed / failed. External purchase quotes last ten minutes. Reuse the operation's request key on retries; a timeout does not prove failure.

03 / PROJECT SUMMARY · V3

How commissions are paid

Every qualifying purchase allocates 100% of its token price across nineteen shares in one transaction.



Allocation	Rate	At a 10-token purchase
Matrix · steps 1 / 2 / 3	10% / 20% / 50%	1.00 / 2.00 / 5.00
Unilevel · parent through step 15	1% each · 15% total	0.10 each · 1.50 total
Base platform share	5%	0.50

The trees can have different recipients. Examples below assume the same members and eligibility at matching depths; combined first-three shares are then 11% / 21% / 51%.

Who can receive an upline payment?

Purchased matching level + active account + wallet for the selected mode. Eligibility is snapshotted in the quote.

Missing or locked recipients

- Missing/ineligible **direct** shares go to the platform; ancestors do not move into those gaps.
- Every missing or locked unilevel depth pays the platform. No shares combine into another member's payout.
- With no eligible ancestor, the platform receives the full price. Its actual receipt can exceed the base 5%.

Examples · price 10

Eligible uplines	Result in token units
Only depth 1	Upline: **1.10**; platform: **8.90**.
Depths 1–5	Depths 1/2/3/4/5: 1.10 / 2.10 / 5.10 / 0.10 / 0.10; platform: 1.50.
Depth 2 gap; 1,3,4,5 eligible	Depths 1/3/4/5: 1.10 / 5.10 / 0.10 / 0.10; platform: 3.60.
None	Platform: **10.00**.

A paid 2/4/8 matrix opens a new same-level slot and queues a full-price next level from the member's wallet. Low balance/approval keeps it queued. Initial all-level approval caps at 327,670 tokens; the current purchase alone is charged now. Level 15 recycles without level 16.

04 / PROJECT SUMMARY · V3

Operations & key conditions

The controls, legacy behavior and operational limits to understand before running or using the platform.

Accounts, permissions and controls

- Member wallet sign-in uses a single-use five-minute message. Sessions last seven days; passwords are disabled for members by default. Admins use /admin/login.
- A sponsor must be active and activated. Attach once; no self-link or cycle. Each placement has two branches; extra invitations spill over below existing members.
- Closing registration blocks new accounts. Closing funding blocks legacy deposit requests only. Contract pause requires the owner. Suspension does not freeze an external wallet.

Legacy settlement stays separate

A funding request is pending and adds no credit. An admin verifies receipt and records a unique reference before atomic approval/credit. Internal transfers require the sender's password. Legacy platform payables are records awaiting settlement, not completed on-chain payouts.

Run, maintain and recover

Node 24+ and PostgreSQL 17+. Install dependencies, configure .env and DATABASE_URL, migrate, create an admin, then run Nuxt. Production requires the Node server; static hosting cannot run the APIs.

The worker reconciles every 15 seconds. Purchase replacements can be found by signed ID; ordinary send replacement discovery is absent. Preserve IDs/hashes and investigate pending receipts before another payment. Back up PostgreSQL, private configuration and contract artifacts.

API documentation coverage

12	18	9	13
auth / public	member / wallet	embedded / legacy	admin management

Gas and policies to keep clear

Approvals, purchases and sends need POL gas, including reverted attempts. A failed purchase reverts its token payouts, while separate approvals/gas can remain. No fiat checkout/cash-out, refund workflow, credit-to-token redemption, MFA, password recovery or linked-wallet replacement is implemented. Refund entitlements, withdrawal fees and commercial guarantees are not defined by the code.

Full documentation

The complete guides are in the repository, alongside this summary:

System guide
docs/en/system-guide.md

Payments and conditions
docs/en/payments-and-conditions.md

Operations and recovery
docs/en/operations.md

All 52 API routes
docs/en/api-reference.md

Source review: 28 October 2026 · revision 614d7cd. Version-3 rules; this does not certify a live deployment.