01 / PROJECT SUMMARY

The system at a glance

A concise guide to UNXO's member workspace, referral network, wallets and administrator tools.

CURRENT DEPLOYMENT WORKFLOW: TESTNET

Polygon Amoy · chain ID 80002. The supplied deployment creates valueless tUSDT, not real USDT or dollars. Test POL pays network gas.

15	52	TH / EN
paid levels	API routes	interface languages

What the project includes

Area	Implemented behavior
Member workspace	Overview, referrals, wallet, explorer, FAQ, rank examples and analytics.
Accounts	Wallet-message sign-in, unique numeric member IDs and editable usernames.
Referral network	Actual sponsor ancestry, public ID search, fifteen generations and CSV/SVG exports.
EVM wallet	Linked address, POL/token reads, signed sends and indexed transaction history.
Administrator	Credential login, account search, rename, suspend/reactivate, settings and audit.
Presentation	Thai/English, light/dark themes, mobile layouts, keyboard controls and reduced motion.

How the components work together



The API attests eligibility; the wallet signs. ReferralDistributor v2 pays recipients on Amoy. A worker verifies receipts before recording activation and earnings.

Separate authorities

Members sign transfers; admins manage accounts. Contract owners alone change on-chain settings or pause. Quote authorities attest eligibility and cannot sign a buyer's transfer.

Three balances with different meanings

Token holdings, confirmed commission history and legacy credits are separate. Linking does not move assets or convert credits.

Source review: 27 October 2026 · revision 3ffa828. This summarizes implemented behavior; it does not certify a live deployment.

02 / PROJECT SUMMARY

Payments & fifteen levels

Buy levels sequentially at their full price. The default flow uses a connected wallet and a smart contract.

Mode	Payment source / signer
External · default	Configured ERC-20 at the linked address; wallet approval.
Embedded + contract	Configured ERC-20; password unlocks the encrypted server keystore.
Embedded + ledger	Explicit legacy mode; spends existing internal credits.

Price schedule

$\text{Price}(L) = 10 \times 2^{L-1}$ · Total through level 15: **327,670**

Level	Price	Cumulative
1	10	10
2	20	30
3	40	70
4	80	150
5	160	310
6	320	630
7	640	1,270
8	1,280	2,550

Level	Price	Cumulative
9	2,560	5,110
10	5,120	10,230
11	10,240	20,470
12	20,480	40,950
13	40,960	81,910
14	81,920	163,830
15	163,840	327,670

All amounts are configured token units; the supplied deployment uses test tUSDT. Gas is additional. A new account begins at level 0; buying level 1 activates its invite code.

Default purchase flow

1. **Prepare**
   Check next level, token balance, ancestry, authority and distributor v2.
2. **Approve**
   Wallet approves the exact price; reset a nonzero insufficient allowance first.
3. **Purchase**
   Wallet signs; the contract collects and distributes all nineteen shares atomically.
4. **Confirm**
   Canonical receipt + all events + two confirmations by default activate the level in the app.

Tracking: awaiting_signature → pending → confirmed / failed. External purchase quotes last ten minutes. Reuse the operation's request key on retries; a timeout does not prove failure.

03 / PROJECT SUMMARY

How commissions are paid

Every qualifying purchase allocates 100% of its token price across nineteen shares in one transaction.



Allocation	Rate	At a 10-token purchase
Direct · depths 1 / 2 / 3	50% / 20% / 10%	5.00 / 2.00 / 1.00
Bonus · depths 1–15	1% each · 15% total	0.10 each · 1.50 total
Base platform share	5%	0.50

Direct and bonus shares overlap: with fifteen eligible uplines, depths 1/2/3 receive 51%/21%/11%; depths 4–15 receive 1% each.

Who can receive an upline payment?

Activated invite + active account + wallet for the selected mode. Eligibility is snapshotted in the quote. No matching rank, two direct referrals or monthly qualification is required.

Missing recipients and the highest eligible upline

- Missing/ineligible **direct** shares go to the platform; ancestors do not move into those gaps.
- Bonus gaps below the furthest eligible ancestor also go to the platform. Unused **trailing** bonus depths combine into that furthest eligible ancestor.
- With no eligible ancestor, the platform receives the full price. Its actual receipt can exceed the base 5%.

Examples · price 10

Eligible uplines	Result in token units
Only depth 1	Upline: **6.50**; platform: **3.50**.
Depths 1–5	Depths 1/2/3/4/5: 5.10 / 2.10 / 1.10 / 0.10 / 1.10; platform: 0.50.
Depth 2 gap; 1,3,4,5 eligible	Depths 1/3/4/5: 5.10 / 1.10 / 0.10 / 1.10; platform: 2.60.
None	Platform: **10.00**.

Payouts arise from purchases, not invitations alone. Matrix/rank projections are illustrations: no implemented recycling or guaranteed return. On-chain commissions are already transferred to recipient wallets; legacy credits are not credited again.

04 / PROJECT SUMMARY

Operations & key conditions

The controls, legacy behavior and operational limits to understand before running or using the platform.

Accounts, permissions and controls

- Member wallet sign-in uses a single-use five-minute message. Sessions last seven days; passwords are disabled for members by default. Admins use /admin/login.
- A sponsor must be active and activated. Attach once; no self-link or cycle. All direct referrals remain beneath their sponsor, including a third or later child.
- Closing registration blocks new accounts. Closing funding blocks legacy deposit requests only. Contract pause requires the owner. Suspension does not freeze an external wallet.

Legacy settlement stays separate

A funding request is pending and adds no credit. An admin verifies receipt and records a unique reference before atomic approval/credit. Internal transfers require the sender's password. Legacy platform payables are records awaiting settlement, not completed on-chain payouts.

Run, maintain and recover

Node 24+ and PostgreSQL 17+. Install dependencies, configure .env and DATABASE_URL, migrate, create an admin, then run Nuxt. Production requires the Node server; static hosting cannot run the APIs.

The worker reconciles every 15 seconds. Purchase replacements can be found by signed ID; ordinary send replacement discovery is absent. Preserve IDs/hashes and investigate pending receipts before another payment. Back up PostgreSQL, private configuration and contract artifacts.

API documentation coverage

12	18	9	13
auth / public	member / wallet	embedded / legacy	admin management

Gas and policies to keep clear

Approvals, purchases and sends need POL gas, including reverted attempts. A failed purchase reverts its token payouts, while separate approvals/gas can remain. No fiat checkout/cash-out, refund workflow, credit-to-token redemption, MFA, password recovery or linked-wallet replacement is implemented. Refund entitlements, withdrawal fees and commercial guarantees are not defined by the code.

Full documentation

The complete guides are in the repository, alongside this summary:

System guide
docs/en/system-guide.md

Payments and conditions
docs/en/payments-and-conditions.md

Operations and recovery
docs/en/operations.md

All 52 API routes
docs/en/api-reference.md

Source review: 27 October 2026 · revision 3ffa828. This summarizes implemented behavior; it does not certify a live deployment.