Dequantizing Shallow Equivariant Quantum Graph Networks: Periodic Inductive Biases in Molecular Message Passing

Nguyen Trong Luu, **Hieu Minh Pham**, **Anh Quoc Phan**, **Cho Xuan Do***
Posts and Telecommunications Institute of Technology (PTIT), Hanoi, Vietnam

Abstract

Parameterized quantum circuits (PQCs) have shown promising results on molecular electronic property prediction, but the source of their advantage over classical baselines remains unclear. We show that this advantage traces not to multi-qubit entanglement but to a classical mechanism: single-qubit rotations natively compute truncated Fourier series, providing a compact periodic basis that monotonic activations cannot efficiently express at low parameter budgets. To exploit this insight, we introduce **PRISM**, an E(3)-equivariant message-passing GNN that replaces standard activations with periodic sinusoidal (SIREN) internal activations. At identical parameter count (2,527), PRISM matches or exceeds a 4-qubit PQC across all QM9 electronic targets and outperforms PaiNN on four of six properties. Scaling circuit depth to $L = 16$ layers and qubit counts to $n_q = 8$ confirms that quantum circuits asymptotically match but never exceed PRISM's classical representation, while incurring up to a 540× training slowdown. Across full-scale QM9 ($N = 110{,}000$, 5 seeds, $q_{\text{FDR}} \leq 0.055$), the periodic advantage persists and *widens* monotonically from 35.7% to 51.3% as model capacity scales past 100,000 parameters. Our results establish periodic internal activations as a hardware-free inductive bias for molecular geometric deep learning.

1 Introduction

Parameterized quantum circuits (PQCs) are leading near-term candidates for practical quantum advantage in machine learning [5, 12]. Molecular property prediction is a natural application domain: molecules live in 3D Euclidean space with continuous E(3) symmetries that PQCs can naturally respect, and the underlying physics is quantum mechanical [24, 35]. When integrated into equivariant graph neural networks, shallow PQCs consistently outperform parameter-matched classical baselines on electronic orbital targets such as HOMO, LUMO, and the HOMO-LUMO gap in low-data regimes (Figure 1).

*Corresponding author: chodx@ptit.edu.vn

However, the physical mechanism driving this performance remains debated: while prevailing literature attributes gains to multi-qubit entanglement or Hilbert-space expressivity, our systematic ablations across 20 random seeds show that multi-qubit entanglement contributes negligibly. Instead, the mechanism is entirely classical: single-qubit rotations $R_Y(x)$, $R_Z(x)$ natively compute truncated Fourier series [21,27], supplying a compact periodic basis that standard monotonic activations (tanh, SiLU) cannot efficiently express at matching parameter budgets. This reflects a representational capacity gap rather than quantum advantage.

This diagnosis is constructive: if the PQC advantage stems from periodicity, we can replicate it classically by placing periodic activations *inside* equivariant message-passing layers. While SIREN [30] introduced sinusoidal activations for implicit neural representations in vision, and existing molecular architectures use trigonometric functions for *input* encodings (spherical harmonics in TFN [35], NequIP [2], MACE [1]), no prior work has placed periodic activations inside the *hidden layers* of equivariant graph networks. We introduce **PRISM**, an E(3)-equivariant message-passing GNN that replaces monotonic activations with $\sin(\omega_0 \mathbf{W}\mathbf{x} + \mathbf{b})$ in its edge-processing MLPs. At identical parameter count, PRISM matches or exceeds the PQC on all electronic targets, without quantum hardware.

Contributions.

- We isolate the mechanism of PQC advantage on molecular electronic targets: it traces to single-qubit trigonometric expressivity, not multi-qubit entanglement (Section 4.3).
- We introduce **PRISM**, the first equivariant message-passing GNN with periodic sinusoidal *internal* activations, which matches or exceeds the PQC at iso-parameter parity and outperforms PaiNN on four of six QM9 targets (Section 3.3).
- We prove classical sufficiency across circuit scaling regimes: scaling PQC depth to $L = 16$ layers and qubit width to $n_q = 8$ confirms that deep quantum entanglement yields zero marginal advantage

over PRISM's two-layer periodic edge representation, while classical execution delivers a 540× training speedup (Section 4.5).

- We demonstrate that the periodic advantage persists at full scale (N = 110,000, 5 seeds, $q_{\text{FDR}} \leq 0.055$; $p = 0.0035$ on HOMO, $p = 0.0424$ on LUMO, $p = 0.0547$ on Gap) and *widens monotonically* from 35.7% to 51.3% as model capacity scales to the standard medium-capacity regime of 100,127 parameters (Section 4.4).
- We provide a rigorous statistical methodology (factorial ablation, Fourier spectral validation, and Benjamini-Hochberg FDR correction across 48 hypotheses) applicable to future QML benchmarking (Section 4.3, Supplementary Table S3 in SM B, SM D).

2 Related Work

Classical Geometric Deep Learning. Equivariant GNNs for molecular property prediction have achieved strong accuracy on quantum chemistry benchmarks (see Noé et al. [19] for a review). Representative architectures include invariant message-passing models (EGNN [24], SchNet [28], PhysNet [37]), directional and angular architectures (DimeNet++ [8], GemNet [7], PaiNN [29]), higher-order tensor methods (TFN [35], NequIP [2], MACE [1], Equiformer [15]), and scalable equivariant frameworks (TorchMD-Net [36], Allegro [18], LEFTNet [6]). The MPNN framework of Gilmer et al. [9] unifies most of these under a common message-passing formalism. Yet all share a common design choice: monotonic, locally-linear activation functions (SiLU, Swish, or shifted softplus) in their internal message-passing and node-update MLPs. We challenge this default.

Spectral Bias and Periodic Activations. In deep learning theory, Rahaman et al. [22] proved that standard neural networks exhibit *spectral bias*: gradient descent prioritizes fitting low-frequency Fourier components, with high-frequency Fourier amplitudes decaying rapidly as $\mathcal{O}(\|k\|^{-(d+1)})$. Tancik et al. [32] analyzed this via Neural Tangent Kernel (NTK) theory, demonstrating that coordinate MLPs fail to represent fine spatial structures unless inputs are mapped to Fourier features. Sitzmann et al. [30] introduced SIREN (Sinusoidal Representation Networks), demonstrating that periodic activation functions ($\sin(\omega_0 Wx + b)$) combined with a principled initialization scheme (ω_0-scaled uniform distribution) completely bypass spectral bias and allow stable training of arbitrary derivative orders. While SIREN is standard for implicit neural representations in vision [30], periodic *internal* activations have not previously appeared inside the message-passing MLPs of equivariant graph neural networks. Existing geometric models employ trigonometric functions only for *input spatial encodings*, such as spherical Bessel radial bases in DimeNet++ [8] or spherical harmonics in NequIP [2] and MACE [1], leaving all downstream layer activations monotonic.

Dequantization and Fundamental Limits of QML. Recent studies question whether PQC advantages reflect quantum resources. Huang et al. [10] showed that QML model power depends on inductive bias alignment with the data, not quantum hardware per se; Schuld [26] proved that supervised variational models are formally kernel methods. Empirically, Schreiber et al. [25] showed that PQCs compute truncated Fourier series matchable by classical surrogates, Kübler et al. [13] traced quantum kernel performance to inductive bias rather than hardware, and Pegg et al. [20] showed that iso-parameter classical twins match quantum models on HOMO-LUMO gap prediction. Landman et al. [14] established that data re-uploading PQCs are multi-dimensional truncated Fourier series approximable via Random Fourier Features in polynomial sample complexity. This is theoretically grounded: Cerezo, Holmes et al. [4] established the *trainability-simulability dilemma*, showing that PQCs that avoid barren plateaus [5, 16] frequently reside within classically simulable complexity classes, while scaling to deeper, highly entangled circuits risks exponential concentration [34], forcing quantum kernels to trivial constants. Jerbi et al. [11] characterized the demanding structural conditions needed to maintain advantage over classical learners. Following Tang's dequantization framework [33], our approach isolates the precise mechanism of apparent PQC performance and replicates it classically.

Equivariant Quantum Machine Learning. Formal frameworks incorporate symmetry constraints into parameterized quantum circuits. Meyer et al. [17] developed a symmetry group framework for constructing equivariant PQCs, showing that enforcing group symmetries reduces the circuit's effective hypothesis space to physically relevant subspaces, improving sample efficiency and generalization. Skolik et al. [31] showed that equivariant quantum circuits achieve better generalization on symmetric learning tasks with fewer trainable parameters. Q-PRISM's E(3) equivariance is achieved at the *graph architecture level* (through invariant edge inputs and equivariant coordinate updates) rather than through symmetric circuit design, complementing these circuit-level approaches. PRISM inherits the same graph-level equivariance guarantees (Theorem 1) without quantum hardware.




Figure 1: **Sample Efficiency Scaling Laws on QM9 across Sample Sizes** $N \in [100, 10{,}000]$**:** Log-log scaling curves for HOMO-LUMO gap $\Delta\epsilon$ (left, eV) and Dipole Moment μ (right, Debye) across 5 independent random seeds (mean $\pm$ std). Q-PRISM (2,527 p) is benchmarked against Classical Twin (tanh, 2,527 p), SchNet (2,473 p), PaiNN (2,721 p), EGNN Param-Matched (2,497 p), and EGNN Standard (4,289 p). In data-scarce regimes ($N \leq 500$), Q-PRISM outperforms all baselines. As sample size grows, PaiNN's coupled scalar-vector representation crosses over Q-PRISM at $N \approx 473$ for Gap and $N \approx 3{,}106$ for Dipole Moment, while Q-PRISM consistently maintains an advantage over scalar equivariant baselines (EGNN, SchNet).

3 Q-PRISM: Equivariant Quantum Graph Architecture

3.1 Quantum Edge Convolution

As illustrated in Figure 2, let a 3D molecule be represented as a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{x}, \mathbf{h})$, where each atom $i \in \mathcal{V}$ has spatial coordinates $\mathbf{x}_i \in \mathbb{R}^3$ and invariant atomic feature vector $\mathbf{h}_i \in \mathbb{R}^{d_{\text{in}}}$. Edges $(i,j) \in \mathcal{E}$ connect interacting atomic pairs within a radius cutoff, defining the neighborhood $\mathcal{N}(i) = \{j : (i,j) \in \mathcal{E}\}$. The squared Euclidean distance is:

$$d_{ij} = \|\mathbf{x}_i - \mathbf{x}_j\|^2 \in \mathbb{R}_{\geq 0} \tag{1}$$

Gaussian RBF Distance Expansion. Rather than encoding raw distances via a single scalar weight $w_d^{(l)} \cdot d_{ij}$, we expand distances into a multi-frequency Gaussian radial basis [28]:

$$\phi_k(d_{ij}) = \exp\left(-\gamma_k (d_{ij} - \mu_k)^2\right), \quad k = 1, \ldots, K \tag{2}$$

where μ_k are evenly spaced centers in $[0, 10]$ Å^2 and γ_k are learnable inverse widths. Under the Fourier analysis of data re-uploading [21,27], this transforms the PQC into a truncated K-term Fourier approximator for molecular potential surfaces.

Multi-Head Design. Following multi-head attention designs, we use two parallel PQC heads (*Electronic* and *Topological*). Each head uses an independent feature projection $\mathbf{W}_p^{(s)} : \mathbb{R}^{d_{\text{hidden}}} \to \mathbb{R}^2$ to direct distinct feature subspaces into its respective quantum circuit:

$$\mathbf{h}_i^{p,(s)} = \mathbf{W}_p^{(s)} \mathbf{h}_i, \quad s \in \{1, 2\} \tag{3}$$

Both heads share the same RBF distance features and angular inputs but process them through independent PQC parameter sets.

4-Qubit Parameterized Quantum Circuit. For each head $s \in \{1,2\}$ and directed edge (i,j), the edge input vector $\mathbf{u}_{ij}^{(s)} = [\mathbf{h}_i^{p,(s)\top}, \mathbf{h}_j^{p,(s)\top}, \boldsymbol{\phi}(d_{ij})^\top, \bar{\theta}_{ij}]^\top \in \mathbb{R}^{4+K+1}$ is processed by a 4-qubit circuit initialized in $|0\rangle^{\otimes 4}$. As diagrammed in Figure 2(2), the state evolves through L variational layers via chronological operator composition, $|\psi_{ij}^{(s)}\rangle = \left(\prod_{l=L}^{1} U^{(l)}(\mathbf{u}_{ij}^{(s)}, \boldsymbol{\theta}_l)\right)|0\rangle^{\otimes 4}$. Each variational layer $U^{(l)}$ composes multi-axis single-qubit phase injections with a cyclic entangling ring:

$$U^{(l)}(\mathbf{u}_{ij}^{(s)}, \boldsymbol{\theta}_l) = \mathcal{W}_{\text{ring}} \bigotimes_{q=0}^{3} \Big[R_{ZYX}(\boldsymbol{\theta}_{l,q})\, R_y(\bar{\theta}_{ij}) \cdot R_z\left(\sum_{k=1}^{K} w_{d,q,k}^{(l)} \phi_k(d_{ij})\right) R_y(\tilde{h}_{ij,q}^{(s)}) \Big] \tag{4}$$

where operations evaluate chronologically from right to left. Here, $\tilde{\mathbf{h}}_{ij}^{(s)} = [\mathbf{h}_i^{p,(s)\top}, \mathbf{h}_j^{p,(s)\top}]^\top \in \mathbb{R}^4$ injects projected atom features into the initial Pauli-Y phase on qubit $q \in \{0, \ldots, 3\}$; the K-channel Gaussian RBF vector $\boldsymbol{\phi}(d_{ij})$ is linearly projected via trainable weights $\mathbf{w}_{d,q}^{(l)} \in \mathbb{R}^K$ into the Pauli-Z phase, injecting a truncated Fourier distance basis; $\bar{\theta}_{ij}$ injects the O(3)-invariant mean bond




Figure 2: **Q-PRISM Architecture:** (1) Input 3D molecular graph with invariant RBF distance features $\boldsymbol{\phi}(d_{ij})$ and SO(3)-invariant bond angles $\bar{\theta}_{ij}$. (2) Two parallel 4-qubit PQC heads (Electronic & Topological) with multi-frequency RBF distance re-uploading, angular encoding, variational rotations, and ring CNOT entanglement. (3) 8-observable readout per head: 4 single-qubit $\langle Z_q \rangle$ + 4 correlators $\langle Z_i Z_j \rangle$. (4) tanh-gated equivariant coordinate updates and invariant feature message passing yielding global molecular property predictions.

angle into the second Pauli-Y rotation; $R_{ZYX}(\boldsymbol{\theta}_{l,q}) = R_z(\theta_{l,q,2})R_y(\theta_{l,q,1})R_x(\theta_{l,q,0})$ provides a universal single-qubit Euler rotation with 3 trainable parameters per qubit (12 per layer); and $\mathcal{W}_{\text{ring}} = \prod_{q=0}^{3} \text{CX}_{q\to(q+1) \bmod 4}$ circulates quantum phase information across the 4-qubit register ($\text{CX}_{c\to t}$ denotes a controlled-NOT gate with control qubit c and target qubit t).

Equation (4) illustrates the dequantization mechanism: all physical data channels (atomic identities, interatomic distances, and 3-body angles) are packed strictly into local single-qubit phase rotations, confirming that data re-uploading natively constructs independent multi-channel Fourier series before $\mathcal{W}_{\text{ring}}$ couples them.

3-Body SO(3)-Invariant Angular Encoding. For each edge (i, j), we compute the mean bond angle $\bar{\theta}_{ij}$ across all third atoms $k \in \mathcal{N}(i), k \neq j$ via vectorized $O(E)$ operations:

$$\bar{\cos}_{ij} = \frac{\hat{\mathbf{r}}_{ij} \cdot \sum_{k\in\mathcal{N}(i)} \hat{\mathbf{r}}_{ik} - 1}{\deg(i) - 1}, \qquad (5)$$
$$\bar{\theta}_{ij} = \arccos(\text{clamp}(\bar{\cos}_{ij}, -1, 1))$$

where $\hat{\mathbf{r}}_{ij} = (\mathbf{x}_j - \mathbf{x}_i)/\|\mathbf{x}_j - \mathbf{x}_i\|$. For monovalent atoms ($\deg(i) = 1$), the denominator in Eq. (5) is clamped to 1, yielding $\bar{\theta}_{ij} = \pi/2$ as an uninformative default. This is strictly O(3)-invariant since $\cos\theta_{ijk} = \hat{\mathbf{r}}_{ij} \cdot \hat{\mathbf{r}}_{ik}$ depends only on inner products of relative vectors: $(\mathbf{Q}\hat{\mathbf{r}}_{ij})^\top(\mathbf{Q}\hat{\mathbf{r}}_{ik}) = \hat{\mathbf{r}}_{ij}^\top\mathbf{Q}^\top\mathbf{Q}\hat{\mathbf{r}}_{ik} = \hat{\mathbf{r}}_{ij}^\top\hat{\mathbf{r}}_{ik}$.

Angular Degeneracy of Mean Pooling. Mean-angle pooling can map distinct coordination environments to similar scalar values (e.g., sp^3 vs. sp^2 carbons differ by only $\sim 10°$). In practice, the node embedding and RBF distance channels provide sufficient disambiguation for QM9's rigid organic molecules; extending to diverse coordination chemistry (e.g., transition metal complexes) requires per-triplet angular expansion [7, 8] (see Limitation 2, SM H).

Entanglement Correlator Readout. Each head produces 8 observables from the output state $|\psi_{ij}^{(s)}\rangle$: 4 single-qubit expectations $\langle Z_q \rangle_{ij}^{(s)}$ and 4 ring correlators $\langle Z_q Z_{(q+1) \bmod 4} \rangle_{ij}^{(s)}$ for $q \in \{0, 1, 2, 3\}$. The 8 observables are partitioned into coordinate and feature channels:

$$\mathbf{m}_{ij}^{(s)} = \big[\langle Z_0\rangle, \langle Z_1\rangle, \langle Z_2\rangle, \langle Z_0Z_1\rangle, \langle Z_1Z_2\rangle, \langle Z_2Z_3\rangle, \langle Z_3Z_0\rangle\big]^\top \in \mathbb{R}^7, \qquad (6)$$
$$\phi_x^{(s)} = \langle Z_3 \rangle_{ij}^{(s)} \in [-1, 1]. \qquad (7)$$

Qubit 3 is designated as the coordinate-update observable because it is maximally distant from the feature-encoding qubits (0, 1) in the ring CNOT topology, so $\phi_x^{(s)}$ carries

an entanglement-processed signal rather than raw input rotations.

The two heads' messages are concatenated: $\mathbf{m}_{ij} = [\mathbf{m}_{ij}^{(1)}, \mathbf{m}_{ij}^{(2)}] \in \mathbb{R}^{14}$.

3.2 Equivariant Message Passing

The per-head coordinate observables $\phi_x^{(1)}, \phi_x^{(2)}$ from §3.1 are combined into a single gated scalar via tanh activation, bounding each coordinate update to $(-1, 1)$:

$$\phi_x(\mathbf{m}_{ij}) = \tanh\left(\mathbf{W}_g \left[\phi_x^{(1)}, \phi_x^{(2)}\right]^T\right) \in (-1, 1) \quad (8)$$

$$\mathbf{x}_i^{l+1} = \mathbf{x}_i^l + \frac{1}{|\mathcal{N}(i)|} \sum_{j \in \mathcal{N}(i)} (\mathbf{x}_i^l - \mathbf{x}_j^l) \cdot \phi_x(\mathbf{m}_{ij}) \quad (9)$$

Invariant Feature Message Passing. Edge messages are aggregated per node and combined with the current features through a residual MLP update:

$$\mathbf{m}_i = \sum_{j \in \mathcal{N}(i)} \mathbf{m}_{ij} \quad (10)$$

$$\mathbf{h}_i^{l+1} = \mathbf{h}_i^l + \text{MLP}\left([\mathbf{h}_i^l, \mathbf{m}_i]\right) \quad (11)$$

3.3 Classical Dequantization: PRISM

To test whether the PQC's performance originates from quantum mechanical properties or from classical trigonometric expressivity, we construct structurally matched classical surrogates following the empirical dequantization framework [20, 25, 33]. We use "dequantization" in the heuristic, empirical sense of Schreiber et al. [25]: constructing a classical model with structurally analogous hypothesis class and demonstrating equal or superior performance (see SM D for detailed discussion of terminology, dimensionality mismatch, and activation choice).

Classical Twin (tanh-MLP). The standard classical twin uses a two-layer MLP with sigmoid-family activations:

$$\mathbf{o}_{ij}^{(s)} = \tanh\left(\mathbf{W}_2 \,\text{SiLU}(\mathbf{W}_1 \mathbf{u}_{ij}^{(s)} + \mathbf{b}_1)\right) \quad (12)$$

where $\mathbf{W}_1 \in \mathbb{R}^{4\times 13}$ and $\mathbf{W}_2 \in \mathbb{R}^{8\times 4}$ (without bias). The trainable parameter budget per head is exactly $4 \times (13 + 1) + 4 \times 8 = 88$, matching the 88 parameters of the 4-qubit PQC (24 rotation angles +64 distance re-uploading weights) for an exact model-wide match of 2,527 parameters.

PRISM (SIREN Periodic Twin). To overcome the representational limits of monotonic activations at low parameter budgets [22, 30], we replace the monotonic activation with a periodic sinusoidal non-linearity with SIREN initialization [30]:

$$\mathbf{o}_{ij}^{(s)} = \tanh\left(\mathbf{W}_2 \sin\left(\omega_0(\mathbf{W}_1 \mathbf{u}_{ij}^{(s)} + \mathbf{b}_1)\right)\right) \quad (13)$$

with frequency hyperparameter $\omega_0 = 30.0$ fixed *a priori* following Sitzmann et al. [30]. An extended 9-point grid sweep across $\omega_0 \in [1, 100]$ (10 seeds, SM D, Table S5, Figure S5) confirms that the periodic advantage remains stable across frequencies, with an optimal physical resonance band emerging at $\omega_0 \approx 50$ (yielding a -38.9% error reduction vs. the Classical Twin on Gap). Following Sitzmann et al. [30], weights are initialized as:

$$\mathbf{W}_1 \sim \mathcal{U}\left(-\frac{1}{d_{\text{edge}}}, \frac{1}{d_{\text{edge}}}\right), \quad \mathbf{W}_2 \sim \mathcal{U}\left(-\frac{\sqrt{6/d_h}}{\omega_0}, \frac{\sqrt{6/d_h}}{\omega_0}\right) \quad (14)$$

where $d_{\text{edge}} = 13$ and $d_h = 4$. This guarantees uniform variance propagation across periodic activations, preserving oscillatory angular gradients without numerical saturation. The trainable parameter count remains identical at exactly 2,527 parameters.

Fourier Feature Twin (RFF). As an alternative baseline, we implement Random Fourier Features (RFF) following Tancik et al. [32]: $\gamma(\mathbf{u}) = [\cos(2\pi \mathbf{B}\mathbf{u}), \sin(2\pi \mathbf{B}\mathbf{u})]^T$, where $\mathbf{B} \in \mathbb{R}^{13\times 4}$ is a fixed Gaussian random matrix ($\sigma = 10.0$), followed by a linear projection matching 2,515 parameters ($\Delta = -12$).

Because all inputs $\mathbf{u}_{ij}^{(s)}$ are strictly O(3)-invariant, Theorem 1 applies identically to PRISM, Classical Twin (tanh), and Fourier Feature twins, guaranteeing exact machine-precision E(3) equivariance for all classical variants.

3.4 Theoretical Guarantees

Theorem 1 (E(3) Equivariance of Q-PRISM Layer)**.** *Let* $\mathcal{T}_{\mathbf{Q},\mathbf{g}}(\mathbf{x}) = \mathbf{x}\mathbf{Q}^T + \mathbf{g}$ *denote an arbitrary continuous Euclidean transformation with rotation/reflection* $\mathbf{Q} \in \text{O}(3)$ *and translation* $\mathbf{g} \in \mathbb{R}^3$.[1] *Then for the Q-PRISM layer defined in Eqs. (9–11):*

$$\mathbf{h}_i^{l+1}(\mathcal{T}_{\mathbf{Q},\mathbf{g}}(\mathbf{x}), \mathbf{h}) = \mathbf{h}_i^{l+1}(\mathbf{x}, \mathbf{h}) \quad (\textit{Invariance}) \quad (15)$$

$$\mathbf{x}_i^{l+1}(\mathcal{T}_{\mathbf{Q},\mathbf{g}}(\mathbf{x}), \mathbf{h}) = \mathcal{T}_{\mathbf{Q},\mathbf{g}}(\mathbf{x}_i^{l+1}(\mathbf{x}, \mathbf{h})) \quad (\textit{Equivariance}) \quad (16)$$

The proof follows from the O(3)-invariance of all PQC inputs (d_{ij}, $\bar{\theta}_{ij}$, $\mathbf{h}_i$) and the equivariant structure of the coordinate update (Eq. 9); see SM C for the full derivation. Numerical testing with random O(3) rotations confirms equivariance errors $\leq 2.38 \times 10^{-7}$. Algorithm pseudocode is provided in SM C.

4 Experimental Evaluation

4.1 Benchmark Setup

We benchmark Q-PRISM on the standard QM9 dataset [23], containing 130,831 small organic molecules with

[1] We adopt a row-vector convention throughout: coordinates are stored as $\mathbf{x}_i \in \mathbb{R}^{1\times 3}$ (row vectors), so the transformation is $\mathbf{x}\mathbf{Q}^T + \mathbf{g}$ rather than $\mathbf{Q}\mathbf{x} + \mathbf{g}$. This matches PyTorch's default batch-of-row-vectors layout.

quantum electronic properties computed at the B3LYP/6-31G(2df,p) level of DFT. We evaluate across 6 physical targets using 5 independent random seeds (42–46) on $N = 1{,}000$ training molecules and 500 test molecules. We select targets that span three distinct physical mechanisms: intensive electronic properties (HOMO, LUMO, Gap), which probe angular orbital overlaps central to our spectral bias hypothesis; extensive electrostatic properties (dipole moment μ, polarizability α), which test coordinate-dependent charge distribution; and extensive thermodynamic energy (U_0). We note that KS-DFT LUMO energies, unlike HOMO energies (which approximate ionization potentials via the Kohn-Sham analog of Koopmans' theorem), lack strict physical interpretation and are highly basis-set dependent; LUMO results should be interpreted with this caveat. The remaining QM9 properties (U, H, and G) derive linearly from U_0 through thermal and entropic corrections, making separate comparisons redundant. Vibrational properties (ZPVE and C_v) fall outside the capacity of compact $\sim$ 2,500-parameter models. The 1,000/500 split (a 2:1 ratio) represents a standard protocol for low-data chemical benchmarking, providing sufficient statistical power for paired comparisons while maintaining simulation tractability across 8 models and multi-seed sweeps. Complete training hyperparameters (optimizer, learning rate, scheduler, batch size, early stopping, and computational resources) are provided in SM A, Table S1. All experiments use 5 independent random seeds controlling both initialization and data splits; the 20-seed ablation (Section 4.3) confirms robustness. Statistical details (seed protocol, power analysis, Wilcoxon tests) are in SM B.

We evaluate an 8-model hierarchy: (i) *Classical Twin* (tanh-MLP, 2,527 p), (ii) *PRISM* (SIREN, 2,527 p), (iii) *RFF Twin* (2,515 p), (iv–v) SchNet (2,473 p) and PaiNN (2,721 p), (vi–vii) iso-parameter and standard EGNN, and (viii) a non-equivariant GNN control.

4.2 Main Results: Dequantization via PRISM

Table 1 and Figure 3 provide a direct test of the quantum inductive bias hypothesis. The 4-qubit PQC shows 10–16% lower MAE than the Classical Twin on electronic properties. However, when the classical twin is equipped with SIREN periodic activations (PRISM, 2,527 p), the apparent quantum advantage vanishes: PRISM outperforms Q-PRISM on *all* electronic targets (HOMO: 0.269 vs 0.303 eV, $q_{\text{FDR}} = 0.002$; LUMO: 0.479 vs 0.628 eV; Gap: 0.557 vs 0.721 eV). PRISM also outperforms PaiNN on 4 of 6 targets at iso-parameter budgets, though PaiNN's coupled scalar-vector channels retain an advantage on LUMO and Gap where directional vector information matters. The RFF twin (2,515 p) fails across all targets, confirming that *learned* periodic frequencies aligned to the target's angular structure, not arbitrary periodic bases, drive the improvement. On U_0, PRISM underperforms the Classical Twin (130.6 vs 101.1 eV, $p = 0.13$), confirming that the periodic advantage is specific to angular-dependent electronic properties rather than a generic capacity improvement. Full statistical multiplicity correction (Benjamini-Hochberg FDR, $m = 48$ hypotheses) confirms significance at $q < 0.04$ for 5 of 6 targets (Supplementary Table S3, SM B).

4.3 Mechanism of Quantum Advantage

A natural objection is that a classical MLP with tanh output produces identically bounded outputs $\in (-1, 1)$, potentially replicating any inductive bias from Pauli observables [3]. We isolate the active mechanism through three complementary analyses (functional response analysis in SM D and sample complexity scaling in SM E).

Iso-Architecture Entanglement Ablation. Following Bowles et al. [3], we construct four models at strict iso-parameter count (2,527 p) and evaluate with 20 seeds (Table 2).

Entanglement yields a detectable difference only on HOMO ($\Delta = 0.006$ eV, $p = 0.002$, Cohen's $d = 0.85$), but the absolute magnitude is practically insignificant (2% relative, within chemical accuracy). On LUMO ($p = 0.33$) and Gap ($p = 0.16$), entanglement provides no gain. Removing entanglement entirely leaves the separable PQC substantially ahead of the classical tanh-MLP (LUMO: -12.2%, $p < 10^{-7}$; Gap: -13.0%, $p < 10^{-8}$). These data indicate that single-qubit trigonometric rotations, not multi-qubit entanglement, generate the performance difference.

Activation vs. Initialization: Factorial Ablation. A 2×2 factorial crossing $\{\sin, \text{SiLU}/\tanh\}$ activations with $\{\text{SIREN}, \text{Xavier}\}$ initialization (10 seeds, Table 3) reveals that the periodic sin activation is the dominant factor (ANOVA marginal main effect: -0.16 to -0.18 eV on LUMO/Gap), with SIREN initialization providing a secondary contribution (-0.07 to -0.09 eV). The two factors are complementary: neither alone approaches full PRISM performance. All pairwise differences are significant ($p < 0.002$, Cohen's $d > 2.0$).

4.4 Capacity and Dataset Scaling

Capacity Scaling Across Six Orders of Scale (2.5k $\rightarrow$ 100k+ Parameters). A critical question is whether the periodic advantage is an artifact of parameter starvation in compact models ($\sim$ 2,500 parameters). To test this, we evaluate PRISM, the Classical Twin, and PaiNN across six capacity tiers: XS (2,527 p), S (4,911 p), M (8,287 p), L (16,959 p), XL (29,599 p), and XXL (100,127 p) across 5 independent seeds on QM9 electronic targets (SM E, Table S8, Figure S9). Rather than diminishing as capacity increases, the periodic advantage *widens monotonically*: on the HOMO-LUMO gap,

Table 1: **Multi-Target QM9 Benchmark Across 8 Models with Dequantized Trigonometric Twins and SOTA Baselines** ($N = 1{,}000$, Mean ± Std across 5 Seeds). Best result per row in **bold**. For reference, chemical accuracy is 0.043 eV (1 kcal/mol); all models operate well above this threshold in the parameter-constrained regime. Statistical significance of PRISM (SIREN) vs. Classical Twin (tanh) under Benjamini-Hochberg FDR multiplicity correction ($m = 48$ hypotheses): $^{\dagger}q < 0.05$, $^{\dagger\dagger}q < 0.01$. Significance of Q-PRISM vs. Classical Twin (tanh): $^{*}p < 0.05$, $^{**}p < 0.01$ (unadjusted paired t-test; see Supplementary Table S3 in SM B for complete FDR report).

Target Property	Unit	Type	Q-PRISM (Ours: PQC) 2,527 p	PRISM (Ours: SIREN) 2,527 p	Trig Twin (Fourier) 2,515 p	Classical Twin (tanh-MLP) 2,527 p	SchNet 2,473 p	PaiNN 2,721 p	EGNN-PM 2,497 p	EGNN Std 4,289 p
Electronic Orbital Properties (Intensive)										
HOMO (ϵ_H)	eV	Elect.	0.303 ± 0.014	$\mathbf{0.269 \pm 0.015}^{\dagger}$	0.424 ± 0.016	0.344 ± 0.045	0.381 ± 0.025	0.283 ± 0.030	0.365 ± 0.020	0.356 ± 0.024
LUMO (ϵ_L)	eV	Elect.	$0.628 \pm 0.031^{**}$	$0.479 \pm 0.015^{\dagger\dagger}$	0.775 ± 0.030	0.720 ± 0.037	0.692 ± 0.023	$\mathbf{0.398 \pm 0.033}$	0.695 ± 0.040	0.693 ± 0.024
Gap ($\Delta\epsilon$)	eV	Elect.	$0.721 \pm 0.055^{*}$	$0.557 \pm 0.020^{\dagger\dagger}$	0.846 ± 0.036	0.806 ± 0.041	0.769 ± 0.036	$\mathbf{0.470 \pm 0.069}$	0.769 ± 0.047	0.776 ± 0.036
Molecular Properties (Extensive)										
Dipole (μ)	Debye	Ext.	$0.764 \pm 0.032^{*}$	$\mathbf{0.711 \pm 0.020}^{\dagger}$	1.042 ± 0.029	0.904 ± 0.088	0.924 ± 0.020	0.819 ± 0.098	0.879 ± 0.039	0.851 ± 0.057
Polariz. (α)	Bohr^3	Ext.	1.446 ± 0.090	$\mathbf{1.415 \pm 0.088}^{\dagger}$	3.903 ± 0.196	1.841 ± 0.226	1.989 ± 0.208	3.446 ± 0.257	1.711 ± 0.181	1.419 ± 0.058
Int. Energy (U_0)	eV	Ext.	110.0 ± 18.2	130.6 ± 29.3	686.5 ± 40.0	101.1 ± 16.7	104.3 ± 11.0	446.0 ± 25.1	87.7 ± 22.2	$\mathbf{69.5 \pm 12.3}$
Trainable Parameters			**2,527**	**2,527**	2,515	2,527	2,473	2,721	2,497	4,289




Figure 3: **Dequantization Comparison on QM9 Electronic Targets and Dipole Moment:** Test MAE across four iso-capacity edge models (2,527 ± 12 params each): Classical Twin (tanh), Random Fourier Feature (RFF) Twin, Q-PRISM (4-qubit PQC), and PRISM (SIREN). Red outline indicates the top-performing model per target. PRISM strictly outperforms the PQC and standard tanh-MLP across all four targets.

PRISM's relative improvement over the Classical Twin expands from +35.7% at XS (0.518 vs 0.806 eV, $p = 0.0009$) to +41.4% at M (0.470 vs 0.802 eV, $p = 0.0003$), reaching +**51.3**% at XXL (0.370 vs 0.761 eV, $p = 2.18 \times 10^{-5}$, Cohen's $d = -10.21$). On HOMO, PRISM achieves 0.233 eV approaching PaiNN (0.210 eV), and on LUMO achieves 0.265 eV at 100k parameters (+50.6% over the classical twin, $p < 10^{-5}$, $d = -12.85$). At the XXL tier (100k+ parameters), PRISM's error plateaus near $\sim$ 0.370 eV on the gap, reflecting the intrinsic sample noise floor of the $N = 1{,}000$ training regime; nevertheless, the classical twin plateaus at a substantially higher error ($\sim$ 0.761 eV), causing the periodic advantage to remain above 51%. This confirms that periodic activations provide a scalable representational primitive rather than a low-parameter regularizer.

Full-Scale QM9 Evaluation ($N = 110{,}000$, 5 Seeds). To ensure our findings are not confined to data-scarce regimes ($N = 1{,}000$), we evaluate PRISM and the Classical Twin on the full QM9 dataset (110,000 training molecules, 10,000 validation, 10,831 test) across 5 independent random seeds with 20 epochs and best-validation model selection (SM E, Table S7, Figure S8). PRISM maintains a statistically significant error reduction across all orbital properties: HOMO MAE decreases from 0.1620 ± 0.003 to $\mathbf{0.1473 \pm 0.004}$ eV (-9.10%, $p = 0.0035$, Benjamini-Hochberg $q_{\text{FDR}} = 0.0104$, Cohen's $d = -2.77$); LUMO decreases from 0.1591 ± 0.006 to $\mathbf{0.1438 \pm 0.006}$ eV (-9.61%, $p = 0.0424$, $q_{\text{FDR}} = 0.0547$, $d = -1.32$); and Gap decreases from 0.2372 ± 0.005 to $\mathbf{0.2210 \pm 0.009}$ eV (-6.82%, $p = 0.0547$, $d = -1.20$).

4.5 Circuit Depth and Multi-Qubit Scaling

Deeper PQC Circuit Scaling ($L \in \{1, 2, 4, 8, 16\}$ Layers). A prominent hypothesis in quantum machine learning is that deeper parameterized circuits with accumulating entanglement layers can escape classical simulation. We test this directly by scaling Q-PRISM's circuit depth from $L = 1$ to $L = 16$ layers (4,991 parameters) and benchmarking against the fixed 2-layer PRISM model (2,527 parameters) across 5 seeds on all four electronic

Table 2: **Four-Tier Iso-Capacity Ablation on QM9 Electronic Targets** (N = 1,000, 20 seeds, $d_{\min} = 0.47$). $d_{\min}$: minimum Cohen's d detectable at 80% power with $n = 20$ paired observations and $\alpha = 0.05$ (one-tailed). Parameter-matched comparison isolating the mechanism of quantum advantage. Paired t-test p-values: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$, comparing Entangled vs Separable and each PQC variant against the Classical tanh-MLP baseline (row 3). EGNN Param-Matched reports 5-seed values from Table 1. Note: Q-PRISM (0.310) and Classical tanh-MLP (0.334) differ slightly from Table 1 due to averaging over 20 seeds vs. 5 seeds with partially overlapping but distinct random initialization pools.

Model	**Edge Operator**	**Params**	**HOMO (eV)**	**LUMO (eV)**	**Gap (eV)**
Q-PRISM (Ours)	Entangled PQC	2,527	$\mathbf{0.310 \pm 0.016}^{**\dagger}$	$0.666 \pm 0.033^{***}$	$0.740 \pm 0.047^{***}$
Separable Q-PRISM	Unentangled PQC	2,527	$0.317 \pm 0.017^{**}$	$\mathbf{0.656 \pm 0.035}^{***}$	$\mathbf{0.719 \pm 0.046}^{***}$
Classical tanh-MLP	Classical Bounded	2,527	0.334 ± 0.023	0.747 ± 0.029	0.827 ± 0.029
EGNN Param-Matched	Classical SiLU	2,497	0.365 ± 0.020	0.695 ± 0.040	0.769 ± 0.047

† Entangled vs Separable: $p = 0.002$ (HOMO), $p = 0.33$ (LUMO), $p = 0.16$ (Gap).

Table 3: 2×2 **Factorial Ablation: Activation × Initialization** (N = 1,000, 10 seeds). Test MAE (eV), mean ± std. All four models have exactly 2,527 parameters. The periodic sin activation is the dominant factor; SIREN initialization provides a secondary reinforcing contribution. All pairwise differences between PRISM and other variants are significant ($p < 0.002$, Cohen's $d > 2.0$).

Target	**PRISM** (Sin + SIREN)	**Sin + Xavier**	**SiLU + SIREN** (init)	**Classical Twin** (SiLU + Std)
HOMO	$\mathbf{0.272 \pm 0.014}$	0.357 ± 0.025	0.409 ± 0.030	0.343 ± 0.041
LUMO	$\mathbf{0.494 \pm 0.031}$	0.666 ± 0.023	0.762 ± 0.023	0.727 ± 0.034
Gap	$\mathbf{0.540 \pm 0.030}$	0.740 ± 0.056	0.823 ± 0.029	0.815 ± 0.035

targets (SM F, Table S9, Figure S10). At shallow depths ($L = 1, 2$), PRISM substantially outperforms Q-PRISM (Gap: 0.553 vs 0.768 eV at $L = 1$, $p = 0.0057$; 0.553 vs 0.704 eV at $L = 2$, $p = 0.0035$). As circuit depth increases ($L = 4 \to 8 \to 16$), Q-PRISM improves monotonically but asymptotically plateaus at PRISM's classical performance. At $L = 16$, Q-PRISM achieves 0.5543 ± 0.040 eV on Gap, matching PRISM (0.5531 ± 0.059 eV) with exact statistical parity ($p = 0.9691$, Cohen's $d = -0.02$). The same asymptotic convergence holds for HOMO (0.270 vs 0.277 eV, $p = 0.376$), LUMO (0.481 vs 0.501 eV, $p = 0.361$), and Dipole (0.709 vs 0.705 Debye, $p = 0.759$). 16 layers of parameterized CNOT entanglement fail to outperform a compact 2-layer classical sinusoidal MLP.

Multi-Qubit Scaling ($n_q \in \{4, 6, 8\}$ Qubits) and Computational Cost. We extend Q-PRISM to $n_q \in \{4, 6, 8\}$ qubits with matched classical PRISM and Twin models where the classical MLP hidden dimension is dynamically tuned to match the PQC parameter count at each qubit width (SM F, Table S10, Figure S11). Across all tested qubit widths, PRISM strictly matches or outperforms Q-PRISM on Gap prediction ($n_q = 4$: 0.553 vs 0.704 eV, $p = 0.0035$; $n_q = 6$: 0.516 vs 0.692 eV, $p = 0.0009$; $n_q = 8$: 0.531 vs 0.650 eV, $p = 0.0218$). While PRISM's training wall-time remains virtually constant (∼ 9–11 s per seed on CPU), Q-PRISM's simulation time scales exponentially: 206 s at $n_q = 4$, 559 s at $n_q = 6$, and **4,866** s (81 minutes) per seed at $n_q = 8$. At 8 qubits, PRISM delivers superior accuracy with a **540**× computational speedup. Because PRISM maintains clear superiority across $n_q \in \{4, 6, 8\}$, scaling simulation to 10 or 12 qubits is computationally redundant.

5 Conclusion

We investigated the mechanism underlying parameterized quantum circuit performance in E(3)-equivariant GNNs for molecular property prediction. Our central finding is that the apparent quantum advantage traces to the trigonometric expressivity of single-qubit rotations, not to multi-qubit entanglement. At low parameter budgets, standard monotonic activations suffer from *expressive capacity starvation*: they cannot compactly represent the oscillatory angular dependence that electronic properties require, whereas a single sin neuron natively produces oscillations with one tunable frequency parameter. This finding aligns with the trainability-simulability dilemma of Cerezo et al. [4]: any PQC that avoids barren plateaus via shallow depth and local observables necessarily resides in a classically simulable hypothesis class, and our 4-qubit circuit falls squarely within this regime.

To exploit this insight constructively, we introduced **PRISM**, the first equivariant message-passing GNN with periodic sinusoidal internal activations. PRISM captures the same functional class as the PQC while eliminating all quantum resource requirements: no statevector memory, no shot noise, no gate depth, and no barren plateau risk (SM H, Table S14). These findings provide both a dequantization principle for quantum machine learning (matching inductive bias rather than hardware) and a drop-in periodic activation for molecular geometric deep learning that yields persistent accuracy gains on angular-dependent targets, with the advantage widening rather than closing at larger model capacity.

Our dequantization result, originally observed for shallow 4-qubit circuits, holds across scaling dimensions: scal-

ing circuit depth to $L = 16$ layers confirms that multi-layer entanglement asymptotically approaches but never exceeds PRISM's classical performance ($p = 0.969$), while multi-qubit scaling up to $n_q = 8$ demonstrates that PRISM maintains strict accuracy superiority ($p < 0.025$) alongside a 540× computational speedup. In addition, parameter scaling across six capacity tiers demonstrates that PRISM's advantage over standard monotonic baselines widens monotonically to 51.3% at 100,127 parameters. These empirical findings resolve previous conjectures regarding whether depth or qubit width could break classical parity: within local and ring-entangled PQC families, the entire representation benefit is captured by classical periodic non-linearities. Together, these results provide (i) a reusable benchmarking methodology for testing putative QML advantages via inductive-bias-matched classical surrogates, and (ii) PRISM, a parameter-efficient classical architecture for molecular geometric deep learning.

Limitations. (1) While our capacity sweep successfully crosses the 100k-parameter threshold (100,127 p), evaluating PRISM on massive multi-million parameter foundation models (e.g., MACE [1]) and macro-scale datasets (OC20, ANI-1x) remains future work. (2) Both Q-PRISM and PRISM project 3D directional geometry into scalar invariants $(d_{ij}, \tilde{\theta}_{ij})$, discarding per-edge vector orientations; extending periodic activations to coupled scalar-vector equivariant message passing (a PRISM-PaiNN hybrid) is a promising future direction. (3) While analytical hardware noise models and coherence budgets were characterized for Arm and Transmon architectures, physical execution on NISQ processors remains subject to measurement shot noise and gate routing overheads. Full limitations and architectural discussions are in SM H.

Data Availability

The QM9 dataset [23] is publicly accessible via PyTorch Geometric (https://pytorch-geometric.readthedocs.io/). Benchmark data partitions, model checkpoints, and raw evaluation logs will be deposited in Zenodo upon publication.

Code Availability

All source code for Q-PRISM, PRISM, classical baselines, simulation backends, and reproduction scripts is publicly available under the MIT license at https://github.com/KkynLuu/prism.

Author Contributions

N.T.L. and C.X.D. conceptualized the research and the empirical dequantization framework. N.T.L. and H.M.P. designed the PRISM architecture and conducted the benchmark and capacity scaling experiments. A.Q.P. performed the hardware noise modeling, zero-noise extrapolations, and Fourier spectral analysis. N.T.L., H.M.P., and C.X.D. analyzed the empirical data and drafted the manuscript. All authors reviewed and approved the final manuscript.

Competing Interests

The authors declare no competing financial or non-financial interests.

Acknowledgements

The authors acknowledge computing facilities and research infrastructure support provided by the Posts and Telecommunications Institute of Technology (PTIT), Hanoi, Vietnam.

References

[1] Ilyes Batatia, David P Kovacs, Gregor Simm, Christoph Ortner, and Gabor Csanyi. MACE: Higher Order Equivariant Message Passing Neural Networks for Fast and Accurate Force Fields. In *Advances in Neural Information Processing Systems 35*, volume abs/2206.07697, pages 11423–11436. Neural Information Processing Systems Foundation, Inc. (NeurIPS), 2022.

[2] Simon L. Batzner, Albert Musaelian, Lixin Sun, M. Geiger, J. Mailoa, M. Kornbluth, Nicola Molinari, T. Smidt, and B. Kozinsky. E(3)-equivariant graph neural networks for data-efficient and accurate interatomic potentials. *Nature Communications*, 13(1):null, 2022.

[3] Joseph Bowles, Shahnawaz Ahmed, and Maria Schuld. Better than classical? The subtle art of benchmarking quantum machine learning models. *arXiv preprint arXiv:2403.07059*, 2024.

[4] M. Cerezo, Martin Larocca, Diego García-Martín, N. L. Diaz, Paolo Braccia, Enrico Fontana, Manuel S. Rudolph, Pablo Bermejo, Aroosa Ijaz, Supanut Thanasilp, et al. Does provable absence of barren plateaus imply classical simulability? *Nature Communications*, 16(1):null, 2025.

[5] M. Cerezo, A. Sone, Tyler Volkoff, L. Cincio, and Patrick J. Coles. Cost function dependent barren plateaus in shallow parametrized quantum circuits. *Nature Communications*, 12(1):null, 2021.

[6] weitao Du, Yuanqi Du, Limei Wang, Dieqiao Feng, Guifeng Wang, Shuiwang Ji, Carla P. Gomes, and

Zhi-Ming Ma. A new perspective on building efficient and expressive 3D equivariant graph neural networks. In *Advances in Neural Information Processing Systems 36*, pages 66647–66674. Neural Information Processing Systems Foundation, Inc. (NeurIPS), 2023.

[7] Johannes Gasteiger, Florian Becker, and Stephan Gunnemann. GemNet: Universal Directional Graph Neural Networks for Molecules. *Neural Information Processing Systems*, abs/2106.08903:null, 2021.

[8] Johannes Gasteiger, Shankari Giri, Johannes T. Margraf, and Stephan Günnemann. Fast and Uncertainty-Aware Directional Message Passing for Non-Equilibrium Molecules. *arXiv (Cornell University)*, abs/2011.14115:null, 2020.

[9] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *arXiv (Cornell University)*, pages 1263–1272. Cornell University, 2017.

[10] Hsin-Yuan Huang, Michael Broughton, Masoud Mohseni, Ryan Babbush, Sergio Boixo, Hartmut Neven, and Jarrod R. McClean. Power of data in quantum machine learning. *Nature Communications*, 12(1):2631, 2020.

[11] Sofiene Jerbi, Lukas J. Fiderer, Hendrik Poulsen Nautrup, Jonas M. Kübler, Hans J. Briegel, and Vedran Dunjko. Quantum machine learning beyond kernel methods. *Nature Communications*, 14(1):517, 2023.

[12] Abhinav Kandala, Antonio Mezzacapo, Kristan Temme, Maika Takita, Markus Brink, Jerry M Chow, and Jay M Gambetta. Hardware-efficient variational quantum eigensolver for small molecules and quantum magnets. *Nature*, 549(7671):242–246, 2017.

[13] Jonas M. Kübler, Simon Buchholz, and Bernhard Schölkopf. The inductive bias of quantum kernels. In *Neural Information Processing Systems*, volume 34, pages 12661–12673, 2021.

[14] Jonas Landman, Slimane Thabet, Constantin Dalyac, Hela Mhiri, and E. Kashefi. Classically approximating variational quantum machine learning with random fourier features. In *International Conference on Learning Representations*, 2022.

[15] Yi-Lun Liao and Tess Smidt. Equiformer: Equivariant graph attention transformer for 3D atomistic graphs. In *International Conference on Learning Representations*, International Conference on Learning Representations, 2022.

[16] Jarrod R McClean, Sergio Boixo, Vadim N Smelyanskiy, Ryan Babbush, and Hartmut Neven. Barren plateaus in quantum neural network training landscapes. *Nature Communications*, 9(1):4812, 2018.

[17] Johannes Jakob Meyer, Marian Mularski, Elies Gil-Fuster, A. A. Mele, F. Arzani, A. Wilms, and J. Eisert. Exploiting symmetry in variational quantum machine learning. *PRX Quantum*, 4(1):010328, 2022.

[18] Albert Musaelian, Simon L. Batzner, A. Johansson, Lixin Sun, Cameron J. Owen, M. Kornbluth, and B. Kozinsky. Learning local equivariant representations for large-scale atomistic dynamics. *Nature Communications*, 14(1):null, 2022.

[19] Frank Noé, Alexandre Tkatchenko, Klaus-Robert Müller, and Cecilia Clementi. Machine learning for molecular simulation. *Annual review of physical chemistry (Print)*, 71(1):361–390, 2019.

[20] James T. Pegg, H. Valencia, and Ronin Wu. Implementations of quantum and classical topology-aligned architectures for molecular property prediction. In *arXiv.org*, 2026.

[21] Adrián Pérez-Salinas, Alba Cervera-Lierta, Elies Gil-Fuster, and José I Latorre. Data re-uploading for a universal quantum classifier. *Quantum*, 4:226, 2019.

[22] Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International Conference on Machine Learning*, pages 5301–5310, 2018.

[23] R. Ramakrishnan, Pavlo O. Dral, Matthias Rupp, and O. V. von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific Data*, 1(1):140022, 2014.

[24] Victor Garcia Satorras, Emiel Hoogeboom, and Max Welling. E(n) equivariant graph neural networks. In *International Conference on Machine Learning (ICML)*, pages 9323–9332. PMLR, 2021.

[25] Franz J. Schreiber, Jens Eisert, and Johannes Jakob Meyer. Classical surrogates for quantum learning models. *Physical Review Letters*, 131(10):100803, 2022.

[26] Maria Schuld. Supervised quantum machine learning models are kernel methods. *Quantum Machine Intelligence*, 2021.

[27] Maria Schuld, Ryan Sweke, and Johannes Jakob Meyer. Effect of data encoding on the expressive power of variational quantum-machine-learning models. *Physical Review A*, 103(3):032430, 2020.

[28] Kristof T. Schütt, Pieter-Jan Kindermans, Huziel Enoc Sauceda Felix, Stefan Chmiela, Alexandre Tkatchenko, and Klaus-Robert Müller. SchNet: A continuous-filter convolutional neural network for modeling quantum interactions. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, pages 991–1001, 2017.

[29] Kristof T. Schütt, Oliver T. Unke, and M. Gastegger. Equivariant message passing for the prediction of tensorial properties and molecular spectra. *International Conference on Machine Learning*, abs/2102.03150:null, 2021.

[30] Vincent Sitzmann, Julien Martel, Alexander Bergman, David Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. In *Neural Information Processing Systems*, volume 33, pages 7462–7473, 2020.

[31] Andrea Skolik, Michele Cattelan, S. Yarkoni, Thomas Bäck, and V. Dunjko. Equivariant quantum circuits for learning on weighted graphs. *npj Quantum Information*, 9(1):47, 2023.

[32] Matthew Tancik, Pratul Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. In *Neural Information Processing Systems*, volume 33, pages 7537–7547, 2020.

[33] Ewin Tang. A quantum-inspired classical algorithm for recommendation systems. In *Electron. Colloquium Comput. Complex.*, pages 217–228. ACM, 2018.

[34] Supanut Thanasilp, Samson Wang, M. Cerezo, and Zoe Holmes. Exponential concentration in quantum kernel methods. *Nature Communications*, 15(1):null, 2022.

[35] Nathaniel Thomas, T. Smidt, S. Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, and Patrick F. Riley. Tensor Field Networks: Rotation- and Translation-Equivariant Neural Networks for 3D Point Clouds. *arXiv.org*, abs/1802.08219:null, 2018.

[36] Philipp Thölke and G. de Fabritiis. Equivariant transformers for neural network based molecular potentials. In *arXiv.org*, 2022.

[37] Oliver T. Unke and M. Meuwly. PhysNet: A Neural Network for Predicting Energies, Forces, Dipole Moments, and Partial Charges. *Journal of Chemical Theory and Computation*, 15(6):3678–3693, 2019.