

TIPE : Propagation de rumeurs dans un réseau social

Listing des programmes

Hugo LEVY-FALK

2017

Table des matières

1	graph.ml	2
2	experiment.ml	4
3	sortFirst.ml	6
4	spread.ml	6
5	experimentSpreading.ml	7
6	experimentSpreadingRandom.ml	8
7	experimentSpreadingDegree.ml	9
8	experimentSpreadingBetween.ml	10
9	experimentSpreadingAll.ml	11
10	drawExperimentSpreadingRandom.py	11
11	drawExperimentSpreadingRandomInitial.py	13
12	drawExperimentSpreadingDegreeInitial.py	14
13	drawExperimentSpreadingBetweenInitial.py	16
14	drawExperimentSpreadingAllInitial.py	17

1 graph.ml

```

open Core.Std;;

(* Builds a random graph with the Watts and Strogatz method.
*)

Random.self_init ();;
let wattsStrogatzMatrix n k beta =
  let l = Array.make_matrix n n false in
  let rec wire i j = if i < 0 then wire (n+i) j
    else if i >= n then wire (i-n) j
    else if j < 0 then wire i (n+j)
    else if j >= n then wire i (j-n)
    else (l.(i).(j) <- true; l.(j).(i) <- true)
  in
  let rec unwire i j = if i < 0 then unwire (n+i) j
    else if i >= n then unwire (i-n) j
    else if j < 0 then unwire i (n+j)
    else if j >= n then unwire i (j-n)
    else (l.(i).(j) <- false; l.(j).(i) <- false)
  in
  let rec wired i j = if i < 0 then wired (n+i) j
    else if i >= n then wired (i-n) j
    else if j < 0 then wired i (n+j)
    else if j >= n then wired i (j-n)
    else l.(i).(j)
  in
  for i=0 to n-1 do
    for j = i-k/2 to i+k/2 do
      if j != i then wire i j
    done
  done;
  for i = 0 to n-1 do
    for j = i+1 to (i+k/2) do
      let r = Random.float 1.0 in
      if r < beta then begin
        unwire i j;
        let k = ref (Random.int n) in
        while (wired i !k) || (!k = i) do
          k := Random.int n
        done;
        wire i !k
      end
    done;
  done;
  l
;;

```

```

(* Betweenness centrality of a graph via its adjacency matrix*)
let betweenness g =
  let n = Array.length g in
  let cB = Array.create n (0.0) in
  for s = 0 to n-1 do
    let stack = Stack.create() in
    let p = Array.create n ([]) in
    let sigma = Array.create n (0.0) in
    sigma.(s) <- 1.0;
    let d = Array.create n ((-1)) in
    d.(s) <- 0;
    let q = Queue.create() in
    Queue.enqueue q s;
    while not (Queue.is_empty q) do
      let v = Queue.dequeue_exn q in
      Stack.push stack v;
      for w = 0 to (n-1) do
        let iw = g.(v).(w) in
        if iw then
          if d.(w) < 0 then begin
            Queue.enqueue q w;
            d.(w) <- d.(v) + 1;
          end;
          if d.(w) = (d.(v) + 1) then begin
            sigma.(w) <- sigma.(w) +. sigma.(v);
            p.(w) <- v::p.(w);
          end;
        end;
      done;
    done;
    let delta = Array.create n (0.0) in
    while not (Stack.is_empty stack) do
      let w = Stack.pop_exn stack in
      List.iter ~f:(fun v -> delta.(v) <-
        delta.(v) +. sigma.(v) /. sigma.(w) *. (1.0 +. delta.(w))) p.(w);
      if w != s then begin cB.(w) <- cB.(w) +. delta.(w); end;
    done;
  done;
  cB
;;

let degree g i =
  let n = Array.length g in
  let r = ref 0 in
  for j = 0 to (n-1) do
    if g.(i).(j) then incr r
  done;
  !r
;;

```

```

let maxDegree g n =
  let deg = degree g in
  let size = Array.length g in
  let rec loop i r = if i >= size then r else
    loop (i+1) ((deg i, i)::r)
  in
  SortFirst.sortFirst n (loop 0 [])
;;

let maxBetweenness g n =
  let a = betweenness g in
  let size = Array.length g in
  let rec loop i r = if i >= size then r else
    loop (i+1) ((a.(i), i)::r)
  in
  SortFirst.sortFirst n (loop 0 [])
;;

```

2 experiment.ml

```

(* Structure de la table experiments:
CREATE TABLE "experiments" ("name" TEXT,"last_id" INT,"infos" TEXT DEFAULT (null))
*)

let silent = true;;

let print_return m r = if silent then () else
  Printf.printf ("%s %s") m (Sqlite3.Rc.to_string r)
;;

let load_db () =
  Sqlite3.db_open "experiments.sqlite"
;;

let close_db db =
  Sqlite3.db_close db
;;

let cleaner target row =
  let l = Array.length row in
  for i = 0 to l-1 do
    target := Some(row.(i))
  done;
;;

let get_exp_last_id db name =
  let last_id = ref None in

```

```

let get_last_id () =
  print_return "Recherche du dernier identifiant."
  (Sqlite3.exec_not_null_no_headers db ~cb:(cleaner last_id)
   ("SELECT last_id FROM experiments WHERE name=\"" ^ name ^ "\";"))
in
get_last_id ();
! last_id
;;

let get_experiment db name =
  let last_id = get_exp_last_id db name in
  let last_result = ref None in
  let create_table () =
    print_return ("Création de la table " ^ name)
    (Sqlite3.exec db ("CREATE TABLE \"" ^ name ^ "\" (id INT, value TEXT);"));
    print_return ("Enregistrement dans 'experiments' de la table " ^ name) (
      Sqlite3.exec db ("INSERT INTO experiments VALUES (\\"" ^ name ^ "\", 0, \\"");"
    ))
  in
  let get_last_result id =
    print_return "Recherche du dernier résultat."
    (Sqlite3.exec_not_null_no_headers db ~cb:(cleaner last_result)
     ("SELECT value FROM \"" ^ name ^ "\" WHERE id=\"" ^ id ^ "\";"))
  in
  let get_last_step () = match last_id with
  | None -> create_table (); !last_result
  | Some s -> get_last_result s; !last_result
  in
  get_last_step ()
;;

let add_step_id db exp id str =
  print_return (Printf.sprintf ("Ajout de l'étape %d à %s") id exp)
  (Sqlite3.exec db
   ("INSERT INTO \"" ^ exp ^ "\" VALUES (\\" ^ (string_of_int id) ^ "\", \\" ^ str ^ "\";"))
  ;;

let change_last_id db exp id =
  print_return (Printf.sprintf
   ("Mise à jour du dernier identifiant (%d) de %s") id exp)
  (Sqlite3.exec db
   ("UPDATE experiments SET last_id = "
    ^ (string_of_int id) ^ " WHERE name=\"" ^ exp ^ "\";"))
  ;;

let add_step db exp str = let id =
  match get_exp_last_id db exp with
  | None -> 0
  | Some(s) -> (1 + (int_of_string s))
in

```

```

    add_step_id db exp id str;
    change_last_id db exp id;
;;

```

3 sortFirst.ml

```

open Core.Std;;

let sortFirst n l =
  let rec sep p l left right len_l = match l with
  | [] -> left, right, len_l
  | (a,b)::tl when a > p -> sep p tl ((a,b)::left) right (len_l + 1)
  | (a,b)::tl -> sep p tl left ((a,b)::right) len_l
  in
  let rec loop n l = match l with
  | [] -> []
  | (a,b)::tl ->
    let left, right, len_l = sep a tl [] [] 0 in
    if len_l >= n then (loop n left)
    else
      (loop n left)@[a,b]@(loop (n-len_l-1) right)
  in
  List.map (loop n l) ~f:(fun (a,b) -> b)
;;

```

4 spread.ml

```

open Core.Std;;

(*
  Spread the rumor and return the amount of nodes aware of it.
  *)
let step_p graph a b s =
  let n = Array.length graph in
  let p_lim = b /. (a +. b) in
  let nb = ref 0 in
  for i = 0 to n-1 do
    if not s.(i) then begin
      let aware = ref 0 in
      let d = ref 0 in
      for j = 0 to n-1 do
        if graph.(i).(j) then(
          incr d;
          if s.(j) then incr aware;
        )
      done;
      let p = (float_of_int !aware) /. (float_of_int !d) in

```

```

        if p > p_lim then (s.(i) <- true; incr nb)
      end
    else incr nb
  done;
  !nb
;;

```

5 experimentSpreading.ml

```

open Core.Std;;
open Yojson.Basic.Util;;

type exp_stat = {
  graph_no:int;
  prop_spread:float array;
};;

let json_of_exp_stat e =
  `Assoc [
    ("graph_no", `Int e.graph_no);
    ("prop_spread",
     `List (List.map (Array.to_list e.prop_spread) ~f:(fun x -> `Float x)))
  ];;

let exp_stat_of_json json =
  {
    graph_no = json |> member "graph_no" |> to_int;
    prop_spread = json |> member "prop_spread" |> to_list
    |> List.map ~f:(fun x -> x |> to_float) |> Array.of_list
  }
;;

let escape_double_quotes s =
  let exp = Str.regexp "\"" in
  Str.global_replace exp "\\\"" s
;;

let save_step db e exp_name=
  json_of_exp_stat e
  |> Yojson.Basic.to_string
  |> escape_double_quotes
  |> Experiment.add_step_id db exp_name e.graph_no;
  Experiment.change_last_id db exp_name e.graph_no
;;

```

```

let process ?(max=99) db graph_size nb_gen k beta max_spread_step a b choose_spread name=
  let step i init=
    let g = Graph.wattsStrogatzMatrix graph_size k beta in
    let prop_spread = Array.create max_spread_step 0.0 in
    let spread = choose_spread g init in
    let j = ref 0 in
    let p = ref (-1.0) in
    while !j <= (max_spread_step-1) && prop_spread.(!j) != !p do
      prop_spread.(!j) <-
        (float_of_int (Spread.step_p g a b spread)) /. (float_of_int graph_size);
      if !j > 0 then (p := prop_spread.(!j-1));
      incr j;
    done;
    {graph_no=i; prop_spread=prop_spread}
  in
  let experiment init db=
    let exp_name = Printf.sprintf ("r_spreading_%s_%d_%d_%d_%d_%d_%d_%d")
      name graph_size (int_of_float (beta*.100.0))
      k nb_gen init max_spread_step (int_of_float a) (int_of_float b) in
    print_endline ("Nom de l'expérience : "^exp_name);
    let cur_step = ref (match Experiment.get_experiment db exp_name
      with
      | None -> {graph_no= (-1);prop_spread=[|]}
      | Some(s) -> s |> Yojson.Basic.from_string |> exp_stat_of_json
    ) in
    let beg = !cur_step.graph_no + 1 in
    for i = beg to nb_gen - 1 do
      cur_step := step i ((float_of_int init)/.100.0);
      save_step db !cur_step exp_name
    done;
  in
  for i = 1 to max do
    experiment i db;
  done
;;

```

6 experimentSpreadingRandom.ml

```

open Core.Std;;

let graph_size = 500;;
let nb_gen = 100;;
let max_spread_step = 500;;

let choose_spread _ init =
  let s = Array.create graph_size false in
  let k = ref 0 in

```



```

let n = int_of_float ((float_of_int graph_size) *. init) in
while !k <= n do
  let i = Random.int graph_size in
  if not s.(i) then (incr k; s.(i) <- true)
done;
s
;;

let () =
  print_endline "Initialisation de Random.";
  Random.self_init ();
  print_endline "Ouverture de la base de données.";
  let db = Experiment.load_db () in
  for b = 0 to 4 do
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 1.0 1.0 choose_spread "random";
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 3.0 1.0 choose_spread "random";
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 1.0 3.0 choose_spread "random";
  done;
  print_endline "Fermeture de la base de données.";
  if (Experiment.close_db db) then
    print_endline "Fermeture réussie."
  else
    print_endline "Echec de la fermeture."

```

7 experimentSpreadingDegree.ml

```

open Core.Std;;

let graph_size = 500;;
let nb_gen = 100;;
let max_spread_step = 500;;

let choose_spread g init =
  let s = Array.create graph_size false in
  let n = int_of_float ((float_of_int graph_size) *. init) in
  let rec loop l = match l with
  | [] -> ()
  | hd::tl -> s.(hd) <- true; loop tl
  in
  loop (Graph.maxDegree g n); s
;;

let () =
  print_endline "Initialisation de Random.";

```

```

Random.self_init ();
print_endline "Ouverture de la base de données.";
let db = Experiment.load_db () in
for b = 0 to 4 do
  ExperimentSpreading.process db graph_size nb_gen 50
    ((float_of_int b) *. 0.25) max_spread_step 1.0 1.0 choose_spread "degree";
  ExperimentSpreading.process db graph_size nb_gen 50
    ((float_of_int b) *. 0.25) max_spread_step 3.0 1.0 choose_spread "degree";
  ExperimentSpreading.process db graph_size nb_gen 50
    ((float_of_int b) *. 0.25) max_spread_step 1.0 3.0 choose_spread "degree";
done;
print_endline "Fermeture de la base de données.";
if (Experiment.close_db db) then
  print_endline "Fermeture réussie."
else
  print_endline "Echec de la fermeture."

```

8 experimentSpreadingBetween.ml

```

open Core.Std;;

let graph_size = 500;;
let nb_gen = 100;;
let max_spread_step = 500;;

let choose_spread g init =
  let s = Array.create graph_size false in
  let n = int_of_float ((float_of_int graph_size) *. init) in
  let rec loop l = match l with
  | [] -> ()
  | hd::tl -> s.(hd) <- true; loop tl
  in
  loop (Graph.maxBetweenness g n); s
;;

let () =
  print_endline "Initialisation de Random.";
  Random.self_init ();
  print_endline "Ouverture de la base de données.";
  let db = Experiment.load_db () in
  for b = 0 to 4 do
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 1.0 1.0 choose_spread "between";
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 3.0 1.0 choose_spread "between";
    ExperimentSpreading.process db graph_size nb_gen 50
      ((float_of_int b) *. 0.25) max_spread_step 1.0 3.0 choose_spread "between";
  done;

```

```

print_endline "Fermeture de la base de données.";
if (Experiment.close_db db) then
  print_endline "Fermeture réussie."
else
  print_endline "Echec de la fermeture."
;;

```

9 experimentSpreadingAll.ml

```

let graph_size = 500;;
let nb_gen = 50;;
let max_spread_step = 500;;
let b = 0.5;;

let () =
  print_endline "Initialisation de Random.";
  Random.self_init ();
  print_endline "Ouverture de la base de données.";
  let db = Experiment.load_db () in
  ExperimentSpreading.process ~max:50 db graph_size nb_gen 50
    b max_spread_step 2.0 1.0 ExperimentSpreadingRandom.choose_spread "random";
  ExperimentSpreading.process ~max:50 db graph_size nb_gen 50
    b max_spread_step 2.0 1.0 ExperimentSpreadingDegree.choose_spread "degree";
  ExperimentSpreading.process ~max:50 db graph_size nb_gen 50
    b max_spread_step 2.0 1.0 ExperimentSpreadingBetween.choose_spread "between";
  print_endline "Fermeture de la base de données.";
  if (Experiment.close_db db) then
    print_endline "Fermeture réussie."
  else
    print_endline "Echec de la fermeture."

```

10 drawExperimentSpreadingRandom.py

```

import matplotlib.pyplot as pl
import numpy as np
import sqlite3
import json

graph_size = 500
nb_gen = 100
k = 50
max_spread_step = 500

X = np.arange(max_spread_step)
conn = sqlite3.connect('experiments.sqlite')
pl.close('all')
fig = pl.figure()

```

```

ax = fig.add_subplot(111)
fig.suptitle(
    "Avancement de la propagation pour une distribution initiale aléatoire.",
    fontweight='bold')
ax.set_title('Taille du graphe={} Nb gen={} K={}'.format(graph_size,nb_gen,k))
ax.set_ylabel("Proportion")
ax.set_xlabel("Étape")

def process_json_mean(j, Y, Y_low, Y_high):
    t = json.loads(j)['prop_spread']
    for x,i in enumerate(t):
        Y[x] += i
        Y_high[x] = max(Y_high[x],i)
        if Y_low[x] == 0:
            Y_low[x] = i
        else:
            Y_low[x] = min(Y_low[x],i)

def process_standard_deviation(j, Y_deviation, Y):
    t = json.loads(j)['prop_spread']
    for x,i in enumerate(t):
        Y_deviation[x] += (i - Y[x])**2

def process_one(init):
    Y = np.zeros(max_spread_step)

    Y_deviation = np.zeros(max_spread_step)
    Y_high = np.zeros(max_spread_step)
    Y_low = np.zeros(max_spread_step)

    cursor = conn.execute(
        "SELECT value FROM r_spreading_random_"+
        "{graph_size}_{beta}_{k}_{nb_gen}_{x}_{max_spread_step}_{a}_{b}".format(
            graph_size, nb_gen, int(init*10), max_spread_step))
    rows = cursor.fetchall()
    for row in rows:
        process_json_mean(row[1], Y, Y_low, Y_high)
    Y = [y/nb_gen for y in Y]
    pl.plot(X, Y, label="Proportion initiale {}".format(init*10))

for i in range(6,15):
    process_one(i/2)
conn.close()

pl.legend(loc="best")
pl.grid()
pl.show()

```

11 drawExperimentSpreadingRandomInitial.py

```

import matplotlib.pyplot as pl
from matplotlib.tikz import save as tikz_save
import numpy as np
import sqlite3
import json

graph_size = 500
nb_gen = 100
k = 50
max_spread_step = 500
conn = sqlite3.connect('experiments.sqlite')
for a,b in [(1,1), (1,3), (3,1)]:
    for beta in [0,25,50,75,100]:
        X = np.arange(1,100)
        pl.close('all')
        fig = pl.figure()
        ax = fig.add_subplot(111)
        ax.set_title('Taille du graphe={} Nb gen={} K={}, q={}, Beta ={}\n%'
                    .format(graph_size,nb_gen,k,b/(a+b),beta))
        ax.set_ylabel("Proportion finale")
        ax.set_xlabel("Proportion initiale (\n%)")

        Y = np.zeros(100)
        Y_high = np.zeros(100)
        Y_low = np.zeros(100)

        x_50 = 0

        for x in X:
            cursor = conn.execute(
                "SELECT value FROM r_spreading_random_"+
                "{graph_size}_{beta}_{k}_{nb_gen}_{x}_{max_spread_step}_{a}_{b}"
                .format(**locals()))
            rows = cursor.fetchall()
            v = 0
            n = len(rows)
            for row in rows:
                v += json.loads(row[0])['prop_spread'][-1]
            Y[x] = v/n
            if abs(0.5-Y[x]) < abs(Y[x_50]-0.5):
                x_50 = x
            v = 0
        for row in rows:
            v += (Y[x] - json.loads(row[0])['prop_spread'][-1])**2

```

```

        v = (v/n)**(1/2)
        Y_high[x] = Y[x] + v
        Y_low[x] = Y[x] - v

    pl.grid()

    pl.plot(X,Y[1:], 'b', label="Propagation finale", lw=2.5)
    pl.plot(X,X/100, 'g--', label="Identité", lw=2.5)
    pl.plot(X, Y_high[1:], 'r--', label="Écart-type", lw=2.5)
    pl.plot(X, Y_low[1:], 'r--', lw=2.5)
    pl.axvline(x_50, c='orange', lw=2.5)
    pl.axhline(0.5, xmin=0, xmax=100, c='orange', lw=2.5)

    pl.text(x_50+1, 0.1, str(x_50)+" \\\%",
            bbox=dict(facecolor='orange', alpha=0.95),
            size="large",
            color="white",
            fontweight="bold")

    pl.legend(loc="lower right")
    tikz_save("resultats/random_finale_f_initiale_q{}_Beta{}_ec.tex"
              .format(int(b/(a+b)*100), beta))
conn.close()

```

12 drawExperimentSpreadingDegreeInitial.py

```

import matplotlib.pyplot as pl
from matplotlib2tikz import save as tikz_save
import numpy as np
import sqlite3
import json

graph_size = 500
nb_gen = 100
k = 50
max_spread_step = 500
conn = sqlite3.connect('experiments.sqlite')
for a,b in [(1,1), (1,3), (3,1)]:
    for beta in [0,25,50,75,100]:
        X = np.arange(1,100)
        pl.close('all')
        fig = pl.figure()
        ax = fig.add_subplot(111)
        ax.set_title('Taille du graphe={} Nb gen={} K={}, q={}, Beta ={}\\\%'
                    .format(graph_size,nb_gen,k,b/(a+b),beta))
        ax.set_ylabel("Proportion finale")
        ax.set_xlabel("Proportion initiale (\\%)")

```

```

Y = np.zeros(100)
Y_high = np.zeros(100)
Y_low = np.zeros(100)

x_50 = 0

for x in X:
    cursor = conn.execute(
        "SELECT value FROM r_spreading_degree_"+
        "{graph_size}_{beta}_{k}_{nb_gen}_{x}_{max_spread_step}_{a}_{b}"
        .format(**locals()))
    rows = cursor.fetchall()
    v = 0
    n = len(rows)
    for row in rows:
        v += json.loads(row[0])['prop_spread'][-1]
    Y[x] = v/n
    if abs(0.5-Y[x]) < abs(Y[x_50]-0.5):
        x_50 = x
    v = 0
    for row in rows:
        v += (Y[x] - json.loads(row[0])['prop_spread'][-1])**2
    v = (v/n)**(1/2)
    Y_high[x] = Y[x] + v
    Y_low[x] = Y[x] - v

pl.plot(X,Y[1:], 'b', label="Propagation finale", lw=2.5)
pl.plot(X,X/100, 'g--', label="Identité", lw=2.5)
pl.plot(X, Y_high[1:], 'r--', label="Écart-type", lw=2.5)
pl.plot(X, Y_low[1:], 'r--')

pl.axvline(x_50, c='orange', lw=2.5)
pl.axhline(0.5, xmin=0, xmax=100, c='orange', lw=2.5)
pl.text(x_50+1, 0.1, str(x_50)+" \\\%",
        bbox=dict(facecolor='orange', alpha=0.95),
        size="large",
        color="white",
        fontweight="bold")

pl.legend(loc="lower right")
pl.grid()
tikz_save("resultats/degree_finale_f_initiale_q{}_Beta{}_ec.tex"
        .format(int(b/(a+b)*100), beta))

conn.close()

```

13 drawExperimentSpreadingBetweenInitial.py

```

import matplotlib.pyplot as pl
from matplotlib.tikz import save as tikz_save
import numpy as np
import sqlite3
import json

graph_size = 500
nb_gen = 100
k = 50
max_spread_step = 500
conn = sqlite3.connect('experiments.sqlite')
for a,b in [(1,1), (1,3), (3,1)]:
    for beta in [0,25,50,75,100]:
        X = np.arange(1,100)
        pl.close('all')
        fig = pl.figure()
        ax = fig.add_subplot(111)
        ax.set_title('Taille du graphe={} Nb gen={} K={}, q={}, Beta ={}\%'
                    .format(graph_size,nb_gen,k,b/(a+b),beta))
        ax.set_ylabel("Proportion finale")
        ax.set_xlabel("Proportion initiale (\%)"

        Y = np.zeros(100)
        Y_high = np.zeros(100)
        Y_low = np.zeros(100)

        x_50 = 0

        for x in X:
            cursor = conn.execute(
                "SELECT value FROM r_spreading_between_"+
                "{graph_size}_{beta}_{k}_{nb_gen}_{x}_{max_spread_step}_{a}_{b}"
                .format(**locals()))
            rows = cursor.fetchall()
            v = 0
            n = len(rows)
            for row in rows:
                v += json.loads(row[0])['prop_spread'][-1]
            Y[x] = v/n
            if abs(0.5-Y[x]) < abs(Y[x_50]-0.5):
                x_50 = x
            v = 0
        for row in rows:
            v += (Y[x] - json.loads(row[0])['prop_spread'][-1])**2

```



```

        v = (v/n)**(1/2)
        Y_high[x] = Y[x] + v
        Y_low[x] = Y[x] - v

    pl.grid()

    pl.plot(X,Y[1:], 'b', label="Propagation finale", lw=2.5)
    pl.plot(X,X/100, 'g--', label="Identité", lw=2.5)
    pl.plot(X, Y_high[1:], 'r--', label="Écart-type", lw=2.5)
    pl.plot(X, Y_low[1:], 'r--', lw=2.5)
    pl.axvline(x_50, c='orange', lw=2.5)
    pl.axhline(0.5, xmin=0, xmax=100, c='orange', lw=2.5)

    pl.text(x_50+1, 0.1, str(x_50)+" \\\%",
           bbox=dict(facecolor='orange', alpha=0.95),
           size="large",
           color="white",
           fontweight="bold")

    pl.legend(loc="lower right")
    # tikz_save("resultats/random_finale_f_initiale_q{}_Beta{}_ec.tex"
    #           .format(int(b/(a+b)*100), beta))
    pl.plot()
    pl.show()
conn.close()

```

14 drawExperimentSpreadingAllInitial.py

```

import matplotlib.pyplot as pl
from matplotlib2tikz import save as tikz_save
import numpy as np
import sqlite3
import json

graph_size = 500
nb_gen = 100
k = 50
max_spread_step = 500
conn = sqlite3.connect('experiments.sqlite')
beta = 50
for a,b in [(1,1), (1,3), (3,1)]:
    X = np.arange(1,100)
    pl.close('all')
    fig = pl.figure()
    ax = fig.add_subplot(111)
    ax.set_title('Taille du graphe={} Nb gen={} K={}, q={}, Beta ={}\\\%'
                .format(graph_size,nb_gen,k,b/(a+b),beta))

```

```

ax.set_ylabel("Proportion finale")
ax.set_xlabel("Proportion initiale (\\%)")

Y = [np.zeros(100) for _ in range(3)]
Y_high = [np.zeros(100) for _ in range(3)]
Y_low = [np.zeros(100) for _ in range(3)]

corres = ["between", "degree", "random"]
x_50 = [0,0,0]
pl.grid()
pl.plot(X,X/100, '--', color="gray", label="Identité", lw=2.5)
for i in range(3):
    for x in X:
        cursor = conn.execute(
            "SELECT value FROM r_spreading_{_}.format(corres[i])+
            \"{graph_size}_{beta}_{k}_{nb_gen}_{x}_{max_spread_step}_{a}_{b}\"
            .format(**locals()))
        rows = cursor.fetchall()
        v = 0
        n = len(rows)
        for row in rows:
            v += json.loads(row[0])['prop_spread'][-1]
        Y[i][x] = v/n
        if abs(0.5-Y[i][x]) < abs(Y[i][x_50[i]]-0.5):
            x_50[i] = x
        v = 0
        for row in rows:
            v += (Y[i][x] - json.loads(row[0])['prop_spread'][-1])**2
        v = (v/n)**(1/2)
        Y_high[i][x] = Y[i][x] + v
        Y_low[i][x] = Y[i][x] - v

    pl.plot(X,Y[i][1:], label="Propagation finale {}".format(corres[i]), lw=2.5)
    # pl.plot(X, Y_high[i][1:], '--', label="Écart-type {}".format(corres[i]), lw=2.5)
    # pl.plot(X, Y_low[i][1:], '--', lw=2.5)
    # pl.axvline(x_50[i], c='orange', lw=2.5)

    # pl.text(x_50[i]+1, 0.1, str(x_50[i])+" \\%",
    #         bbox=dict(facecolor='orange', alpha=0.95),
    #         size="large",
    #         color="white",
    #         fontweight="bold")

pl.axhline(0.5, xmin=0, xmax=100, c='orange', lw=2.5)
pl.legend(loc="lower right")
# tikz_save("resultats/all_finale_f_initiale_q{}_Beta{}_ec.tex"
#           .format(int(b/(a+b)*100), beta))
pl.plot()

```

```
    pl.show()  
conn.close()
```