



Budapest University of Technology and Economics  
Department of Artificial Intelligence and Systems Engineering

# Artificial intelligence – VIMIAC16-EN, VIMIAC10

2024 Fall Semester

Dr. Gábor Hullám

Slides Adapted from Berkeley CS188, from Dan Klein, Pieter Abbeel and Sergey Levine  
<http://ai.berkeley.edu>






# Artificial intelligence lectures

Az előadás diái az AIMA könyvre épülve (<http://aima.cs.berkeley.edu>) készültek a University of California, Berkeley mesterséges intelligencia kurzusának anyagainak felhasználásával (<http://ai.berkeley.edu>).

These slides are based on the AIMA book (<http://aima.cs.berkeley.edu>) and were adapted from the AI course material of University of California, Berkeley (<http://ai.berkeley.edu>).

# Classification

---



# Example: Spam Filter

- Input: an email
- Output: spam/ham
- Setup:
  - Get a large collection of example emails, each labeled “spam” or “ham”
  - Note: someone has to hand label all this data!
  - Want to learn to predict labels of new, future emails
- Features: The attributes used to make the ham / spam decision
  - Words: FREE!
  - Text Patterns: \$dd, CAPS
  - Non-text: SenderInContacts
  - ...



Dear Sir.

First, I must solicit your confidence in this transaction, this is by virtue of its nature as being utterly confidential and top secret. ...



TO BE REMOVED FROM FUTURE MAILINGS, SIMPLY REPLY TO THIS MESSAGE AND PUT "REMOVE" IN THE SUBJECT.



99 MILLION EMAIL ADDRESSES  
FOR ONLY \$99



Ok, I know this is blatantly OT but I'm beginning to go insane. Had an old Dell Dimension XPS sitting in the corner and decided to put it to use, I know it was working pre being stuck in the corner, but when I plugged it in, hit the power nothing happened.

# Example: Digit Recognition

- Input: images / pixel grids
- Output: a digit 0-9
- Setup:
  - Get a large collection of example images, each labeled with a digit
  - Note: someone has to hand label all this data!
  - Want to learn to predict labels of new, future digit images
- Features: The attributes used to make the digit decision
  - Pixels: (6,8)=ON
  - Shape Patterns: NumComponents, AspectRatio, NumLoops
  - ...




# Other Classification Tasks

- Classification: given inputs  $x$ , predict labels (classes)  $y$

- Examples:


- Spam detection (input: document, classes: spam / ham)
- OCR (input: images, classes: characters)
- Medical diagnosis (input: symptoms, classes: diseases)
- Automatic essay grading (input: document, classes: grades)
- Fraud detection (input: account activity, classes: fraud / no fraud)
- Customer service email routing
- ... many more



- Classification is an important commercial technology!

# Model-Based Classification

---



# Model-Based Classification

- Model-based approach
  - Build a model (e.g. Bayes' net) where both the label and features are random variables
  - Instantiate any observed features
  - Query for the distribution of the label conditioned on the features
- Challenges
  - What structure should the BN have?
  - How should we learn its parameters?






# Naïve Bayes for Digits

- Naïve Bayes: Assume all features are independent effects of the label

- Simple digit recognition version:


- One feature (variable)  $F_{ij}$  for each grid position  $\langle i,j \rangle$
- Feature values are on / off, based on whether intensity is more or less than 0.5 in underlying image
- Each input maps to a feature vector, e.g.

  $\rightarrow \langle F_{0,0} = 0 \ F_{0,1} = 0 \ F_{0,2} = 1 \ F_{0,3} = 1 \ F_{0,4} = 0 \ \dots F_{15,15} = 0 \rangle$

- Here: lots of features, each is binary valued

- Naïve Bayes model:  $P(Y|F_{0,0} \dots F_{15,15}) \propto P(Y) \prod_{i,j} P(F_{i,j}|Y)$

- What do we need to learn?



# General Naïve Bayes


- A general Naive Bayes model:

$|Y|$  parameters

$$P(Y, F_1 \dots F_n) = P(Y) \prod_i P(F_i|Y)$$

$|Y| \times |F|^n$  values

$n \times |F| \times |Y|$   
parameters



- We only have to specify how each feature depends on the class
- Total number of parameters is *linear* in  $n$
- Model is very simplistic, but often works anyway

# Inference for Naïve Bayes

- Goal: compute posterior distribution over label variable  $Y$ 
  - Step 1: get joint probability of label and evidence for each label

$$P(Y, f_1 \dots f_n) = \begin{bmatrix} P(y_1, f_1 \dots f_n) \\ P(y_2, f_1 \dots f_n) \\ \vdots \\ P(y_k, f_1 \dots f_n) \end{bmatrix} \Rightarrow \begin{bmatrix} P(y_1) \prod_i P(f_i|y_1) \\ P(y_2) \prod_i P(f_i|y_2) \\ \vdots \\ P(y_k) \prod_i P(f_i|y_k) \end{bmatrix}$$

---

$$P(f_1 \dots f_n)$$

↪ +

- Step 2: sum to get probability of evidence
- Step 3: normalize by dividing Step 1 by Step 2

$$P(Y|f_1 \dots f_n)$$

# General Naïve Bayes


---

- What do we need in order to use Naïve Bayes?
  - Inference method (we just saw this part)
    - Start with a bunch of probabilities:  $P(Y)$  and the  $P(F_i|Y)$  tables
    - Use standard inference to compute  $P(Y|F_1...F_n)$
    - Nothing new here
  - Estimates of local conditional probability tables
    - $P(Y)$ , the prior over labels
    - $P(F_i|Y)$  for each feature (evidence variable)
    - These probabilities are collectively called the *parameters* of the model and denoted by  $\theta$
    - Up until now, we assumed these appeared by magic, but...
    - ...they typically come from training data counts: we'll look at this soon

# Example: Conditional Probabilities

$P(Y)$

1	0.1
2	0.1
3	0.1
4	0.1
5	0.1
6	0.1
7	0.1
8	0.1
9	0.1
0	0.1



$P(F_{3,1} = \text{on}|Y)$   $P(F_{5,5} = \text{on}|Y)$

1	0.01
2	0.05
3	0.05
4	0.30
5	0.80
6	0.90
7	0.05
8	0.60
9	0.50
0	0.80

1	0.05
2	0.01
3	0.90
4	0.80
5	0.90
6	0.90
7	0.25
8	0.85
9	0.60
0	0.80

# A Spam Filter

- Naïve Bayes spam filter

- Data:

- Collection of emails, labeled spam or ham
- Note: someone has to hand label all this data!
- Split into training, held-out, test sets



Dear Sir.

First, I must solicit your confidence in this transaction, this is by virtue of its nature as being utterly confidential and top secret. ...



TO BE REMOVED FROM FUTURE MAILINGS, SIMPLY REPLY TO THIS MESSAGE AND PUT "REMOVE" IN THE SUBJECT.

99 MILLION EMAIL ADDRESSES  
FOR ONLY \$99

- Classifiers

- Learn on the training set
- (Tune it on a held-out set)
- Test it on new emails



Ok, I know this is blatantly OT but I'm beginning to go insane. Had an old Dell Dimension XPS sitting in the corner and decided to put it to use, I know it was working pre being stuck in the corner, but when I plugged it in, hit the power nothing happened.

# Naïve Bayes for Text

## ■ Bag-of-words Naïve Bayes:

- Features:  $W_i$  is the word at position  $i$   
how many variables are there?  
how many values?
- As before: predict label conditioned on feature variables (spam vs. ham)
- As before: assume features are conditionally independent given label
- New: each  $W_i$  is identically distributed

## ■ Generative model: $P(Y, W_1 \dots W_n) = P(Y) \prod_i P(W_i|Y)$

*Word at position  
 $i$ , not  $i^{th}$  word in  
the dictionary!*

## ■ “Tied” distributions and bag-of-words

- Usually, each variable gets its own conditional probability distribution  $P(W_i|Y)$
- In a bag-of-words model
  - Each position is identically distributed
  - All positions share the same conditional distribution
  - Why make this assumption?
- Called “bag-of-words” because model is insensitive to word order or reordering

**in is lecture lecture next over person remember room  
sitting the the the to to up wake when you**

# Example: Spam Filtering

- Model:  $P(Y, W_1 \dots W_n) = P(Y) \prod_i P(W_i|Y)$
- What are the parameters?

$P(Y)$

ham : 0.66
spam: 0.33

$P(W|\text{spam})$

the : 0.0156
to : 0.0153
and : 0.0115
of : 0.0095
you : 0.0093
a : 0.0086
with: 0.0080
from: 0.0075
...

$P(W|\text{ham})$


the : 0.0210
to : 0.0133
of : 0.0119
2002: 0.0110
with: 0.0108
from: 0.0107
and : 0.0105
a : 0.0100
...

- Where do these tables come from?





**ANSWER KEY**

# Training and Testing





# Important Concepts



- Data: labeled instances, e.g. emails marked spam/ham
  - Training set
  - Held out set
  - Test set
- Features: attribute-value pairs which characterize each  $x$
- Experimentation cycle
  - Learn parameters (e.g. model probabilities) on training set
  - (Tune hyperparameters on held-out set)
  - Compute accuracy of test set
  - Very important: never “peek” at the test set!
- Evaluation
  - Accuracy: fraction of instances predicted correctly
- Overfitting and generalization
  - Want a classifier which does well on *test* data
  - Overfitting: fitting the training data very closely, but not generalizing well
  - Underfitting: fits the training set poorly



# Underfitting and Overfitting



# Overfitting



# Example: Overfitting

$P(\text{features}, C = 2)$


$$P(C = 2) = 0.1$$

$$P(\text{on}|C = 2) = 0.8$$

$$P(\text{on}|C = 2) = 0.1$$

$$P(\text{off}|C = 2) = 0.1$$

$$P(\text{on}|C = 2) = 0.01$$



$P(\text{features}, C = 3)$

$$P(C = 3) = 0.1$$


$$P(\text{on}|C = 3) = 0.8$$

$$P(\text{on}|C = 3) = 0.9$$

$$P(\text{off}|C = 3) = 0.7$$

$$P(\text{on}|C = 3) = 0.0$$

*2 wins!!*




# Generalization and Overfitting

---

- Relative frequency parameters will **overfit** the training data!
  - Just because we never saw a 3 with pixel (15,15) on during training doesn't mean we won't see it at test time
  - Unlikely that every occurrence of "minute" is 100% spam
  - Unlikely that every occurrence of "seriously" is 100% ham
  - What about all the words that don't occur in the training set at all?
  - In general, we can't go around giving unseen events zero probability
- As an extreme case, imagine using the entire email as the only feature
  - Would get the training data perfect (if deterministic labeling)
  - Wouldn't *generalize* at all
  - Just making the bag-of-words assumption gives us some generalization, but isn't enough
- To generalize better: we need to **smooth** or **regularize** the estimates

# Parameter Estimation






# Parameter Estimation

- Estimating the distribution of a random variable
- *Elicitation*: ask a human (why is this hard?)
- *Empirically*: use training data (learning!)
  - E.g.: for each outcome  $x$ , look at the *empirical rate* of that value:

$$P_{\text{ML}}(x) = \frac{\text{count}(x)}{\text{total samples}}$$




$$P_{\text{ML}}(r) = 2/3$$

- This is the estimate that maximizes the *likelihood of the data*

$$L(x, \theta) = \prod_i P_{\theta}(x_i) = \theta \cdot \theta \cdot (1 - \theta)$$

$$P_{\theta}(x = \text{red}) = \theta$$

$$P_{\theta}(x = \text{blue}) = 1 - \theta$$



# Your First Consulting Job

- A billionaire tech entrepreneur asks you a question:
  - **He says:** I have thumbtack, if I flip it, what's the probability it will fall with the nail up?
  - **You say:** Please flip it a few times:



- **You say:** The probability is:
  - $P(H) = 3/5$
- **He says: Why???**
- **You say:** Because...

# Your First Consulting Job

- $P(\text{Heads}) = \theta$ ,  $P(\text{Tails}) = 1 - \theta$



- Flips are *i.i.d.*:  $D = \{x_i \mid i=1 \dots n\}$ ,  $P(D \mid \theta) = \prod_i P(x_i \mid \theta)$ 
  - Independent events
  - Identically distributed according to unknown distribution
- Sequence  $D$  of  $\alpha_H$  Heads and  $\alpha_T$  Tails

$$P(\mathcal{D} \mid \theta) = \theta^{\alpha_H} (1 - \theta)^{\alpha_T}$$

# Maximum Likelihood Estimation

---

- **Data:** Observed set  $D$  of  $\alpha_H$  Heads and  $\alpha_T$  Tails
- **Hypothesis space:** Binomial distributions
- **Learning:** finding  $\theta$  is an optimization problem
  - What's the objective function?

$$P(\mathcal{D} \mid \theta) = \theta^{\alpha_H} (1 - \theta)^{\alpha_T}$$

- **MLE:** Choose  $\theta$  to maximize probability of  $D$

$$\begin{aligned}\hat{\theta} &= \arg \max_{\theta} P(\mathcal{D} \mid \theta) \\ &= \arg \max_{\theta} \ln P(\mathcal{D} \mid \theta)\end{aligned}$$

# Maximum Likelihood Estimation

$$\begin{aligned}\hat{\theta} &= \arg \max_{\theta} \ln P(\mathcal{D} \mid \theta) \\ &= \arg \max_{\theta} \ln \theta^{\alpha_H} (1 - \theta)^{\alpha_T}\end{aligned}$$

- Set derivative to zero, and solve!

$$\frac{d}{d\theta} \ln P(\mathcal{D} \mid \theta) = \frac{d}{d\theta} [\ln \theta^{\alpha_H} (1 - \theta)^{\alpha_T}]$$


$$= \frac{d}{d\theta} [\alpha_H \ln \theta + \alpha_T \ln(1 - \theta)]$$

$$= \alpha_H \frac{d}{d\theta} \ln \theta + \alpha_T \frac{d}{d\theta} \ln(1 - \theta)$$

$$= \frac{\alpha_H}{\theta} - \frac{\alpha_T}{1 - \theta} = 0$$

$$\boxed{\hat{\theta}_{MLE} = \frac{\alpha_H}{\alpha_H + \alpha_T}}$$

# Smoothing



# Maximum Likelihood?



- Relative frequencies are the maximum likelihood estimates

$$\begin{aligned}\theta_{ML} &= \arg \max_{\theta} P(\mathbf{X}|\theta) \\ &= \arg \max_{\theta} \prod_i P_{\theta}(X_i)\end{aligned} \quad \Rightarrow \quad P_{ML}(x) = \frac{\text{count}(x)}{\text{total samples}}$$

- Another option is to consider the most likely parameter value given the data

$$\begin{aligned}\theta_{MAP} &= \arg \max_{\theta} P(\theta|\mathbf{X}) \\ &= \arg \max_{\theta} P(\mathbf{X}|\theta)P(\theta)/P(\mathbf{X}) \quad \Rightarrow \quad \text{????} \\ &= \arg \max_{\theta} P(\mathbf{X}|\theta)P(\theta)\end{aligned}$$

# Unseen Events






# Laplace Smoothing

- Laplace's estimate:

- Pretend you saw every outcome once more than you actually did

$$\begin{aligned} P_{LAP}(x) &= \frac{c(x) + 1}{\sum_x [c(x) + 1]} \\ &= \frac{c(x) + 1}{N + |X|} \end{aligned}$$

- Can derive this estimate with *Dirichlet priors*



$$P_{ML}(X) =$$

$$P_{LAP}(X) =$$

# Laplace Smoothing

- Laplace's estimate (extended):

- Pretend you saw every outcome  $k$  extra times


$$P_{LAP,k}(x) = \frac{c(x) + k}{N + k|X|}$$

- What's Laplace with  $k = 0$ ?
- $k$  is the **strength** of the prior

- Laplace for conditionals:

- Smooth each condition independently:

$$P_{LAP,k}(x|y) = \frac{c(x, y) + k}{c(y) + k|X|}$$




$$P_{LAP,0}(X) =$$

$$P_{LAP,1}(X) =$$



$$P_{LAP,100}(X) =$$

# Tuning



# Tuning on Held-Out Data

- Now we've got two kinds of unknowns
  - Parameters: the probabilities  $P(X|Y)$ ,  $P(Y)$
  - Hyperparameters: e.g. the amount / type of smoothing to do,  $k$ ,  $\alpha$
- What should we learn where?
  - Learn parameters from training data
  - Tune hyperparameters on different data
    - Why?
  - For each value of the hyperparameters, train and test on the held-out data
  - Choose the best value and do a final test on the test data



# What to Do About Errors?

- Need more features— words aren't enough!
  - Have you emailed the sender before?
  - Have 1K other people just gotten the same email?
  - Is the sending information consistent?
  - Is the email in ALL CAPS?
  - Do inline URLs point where they say they point?
  - Does the email address you by (your) name?
- Can add these information sources as new variables in the NB model
- Next class we'll talk about classifiers which let you easily add arbitrary features more easily



# Baselines

---

- First step: get a **baseline**
  - Baselines are very simple “straw man” procedures
  - Help determine how hard the task is
  - Help know what a “good” accuracy is
- Weak baseline: most frequent label classifier
  - Gives all test instances whatever label was most common in the training set
  - E.g. for spam filtering, might label everything as ham
  - Accuracy might be very high if the problem is skewed
  - E.g. calling everything “ham” gets 66%, so a classifier that gets 70% isn’t very good...
- For real research, usually use previous work as a (strong) baseline

# Confidences from a Classifier

- The **confidence** of a probabilistic classifier:

- Posterior over the top label

$$\text{confidence}(x) = \max_y P(y|x)$$

- Represents how sure the classifier is of the classification
- Any probabilistic model will have confidences
- No guarantee confidence is correct

