

# Data-driven systems

## Transactions in relational databases



Automatizálási és  
Alkalmazott  
Informatikai Tanszék

# Transactions

# Problems



# Problems 2 😊



# Problems



- Concurrent transactions
- A unit of data (here: a record of a database table) is used by **multiple actors** at the same time, and **at least one of the actors edits** the data.




Image source: <https://blog.yugabyte.com/a-primer-on-acid-transactions/>

# Transaction

- The logical unit of a process; a series of operations that only make sense together.
- Basic properties:
  - > Atomicity
  - > Consistency
  - > Isolation
  - > Durability



# Atomicity and Consistency






Image source: <https://vladimihalcea.com/current-database-transaction>

# Isolation







# Isolation



# Durability

- Transactional logging



# Transaction boundaries

- We can start and close a transaction explicitly
- begin transaction -> commit / rollback
- We can set the transaction level
- Nested transactions
- If not in a transaction, each statement runs as a transaction by itself
- A delete statement that deletes multiple rows cannot delete only half of the records


# Transaction isolation

# Isolation problems




- Multiple concurrent transactions
- Must be executed *as if* they were executed after each other and not concurrently
- Problems
  - > Dirty read
  - > Lost update
  - > Non-repeatable read
  - > Phantom records
- **Problem is not specific to relational data bases!**
  - > Same issue is present in some form in all distributed systems.

# Dirty read




<https://vladmihalcea.com/2014/01/05/a-beginners-guide-to-acid-and-database-transactions/>

# Lost update




# Non-repeatable read



<https://vladmihalcea.com/2014/01/05/a-beginners-guide-to-acid-and-database-transactions/>



# Phantom records



<https://vladmihalcea.com/2014/01/05/a-beginners-guide-to-acid-and-database-transactions/>

# Solution

- Transaction scheduling
- Only operations that do not violate right scheduling are allowed
- If the scheduling is violated, the transaction must wait
- A scheduling is allowed if there exists a conflict-equivalent serial scheduling
  - Can be transformed to a serial scheduling that avoids conflicts

# Isolation levels


- Isolation levels in the SQL standard
  - > Read uncommitted → all 4 problems
  - > Read committed → no dirty read
  - > Repeatable read → no dirty read, no non-repeatable read
  - > Serializable → no problems
- Non-standard isolation levels (MS SQL)
  - > Read committed snapshot isolation
  - > Snapshot isolation

# Isolation with locks

- Locks: the data has only one storage location, it is protected by the lock
- One transaction modifies it -> puts a lock on it
- The others cannot read it, because they would read the new, dirty data
- Depending on the implementation, there are several types of locks
  - > Read / write
  - > Row / page / table

# Provides scheduling

- Two-phase locking



# Snapshot isolation

- Instead of locks, we store previous versions of the data
- Before each write, we copy the record to tempdb (copy-on-write)
- The other transactions read the previous data version

# Snapshot isolation

SQLQuery\_1 - (Local...grated)

Run Cancel Disconnect Change Connection MyOrders

Explain

```
1 USE MyOrders;  
2 GO  
3  
4 SET TRANSACTION ISOLATION LEVEL SERIALIZABLE;  
5 BEGIN TRANSACTION;  
6  
7 SELECT * FROM Orders.Orders;  
8  
9 COMMIT;
```

Transaction not committed

Results		Messages				
	OrderID	OrderYear	OrderDate	OrderRequestedDate	OrderDeliveryDate	
1	1	2019	2019-03-01	3000-01-01	NULL	
2	2	2019	2019-03-01	2019-06-01	NULL	

SQLQuery\_2 - (Local...grated)

Run Cancel Disconnect Change Connection MyOrders

Explain

```
1 USE MyOrders;  
2 GO  
3  
4 SET TRANSACTION ISOLATION LEVEL READ COMMITTED;  
5 BEGIN TRANSACTION;  
6  
7 SELECT * FROM Orders.Orders;  
8  
9 COMMIT;
```

Transaction not committed

Results		Messages				
	OrderID	OrderYear	OrderDate	OrderRequestedDate	OrderDeliveryDate	
1	1	2019	2019-03-01	3000-01-01	NULL	
2	2	2019	2019-03-01	2019-06-01	NULL	


# Snapshot vs standard

- The previous four levels work with locks, pessimistic
  - > Stops the transaction
- Snapshot creates versions, optimistic
  - > Later, during the commit, it detects the collision and kills one of the transactions
- Fewer locks, waits, deadlocks - more tempdb usage
- Useful for fewer writing and more reading



# Transaction log

- Tracking transactions
  - Rollback / soft crash



T:  
 $A = A - 2$   
 $B = B + 2$

# Undo logging 1

$$A = A - 2$$
$$B = B + 2$$

- Read data from disk into memory

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Begin(T1)	10	20	-	-	<b>Begin T1</b>
Input(A)	10	20	<b>10</b>	-	
Input(B)	10	20	10	<b>20</b>	

# Undo logging 2

$$A = A - 2$$
$$B = B + 2$$

- Actions are performed in memory
- The value *before* the modification is entered in the log

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Read(A)	10	20	10	20	
Write(A)	10	20	8	20	T1, A, 10
Read(B)	10	20	8	20	
Write(B)	10	20	8	22	T1, B, 20

# Undo logging 3

$$A = A - 2$$
$$B = B + 2$$

- Commit
  - > Write transaction log to the disk
  - > Modifies the database file

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Flush_LOG	10	20	8	22	
Output(A)	8	20	8	22	
Output(B)	8	22	8	22	
					Commit T1

# Undo logging

- The transaction log must be written first, then the database file
- A commit entry can only be made after the database has been written
- Having to write a transaction log twice - expensive
- Recovery
  - > Before commit: there is no task, it is lost (in memory)
  - > Reading the transaction log from the back, for uncommitted transactions, the original values must be written back to the database from the log

# Redo logging 1

$$A = A - 2$$
$$B = B + 2$$

- Read data from disk into memory
- Actions are performed and the value after modification is written into the log

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Begin(T1)	10	20	-	-	Begin T1
Input(A)	10	20	10	-	
Input(B)	10	20	10	20	
Read(A)	10	20	10	20	
Write(A)	10	20	8	20	T1, A, 8
Read(B)	10	20	8	20	
Write(B)	10	20	8	22	T1, B, 22

# Redo logging 2

$$A = A - 2$$
$$B = B + 2$$

- Commit
  - > Write the transaction log, commit entry
  - > Write data to the database file

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
					Commit T1
Flush_LOG	10	20	8	22	
Output(A)	8	20	8	22	
Output(B)	8	22	8	22	

# Redo logging

- The transaction log must be written first, then the database file
- A commit entry must be made before writing to the database
- Less cost, longer recovery process
- Recovery
  - > Before commit: there is no task, it is lost
  - > The log must be processed from the beginning and all committed transactions must be redone



# Undo/redo logging 1

$$A = A - 2$$
$$B = B + 2$$

- Read data from disk into memory
- Actions are performed and the value before AND after the modification is logged

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Begin(T1)	10	20	-	-	Begin T1
Input(A)	10	20	10	-	
Input(B)	10	20	10	20	
Read(A)	10	20	10	20	
Write(A)	10	20	8	20	T1, A, 10, 8
Read(B)	10	20	8	20	
Write(B)	10	20	8	22	T1, B, 20, 22

# Undo/redo logging 2

$$A = A - 2$$
$$B = B + 2$$

- Commit

- > Write a transaction log
- > Write the commit signal and data in parallel

Command	A (database)	B (database)	A (buffer)	B (buffer)	Transaction log
Flush_LOG	10	20	8	22	
Output(A)	8	20	8	22	
					Commit T1
Output(B)	8	22	8	22	

# Undo/redo logging

- The transaction log must be written first, then the database
- The commit entry can be made in parallel with the database write
- Less internal synchronization
- Recovery
  - > Before commit: there is no task, it is lost
  - > Replay a committed transaction from the beginning (redo), restore interrupted transactions (undo)

# Size of transaction log

- It is reduced from time to time
- All transaction data that has already been entered into the database files can be deleted
- Long-running transactions can increase the size of the log!

# Distributed transactions

- Several database servers participate in a transaction
  - > There is a dedicated transaction manager that controls the execution, two phase commits
- It has ACID properties
  - > Short transaction and commit time
- A tightly coupled system
  - > Database level integration

# Long running transactions

- No database-like commit/rollback
- Custom manual mechanism ensures the restoration of data consistency
- Special data repositories
- Distributed heterogeneous solutions
- "Saga" transactions
  - > User input is also part of the transaction!

# Globally distributed transactions

- Huge amount of data, big load, large distances
  - > AWS, Azure, etc.
  - > Multiple copies of data, far apart
- CAP theorem: any distributed data store can provide only two of the following three guarantees
  1. Consistency: Every read receives the most recent write or an error
  2. Availability: every request receives a (non-error) response, without the guarantee that it contains the most recent write
  3. Partition tolerance: The system continues to operate despite an arbitrary number of messages being dropped (or delayed) by the network between nodes

# Alternatives

- Single server -> no partitioning
  - > It is consistent AND available
  - > One server -> doesn't scale, SPoF
- More servers -> there will be network failure -> there will be more partitions
  - > Consistency OR availability
- Alt1: stop the service until network is problems are solved
- Alt2: consistency in a given time window
  - > Like DNS registration or an FB comment etc.



# Strong vs eventual consistency

- Strong consistency: the system synchronizes internally and serves external requests based on this
- Eventual consistency: prioritizes availability over consistency
  - > It lets you read data that is not the most recent
  - > Inconsistency window: depends on load
  - > Different nodes have different data versions
  - > DNS, Facebook message board, etc.
  - > Financial transactions often allow 24 hours