

Deep Learning

Vazgen Mikayelyan

YSU, Krisp

December 18, 2019


1 Ensemble of Neural Networks

2 Bayesian Neural Networks

3 Word2Vec

Ensemble Learning

- ◆ Ensemble learning that combines the decisions of multiple hypotheses is some of the strongest existing machine learning methods.



Note that

$$(y - \hat{y})^2 = \left(\sum_{i=1}^n w_i y_i - \hat{y} \right)^2$$

Ensemble of Neural Networks

Note that

$$(y - \hat{y})^2 = \left(\sum_{i=1}^n w_i y_i - \hat{y} \right)^2 = \left(\sum_{i=1}^n w_i (y_i - \hat{y}) \right)^2$$

Ensemble of Neural Networks

Note that

$$(y - \hat{y})^2 = \left(\sum_{i=1}^n w_i y_i - \hat{y} \right)^2 = \left(\sum_{i=1}^n w_i (y_i - \hat{y}) \right)^2 \leq \sum_{i=1}^n w_i^2 \sum_{i=1}^n (y_i - \hat{y})^2.$$

Ensemble of Neural Networks

Note that

$$(y - \hat{y})^2 = \left(\sum_{i=1}^n w_i y_i - \hat{y} \right)^2 = \left(\sum_{i=1}^n w_i (y_i - \hat{y}) \right)^2 \leq \sum_{i=1}^n w_i^2 \sum_{i=1}^n (y_i - \hat{y})^2.$$

Let $w_1 = \dots = w_n = \frac{1}{n}$, then

$$(y - \hat{y})^2 \leq \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y})^2$$

Ensemble of Neural Networks

Note that

$$(y - \hat{y})^2 = \left(\sum_{i=1}^n w_i y_i - \hat{y} \right)^2 = \left(\sum_{i=1}^n w_i (y_i - \hat{y}) \right)^2 \leq \sum_{i=1}^n w_i^2 \sum_{i=1}^n (y_i - \hat{y})^2.$$

Let $w_1 = \dots = w_n = \frac{1}{n}$, then


$$(y - \hat{y})^2 \leq \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y})^2$$


Can we do ensemble learning with infinite number of neural networks?


1 Ensemble of Neural Networks

2 Bayesian Neural Networks

3 Word2Vec


$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$





Let $\mathcal{D} = \{(x_i, y_i) : i = 1, \dots, n\}$ be our training data.

Let $\mathcal{D} = \{(x_i, y_i) : i = 1, \dots, n\}$ be our training data. Recall MLE:

$$\begin{aligned} w^{MLE} &= \operatorname{argmax}_w p(\mathcal{D}|w) = \operatorname{argmax}_w \prod_{i=1}^n p(y_i|x_i, w) \\ &= \operatorname{argmax}_w \sum_{i=1}^n \log p(y_i|x_i, w) \end{aligned}$$

Let $\mathcal{D} = \{(x_i, y_i) : i = 1, \dots, n\}$ be our training data. Recall MLE:

$$\begin{aligned} w^{MLE} &= \operatorname{argmax}_w p(\mathcal{D}|w) = \operatorname{argmax}_w \prod_{i=1}^n p(y_i|x_i, w) \\ &= \operatorname{argmax}_w \sum_{i=1}^n \log p(y_i|x_i, w) \end{aligned}$$

Here the weights of our model are fixed, but the data is viewed as a random variable. If we instead view the data as being fixed and the model weights as being a random variable, we can train to maximize the posterior distribution $p(w|\mathcal{D})$:

Let $\mathcal{D} = \{(x_i, y_i) : i = 1, \dots, n\}$ be our training data. Recall MLE:

$$\begin{aligned} w^{MLE} &= \operatorname{argmax}_w p(\mathcal{D}|w) = \operatorname{argmax}_w \prod_{i=1}^n p(y_i|x_i, w) \\ &= \operatorname{argmax}_w \sum_{i=1}^n \log p(y_i|x_i, w) \end{aligned}$$

Here the weights of our model are fixed, but the data is viewed as a random variable. If we instead view the data as being fixed and the model weights as being a random variable, we can train to maximize the posterior distribution $p(w|\mathcal{D})$:

$$\begin{aligned} w^{MAP} &= \operatorname{argmax}_w p(w|\mathcal{D}) = \operatorname{argmax}_w \frac{p(\mathcal{D}|w) p(w)}{p(\mathcal{D})} \\ &= \operatorname{argmax}_w (\log p(\mathcal{D}|w) + \log p(w)). \end{aligned}$$

We will construct a new distribution for $q(w|\theta)$, for approximating $p(w|\mathcal{D})$.

We will construct a new distribution for $q(w|\theta)$, for approximating $p(w|\mathcal{D})$. So we need to do the following optimization:

$$\theta^* = \underset{\theta}{\operatorname{argmin}} KL(q(w|\theta) || p(w|\mathcal{D}))$$

We will construct a new distribution for $q(w|\theta)$, for approximating $p(w|\mathcal{D})$. So we need to do the following optimization:

$$\begin{aligned}\theta^* &= \operatorname{argmin}_{\theta} KL(q(w|\theta) || p(w|\mathcal{D})) \\ &= \operatorname{argmin}_{\theta} (KL(q(w|\theta) || p(w)) - \mathbb{E}_{q(w|\theta)} [\log p(\mathcal{D}|w)])\end{aligned}$$

We will construct a new distribution for $q(w|\theta)$, for approximating $p(w|\mathcal{D})$. So we need to do the following optimization:

$$\begin{aligned}\theta^* &= \operatorname{argmin}_{\theta} KL(q(w|\theta) || p(w|\mathcal{D})) \\ &= \operatorname{argmin}_{\theta} (KL(q(w|\theta) || p(w)) - \mathbb{E}_{q(w|\theta)} [\log p(\mathcal{D}|w)])\end{aligned}$$

We will assume that prior $p(w)$ is mixture of two Gaussians:

$$p(w) = \prod_j (\alpha \mathcal{N}(w_j | 0, \sigma_1^2) + (1 - \alpha) \mathcal{N}(w_j | 0, \sigma_2^2))$$

where the first mixture component of the prior is given a larger variance than the second: $\sigma_1 > \sigma_2$.

1. Sample $\epsilon \sim \mathcal{N}(0, I)$.
2. Let $\mathbf{w} = \mu + \log(1 + \exp(\rho)) \circ \epsilon$.
3. Let $\theta = (\mu, \rho)$.
4. Let $f(\mathbf{w}, \theta) = \log q(\mathbf{w}|\theta) - \log P(\mathbf{w})P(\mathcal{D}|\mathbf{w})$.
5. Calculate the gradient with respect to the mean

$$\Delta_{\mu} = \frac{\partial f(\mathbf{w}, \theta)}{\partial \mathbf{w}} + \frac{\partial f(\mathbf{w}, \theta)}{\partial \mu}. \quad (3)$$

6. Calculate the gradient with respect to the standard deviation parameter ρ

$$\Delta_{\rho} = \frac{\partial f(\mathbf{w}, \theta)}{\partial \mathbf{w}} \frac{\epsilon}{1 + \exp(-\rho)} + \frac{\partial f(\mathbf{w}, \theta)}{\partial \rho}. \quad (4)$$

7. Update the variational parameters:

$$\mu \leftarrow \mu - \alpha \Delta_{\mu} \quad (5)$$

$$\rho \leftarrow \rho - \alpha \Delta_{\rho}. \quad (6)$$

Outline

1 Ensemble of Neural Networks

2 Bayesian Neural Networks

3 Word2Vec

- We can easily collect very large amounts of unlabeled text data.

- We can easily collect very large amounts of unlabeled text data.
- Can we learn useful representations (e.g., word embeddings) from unlabeled data?

Bigrams from Unlabeled Data

- Given a corpus, extract a training set $(x_i, y_i)_{i=1}^n$, where $x_i, y_i \in \mathcal{V}$ and \mathcal{V} is the vocabulary.

Bigrams from Unlabeled Data

- Given a corpus, extract a training set $(x_i, y_i)_{i=1}^n$, where $x_i, y_i \in \mathcal{V}$ and \mathcal{V} is the vocabulary.
- For example:

Hispaniola quickly became an important base from which Spain expanded its empire into the rest of the Western Hemisphere.

Given a window size of $+/- 3$, for $x = \text{base}$ we get the pairs

(base, became), (base, an), (base, important),
(base, from), (base, which), (base, Spain).

The Skip-gram Model

- The training objective of the Skip-gram model is to find word representations that are useful for predicting the surrounding words in a sentence or a document.

The Skip-gram Model

- The training objective of the Skip-gram model is to find word representations that are useful for predicting the surrounding words in a sentence or a document.
- More formally, given a sequence of training words w_1, \dots, w_T , the objective of the Skip-gram model is to maximize the average log probability

$$\frac{1}{T} \sum_{t=1}^T \sum_{-c \leq j \leq c, j \neq 0} \log p(w_{t+j} | w_t)$$

where c is the size of the training context.

The Skip-gram Model

- The training objective of the Skip-gram model is to find word representations that are useful for predicting the surrounding words in a sentence or a document.
- More formally, given a sequence of training words w_1, \dots, w_T , the objective of the Skip-gram model is to maximize the average log probability

$$\frac{1}{T} \sum_{t=1}^T \sum_{-c \leq j \leq c, j \neq 0} \log p(w_{t+j} | w_t)$$

where c is the size of the training context.

- We model $p(w_{t+j} | w_t)$ using the softmax function:

$$p(w_o | w_l) = \frac{\exp(v'_{w_o} v_{w_l})}{\sum_{w=1}^W \exp(v'_w v_{w_l})},$$

where v_w and v'_w are the “input” and “output” vector representations of w , and W is the number of words in the vocabulary.

Negative Sampling

Negative Sampling

- We define Negative sampling by the objective

$$\log \sigma \left(v_{w_O}'^T v_{w_I} \right) + \sum_{i=1}^k \mathbb{E}_{w_i \sim P_n(w)} \left[\log \sigma \left(-v_{w_i}'^T v_{w_I} \right) \right]$$

which is used to replace every $\log p(w_O|w_I)$ term in the Skip-gram objective.

Negative Sampling

- We define Negative sampling by the objective

$$\log \sigma \left(v_{w_O}'^T v_{w_I} \right) + \sum_{i=1}^k \mathbb{E}_{w_i \sim P_n(w)} \left[\log \sigma \left(-v_{w_i}'^T v_{w_I} \right) \right]$$

which is used to replace every $\log p(w_O|w_I)$ term in the Skip-gram objective.

- Thus the task is to distinguish the target word w_O from draws from the noise distribution $P_n(w)$ using logistic regression, where there are k negative samples for each data sample.

Negative Sampling

- We define Negative sampling by the objective

$$\log \sigma \left(v_{w_O}'^T v_{w_I} \right) + \sum_{i=1}^k \mathbb{E}_{w_i \sim P_n(w)} \left[\log \sigma \left(-v_{w_i}'^T v_{w_I} \right) \right]$$

which is used to replace every $\log p(w_O|w_I)$ term in the Skip-gram objective.

- Thus the task is to distinguish the target word w_O from draws from the noise distribution $P_n(w)$ using logistic regression, where there are k negative samples for each data sample.
- In the original paper authors chose P_n to be the unigram distribution raised to the 3/4rd power.

Thank you!