

Deep Learning

Vazgen Mikayelyan

YSU, Krisp

October 31, 2019

1 Metrics for Classification Problems

2 Basic Recurrent Neural Networks

ROC Curve

- A receiver operating characteristic curve, i.e. ROC curve is a graphical plot that illustrates the diagnostic ability of a binary classifier system as its discrimination threshold is varied.

- A receiver operating characteristic curve, i.e. ROC curve is a graphical plot that illustrates the diagnostic ability of a binary classifier system as its discrimination threshold is varied.
- The diagnostic performance of a test or the accuracy of a test to discriminate diseased cases from normal cases is evaluated using ROC curve analysis.

- A receiver operating characteristic curve, i.e. ROC curve is a graphical plot that illustrates the diagnostic ability of a binary classifier system as its discrimination threshold is varied.
- The diagnostic performance of a test or the accuracy of a test to discriminate diseased cases from normal cases is evaluated using ROC curve analysis.
- A ROC curve is a way to compare diagnostic tests. It is a plot of true positive rate against the false positive rate:

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

- What if *threshold* = 0?

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

- What if *threshold* = 0?
 - $TN = 0, FN = 0$

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

- What if *threshold* = 0?
 - $TN = 0, FN = 0$
 - $TPR = 1, FPR = 1$

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

- What if *threshold* = 0?
 - $TN = 0, FN = 0$
 - $TPR = 1, FPR = 1$
- What if *threshold* = 1?

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$


- What if *threshold* = 0?
 - $TN = 0, FN = 0$
 - $TPR = 1, FPR = 1$
- What if *threshold* = 1?
 - $TP = 0, FP = 0$

$$TPR = Recall = Sensitivity = \frac{TP}{TP + FN}$$

$$FPR = 1 - Specificity = 1 - \frac{TN}{TN + FP} = \frac{FP}{TN + FP}$$

- What if *threshold* = 0?
 - $TN = 0, FN = 0$
 - $TPR = 1, FPR = 1$
- What if *threshold* = 1?
 - $TP = 0, FP = 0$
 - $TPR = 0, FPR = 0$

ROC Curve



Definition 1

AUC (area under the curve) is the area under the ROC curve.

Definition 1

AUC (area under the curve) is the area under the ROC curve.

- What if $AUC \approx 0.5$?

Definition 1

AUC (area under the curve) is the area under the ROC curve.

- What if $AUC \approx 0.5$?
- What if $AUC \approx 1$?

Definition 1

AUC (area under the curve) is the area under the ROC curve.

- What if $AUC \approx 0.5$?
- What if $AUC \approx 1$?
- How to choose threshold?

Definition 1

AUC (area under the curve) is the area under the ROC curve.

- What if $AUC \approx 0.5$?
- What if $AUC \approx 1$?
- How to choose threshold?
- How to use ROC curve for multi-class model?

- Simple Cross Entropy

$$L(w) = \frac{1}{n} \sum_{i=1}^n \left(-y_i^T \log f_w(x_i) \right).$$

Balanced Cross Entropy

- Simple Cross Entropy

$$L(w) = \frac{1}{n} \sum_{i=1}^n \left(-y_i^T \log f_w(x_i) \right).$$

- Balanced Cross Entropy

$$L(w) = \frac{1}{n} \sum_{i=1}^n \left(-(\alpha * y_i)^T \log f_w(x_i) \right).$$

Where $\alpha^T = [\alpha_1, \dots, \alpha_k]$, $\alpha_i \in (0, 1)$ and $\sum_{i=1}^k \alpha_i = 1$.

1 Metrics for Classification Problems

2 Basic Recurrent Neural Networks

Sequential Data

- What is sequential data?

Sequential Data

- What is sequential data?
 - Time series

Sequential Data

- What is sequential data?
 - Time series
 - Text

Sequential Data

- What is sequential data?
 - Time series
 - Text
 - Speech

Sequential Data

- What is sequential data?
 - Time series
 - Text
 - Speech
 - Audio

- What is sequential data?
 - Time series
 - Text
 - Speech
 - Audio
 - Video


Sequential Data


- What is sequential data?
 - Time series
 - Text
 - Speech
 - Audio
 - Video
- Why don't to use known networks?

- What is sequential data?
 - Time series
 - Text
 - Speech
 - Audio
 - Video
- Why don't to use known networks?
 - Inputs, outputs can be different lengths in different examples.

- What is sequential data?
 - Time series
 - Text
 - Speech
 - Audio
 - Video
- Why don't to use known networks?
 - Inputs, outputs can be different lengths in different examples.
 - Doesn't share features learned across different positions of sequence.

Basic RNNs





$$h_t = f_W(h_{t-1}, x_t)$$



$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$


$$y_t = W_{hy}h_t$$

Different Types of RNNs

- Many to many


Different Types of RNNs

- Many to many



Different Types of RNNs

- Many to many




Different Types of RNNs

- Many to one

Different Types of RNNs

- Many to one




Different Types of RNNs

- One to many


Different Types of RNNs

- One to many



Different Types of RNNs

- One to many



- One to one?

Problem of Long Term Dependencies

