ASSIGNMENT – 3

```
Code:
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT22 // define type of sensor DHT 11
#define LED 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht connected
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "9u4b2o"//IBM ORGANITION ID
#define DEVICE TYPE "abcd"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "1234"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678" //Token
String data3;
float h, t;
//----- Customise the above values ------
```

```
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and
format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type
AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by
passing parameter like server id, portand wificredential
void setup()// configureing the ESP32
{
 Serial.begin(115200);
 dht.begin();
 pinMode(LED,OUTPUT);
```

delay(10);

Serial.println();

wificonnect();

mqttconnect();

}

```
void loop()// Recursive Function
{
h = dht.readHumidity();
t = dht.readTemperature();
Serial.print("temp:");
Serial.println(t);
Serial.print("Humid:");
 Serial.println(h);
 PublishData(t, h);
 delay(4000);
if (!client.loop()) {
 mqttconnect();
}
}
/*.....*/
void PublishData(float temp, float humid) {
mqttconnect();//function call for connecting to ibm
/*
  creating the String in in form JSon to update the data to ibm cloud
```


```
*/
 String payload = "{\"temp\":";
 payload += temp;
 payload += "," "\"Humid\":";
 payload += humid;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print
publish ok in Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
 }
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
```


```
while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
   delay(500);
  }
  initManagedDevice();
  Serial.println();
}
}
void wificonnect() //function defination for wificonnect
{
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
 }
 Serial.println("");
Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
```


```
if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
}
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
 }
 Serial.println("data: "+ data3);
 if(data3=="lighton")
 {
Serial.println(data3);
digitalWrite(LED,HIGH);
}
 else
 {
Serial.println(data3);
digitalWrite(LED,LOW);
```


```
}
data3="";
}
```

OUTPUT









6/6/2023, 2:37:01 PM node: debug 1

msg.payload : string[7]

"lighton"