Knowing How Logics

Rens Doodeman, Ziqi Wang, and Zixuan Chen

Friday 13th March, 2026

Abstract

TODO!

Contents

1 How to use this? **2**

2 Project Description **2**

3 Language Knowing How **3**

4 Simple Tests **6**

5 Conclusion **6**

Bibliography **6**

1 How to use this?

To generate the PDF, open `report.tex` in your favorite LaTeXeditor and compile. Alternatively, you can manually do `pdflatex report; bibtex report; pdflatex report; pdflatex report` in a terminal.

You should have stack installed (see `https://haskellstack.org/`) and open a terminal in the same folder.

- To compile everything: `stack build`.
- To open ghci and play with your code: `stack ghci`
- To run the executable from Section **??**: `stack build && stack exec myprogram`
- To run the tests from Section 4: `stack clean && stack test --coverage`

2 Project Description

Ability-based epistemic logics are found many places in computer science, as arguably they provide us with a formal approach for strategic reasoning and AI planning. Several logics in this family have been studied lately. In particular, epistemic logics describing the notion of *knowing how* received a lot of attention, due to their simplicity and good meta-logical properties.

The simplest version of *knowing how*, $\mathcal{L}_{Kh}$, based on the paper by (Wang 2015[Wan15]), with the semantics reformulated in (Areces et al. 2021[AFSVQ21]). This logic captures the agent's ability to guarantee the completion of a task under a given condition. This idea is ideal in a sense, since even though the agent manages to do something under a condition, it does not imply the agent really know how. For example, one can win a lottery does not imply one can guarantee how to win. The uncertainty is involved in this case. Therefore, another logic may be prefered, $\mathcal{L}^U_{Kh}$. In this logic, an agent may have *indistinguishability* among several plans they might take, a critical concept in epistemic logic. Indistinguishable plans form equivalence classes, partitioning the set of available plans. Intuitively, plans considered identical by the agent are placed in the same class. Furthermore, this logic involves multi-agents, as opposed to a single agent. Finally, a new logic, $reg - \mathcal{L}^U_{Kh}$, a variation of the second version, introduces equivalence classes that are defined in terms of finite automatons.

In this project, we aim to model this family of knowing-how logics. We also intend to implement the model checking for the logic $reg - \mathcal{L}^U_{Kh}$ defined in [DF23]. Our project goals are defined as follows.

- Get familiar with the family of knowing-how logics;
- Implement the the family of knowing-how logics (syntax, semantics) in Haskell;
- Implement testing for knowing-how languages;
- (Optional) Implement model checking problem for the logic $reg - \mathcal{L}^U_{Kh}$ defined in [DF23];
- (Optional) Implement testing for model checking.

- (Optional) Implement a user-interface or at the very least an executable (using parsing) for model checking.

3 Language Knowing How

In this section we model the language of Knowing How L_{KH} as by the definition of Y. Wang [Wan15].

Given a set of proposition letters P, the language L_{KH} is defined as follows s.t. $Kh(\psi, \varphi)$ is the modality expressing "the agent knows how to achieve φ given ψ". The abbreviations $\bot$, $\vee$, $\rightarrow$, and the universal modality $U_\varphi := Kh(\neg\varphi, \bot)$ have been left out for simplicity.

```
module KnowingHow where

import Data.List (nub, delete)
-- import NoneEmpty including its constructor :|
import Data.List.NonEmpty (NonEmpty(..), toList)
import Test.QuickCheck
import GHC.Conc (par)

type Proposition = Int

data Form = P Proposition | Neg Form | Conj Form Form | KH Form Form | T
    deriving (Eq, Show, Ord)
```

Instead of a Kripke semantics, the Logic opts for a labelled transition system (LTS) $(\mathcal{S}, \mathcal{R}, \mathcal{V})$ s.t. $\mathcal{S}$ is a non-empty set of states, $\mathcal{R} : \Sigma \rightarrow 2^{\mathcal{S}\times\mathcal{S}}$ is a collection of transitions labelled by actions in Σ, and $\mathcal{V} : \mathcal{S} \rightarrow 2^P$ is a valuation function. In the literature by Y. Wang the LTS is called an ability map.

When creating a LTS, consider that states :: NonEmpty State, and therefore must use the :| constructor, i.e. (n :| [n+1..]). For more information see NonEmpty on Hoogle.

```
type Action = Integer
type Plan = [Action]
type State = Int
type Valuation = [(State, [Proposition])]

data AbilityMap = LTS {
    states :: NonEmpty State,
    transitions :: Relations,
    valuation :: Valuation
} deriving(Show)
```

In (Wang2015), two relational notions are introduced:

- R_a, the atomic relation associated with an action a;
- R_σ, the composite relation associated with a plan σ.

Both of these are binary relations on states. Therefore, in our implementation, we use the same Haskell type `Rel` to represent them, since both can be understood as sets of pairs of states.

To represent the family of atomic relations $R = (R_a)_a$, we index relations by actions. This gives rise to the type `Relations`, corresponding to the collection of action-labelled transitions in the literature.

We do not model R_σ explicitly as a separate data structure. Instead, we only implement the operations needed to reason about plan execution and strong executability.

For this purpose, we define the following helper functions:

- `image`, which computes the image of a state under a relation, i.e. it collects all successor states of a given state;
- `r_a`, which takes an action a and the family of relations R, and returns the indexed relation R_a;
- `executePlan`, which computes all possible end states obtained after executing a plan from a given initial state;
- `stronglyExecutableAt`, which determines whether a plan is strongly executable at a given state.

```
-- Both $R_a$ and $R_\sigma$ share the same type.
-- Here we model the whole set of relations, without classification.
type Rel = [(State, State)]

-- The family of action-indexed relations (R_a)_a
type Relations = [(Action, Rel)]

-- Image of a state under R_a
image :: Rel -> State -> [State]
image r u = [v | (x, v) <- r, x == u]

-- Given (R_a)_a and an action x, return R_x
r_a :: Relations -> Action -> Rel
r_a rs a =
    case lookup a rs of
        Just r  -> r
        Nothing -> []

-- Execute a plan from a given start state
-- This corresponds to R_sigma(u)
executePlan :: Relations -> State -> Plan -> [State]
executePlan _  u []       = [u]
executePlan rs u (a:sigma) =
    nub (concat [ executePlan rs v sigma | v <- image (r_a rs a) u ])

-- Plan is SE or not at a state
stronglyExecutableAt :: Relations -> State -> Plan -> Bool
stronglyExecutableAt _  _ []       = True
stronglyExecutableAt rs u (a:sigma) =
    let next = image (r_a rs a) u
    in  not (null next) &&
        all (\v -> stronglyExecutableAt rs v sigma) next
```

The satisfaction relation $\models$ defines when a formula φ is true in a given state s of an ability map $\mathcal{M}$. Before specifying the semantics, we first introduce two helper functions for the semantics of the Kh operator.

```
-- Given an LST and formula, returns the states that satify said formula
statesSatisifying :: AbilityMap -> Form -> [State]
statesSatisifying m f = [s | s <- toList (states m), isTrue (m, s) f]

-- Given an LST, find all plans.
findPlans :: AbilityMap -> [Plan]
findPlans m = nub (concatMap (plansFrom depth) (toList (states m)))
  where
    -- For now we limit the depth to avoid infinite loops.
    depth = 5
```

```haskell
    -- Flatten transitions
    edges :: [(Action,(State,State))]
    edges = [ (a,(u,v))| (a,rel) <- transitions m, (u,v) <- rel ]

    -- Generate all plans from a given state up to our specified depth
    plansFrom :: Int -> State -> [Plan]
    plansFrom 0 _ = []
    plansFrom d s =
        [ [a] | (a,(x,_)) <- edges, x == s ] -- single action plans
        ++ [ a:p | (a,(x,y)) <- edges, x == s, p <- plansFrom (d-1) y ]

isTrue :: (AbilityMap, State) -> Form -> Bool
isTrue _ T = True
isTrue (m, s) (P p) =
  case lookup s (valuation m) of
    Just props -> p `elem` props
    Nothing -> False
isTrue (m, s) (Neg f) = not (isTrue (m, s) f)
isTrue (m, s) (Conj f g) = isTrue (m, s) f && isTrue (m, s) g
-- KH is NOT local; its truth does not depend on the state at which it is evaluated.
-- KH either holds at all states, or none of them.
isTrue (m, _) (KH f g) =
    any (\a ->
        all (\s ->
            stronglyExecutableAt rs s a
            && all (\t -> isTrue (m,t) g) (executePlan rs s a)
        ) statesF
    ) candidatePlans
  where
    rs = transitions m
    statesF = statesSatisifying m f
    candidatePlans = findPlans m

-- Infix alias for the satisfaction relation
(|=) :: (AbilityMap, State) -> Form -> Bool
(|=) = isTrue
```

Finally, for this section we define the instances of Arbitrary for `Form` and `Arbitrary` respectively. For `Form` we use the `sized` function to ensure that the generated formulas remain finite in size.

```haskell
instance Arbitrary Form where
    arbitrary = sized randomForm where
        -- Helper function to generate random formulas of a given size
        randomForm :: Int -> Gen Form
        randomForm 0 = oneof [P <$> choose (1, 5), return T]
        randomForm n = oneof
            [ P <$> choose (1, 5)
            , return T
            , Neg <$> randomForm (n - 1)
            , Conj <$> randomForm (n `div` 2) <*> randomForm (n `div` 2)
            , KH <$> randomForm (n `div` 2) <*> randomForm (n `div` 2)
            ]

instance Arbitrary AbilityMap where
    arbitrary = do
        n <- choose (1,10)
        let sts = [1..n] -- n states
        rels <- generateRelations n sts
        vals <- mapM generateValuation sts
        return $ LTS (head sts :| tail sts) rels vals
        where
            generateRelations n sts
                | n == 1 = return []
                | otherwise = do
                    m <- choose (1,n) -- decide how many actions to generate
                    actions <- vectorOf m (choose (1,5))
                    mapM (generateRel sts) actions

             -- for each action a, generate a relation labeled by a
            generateRel sts a = do
                x <- elements sts
                y <- elements (delete x sts) -- avoid loops
```

```
            return (a, [(x,y)])

        -- for each state s, generate a list of propositions
        generateValuation s = do
            props <- listOf (choose (1,5))
            return (s, nub props)
```

4 Simple Tests

We now use the library QuickCheck to randomly generate input for our functions and test some properties.

```
module Main where

import Basics

import Test.Hspec
import Test.QuickCheck
```

The following uses the HSpec library to define different tests. Note that the first test is a specific test with fixed inputs. The second and third test use QuickCheck.

```
main :: IO ()
main = hspec $ do
  describe "Basics" $ do
    it "somenumbers should be the same as [1..10]" $
      somenumbers `shouldBe` [1..10]
    it "if n > - then funnyfunction n > 0" $
      property (\n -> n > 0 ==> funnyfunction n > 0)
    it "myreverse: using it twice gives back the same list" $
      property $ \str -> myreverse (myreverse str) == (str::String)
```

To run the tests, use `stack test`.

To also find out which part of your program is actually used for these tests, run `stack clean && stack test` Then look for "The coverage report for ... is available at ... .html" and open this file in your browser. See also: `https://wiki.haskell.org/Haskell_program_coverage`.

5 Conclusion

Finally, we can see that [?] is a nice paper.

References

[AFSVQ21] C. Areces, R. Fervari, A. R. Saravia, and F. R. Velázquez-Quesada. Uncertainty-based semantics for multi-agent knowing how logics. In *Proceedings of the 18th Conference on Theoretical Aspects of Rationality and Knowledge (TARK 2021)*, volume 335 of *EPTCS*, pages 23–37, 2021.

[DF23] S. Demri and R. Fervari. Model-checking for ability-based logics with constrained plans. In *Proceedings of the 37th AAAI Conference on Artificial Intelligence (AAAI-23)*, volume 37, pages 6305–6312, 2023.

[Wan15] Y. Wang. A logic of knowing how. In *Logical Reasoning and Interaction (LORI'15)*, volume 9394 of *Lecture Notes in Computer Science (LNCS)*, pages 392–405. Springer, 2015.