

# Custom Manifold Assemblies

For a Quick Quote, check preference boxes below and fax to (508) 842-4406, or call us Toll Free at **(888) 792-2223** for assistance.

## Aluminum Manifold

Inlet Size	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> 2"			
Port Size	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"		
Number of Ports	<input type="checkbox"/> 4	<input type="checkbox"/> 6	<input type="checkbox"/> 8	<input type="checkbox"/> 10	<input type="checkbox"/> 12	<input type="checkbox"/> 16	<input type="checkbox"/> Other _____
Special Port location/spacing	Specify: _____						
Color Anodizing	<input type="checkbox"/> Red	<input type="checkbox"/> Blue					

## Stainless Steel Manifold

Inlet Size	<input type="checkbox"/> 1"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> Other _____			
Port Size	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"	
Number of Ports	<input type="checkbox"/> 4	<input type="checkbox"/> 6	<input type="checkbox"/> 8	<input type="checkbox"/> 10	<input type="checkbox"/> 12	<input type="checkbox"/> 16
Special Port location/spacing	Specify: _____					
Low Profile Ports	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"				

## Valves and Fittings

Standard Brass Ball Valves	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"
Mini Brass Ball Valves	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"		
Hose Barbs	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"
Swivel Hose Barbs	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"		
Quick Connect Plugs (Male)	<input type="checkbox"/> 1/4" (200)	<input type="checkbox"/> 3/8" (300)	<input type="checkbox"/> 1/2" (500)		

## Flow Meters and Regulators

Mechanical Flow Meter	Port Size:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 1"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> 2"	
		<input type="checkbox"/> 1.5 GPM	<input type="checkbox"/> 2.5 GPM	<input type="checkbox"/> 8.0 GPM	<input type="checkbox"/> 20 GPM	<input type="checkbox"/> 40 GPM	<input type="checkbox"/> 100 GPM
		<input type="checkbox"/> Temperature Gauge		<input type="checkbox"/> Pressure Gauge			
Digital Flow Meter	Port Size:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 1"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> 2"	
		<input type="checkbox"/> Battery	<input type="checkbox"/> Switching				
Flow Regulator	Inlet Size:	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"			
		<input type="checkbox"/> Temperature Gauge		<input type="checkbox"/> Pressure Gauge			

## High Temperature Hose\* and Couplings

EPDM (285°F Max Water Temperature)	Size:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"
	Color:	<input type="checkbox"/> Red	<input type="checkbox"/> Blue	<input type="checkbox"/> Black
Silicone with SS Braid (335°F Max Water Temp)	Size:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	
	Color:	<input type="checkbox"/> Red	<input type="checkbox"/> Blue	<input type="checkbox"/> Silver
Viton Hose with SS Braid (395°F Max Oil Temp)		<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	
<input type="checkbox"/> High Temp Silicone Hose Insulation (600°F Rated)				
Safe-Lock™ Hi-Temp Safety Hose Couplers		<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	
	Hose Barb Size:	_____		
		<input type="checkbox"/> Straight	<input type="checkbox"/> 90°	
Ferrules	EPDM:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"
	Silicone:	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	
<input type="checkbox"/> Hose Crimper				

\* Designed for use with SafeLock Hi-Temp Fittings  
(See Valves and Fittings) and Hose Crimper

## Standard Water Hose and Couplings

ClearBraid™ PVC Hose Series K3150/3130	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"
	<input type="checkbox"/> 1 1/4"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> 2"		
	<input type="checkbox"/> Std Wall 3150		<input type="checkbox"/> Heavy Wall 3130		
PVC/Polyurethane Alloy Hose Series A114	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"
	<input type="checkbox"/> 1 1/4"	<input type="checkbox"/> 1 1/2"	<input type="checkbox"/> 2"		
	<input type="checkbox"/> Red	<input type="checkbox"/> Blue	<input type="checkbox"/> Yellow	<input type="checkbox"/> Grey	
PolyAir Air/Water Hose Series K113	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 5/16"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 5/8"
	<input type="checkbox"/> 3/4"	<input type="checkbox"/> 1"			
	<input type="checkbox"/> Red	<input type="checkbox"/> Blue	<input type="checkbox"/> Yellow	<input type="checkbox"/> Grey	
Push Lock Hose	<input type="checkbox"/> 1/4"	<input type="checkbox"/> 3/8"	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 5/8"	<input type="checkbox"/> 3/4"
	<input type="checkbox"/> Red	<input type="checkbox"/> Blue	<input type="checkbox"/> Black		
Standard Quick Hose Couplers	<input type="checkbox"/> 1/4" (200)	<input type="checkbox"/> 3/8" (300)	<input type="checkbox"/> 1/2" (500)		
	Hose Barb Size: _____			<input type="checkbox"/> Push Lock Barb	
	<input type="checkbox"/> Straight	<input type="checkbox"/> 90°	<input type="checkbox"/> 45°		

## Efficiency Accessories

- ☐ Magnetic Manifold Bases
- ☐ Mold Purge Swap® Valve
- ☐ FasTie® Ejector Coupler
- ☐ Ferrogard® Magnetic Water Filter
- ☐ IPS Mold Shields™ Mold Side Curtains
- ☐ Mold Chutes
- ☐ Mold Cleaning Wipes

## Assembly Options

- ☐ Valves and Fittings Installed
- ☐ Hose Assemblies with Standard or Safe-Lock™ Fittings (made to order)
- ☐ Color Coded Hose Sleeves (Silicone Hose Assemblies)
- ☐ Labels for In/Out Directional Flow

## Please Provide a Hand Sketch of Your Application

151 Memorial Drive, Unit H  
Shrewsbury, MA 01545 USA  
**888-792-2223**  
www.plastixs.com  
sales@plastixs.com

