




#### Java 15: What's in It for Me?


@Sander\_Mak

### Keeping up with Java






## Keeping up with Java



**Module System** 



Type inference with var





Switch Expressions



**Continuous JVM Improvements** 



## A small but very useful feature...


```
Exception in thread "main" java.lang.NullPointerException at Example.main(Example.java:5)
```


```
a().b().c.doSomething();
```

```
A a = a();
B b = a.b();
C c = b.c;
c.doSomething();
```

-XX:+ShowCodeDetailsInExceptionMessages

```
Exception in thread "main" java.lang.NullPointerException:
   Cannot invoke "Example$C.doSomething()" because
   "Example$A.b().c" is null
   at Example.main(Example.java:5)
```







## Today's topics Text Blocks Records 2 Sealed Classes 3 Pattern Matching



## Today's topics Text Blocks Records 2 Sealed Classes 3 Pattern Matching



### Text Blocks

```
String json = "{\n \"firstName\": \"Sander\",\n \"lastName\" ...
```



### Text Blocks

#### Multi-line Strings in Java source code

```
String json = """
{
    "firstName": "Sander",
    "lastName": "Mak"
}""";
```





### Text Blocks @ Picnic?

```
@Operation(description = """
   Find all users that satisfy the following conditions:
   * Condition 1
   * Condition 2
   * Condition 3
   _Note_: only active users are returned.""")
@GetMapping
Flux<User> findUsers(@RequestBody FindRequest request) {
   // ...
}
```

#### **OpenAPI** documentation

```
String pushMessage = """
  "GCM": {
    "data": {
      "type": "text-push",
      "title": "%s",
      "message": "%s"
    }
}""".formatted(title, message)
```

**Assertion values in code rather than files** 




## Today's topics Text Blocks 2 Records Sealed Classes 3 Pattern Matching



### Records

One of the three preview features we'll look at.





#### How to think about Records

A new restricted form of a class to model data as data

**Nominal tuples** 

**Immutable** 



Boilerplate reduction mechanism

JavaBeans replacement

Value types (memory layout/identity)





### Records @ Picnic?



http://immutables.org

DTOs
Document classes
Compound Map keys
Intermediate results in stream/reactive pipelines



## Today's topics Text Blocks Records 2 Sealed Classes 3 Pattern Matching



### Why Sealed Classes?

Goal: limit unrestriced inheritance

Use final? No inheritance at all

Supertype + subtypes in same package: limiting

```
public abstract class Option<T> {
    private Option() {)
    public final static class Some<T> extends Option<T> { ... }
    public final static class Empty<T> extends Option<T> { ... }
    // ...
}
```



#### Sealed classes

```
public sealed class Option<T> permits Some, Empty {
   // ...
}
```

```
public final class Empty<T> extends Option<T> {
    // ..
}
```



```
public final class Some<T> extends Option<T> {
    // ..
}
```



### Sealed classes

With subclasses in same source file, permits not required:

```
public sealed class Option<T> {
    // ..
}

final class Empty<T> extends Option<T> {}


final class Some<T> extends Option<T> {}
```







### Sealed classes





## Today's topics Text Blocks Records 2 Sealed Classes 3 4 Pattern Matching



### Pattern Matching

\* with instanceof

```
if (obj instanceof String) {
    String text = (String) obj;
    text.startsWith("Java 15 rules!");
} else {
    // not a String
}
```

```
if (obj instanceof String text) {
    text.startsWith("Java 15 rules!");
} else {
    // still not a String
}
```

- Test
- Cast
- New variable

- Type pattern
- Binding variable



## Pattern Matching





### Familiar use-case for Pattern Matching

```
@Override
public boolean equals(Object o) {
    return (o instanceof MyClass m) &&
    m.name.equals(name);
}
```



### Beyond Pattern Matching with instanceof



```
int value = switch (object) {
   case BigDecimal b -> b.intValue();
   case String s -> Integer.parseInt(s);
   case Integer i -> i;
}
```



## Records & Pattern Matching & Switch Expressions

```
int eval(Expr e) {
    return switch (e) {
        case ConstantExpr(var i) -> i;
        case PlusExpr(var a, var b) -> eval(a) + eval(b);
        case MulExpr(var a, var b) -> eval(a) * eval(b);
        case NegExpr(var e) -> -eval(e);
        // no default needed, Expr is sealed
```





## Today's topics Text Blocks Records 2 Sealed Classes 3 Pattern Matching



### But wait, there's more!

- ZGC marked non-experimental
- Shenandoah GC marked non-experimental
- Hidden classes
- Nashorn JS engine removed

Java Enhancement Proposals (JEPs) openjdk.java.net/projects/jdk/15/







# Help build Picnic Tech: join.picnic.app





Building the best milkman on earth serving millions of families

