REACT – Practica Guiada

1. Crear la aplicación React



2 Ejecutar la aplicación



3. Pantalla del navegador mostrando la aplicación inicial de React



4. Abrir src/app.js y reemplazar el contenido



Lista de Eventos

Conferencia de Ciberseguridad

Fecha: 12/12/2025

Taller de React

Fecha: 15/12/2025

Hackathon Universitario

Fecha: 20/12/2025

5. Cambiar el estilo de las tarjetas



```
// App.js
import React from "react";
function App() {
  const eventos = [
    { id: 1, nombre: "Conferencia de Ciberseguridad", fecha: "12/12/2025" },
    { id: 2, nombre: "Taller de React", fecha: "15/12/2025" },
    { id: 3, nombre: "Hackathon Universitario", fecha: "20/12/2025" },
  ];
  return (
    <div className="border rounded border-primary p-3 m-2 bg-primary text-light">
      <h1 className="display-3"> Lista de Eventos</h1>
      <ul style={{ listStyle: "none", padding: 0 }}>
        {eventos.map((evento) => (
          <li className="border rounded border-primary p-3 m-2 bg-warning text-dark"
            key={evento.id}

          >
            <h2>{evento.nombre}</h2>
            <p className="display-7"> Fecha: {evento.fecha}</p>
          </li>
        ))}
      </ul>
    </div>
  );
}
export default App;
```

```
// index.js
import React from 'react';
import ReactDOM from 'react-dom/client';
import './index.css';
import App from './App';
import reportWebVitals from './reportWebVitals';
import "bootstrap/scss/bootstrap.scss";

const root = ReactDOM.createRoot(document.getElementById('root'));
root.render(
  <React.StrictMode>
    <App />
  </React.StrictMode>
);

// If you want to start measuring performance in your app, pass a func
// to log results (for example: reportWebVitals(console.log))
// or send to an analytics endpoint. Learn more: https://bit.ly/CRA-vi
reportWebVitals();
```