

DHCP Configuration Commands:

Router(config)# ip dhcp pool VLAN_10

Creates a DHCP Pool named VLAN_10. Within this Pool we will specify the items mentioned above.

Router(dhcp-config)# network 172.16.10.0 255.255.255.0

Specifies the network for the DHCP Pool VLAN_10 as the 172.16.10.0/24 network.

Router(dhcp-config)# default-router 172.16.10.1

Specifies the "default gateway" for the dhcp clients will be 172.16.10.1.

Router(dhcp-config)# dns-server 172.16.2.10

Specifies the DNS Server will be 172.16.2.10

Router(config)# ip dhcp excluded-address 172.16.10.1 172.16.10.20

The above command tells the router to exclude addresses 172.16.10.1 thru 172.16.10.20 from DHCP allocation. These addresses will not be handed out to clients. The first address to be used will be 172.16.10.21.

Optional

Router(dhcp-config)# option 150 ip 172.16.2.20

Specifies optional DHCP options needed. Above the DHCP option of 150 for TFTP Server has been set to 172.16.2.20.

Verification:

MORE READING: Redistribution Between Cisco EIGRP into OSPF and Vice Versa (Example)

Show ip dhcp binding

The above command will display all allocated DHCP IP Addresses and their lease time.