


On the Subject of Needy Augmentation

Houston, we still have a problem. A less annoying problem, but a problem.

- This utility needy balances or otherwise changes activation behavior of other needy modules.
- This module can only affect modules on the same bomb.
- Behavior and difficulty changes are mission-specific.*

** Module's configuration has to be placed in the mission's description.
Refer to "On the Subject of Setting Up Needy Augmentation".*



When Configured

- The display will read **"AUGMENTED"** if augmentations are in effect.
- The display will read **"UNCHANGED"** otherwise.
- Needy Augmentation itself will never activate.
- Only 1 Needy Augmentation can behave like this on each bomb. Every other instance of Needy Augmentation will behave like it is not configured.

If the configuration has an error, it will be logged and a strike sound will play.

No actual strike is recorded and no augmentations are made, however the module will still not activate.

When Not Configured

- The display will read **"NO CONFIG"**.
- When this module activates, the display will show a draining bar.
- Press the "Refill" button before the bar is fully drained.

On the Subject of Setting Up Needy Augmentation

They can finally stop beeping. For five minutes.

- To augment needy modules you need:
 - A single[†] instance of Needy Augmentation on the bomb.
 - A configuration in the mission description.[‡]
- Each needy module can be augmented independently.
- This module is only a tool. It is still up to you, as the mission creator, to make missions fun. You do not have to use it either if you don't want to.

† One Needy Augmentation module can augment multiple needy modules, but they have to be on the same bomb. You may need to use multiple Needy Augmentation modules in the same mission in cases of multiple bombs.

‡ Dynamic Mission Generator places the whole mission source as the description.

Use a / */ comment to configure Needy Augmentation without format violations if you are using DMG.*

Configuration

- A configuration has the following format:


```
[NeedyAugmentation]module:property=expression,property=expression,...;
```
- Alternatively, bigger configurations can be written on multiple lines:


```
[NeedyAugmentation]
module:property=expression,...;
module:property=expression,...;
module:property=expression,...;
[/NeedyAugmentation]
```
- Properties are separated by commas, modules are separated by semicolons.
- Consider using <hidden> for players with the [Description Hider](#) mod.

Module ID

- `module` is the ID of the module to augment.
- You may specify the same ID multiple times to augment multiple copies of the same needy differently. The augmentations will be picked in order.
- Augmentations for modules that could not be found are skipped.
- `*` is a wildcard and will affect all otherwise unspecified needy modules.
- Without the wildcard, unspecified modules retain their original behavior.
- When augmenting [Black](#) and [White](#), only augment `blackModule`.

Properties And Expressions

- The table below lists all possible properties. Every property is optional.
- Seconds are based on the countdown timer.
- Whitespace is not significant.

Property	Expressions	Description
acttime	<code>seconds</code> <code>seconds s</code>	<u>(Initial) Activation Time</u> <i>Default: use mission's setting.</i> • Overrides the initial activation time. • The needy still reacts to solves and strikes. • <code>seconds</code> is a float (decimal number).
cd	<code>*mult</code> <code>+addend</code> <code>-subtrahend</code> <code>*mult+addend</code> <code>*mult-subtrahend</code>	<u>Reactivation Cooldown</u> <i>Default: no change.</i> • Multiplies the time between needy activations by <code>mult</code> (if present), then adds <code>addend</code> or subtracts <code>subtrahend</code> seconds. • <code>mult</code>, <code>addend</code> and <code>subtrahend</code> are all floats.
acts	<code>base</code> <code>base+perSolve</code> <code>base-perSolve</code> <code>base+per/solves</code> <code>base-per/solves</code>	<u>Activations / Activation Limit</u> <i>Default: unlimited number of activations.</i> • Limits the number of times the module can activate to <code>base</code> times. • <code>per</code> and <code>solves</code> add or remove <code>per</code> activations every <code>solves</code> solved regular modules. • <code>perSolve</code> is equivalent to <code>per/1</code>. • <code>base</code>, <code>perSolve</code>, <code>per</code> and <code>solves</code> are integers.
start	<code>seconds s</code> <code>modules m</code>	<u>Start At</u> <i>Default: start when the bomb starts.</i> • Prevents the module from activating until either <code>modules</code> regular modules are solved or <code>seconds</code> seconds have passed. • The module behaves as if the bomb was just started afterwards. • <code>seconds</code> is a float (decimal number). • <code>modules</code> is an integer.

Properties And Expressions (cont.)

Property	Expressions	Description
term	<code>secondsLeft s1</code> <code>modulesLeft m1</code>	<u>Terminate At</u> <i>Default: do not terminate until the bomb is defused.</i> • Permanently disables the module when either <code>modulesLeft</code> unsolved regular modules remain or <code>secondsLeft</code> seconds remain. • The module is deactivated, if it is active. • <code>secondsLeft</code> is ignored in Zen and Time modes. • <code>secondsLeft</code> is a float (decimal number). • <code>modulesLeft</code> is an integer.
stop	<code>secondsLeft s1</code> <code>modulesLeft m1</code>	<u>Stop At</u> <i>Default: do not stop until the bomb is defused.</i> • Equivalent to “Terminate At”, except the module is not automatically deactivated, if it is currently armed.