

Basic Possibilistic Logic: Examples and Visualization

Seminar Paper

submitted by

Alexander Köhn

Abstract

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua.

1 Introduction

The goal of this paper is to introduce Basic Possibilistic Logic with the use of examples and visualization. Possibilistic logic is a weighted logic that handles uncertainty in a qualitative way by adding certainty to classical logic formulas. Its strength lies in modeling uncertainty and its ability to deal with inconsistency. It has been developed for about thirty years. It still remains very close to classical logic. In this paper we will only focus on basic Possibilistic Logic.

This work is structured as follows. In the Section 2 Basic Possibilistic Logic is explained with its Preliminaries for understanding the syntax and semantics of the logic. The Section 3 shows the use of Basic Possibilistic Logic with multiple examples. Section 4 explains Basic Possibilistic Logic with graphical explanations. The last Section 5 discusses the results of the previous sections.

2 Fundamentals of Basic Possibilistic Logic

As a main source the overview chapter: Possibilistic Logic - An Overview from the authors Dubois and Prade [1] is used.

2.1 Introduction to Possibility Theory

2.1.1 Possibility Distribution

A possibility distribution is a mapping π from U to a totally ordered scale S , with top denoted by 1 and bottom by 0:

$$\pi : U \rightarrow S,$$

where U is the set of states. $\pi(u)$ can be understood as the degree of possibility of the state u . The function π represents the state of knowledge of an agent and distinguishes what is plausible from what is less plausible. The state u is impossible, if $\pi(u)$ equals 0. The state is fully possible, if $\pi(u)$ equals 1.

A distribution π is at least as specific as π' if

$$\pi(u) \leq \pi'(u), \quad \forall u \in U.$$

An agent has complete knowledge if the possibility of one state is 1 and the possibility of all other states is 0. Complete ignorance is given if the possibility of all states is 1. The Principle of minimal specificity states that any hypothesis not known to be impossible cannot be ruled out. It is a minimal commitment, cautious, information principle.

2.1.2 Possibility and Necessity Functions

If we want to know if the event A occurs we can respond in possibility theory with two measures calculated from the possibility distribution to A . A is a subset of states. The two measures are the possibility and the necessity of an event.

The Possibility is defined as $\Pi(A) = \sup_{u \in A} \pi(u)$. It is the maximum of possibility of all the states of A . The Possibility evaluates the extent to which A is consistent with π . Possibility measures satisfy the characteristic maximality property $\Pi(A \cup B) = \max(\Pi(A), \Pi(B))$.

The Necessity is defined as $N(A) = \inf_{u \notin A} (1 - \pi(u))$. It is the minimum of the inversed possibility value of all states which are not in A . The Necessity evaluates the extent to which A is certainly implied by π . Necessity measures satisfy the characteristic minimization property $N(A \cap B) = \min(N(A), N(B))$. The minimization property expresses that to be certain about A and B , one has to be certain about A and to be certain about B .

The duality of the two measures is expressed as $N(A) = 1 - \Pi(A^c)$, where A^c is the complement of A .

2.2 Formal foundations of Basic Possibilistic Logic

2.2.1 Syntax

A basic possibilistic logic formula is represented as:

$$(a, \alpha)$$

where a is a classical logic formula (e.g., $p \rightarrow q$) and α is the certainty level (minimum necessity degree of a). It can be viewed as a lower bound of a necessity measure. The pair (a, α) is understood as $N(a) > \alpha$. We can interpret that the formula a is at least certain to degree α . The higher α , the stronger the belief in a . For example $(b \rightarrow f, 0.9)$ means that birds fly with certainty 0.9.

2.2.2 Axioms

The axioms of Possibilistic Logic are those of propositional logic. In the following the inference rules of basic possibilistic logic will be explained. The Certainty weakening rule states that if a formula is valid with a high certainty level, it is also valid with any lower certainty level. If a formula holds with a certainty level α , it automatically implies that it holds with any lower level of certainty beta because we are being less demanding, see equation 1.

$$\text{If } \beta \leq \alpha, \quad (a, \alpha) \vdash (a, \beta) \quad (1)$$

The Modus ponens rules states that if a to b is true with certainty level α , and a is also true with certainty level α then b must be true with certainty level α , see equation 2.

$$(\neg a \vee b, \alpha), (a, \alpha) \vdash (b, \alpha), \quad \forall \alpha \in (0, 1] \quad (2)$$

In classical logic, the resolution rule allows us to combine two clauses that share a literal to eliminate that literal and infer a new clause. In possibilistic logic, the resolution rule preserves the certainty level α , because the inferred formula $b \vee c$ cannot be more certain than the least certain premise, see equation 3.

$$(\neg a \vee b, \alpha), \quad (a \vee c, \alpha) \vdash (b \vee c, \alpha) \quad (3)$$

The weakest link resolution rule extends the resolution rule by the concept of different certainty levels α and β in the premises. The weakest link resolution reflects the idea that the certainty of the conclusion cannot exceed the weakest certainty of the premises. If one of the premises is less certain, it becomes the bottleneck for the certainty of the conclusion, see equation 4.

$$(\neg a \vee b, \alpha), \quad (a \vee c, \beta) \vdash (b \vee c, \min(\alpha, \beta)) \quad (4)$$

2.2.3 Inference Rules

We can define a possibilistic knowledge base as a collection of possibilistic formulas, see equation 5.

$$\Gamma = \{(a_i, \alpha_i), i = 1, \dots, m\} \quad (5)$$

Further we can define the α -cut of knowledge base, see equation 6. It only contains those formulas from the origin knowledge base with a certainty level of at least α . It has a nested structure where the α knowledge base is a part of the β knowledge base if α is higher than β .

$$\Gamma_\alpha = \{(a_i, \alpha_i) \in \Gamma \mid \alpha_i \geq \alpha\} \quad (6)$$

A possibilistic inference (a, α) depends only on formulas with certainty levels $\geq \alpha$, see equation 7.

$$\Gamma \vdash (a, \alpha) \iff \Gamma_\alpha \vdash (a, \alpha) \quad (7)$$

If we want to infer from the knowledge, we can only look on the formulas with a certainty of at least α . This means that a inference is only valid if it is valid with the α -cut of a knowledge base.

An important attribute of knowledge bases is the inconsistency level. It is the highest certainty level at which the knowledge base becomes inconsistent. The properties of the inconsistency level shows that all formulas which have a higher certainty level than the inconsistency level are safe form inconsistency, see equation 8.

$$\text{inc-l}(\Gamma) = \max\{\alpha \mid \Gamma \vdash (\perp, \alpha)\}. \quad (8)$$

2.2.4 Semantic Aspects

The semantics of possibilistic logic, as introduced in [?], is based on the concepts of possibility distributions, weak possibility measures, and strong necessity measures.

Consider a possibilistic logic formula (a, α) , representing the constraint $N(a) \geq \alpha$. The semantics of this formula is expressed using a possibility distribution $\pi(a, \alpha)$, defined as:

$$\pi(a, \alpha)(\omega) = \begin{cases} 1 & \text{if } \omega \models a, \\ 1 - \alpha & \text{if } \omega \models \neg a. \end{cases}$$

The intuitive interpretation is that models of a are fully possible ($\pi = 1$), while counter-models of a are less possible as α increases. When $\alpha = 0$, the formula $(a, 0)$ provides no additional information and can be ignored.

The associated necessity measure satisfies:

$$N_{a, \alpha}(a) = \alpha,$$

and $\pi(a, \alpha)$ is the least informative possibility distribution that satisfies this constraint.

2.3 Differences from classical logic

Possibilistic logic extends classical logic to address reasoning under uncertainty, offering mechanisms to represent degrees of belief and certainty. This section highlights the fundamental differences between the two logical frameworks, focusing on their semantics, expressive power, and handling of inconsistency.

2.3.1 Representation of Uncertainty

Classical logic operates within a binary truth-value system where every statement is either true (1) or false (0) [?]. This simplicity facilitates precise reasoning but limits the capacity to model uncertainty or graded beliefs. For instance, in classical logic, if p is true, the disjunction $p \vee q$ is true regardless of q .

In contrast, possibilistic logic incorporates a certainty degree $\alpha \in [0, 1]$ into formulas. A formula (a, α) encodes the constraint $N(a) \geq \alpha$, where $N(a)$ is a necessity measure representing the certainty of a . As Dubois et al. explain, this framework allows for "a more nuanced reasoning where uncertainty is explicitly quantified" [?]. This makes possibilistic logic particularly suitable for applications such as decision-making and expert systems.

2.3.2 Semantics

The semantics of classical logic are based on truth assignments, where a model is a complete assignment of truth values to all propositions. A formula is true if it holds in all models satisfying the formula [?].

Possibilistic logic employs possibility distributions to rank interpretations by their plausibility. A possibility distribution $\pi(\omega)$ assigns a degree of possibility $[0, 1]$ to each interpretation ω . Models of a formula a have maximum possibility ($\pi = 1$), while countermodels have reduced possibility proportional to the certainty level α . This richer semantic framework accommodates reasoning with uncertainty and vagueness [?].

2.3.3 Handling Inconsistency

Classical logic adopts a strict approach to inconsistency: the presence of a contradiction $(a \wedge \neg a)$ renders the entire knowledge base invalid, allowing any formula to be derived [?].

Possibilistic logic, on the other hand, quantifies inconsistency. The inconsistency degree of a knowledge base reflects the extent to which it is contradictory. As Dubois et al. note, possibilistic logic "enables reasoning to proceed by prioritizing more certain information and disregarding less certain, conflicting data" [?]. This feature makes it robust for reasoning in incomplete and inconsistent environments.

2.3.4 Expressiveness

Classical logic excels in deterministic reasoning, where propositions are crisp and well-defined. It forms the foundation of mathematics, formal verification, and theoretical computer science [?]. However, it cannot represent graded uncertainty.

Possibilistic logic extends the expressive power of classical logic by introducing mechanisms to model partial beliefs and degrees of certainty. This capability is crucial in fields like artificial intelligence, where uncertainty is inherent to problem-solving [?].

2.3.5 Entailment

Entailment in classical logic is binary: $\Delta \models a$ indicates that a is true in all models of Δ . For example, if $\Delta = \{p, p \rightarrow q\}$, then q is entailed if p is true [?].

In possibilistic logic, entailment is graded. $\Delta \models (a, \alpha)$ implies that a is true in all interpretations with at least the certainty level α . This certainty-based entailment enables reasoning about the strength of conclusions, a key feature in real-world applications [?].

2.3.6 Applications

Classical logic is well-suited for deterministic problems with clear, unambiguous rules, such as mathematical reasoning and logic programming [?].

Possibilistic logic, by contrast, is tailored for reasoning under uncertainty. Its ability to handle graded beliefs makes it a powerful tool in domains like artificial intelligence, decision support systems, and fuzzy logic applications. For example, possibilistic logic integrates seamlessly with fuzzy systems to facilitate approximate reasoning [?, ?].

2.3.7 Summary

The primary distinctions between classical and possibilistic logic are summarized in Table 1.

Table 1: Comparison of Classical Logic and Possibilistic Logic

Aspect	Classical Logic	Possibilistic Logic
Truth Values	Binary (0, 1)	Graded ([0, 1])
Semantics	Truth Assignments	Possibility Distributions
Uncertainty Handling	Not Supported	Explicitly Represented
Inconsistency Handling	All-or-Nothing	Quantified and Managed
Applications	Deterministic Problems	Uncertain or Vague Reasoning
Entailment	Binary	Certainty-Based

Possibilistic logic, by building upon classical logic, provides the means to address the limitations of classical reasoning in uncertain and inconsistent environments. As Dubois et al. summarize, "its ability to combine logical precision with graded uncertainty makes it a valuable tool for real-world reasoning tasks" [?].

2.4 Relation to Artificial Intelligence

Possibilistic logic has a significant role in the field of artificial intelligence (AI), where reasoning under uncertainty is a fundamental challenge. Unlike classical logic, which assumes a deterministic world, possibilistic logic provides a framework to model and reason about incomplete, inconsistent, or uncertain information. This capability makes it particularly relevant to AI systems that must operate in real-world environments.

2.4.1 Reasoning Under Uncertainty

In AI, systems frequently encounter scenarios where the available information is uncertain or imprecise. Classical logic, which relies on binary truth values, is insufficient for such cases. Possibilistic logic addresses this limitation by introducing graded measures of certainty and possibility. Each formula in possibilistic logic is associated with a certainty degree, allowing AI systems to represent and process partial beliefs [?].

For example, in expert systems, possibilistic logic can encode the varying reliability of rules provided by human experts. A rule with a higher certainty degree is given more weight in inference processes, enabling the system to prioritize more reliable information [?].

2.4.2 Handling Inconsistency

Inconsistencies are inevitable in real-world AI applications, particularly when combining knowledge from multiple sources. Classical logic treats any inconsistency as catastrophic, rendering the entire knowledge base unusable. Possibilistic logic, by contrast, quantifies inconsistency and allows reasoning to continue by prioritizing more certain information [?]. This feature is crucial for applications such as multi-agent systems and knowledge integration, where conflicting data is common.

2.4.3 Applications in AI

Possibilistic logic has been applied in various AI domains, demonstrating its versatility and utility. Key applications include:

- **Decision Support Systems:** Possibilistic logic enables decision-making under uncertainty by modeling degrees of belief and their impact on outcomes. This is particularly useful in medical diagnosis and risk assessment systems [?].
- **Natural Language Processing (NLP):** Uncertainty is inherent in NLP tasks, such as semantic analysis and information retrieval. Possibilistic logic provides a robust framework for modeling linguistic uncertainty and ambiguity [?].
- **Fuzzy Systems:** Possibilistic logic integrates seamlessly with fuzzy logic to facilitate approximate reasoning, making it a natural choice for control systems and robotics [?].

2.4.4 Relation to Other AI Frameworks

Possibilistic logic is closely related to other uncertainty reasoning frameworks in AI, such as probabilistic reasoning and fuzzy logic. While probabilistic approaches focus on quantifying uncertainty in terms of likelihoods, possibilistic logic emphasizes qualitative reasoning based on plausibility and necessity measures [?]. This distinction makes possibilistic logic particularly suited to scenarios where precise probability distributions are unavailable or unnecessary.

Moreover, possibilistic logic complements fuzzy logic by providing a logical foundation for reasoning about fuzzy sets. As Zadeh [?] observed, the integration of fuzzy logic and possibilistic reasoning enables more sophisticated modeling of real-world problems, particularly those involving vague or imprecise concepts.

2.4.5 Conclusion

The ability of possibilistic logic to handle uncertainty, inconsistency, and imprecision makes it a valuable tool in AI. By extending classical logic with measures of certainty and possibility, it bridges the gap between theoretical rigor and practical applicability in uncertain environments. As Dubois and Prade note, "possibilistic logic combines logical precision with the flexibility required for real-world reasoning" [?].

3 Analysis and Development of Examples

3.1 Elaboration on existing examples from the literature

The „Tweety penguin problem “
Other relevant examples from Dubois’ works

3.2 Extension of existing examples

Detailed discussion and interpretation

3.3 Development of new examples

Motivation for the new examples
Presentation and analysis

4 Visualization in Possibilistic Logic

4.1 The need for and benefits of visualization

4.2 Approaches to visualization

Graphical representations of possibility and necessity
Diagrams illustrating inference processes

4.3 Implementation and evaluation

5 Discussion and Conclusion

5.1 Summary of findings

5.2 Limitations of the study

5.3 Outlook on future research

6 Example Figures and Tables

Figure 1 shows an example of an abstract argumentation framework.




Figure 1: An abstract argumentation framework.

1	2	3
4	5	6

Table 2: Table caption.

6.1 Encoding Test

Städte, Länder, Flüsse

References

- [1] Didier Dubois and Henri Prade. Possibilistic logic — an overview. In Jörg H. Siekmann, editor, *Computational Logic*, volume 9 of *Handbook of the History of Logic*, pages 283–342. North-Holland, 2014.

Statement

Ich erkläre, dass ich die schriftliche Ausarbeitung zum Seminar selbstständig und ohne unzulässige Inanspruchnahme Dritter verfasst habe. Ich habe dabei nur die angegebenen Quellen und Hilfsmittel verwendet und die aus diesen wörtlich oder sinngemäß entnommenen Stellen als solche kenntlich gemacht. Die Versicherung selbstständiger Arbeit gilt auch für enthaltene Zeichnungen, Skizzen oder graphische Darstellungen. Die Ausarbeitung wurde bisher in gleicher oder ähnlicher Form weder derselben noch einer anderen Prüfungsbehörde vorgelegt und auch nicht veröffentlicht. Mit der Abgabe der elektronischen Fassung der endgültigen Version der Ausarbeitung nehme ich zur Kenntnis, dass diese mit Hilfe eines Plagiatserkennungsdienstes auf enthaltene Plagiate geprüft werden kann und ausschließlich für Prüfungszwecke gespeichert wird.

.....
(Place, Date)

(Signature)