

I-X IT SOLUTIONS · REFERENCE ARCHITECTURE

Reference Architecture — Foundations for an Enterprise- ready, Multi-tenant ERP

Proven in production on the Raak community platform, built AI-first, carried forward by I-X IT Solutions

1.0 — 7 September 2026

master @ b373f864 (v2.0.0 release candidate); production runs v1.14.0

Koen Renders — I-X IT Solutions

every claim in this document is traceable to code in the repository; see Appendix B

Contents

1. Executive summary	3
2. Architecture principles	4
3. Logical architecture and domain model	5
3.1 System context and deployment	5
3.2 Component map	6
3.3 Master data and membership	8
3.4 Activities, registrations and the payment ledger	8
3.5 Form engine, CMS, media and workflow	9
4. Request flow, gatekeepers and roles	11
4.1 The gatekeeper ladder	11
4.2 A request, end to end	13
4.3 Money: online payment and the untrusted webhook	14
4.4 Roles and how a user reaches their work	14
4.5 The workbench: management by exception	15
5. Multi-tenancy and security in detail	17
5.1 Tenant model and resolution	17
5.2 Honest gaps in the tenancy story	18
5.3 Security controls	18
6. Development process: how an AI agent works inside the gates	20
6.1 The loop	20
6.2 Test layers	21
6.3 What the gates caught	21
6.4 Two read-only agents	22
7. AI in the solution, today and next	23
7.1 What runs today	23
7.2 Extensibility: the mailing engine for member recruitment roadmap	24
8. From association to enterprise: the same building blocks	25
9. Way forward	27
Appendix A — Documentation versus code	28
Appendix B — Evidence index	30
Gespreksleidraad	31

1. Executive summary

What this document is. The reference architecture of a platform that runs in production today for one community association and is designed as the foundation of an enterprise-ready, multi-tenant ERP that I-X IT Solutions develops further. The first tenant is small on purpose; the structure underneath is not.

What runs today. Activity registration, family membership with renewal, online and bank-transfer payments through Mollie, a form engine, a CMS, a chatbot and a back office. In production for Raak Millegem since June 2026.

Why it is an ERP foundation and not a club portal. The functional surface is small; the *structure* is that of business software: thirteen domain packages behind facades with one Postgres schema each, master data with merge and survivorship, a payment ledger with a stated reconciliation invariant, row-level multi-tenancy, a kernel with in-transaction events and a durable job queue, and a workbench that turns every exception into a task. None of that is needed to sell tickets for a barbecue; all of it is needed the day the same code runs an order book, a warehouse or a second customer (Chapter 8).

How it was built. By one architect directing AI coding agents. That only works when agents cannot quietly break things, so much of the engineering went into *gates*: 1,343 tests against a real PostgreSQL, twelve gate files that fail the build on architectural drift, a rendered-HTML gate, browser flows where money moves, and a CI that boots the real startup script. The agent corrects itself on the failing test (Chapter 6).

The five architectural choices that make it scale to business software

- 1. Domain packages behind facades, one schema each.** Thirteen packages, each with `api.py` as its only public door and its own Postgres schema; two AST-based tests enforce it on every push.
- 2. ERP-style master data.** Never hard-deleted; duplicates merge into a golden record with a survivorship chain; every entity has an append-only history table; other domains reference it by value, without cross-schema foreign keys.
- 3. A ledger, not a payment field.** Every charge and refund is a record with a polymorphic reference to what is paid; one function owns the invariant *sum of records equals amount due*; the Mollie webhook never trusts its own body.
- 4. Row-level multi-tenancy from the kernel.** A `tenant_id` mixin on 43 tables, resolved per request and applied as a global ORM filter no query can forget. A third tenant is configuration, not code.
- 5. Quality as infrastructure, because AI writes most of the code.** Issue-driven changes, four blocking CI jobs, allowlists that must shrink to zero, and the written rule that *a test must be able to go red*.

Status tags. in production on production (v1.14.0, 13 July 2026) · v2.0.0 · HDEV on master, validated on HDEV, pending as v2.0.0 · designed / partial partly built · roadmap designed only. Unless stated otherwise the text describes `master`.

Table 1 — The platform in numbers (master @ b373f864)

Measure	Value
Domain packages / Postgres schemas	13 / 11, plus <code>public</code> for the kernel
ORM-mapped tables, of which tenant-scoped	55 / 43
Tests, of which browser end-to-end flows	1,343 / 19
Gate files enforcing architecture and conventions	12, all allowlists empty

2. Architecture principles

Each principle is followed by where it is enforced. A principle that is only written down is a wish; these are tests.

2.1 Domain separation with facades. Every domain owns its models, service, routers, screens and templates. Other code reaches it only through `api.py`. Enforced by `tests/test_import_boundaries.py` (an import linter written as a pytest: kernel never imports domains, cross-domain imports only target `.api`) and `tests/test_schema_boundaries.py` (no foreign keys across schemas). v2.0.0 · HDEV

2.2 Screens build a view-model and choose a template. Nothing else. A UI module may not touch the database session, may not import ORM classes or router functions, and passes a typed `ViewModel` to its template. Enforced by `tests/test_layer_gate.py` (AST-based, five rules) and `tests/test_template_variables_gate.py` (a template may not ask for a variable the view-model does not promise). Templates render under `StrictUndefined` in development, test and HDEV, so a typo fails instead of rendering blank. v2.0.0 · HDEV

2.3 ERP-ready data model. Master data is never hard-deleted; merges keep a survivorship pointer; every business entity has a history table written in the same transaction as the change; references between domains are values, not database constraints, so a domain can be extracted later. Money is a ledger with a reconciliation invariant. See Chapter 3. [HDEV, ledger since v1.x in PROD]

2.4 Multi-tenant by construction. Tenant scoping is a kernel mixin plus a global ORM filter, not a `WHERE` clause developers must remember. Configuration and secrets are per tenant in the database, with `.env` as fallback. See Chapter 5. v2.0.0 · HDEV

2.5 Gatekeepers in the request path. Eighteen distinct checks stand between a request and a row, from TLS and security headers at the edge to Jinja auto-escaping and HTML sanitisation on the way out. Chapter 4 lists them in order. The financial gate is separate from the administrative gate: an administrator can read payments but cannot mutate them. [PROD for most, HDEV for the UI gates]

2.6 Security by design, refused at startup. A weak or short `SECRET_KEY`, `DEBUG` or SQL echo make the application refuse to start in UAT and production. API documentation is disabled there. Logs carry an allow-list of fields and never a query string, a body or a token. in production

2.7 Test automation as the safety net for AI-driven development. The agent's feedback is the failing test, not a human review of every line. Hence the investment in gates that cannot pass by looking nowhere (`tests/test_gate_niet_leeg.py`), a rendered-HTML gate, a query budget per screen, and browser flows that fail rather than skip when the seed data is present. See Chapter 6. v2.0.0 · HDEV

2.8 AI-first, in both directions. The product is built *with* AI agents inside the gates above, and it embeds AI *in* the solution: a chatbot over the site's own content with an allow-listed tool boundary, OCR of posters and documents, and speech-to-text. Every AI feature ships dark and is switched on per environment. See Chapter 7. [PROD for the chatbot, HDEV for the rest]

2.9 Europe first. Hosting on an EU provider (Hetzner, Germany), Mistral for language, OCR and speech, Mollie (NL) for payments, self-hosted Umami instead of a tracking SaaS, OpenDocument instead of proprietary spreadsheet formats. Where no EU option exists the trade-off is written down before the dependency is added (the rule lives in the project's `CLAUDE.md`). in production

3. Logical architecture and domain model

3.1 System context and deployment

Every environment is a Docker Compose stack with an explicit project name. Development and the integration environment (HDEV) carry their own reverse proxy. UAT and production publish no host ports at all; they sit behind one shared Caddy container that terminates TLS for both and is deployed with an expand/contract discipline, because its configuration serves two releases at once. The backend serves HTML and JSON from one process; there is no separate frontend container since the React exit.




Figure 1. Deployment topology per environment

Points an operator will look for: images are pinned (`caddy:2.11.4`, `postgres:16`); the backend runs as a non-root user; production compose fails fast on any missing secret (`${VAR:?...}`); the deploy script takes a pre-migration database dump, checks out the release tag detached, rebuilds, runs a read-only smoke test and rolls back once automatically if the smoke test fails. A single entry point, `raakctl`, resolves an environment name to its checkout so nobody runs the UAT script against production. **in production**

3.2 Component map

The map below is the intended structure and, since v2.0.0, the actual one. Layer 1 holds identity, master data and mail: the three things every business domain needs, which is why master data sits *under* the business domains rather than among them (working document, decision 3). Layer 2 holds the business domains; capabilities are cross-cutting services. Everything rests on a kernel that contains no business logic and imports no domain.




Figure 2. Layered package structure (master)

Domains talk to each other in exactly two ways, both visible in the code: a call on the other domain's facade, or an event published through the kernel and handled in the same transaction. The figure below shows every such link that exists on master.




Figure 3. Cross-domain links on master: facade calls and kernel events

Table 2 — Domains on master

Domain	Schema	Facade	Service	JSON API	Screens	Contract
activities	activities	yes	779 lines	yes	public + admin	yes
membership	membership	yes	yes	yes	public portal	yes
payment	payment	yes	1,178 lines	3 routers	admin	yes
forms	form	yes	982 lines	yes	public + admin	yes
mdm	mdm	yes	yes	2 routers	admin	yes
auth	auth	yes	yes	yes	login + users	yes
mail	mail	yes	yes	yes	e-mail log	yes
cms	cms	yes	yes	yes	public + admin	yes
media	media	yes	yes	yes	admin	yes
chatbot	ai	yes	yes	2 routers	widget + admin	yes
workflow	workflow	yes	in facade	none	werkbank	yes
audit	(uses domain schemas)	yes	yes	yes	changes screen	no
stt	none	none	none	WebSocket	none	no

Rules that hold on master: kernel imports no domain; cross-domain imports target only `.api`; no cross-schema foreign keys; a UI module never touches the session. Two facades still delegate part of their implementation back into a router (`activities`, `forms`), which the layer gate tolerates for services but not for screens. That is honest debt, and it is listed in Chapter 9.

3.3 Master data and membership

The MDM domain is generic on purpose: an `Organization` tree (`ACCOUNT` above `UNIT`) is the tenant registry; `Person` and `Member` (a household) are linked through a junction with a relation type; addresses use a postal-code lookup table; contact details are typed rows rather than columns on the person; legacy identifiers live in a separate external-number table. Every entity has an append-only history table with no foreign keys, so history survives the deletion of its subject (the figure shows the person's; membership has its own).

Merge and survivorship are implemented: `merge_persons` flattens chains so `resolve()` is $O(1)$, writes a `person_merged` snapshot as the anchor for `unmerge_person`, and publishes an `EntityMerged` event. Nothing is hard-deleted; a global soft-delete filter hides `deleted_at` rows from every ORM query, including relationship loads, with an explicit escape hatch for the audit screen. **v2.0.0 · HDEV**




Figure 4. Master data and membership (schemas `mdm`, `membership`) - key columns per entity

3.4 Activities, registrations and the payment ledger

An activity has dates, components (the thing you register for, with capacity and its own price) and products (order lines with quantity, member price, free or pay-on-site). A registration holds contact data and order lines. Money lives in a separate ledger domain: every charge and refund is a `PaymentRecord` that points at what is being paid through a polymorphic reference (`payable_type`, `payable_id`) without a foreign key, so the same ledger serves registrations and memberships and can serve invoices later.

The ledger's single invariant is stated in code (`payment/service.py`, `reconcile_charges`): *after reconciliation, the sum of all non-deleted records equals the amount due*. Paid amounts are the truth; unpaid records are re-derived; a shortfall becomes one transfer charge with a Belgian structured communication generated from a Postgres sequence with the mod-97 check; a surplus becomes one refund that is a pending *obligation* until the treasurer confirms it, and the workbench shows it within minutes. The same function reconciles memberships. [PROD for the ledger and Mollie flow; HDEV for the generalised reconciliation]




Figure 5. Activities, registrations and the payment ledger - key columns per entity

3.5 Form engine, CMS, media and workflow

The form engine is a complete server-side builder: ten field types with typed answer columns, sections with branching at section and option level computed on the server, a step-by-step wizard that follows exactly the route the server computed, JSON import and export with a published format guide written for AI assistants, server-side statistics so raw answers never reach the browser, and OpenDocument export. The CMS is one table of pages with text placeholders for prices that resolve from tenant configuration on public read only, and an HTML sanitiser at every public render. Media assets (posters, photos, sponsor

logos, component documents) are stored in Postgres with generated thumbnails. The workflow domain provides tasks with a subject reference, a step definition as data, and the workbench that Chapter 4 describes.

4. Request flow, gatekeepers and roles

4.1 The gatekeeper ladder

Eighteen distinct checks stand between a request and a database row. Most are not middleware but explicit dependencies on routes, which is what makes them testable one by one.

Two decisions in this ladder are worth a conversation. First, capabilities are derived per request from the database, never baked into the token: the JWT carries only the e-mail address, so a revoked role takes effect on the next request. Second, the UI session is a stateless, HMAC-signed HttpOnly cookie (`email|expiry|signature`) from which the CSRF token is derived, so rotating a session rotates its CSRF token with it and there is no session store to operate.




Figure 6. Gatekeepers in request order

4.2 A request, end to end




Figure 7. Server-rendered request with htmx (admin action)

The public side follows the same shape without a session: registration, form submission and chatbot posts are rate-limited instead of CSRF-gated, and the total of an activity registration is always recomputed on the server before it is shown or stored.

4.3 Money: online payment and the untrusted webhook




Figure 8. Online registration, Mollie webhook and reconciliation

The rule *never trust the webhook body* is written into the repository's instructions as a security invariant and covered by a regression test that posts a forged `status=paid&amount=999` and asserts the record stays pending. in production

4.4 Roles and how a user reaches their work

One login flow serves everyone: an e-mail address receives a magic link and a six-digit code; the code is stored hashed with a pepper, one live code per address, five attempts, fifteen minutes. Whether the address belongs to a back-office user or to a member is decided per request, not at login. After login the platform routes the person to their work: administrators land on the workbench, a treasurer on the payments screen, a member in the household portal.




Figure 9. Login and role-based routing

Table 3 — Role matrix (verified against `auth/session.py` and `auth/service.py`)

Capability	Anonymous	Member	FINANCE	ADMIN	OPERATOR
Public site, registration, forms, chatbot (rate-limited)	yes	yes	yes	yes	yes
Household portal (own household only)	—	yes	—	—	—
General back office (members, activities, CMS, forms, media)	—	—	—	yes	yes
View and export payments	—	—	yes	yes	yes
Confirm, refund, edit, void payments	—	—	yes	no	yes
Manage users and roles	—	—	—	yes	yes
Tenants and per-tenant settings	—	—	—	no	yes

The treasurer's separation is enforced by a single function called on all seven mutating payment routes, and by the JSON API in the same way. The ADMIN-only user management deliberately does not accept OPERATOR-widening, so a FINANCE account cannot escalate itself. [v2.0.0 · HDEV](#)

4.5 The workbench: management by exception

Human work is an exception or a decision, and it lands in one place. Six task kinds exist today, raised by events or by an hourly sweep: a message to handle, a refund to confirm, a payment whose gateway state disagrees with the ledger, an orphaned payment record, a mail that failed after retries, and any other job

that failed for good. The sweep is idempotent on the task title and closes tasks whose cause disappeared, but only for the kinds it created itself. Tasks are filtered by required role and refreshed by polling.

v2.0.0 · HDEV

5. Multi-tenancy and security in detail

5.1 Tenant model and resolution




Figure 10. Tenant hierarchy and per-request resolution

Data. A TenantMixin adds `tenant_id` NOT NULL with an index and a default taken from the request context; migration 086 backfilled 41 tables. The filter is applied by an ORM event listener with `with_loader_criteria`, the same recipe as the soft-delete filter, so relationship lazy-loads are covered and no query can forget the clause. Row-level security in PostgreSQL is prepared for (non-null, indexed) but not enabled. v2.0.0 · HDEV

Configuration and secrets. `kernel_tenant_settings` holds 25 known keys per tenant (display name, base URL, social links, language, membership prices and dates, payment IBAN, mail settings, analytics, limits) and two secrets, the Mollie API key and the mail app password, encrypted with Fernet using a key derived from `SECRET_KEY`. Secrets are never rendered back; an empty field means unchanged. Infrastructure secrets stay in `.env` because they are not tenant-scoped. One deliberate safety rule: outside production, the environment's `FRONTEND_URL` always beats a tenant's stored base URL, so a production database restored into a test environment cannot send real payment redirects. v2.0.0 · HDEV

What is shared by design. Back-office identity (`auth.users`, roles, API keys, login tokens), the organisation table itself, postal codes and code tables carry no tenant. A user is a platform account granted roles; which tenant they act in is decided by the request.

5.2 Honest gaps in the tenancy story

An architect will find these, so they are listed here rather than discovered later.

- **Background jobs run tenant-less.** The job table has no `tenant_id`; the hourly sweep and the orphan reconciler scan all tenants and file their tasks under the default tenant. Correct for one paying tenant, wrong for two. Roadmap item R3.
- **OPERATOR widens roles, not scope.** The `include_all_tenants` escape hatch exists but has no call site; cross-tenant reach exists only for the unfiltered organisation and settings tables. The role document overstates this; the code is the truth.
- **The tenant filter is ORM-only.** Raw SQL, such as the OGM sequence call, bypasses it. Row-level security would close that; it is a migration away.
- **Rate limiters are in-memory per process.** The startup script refuses more than one uvicorn worker for that reason. Horizontal scaling needs a shared store.

5.3 Security controls

Table 4 — Controls and where they live

Control	Implementation	Status
Startup refuses weak config	<code>config.py</code> validator: weak/short <code>SECRET_KEY</code> , <code>DEBUG</code> , <code>SQL_ECHO</code> raise in uat/prod	in production
No API docs in production	<code>/docs</code> , <code>/redoc</code> , <code>/openapi.json</code> return 404 in uat/prod, tested	in production
Session and CSRF	HMAC-signed HttpOnly cookie, <code>secure</code> in uat/prod, 12 h; CSRF = HMAC over the session value, constant-time compare, four failure reasons logged, token never logged	v2.0.0 · HDEV

Control	Implementation	Status
OTP hardening	hashed with pepper, one live code, 5 attempts, generic errors, no account enumeration	in production
Financial separation	<code>require_finance_mutation</code> on every mutating payment route; ADMIN reads only	v2.0.0 · HDEV
Webhook integrity	re-fetch from Mollie, amount and currency check, <code>needs_review</code> on mismatch, row lock, idempotent	in production
IDOR on the household portal	<code>_assert_in_household</code> on every person mutation, tested with 403	in production
Output sanitisation	Jinja <code>autoescape=True</code> guarded by a lint rule; nh3 allow-lists, stricter for LLM output than for CMS	v2.0.0 · HDEV
Logging hygiene	allow-list of extra fields; no query strings, bodies or tokens; SQL logger pinned to WARNING	v2.0.0 · HDEV
Secrets in the repository	none; <code>.env.*.example</code> only; a read-only agent screens diffs and issues for leaks before every push	in production
Dependency audit	<code>pip-audit</code> on every push, reporting but never silent (annotations + job summary); whether a finding blocks is a human decision	v2.0.0 · HDEV
Formula injection in exports	ODS cells typed as strings, never CSV	in production

Known weaknesses, in the open: the CSP still allows `unsafe-inline` and `unsafe-eval` for scripts, and its comment still cites the removed React stack as the primary defence; history tables are append-only by convention (every writer only inserts) but not by database grant; the API-key mechanism is implemented and manageable but no endpoint consumes it yet. All three are roadmap items in Chapter 9.

6. Development process: how an AI agent works inside the gates

6.1 The loop

The working model is written down in the repository's `CLAUDE.md` and enforced by CI. Three rules from it, verbatim:

Every deployable code change goes through an issue. No "drive-by" commits without an issue.

A test must be able to go red. Ask for every new test: would it also be green if the subject were broken? If so, it proves nothing, and that is worse than no test, because it suggests protection that is not there.

For a gate or a guard that question is not enough: prove it. Make one violation, check that it fails with the intended message, restore it, and note in the docstring what you broke.




Figure 11. Issue to production: the self-correcting loop

The agent is autonomous *inside* a release: implement, test, get CI green, merge, close the issue with a "how to test on HDEV" comment, update the release tracker. Exactly three steps stop for a human: the UAT deploy, a change to the shared proxy, and the production deploy. Every closed issue carries the CI run id, the test count and the audit outcome as evidence; the release tracker is the single source of truth for what ships and how.

6.2 Test layers




Figure 12. Test layers and what each one catches

Two design choices explain the shape. First, every test session drops the thirteen schemas and rebuilds them through all 92 migrations against a real PostgreSQL 16, so the migration chain is exercised on every run. Second, gates use an *allowlist-to-zero* pattern: when a rule is introduced, the current violators are listed explicitly with a reason; every fix removes a line; when the list is empty the rule is absolute and adding an exception is a visible diff. On master every such list is empty.

6.3 What the gates caught

The gates exist because of specific failures, and the failures are documented in the tests themselves.

- **The escaping class.** Three times an htmx attribute was HTML-escaped and a button silently did nothing while all endpoint tests passed. Answer: the render-gate over the *rendered* HTML of every admin page, a shared money-invariant helper, and browser flows on the admin screens.

- **Green by looking nowhere.** Fourteen gate functions scanned files without asserting they found any. Answer: a meta-gate that fails when a gate's file set is empty, and a rule in the working instructions.
- **Green while undeployable.** A renamed module passed CI and failed only in the Docker build. Answer: the real `startup.sh` boots in CI against an empty database and the import check derives its module list from the package.
- **The typo that rendered blank.** Jinja renders an unknown variable as an empty string. Answer: `StrictUndefined` outside production, typed view-models, and a gate that compares each template's variables with its view-model's fields. Its first run found five real gaps, including role checkboxes that had silently disappeared from a form.

6.4 Two read-only agents

Judgment that regexes cannot express is delegated to two agents defined in the repository. The *design-conformity guard* reviews templates and UI modules against the design system on three axes (mechanical rules are left to the gate; patterns, and since v2.0.0 the layering of Python UI modules) and reports findings with a proposed issue title; it changes nothing. The *public-repository guard* screens every diff and every issue text for secrets, real hosts, credentials and personal data, because the repository and its issue tracker are public. Both are on-request and produce reports, not commits.

7. AI in the solution, today and next

7.1 What runs today

- **Raakje, the chatbot** [PROD, dark-launched by `CHAT_ENABLED`]. Context stuffing rather than retrieval: the data volume is small, so published pages, notes and aggregates go straight into the system prompt with a hard character limit. The security boundary is the tool list: three functions, no member data, no payments, no admin; an unknown tool name is refused; empty values are rendered as the literal *not stated* to suppress invention. Output passes through a markdown-to-HTML step and a sanitiser stricter than the CMS one. Per-IP rate limit and a daily character budget shared between the JSON route and the widget.
- **Document extraction** `v2.0.0 · HDEV`. A poster or component document is read through its PDF text layer first (free) and only sent to OCR when that yields too little; the result is cleaned and stored next to the asset, where an administrator can override or extend it. Runs as a background task after upload; an explicit *read again* action exists.
- **Speech-to-text** [HDEV, dark-launched by `STT_MODE`]. A WebSocket proxy to Voxtral realtime so the key never reaches the browser, with a per-IP handshake limit, a daily audio budget, idle and size limits, and a browser-native fallback. Text-to-speech is browser-only and sends nothing anywhere.
- **Provider seams**. Chat, OCR and STT each sit behind an abstraction with a deterministic mock, so CI runs without keys and a provider can be swapped without touching a domain. Mail and payments follow the same pattern for Mollie; mail does not yet.




Figure 13. AI features and their boundaries - orange is Mistral (EU), mocked in CI

7.2 Extensibility: the mailing engine for member recruitment roadmap

The design for AI-assisted recruitment and communication exists (working document §23) and reuses only components that are already there. It starts with consent as data in MDM (opt-in per capture, scope and source recorded, a suppression list every send passes), then segments as saved queries rather than copied lists (members, first-time participants, lapsed members, interest profiles from participation history), then an AI-drafted newsletter that appears as a *decision task* in the workbench: a human edits and approves, the mail domain sends and logs, nothing generated leaves unread. Lifecycle flows (thank-you after participation, first-time participant to membership, renewal reminder, win-back) become workflow definitions with a kill switch each, measured in-house. None of it is in code today; the consent model is the first brick, and it is small.

8. From association to enterprise: the same building blocks

The platform was built for a community, but the blocks were chosen for what they become: the foundation of a multi-tenant ERP that I-X IT Solutions develops further for distribution, warehousing, production and web-shop companies. Table 5 names, per block, what exists in code today, its enterprise counterpart and the gap in code terms, so that the distance is sized rather than assumed; the figure that follows shows the same mapping.

Table 5 — What each block does today and what it would take

Block	Today, in code	Enterprise counterpart	Gap
Master data	persons, households, organisation tree, typed contacts, addresses via lookup, merge/unmerge, history	customers, suppliers, sites, contacts	entity types and roles on the organisation tree; same patterns
Orders	activity → component → product → registration → order line, server-computed totals, member pricing	catalogue, price lists, sales and purchase orders	quantities on stock, units of measure, price-list dimension
Ledger	charge/refund records, polymorphic payable, reconciliation invariant, structured communication, Mollie	invoices, credit notes, open items, payment matching	document numbering, VAT, bank-statement import; the invariant already fits
Forms	builder, branching, wizard, statistics, ODS, AI format guide	intake, inspection, quality and return forms	attach a form to any subject via the existing soft-reference
Workflow	tasks by role, step definitions as data, sweep that opens and closes by state	approvals, exceptions, SLA queues	definitions editor, deadlines, escalation
Tenancy and roles	account/unit tree, row-level filter, per-tenant config and secrets, role-derived capabilities	one instance per group, units per company	tenant-aware background jobs, RLS, SSO
AI	context-stuffed assistant with tool boundary, OCR, speech	document intake, voice order entry, assistant over orders	retrieval over larger corpora; the tool boundary pattern carries over
Forecasting and planning	not present	demand forecasting, reorder proposals as workbench tasks	a read model over order lines; the exception-as-task delivery already exists

The honest conclusion: the *shape* transfers, the *volume* does not yet. Nothing in the codebase has been load-tested beyond an association's traffic, media is stored in the database, and the rate limiter is per process. Those are known, sized items, not surprises.




Figure 14. Building blocks today and their enterprise counterparts

9. Way forward

The roadmap has two horizons. R0 to R5 finish the platform as it runs for the first tenant; R6 to R9 are the first steps toward the enterprise use of Chapter 8. Everything is grouped by what it unlocks, and each item carries its status in the same vocabulary as the rest of the document.

Table 6 — Roadmap, grouped by what it unlocks

#	Item	Why	Status
R0	v2.0.0 cutover — server-rendered UI, modular domains, multi-tenancy, gates	277 commits validated on HDEV; production still runs the React build of 13 July	v2.0.0 · HDEV , release pending: env vars per host, Caddy expand/contract, memory headroom on the host, tag
R1	Contract step for the shared proxy (v2.0.1) and removal of the deploy wrappers	closes the expand/contract cycle of the cutover	designed / partial
R2	Security audit against the code that actually runs (v2.1)	CSP without <code>unsafe-inline/unsafe-eval</code> ; append-only history by grant; wire or remove the API-key mechanism; shared rate-limit store	roadmap , issue exists
R3	Tenant-aware background jobs and the OPERATOR cross-tenant view	the two real gaps in the tenancy story (5.2)	roadmap
R4	Row-level security in PostgreSQL as the second line behind the ORM filter	prepared for since migration 086; one migration plus a session variable	roadmap
R5	Remaining view-model conversions (14 modules) and facade clean-up (<code>activities</code> , <code>forms</code> still delegate into routers)	finishes principle 2.2 for every screen	designed / partial , gated by allowlists
R6	Consent register in MDM, then segments, then the AI-drafted newsletter with workbench review	the recruitment engine of 7.2; consent first, by law and by design	roadmap
R7	Transactional outbox for events; component extraction where a driver appears (STT first)	today's events are synchronous and in-transaction by design; extraction is a deployable decision, not a code decision	roadmap
R8	Object storage adapter for media	blobs live in Postgres today; the adapter seam is named in the media facade	roadmap
R9	PWA manifest and service worker	designed in the frontend decision, not started	roadmap

What is deliberately *not* on the list: a return to a JavaScript frontend. The decision record in the working document weighed React against server-rendered htmx along eleven dimensions and chose one language for one architect plus agents; the v2.0.0 validation confirmed that the feel of the interface is a matter of polish (navigation without reload, feedback on every action, server latency under 150 ms on every admin route), not of framework.

Appendix A — Documentation versus code

The working document `docs/intermediate-architecture-upgrade-v1.md` (July 2026) was compared claim by claim with `master`. This is the condensed result; it is the list a reviewer should use to calibrate the rest of this document.

Table A1 — Claims in the working document

Claim	Verdict	Evidence on master
Package-by-domain with <code>api.py</code> as the only door	in code	13 packages; import-boundary test with an empty allowlist
Import linter enforcing the boundary	in code, as a pytest	<code>tests/test_import_boundaries.py</code> ; no third-party tool
Own Postgres schema per component, one Alembic chain	in code	11 schemas, 92 migrations, one head
<code>CONTRACT.md</code> per component	partial	11 of 13; missing for <code>audit</code> and <code>stt</code>
Per-component <code>tests/</code> and <code>seeds.py</code>	not in code	tests are central; seeds are top-level scripts
OpenAPI export with a drift gate (§19.4)	not in code	the opposite exists: docs are hidden in <code>uat/prod</code>
Synchronous in-transaction events (ladder rung 1)	in code	<code>kernel/events.py</code> , four contracts
Transactional outbox (rung 2)	not in code, deferred by design	documented in <code>kernel/events.py</code>
Job primitive with retry and locking	in code	<code>kernel/jobs.py</code> : <code>FOR UPDATE SKIP LOCKED</code> , backoff, savepoint isolation
MDM merge and survivorship	in code	<code>mdm/service.py</code> : <code>merge</code> , <code>flattened resolve</code> , <code>unmerge</code> , <code>EntityMerged</code>
Tombstones as a distinct concept	not as such	soft delete plus survivorship pointer cover the intent
Row-level tenancy, RLS-ready	in code; RLS not enabled	<code>kernel/tenancy.py</code> , migration 086
Per-tenant config in the database	in code	<code>kernel/tenant_config.py</code> , migration 087
Contract tests with schema-validated stubs as a distinct layer	not in code	covered by boundary tests and component tests instead
<code>alembic check drift gate</code>	not in code	—
Record-centric navigation (§20)	partial	the records-list pattern is real and gated; generated relation navigation is not
Workbench, zero-touch, management by exception	in code, v1 scope	six task kinds; not all proto-queues consolidated
BPMN/DMN vocabulary and export	partial	step definitions as data; no editor, no XML
PWA	not in code	—

Claim	Verdict	Evidence on master
AI-assisted recruitment (§23)	not in code	no consent model, segments or newsletter; the LLM adapter it would reuse exists
"Three services" end state	true for UAT; prod has five (two backup sidecars)	the frontend container is gone everywhere
Analytics read-model component	not in code	Umami configuration only
<code>search()</code> on every facade	not in code	search is per screen
Security batch: non-root, OTP hash, strict CSP, blocking audit	partial	non-root and OTP hashing done; CSP still permissive; audit reporting by choice
<code>mistralai</code> SDK replaced by plain <code>httpx</code>	half	chat and OCR use <code>httpx</code> ; STT still pins the SDK

Table A2 — What the code does that the documents do not say

Finding	Where
Some facades delegate back into routers; the layer gate imports facades at runtime to catch screens pulling those functions out	<code>activities/api.py</code> , <code>forms/api.py</code> , <code>test_layer_gate.py</code>
Authentication is platform-wide, not tenant-scoped, by design	<code>auth/models.py</code>
<code>Form.requires_login</code> is stored and editable but enforced nowhere	<code>forms/router.py</code> , <code>forms/service.py</code>
Extracted document text reaches the chatbot only through tools, never the system prompt; a keyword list forces a tool call on the first round	<code>chatbot/context.py</code> , <code>chatbot/tools.py</code> , <code>chatbot/service.py</code>
Refunds are pending obligations that pre-empt the hourly sweep; the sweep closes only the task kinds it created	<code>payment/service.py</code> , <code>workflow/handlers.py</code>
Outside production the environment URL beats a tenant's stored base URL, so a restored production database cannot leak real redirects	<code>kernel/tenant_config.py</code>
The hosting provider is named in the README and the specification; no hosts or addresses are	<code>README.md</code> , <code>docs/spec.md</code>

Stale documents. The README still describes a Next.js frontend, `docs/umami.md` still references a React component, and `docs/rollen-en-rechten.md` points at two files that no longer exist and overstates OPERATOR's cross-tenant reach. The instructions to *check parity against the tag, never a loose commit* were added after exactly that mistake.

Appendix B — Evidence index

Topic	Files
Working instructions and release process	CLAUDE.md
Kernel	backend/app/kernel/{tenancy,tenant_config,events,jobs,history,ordering,ods}.py, kernel/contracts/
Gatekeepers	backend/app/main.py, app/limiter.py, app/soft_delete.py, domains/auth/{session,service,login}.py, caddy/parts/snippets.caddy
Ledger and Mollie	domains/payment/{service,gateway_service,gateway_router,structured_communication,exports}.py, providers/{base,mollie}.py
Master data	domains/mdm/{models,service,tenant_service,import_service}.py, domains/audit/{service,changes}.py
Form engine	domains/forms/{models,service,results,export,ui}.py, app/static/form-json-formaat.md
AI	domains/chatbot/{context,tools,service,render}.py, chatbot/providers/, domains/media/extraction.py, domains/stt/
Gates	backend/tests/test_{import_boundaries,schema_boundaries,layer_gate,template_variables_gate,ui_conventions_gate,gate_niet_leeg,payable_delete_gate,query_budget,render_gate,docs_gating,i18n_gate}.py
Browser flows and seed	backend/tests_e2e/, backend/seed_e2e.py
CI and deployment	.github/workflows/backend-tests.yml, deploy.sh, deploy-caddy.sh, raakctl, backend/startup.sh, backend/Dockerfile, docker-compose.*.yml
Agents	.claude/agents/design-conformiteit-bewaker.md, .claude/agents/publieke-repo-bewaker.md
Design system and conventions	docs/design-system.html, docs/ui-conventies.md, docs/ui-conformiteit.md, docs/rollen-en-rechten.md
Decision record on the frontend	docs/intermediate-architecture-upgrade-v1.md §21

Gespreksleidraad

Kernboodschap. Dit zijn de fundamenteën van een enterprise-ready, multi-tenant ERP, en ze draaien vandaag al in productie. Ik bouw bedrijfssoftware met een klein team dat AI-agents aanstuurt, en ik kan dat bewijzen met een product dat geld, persoonsgegevens en meerdere tenants aankan, gebouwd in drie maanden, met een kwaliteitslaag die de meeste bedrijven pas na jaren hebben. I-X IT Solutions ontwikkelt dit platform verder.

Waarom dit meer is dan een verenigingssite. De functionaliteit is klein, de structuur is die van een ERP: dertien domeinpakketten achter facades met elk een eigen schema, masterdata met merge en historiek, een betaal grootboek met één reconciliatie-invariant, rijniveau-multitenancy vanuit de kernel, een werkbank die elke uitzondering een taak maakt. Hetzelfde skelet draagt morgen orders, facturen en een magazijn.

Bewijspunten (allemaal in de code, zie bijlage B).

1. 1.343 tests tegen een echte PostgreSQL, twaalf gate-bestanden, vier blokkerende CI-jobs, coverage-drempel 85 %.
2. Achttien gatekeepers tussen request en rij; de penningmeester kan betalingen wijzigen, de beheerder niet; de Mollie-webhook wordt nooit vertrouwd.
3. Multitenancy als kernel-mixin plus globaal ORM-filter; tweede tenant is configuratie, geen code.
4. AI in beide richtingen: gebouwd mét agents binnen de gates, en AI ín het product (chatbot met toolgrens, OCR, spraak), alles Europees en dark-launched.
5. Eerlijkheid als methode: het document noemt zijn eigen gaten (achtergrondjobs zonder tenant, CSP, API-keys zonder consument) en de tests bewijzen dat een test rood kán worden.

Hoe ik werk met AI-agents. Elke wijziging start bij een issue. De agent implementeert op een feature branch, de gates zijn zijn feedback, CI is zijn reviewer, en ik valideer op HDEV wat CI niet kan zien. Drie stappen stoppen voor een mens: UAT, de gedeelde proxy, PROD. Twee leesagenten bewaken design-conformiteit en de publieke repo. Wat de agent fout deed, werd een gate; zo groeit de kwaliteit met elke fout.

Wat ik zoek in dit gesprek. Een klankbord op twee vragen: welke van deze bouwstenen zijn voor een bedrijf het meest waard als startpunt, en welke ontbrekende schakel (SSO, RLS, objectopslag, load) zou u als eerste willen zien voordat u dit in een organisatie zou vertrouwen?

I-X IT Solutions. AI-first softwarebedrijf in oprichting: kleine teams die agents aansturen, met kwaliteit als infrastructuur. Referentie: deze repository. Contact: *[link en contactgegevens I-X invullen]*.