Chapter IV

Exercise 00 : ft_ft

	Exercise 00
ft_ft	
Turn-in directory: $ex00/$	
Files to turn in: `ft_ft.c`	
Allowed functions: `None`	

- Create a function that takes a pointer to an int as a parameter and sets the value of that int to "42".
- The function should be prototyped as follows:

```
void        ft_ft(int *nbr);
```

Chapter V

Exercise 01 : ft_ultimate_ft

	Exercise 01
ft_ultimate_ft	
Turn-in directory: $ex01/$	
Files to turn in: `ft_ultimate_ft.c`	
Allowed functions: `None`	

- Create a function that takes a pointer to a pointer to a pointer to a pointer to a pointer to a pointer to a pointer to a pointer to a pointer to an int as a parameter and sets the value of that int to "42".
- The function should be prototyped as follows:

```
void        ft_ultimate_ft(int *********nbr);
```

Chapter VI

Exercise 02 : ft_swap

	Exercise 02
ft_swap	
Turn-in directory: $ex02/$	
Files to turn in: `ft_swap.c`	
Allowed functions: `None`	

- Create a function that swaps the values of two integers using their addresses received as parameters.
- The function should be prototyped as follows:

```
void    ft_swap(int *a, int *b);
```

Chapter VII

Exercise 03 : ft_div_mod

	Exercise 03
ft_div_mod	
Turn-in directory: *ex*03/	
Files to turn in: `ft_div_mod.c`	
Allowed functions: `None`	

- Create a function **ft_div_mod** with the following prototype:

```
void    ft_div_mod(int a, int b, int *div, int *mod);
```

- This function divides '`a`' by '`b`' and stores the result in the integer pointed to by '`div`'. It also stores the remainder of the division of '`a`' by '`b`' in the integer pointed to by '`mod`'.

Chapter VIII

Exercise 04 : ft_ultimate_div_mod

	Exercise 04
ft_ultimate_div_mod	
Turn-in directory: *ex*04/	
Files to turn in: `ft_ultimate_div_mod.c`	
Allowed functions: `None`	

- Create a function **ft_ultimate_div_mod** with the following prototype:

```
void    ft_ultimate_div_mod(int *a, int *b);
```

- This function divides the value pointed to by '`a`' by the value pointed to by '`b`'. The result of the division is stored in the integer pointed to by '`a`', while the remainder is stored in the integer pointed to by '`b`'.

Chapter IX

Exercise 05 : ft_putstr

	Exercise 05
ft_putstr	
Turn-in directory: $ex05/$	
Files to turn in: `ft_putstr.c`	
Allowed functions: `write`	

- Create a function that displays a string of characters on the standard output.
- The function should be prototyped as follows:

```
void    ft_putstr(char *str);
```

Chapter X

Exercise 06 : ft_strlen

	Exercise 06
	ft_strlen
Turn-in directory: *ex06/*	
Files to turn in: `ft_strlen.c`	
Allowed functions: `None`	

- Create a function that counts and returns the number of characters in a string.
- The function should be prototyped as follows:

```
int        ft_strlen(char *str);
```

Chapter XI

Exercise 07 : ft_rev_int_tab

	Exercise 07
ft_rev_int_tab	
Turn-in directory: *ex*07/	
Files to turn in: `ft_rev_int_tab.c`	
Allowed functions: `None`	

- Create a function that reverses a given array of integers (the first element becomes the last, and so on).
- The function takes two arguments: a pointer to an int and the number of elements in the array.
- The function should be prototyped as follows:

```
void    ft_rev_int_tab(int *tab, int size);
```

Chapter XII

Exercise 08 : ft_sort_int_tab

	Exercise 08
	ft_sort_int_tab
Turn-in directory: *ex*08/	
Files to turn in: `ft_sort_int_tab.c`	
Allowed functions: `None`	

- Create a function that sorts an array of integers in ascending order.
- The function takes two arguments: a pointer to an int and the number of elements in the array.
- The function should be prototyped as follows:

```
void    ft_sort_int_tab(int *tab, int size);
```