Chapter IV

Exercise 00 : ft_strcmp

	Exercise 00
	ft_strcmp
Turn-in directory: *ex*00/	
Files to turn in: `ft_strcmp.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strcmp` (man strcmp).
- The function should be prototyped as follows:

```
int        ft_strcmp(char *s1, char *s2);
```

Chapter V

Exercise 01 : ft_strncmp

	Exercise 01
ft_strncmp	
Turn-in directory: *ex*01/	
Files to turn in: `ft_strncmp.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strncmp` (man strncmp).
- The function should be prototyped as follows:

```
int        ft_strncmp(char *s1, char *s2, unsigned int n);
```

Chapter VI

Exercise 02 : ft_strcat

	Exercise 02
ft_strcat	
Turn-in directory: $ex02/$	
Files to turn in: `ft_strcat.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strcat` (man strcat).
- The function should be prototyped as follows:

```
char *ft_strcat(char *dest, char *src);
```

Chapter VII

Exercise 03 : ft_strncat

	Exercise 03
ft_strncat	
Turn-in directory: $ex03/$	
Files to turn in: `ft_strncat.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strncat` (man strncat).
- The function should be prototyped as follows:

```
char *ft_strncat(char *dest, char *src, unsigned int nb);
```

Chapter VIII

Exercise 04 : ft_strstr

	Exercise 04
	ft_strstr
Turn-in directory: *ex*04/	
Files to turn in: `ft_strstr.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strstr` (man strstr).
- The function should be prototyped as follows:

```
char        *ft_strstr(char *str, char *to_find);
```

Chapter IX

Exercise 05 : ft_strlcat

	Exercise 05
ft_strlcat	
Turn-in directory: $ex05/$	
Files to turn in: `ft_strlcat.c`	
Allowed functions: `None`	

- Reproduce the behavior of the function `strlcat` (man strlcat).
- The function should be prototyped as follows:

```
unsigned int ft_strlcat(char *dest, char *src, unsigned int size);
```