Chapter IV

Exercise 00 : ft_print_program_name

	Exercise 00
ft_print_program_name	
Turn-in directory: $ex00/$	
Files to turn in: `ft_print_program_name.c`	
Allowed functions: `write`	

- Since this is a program, your `.c` file must contain a `main` function.
- Write a program that displays its own name, followed by a new line.
- Example:

```
$>./a.out | cat -e
./a.out$
$>
```

Chapter V

Exercise 01 : ft_print_params

	Exercise 01
	ft_print_params
Turn-in directory: $ex01/$	
Files to turn in: `ft_print_params.c`	
Allowed functions: `write`	

- Since this is a program, your `.c` file must contain a `main` function.
- Write a program that displays its given arguments.
- Each argument should be printed on a new line, in the same order as in the command line.
- The program should display all arguments except `argv[0]`.
- Example:

```
$>./a.out test1 test2 test3 | cat -e
test1$
test2$
test3$
$>
```

Chapter VI

Exercise 02 : ft_rev_params

	Exercise 02
ft_rev_params	
Turn-in directory: $ex02/$	
Files to turn in: `ft_rev_params.c`	
Allowed functions: `write`	

- Since this is a program, your `.c` file must contain a `main` function.
- Write a program that displays its given arguments.
- Each argument should be printed on a new line, in the reverse order from the command line.
- The program should display all arguments except `argv[0]`.

Chapter VII

Exercise 03 : ft_sort_params

	Exercise 03
ft_sort_params	
Turn-in directory: $ex03/$	
Files to turn in: `ft_sort_params.c`	
Allowed functions: `write`	

- Since this is a program, your `.c` file must contain a `main` function.
- Write a program that displays its given arguments sorted in ASCII order.
- The program should display all arguments except `argv[0]`.
- Each argument should be printed on a new line.