
Understanding graph representation learning in reinforcement learning based logic synthesis

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Computer chips ought to be as small as possible for cost efficiency. The problem
2 of minimizing chip size while preserving the chip’s functionality has been studied
3 through the prism of and-inverter graphs (AIGs), since any Boolean function can
4 be represented by an AIG. Because the complexity of AIG size minimization is
5 unknown—it is an instance of the Minimum Circuit Size Problem, which lies
6 in NP but is not known to be NP-hard—no procedure returns optimal AIGs at
7 the sizes of interest, and there is therefore no supervision signal in the form of
8 optimal AIGs to imitate. Reinforcement learning, and more generally planning,
9 have been used to optimize AIGs in the absence of such a signal. Contemporarily,
10 graph representation learning has been applied to train machine learning models
11 to perform tasks on graph data. More recently, those two technologies have been
12 combined and reported to outperform state-of-the-art logic synthesis heuristics, but
13 the relative importance of graph representation learning in those methods remains
14 unknown. Is graph representation learning useful when optimizing and-inverter
15 graphs with reinforcement learning?

16 1 Introduction

17 A circuit that computes a given Boolean function with fewer logic gates occupies less area and is
18 cheaper to manufacture [30]. Given a Boolean function, logic synthesis methods [7, 31, 23] are used
19 to find a small circuit that computes it. Because every Boolean function can be represented with
20 AND and NOT gates only, logic synthesis methods represent circuits with and-inverter graphs (AIGs)
21 which nodes are AND gates and edges can invert incoming bits.

22 However, finding the smallest AIG encoding a given Boolean function is an open problem. It is an
23 instance of the Minimum Circuit Size Problem, which lies in NP but is not known to be NP-hard [15],
24 and which is related to Graph Isomorphism [2]. In practice, AIGs are reduced by applying sequences
25 of heuristics that rewrite the graph while preserving functional equivalence. Many such heuristics are
26 implemented in the ABC [5] software. Choosing the best heuristics sequence is a search problem.

27 In the absence of exact solvers, machine learning, such as supervised learning, has been applied to
28 AIG minimization [38]. However it suffered from two major weaknesses: first, the supervision signal
29 to train from could be a suboptimal AIG since no exact solver exists, and second, graphs generative
30 models are still quite limited [38]. Successful machine learning approaches are unsupervised ones
31 that only require a scalar signal, often the size of a given AIG which is cheap to obtain: Bayesian
32 optimization [11], multi-armed bandits [29], reinforcement learning (RL) [14, 48] and Monte Carlo
33 tree search [32]. Contemporarily, graph representation learning has been applied to train models
34 on graph data, and circuits are graphs: task-agnostic encoders built specifically for AIGs are now
35 available [18, 21, 46, 47]. The two lines of work have since been combined. Several of the methods
36 above encode the current AIG with a graph neural network rather than with a fixed set of summary

statistics [48, 32, 3], and achieve reductions beyond the expert ABC heuristics. The motivation is the same as the one behind the very first deep RL algorithm, which was designed specifically for Backgammon [40]: the state space of AIG minimization is huge and cannot be enumerated, so the value of a state has to be generalized from other states. A learned representation of the circuit should carry structural information that statistics discard, and that is what should allow a deep reinforcement learning algorithm [36] to generalize to unseen circuits: “I have seen a similar graph before, I should probably edit the AIG in a similar way to get good results”.

What those RL methods do not report is how much of their performance is attributable to the learned representation design. We are not aware of a study that isolates the contribution of the AIG encoder to RL training. Our work reports such an ablation, in the fixed-horizon setting that Zhu et al. [48] introduced and that later work reuses. We keep that pipeline fixed—the Markov decision process, the policy and value heads, the training algorithm and the hyper-parameter grid—and vary only how the AIG is presented to the policy. We show the following results.

Contributions: First, we show that adding a graph convolutional network to the policy does not improve AIG reduction beyond a multi-layer perceptron that reads graph statistics (number of nodes, of levels, ...). Second, we give a candidate explanation: we compute, for AIG value prediction, the best error achievable by any model whose separating power is bounded by the 1-dimensional Weisfeiler-Leman refinement—which covers message passing networks—and find it no better than the one achievable from the graph statistics alone. Next, we present existing AIG minimization methods.

2 Related work

2.1 Combinational optimization

Combinational synthesis is a class of fast heuristics that reduce an AIG by rewriting it locally, and that work well in practice [23, 24, 7]. ABC [5] is the reference implementation and is widely used both in industry and academia. Throughout this paper we call *primitives* its standard local transformations, `balance`, `rewrite`, `resub` and `refactor`, and *heuristics* the named sequences of primitives it ships, such as `resyn2`. Since no primitive is globally optimal, reduction is done by composing them into heuristics. Hand-designed heuristics are the reference points against which learned methods are measured: `resyn` [31] applies `balance`, `rewrite`, `balance`, `rewrite`, `balance`. Searching over sequences of primitives has been automated without learned circuit representations, with Bayesian optimization [11] and with multi-armed bandits [29].

2.2 Graph representation learning for AIGs

A separate line of work learns representations of circuits that are meant to transfer across circuits, rather than a policy for one circuit. DeepGate4 [47] is a foundation model that learns node embeddings of AIGs, supposedly useful for various downstream tasks on AIGs. Three encoders from this line—DeepGate [18], PolarGate [21] and FuncGNN [46]—are among the models we evaluate in section 7. GraphBench [38] is, to our knowledge, the first AIG reduction benchmark built for methods that must perform on unseen AIGs. It provides a training set of Boolean functions of varying input and output dimension and a disjoint test set, and it reports node reduction relative to the expert ABC heuristic: `resyn2`, `resyn2`, `dc2`, `resyn2rs`, `resyn2`, applied in that order. Its main result is negative: given the AIG obtained by the naive construction from a truth table, specialized DAG generative models [6, 19] do not preserve functional equivalence while reducing size.

2.3 Reinforcement learning for AIGs

The works discussed in this section use similar AIG minimization formulations: the state observed by the trained policy is some representation of the AIG to minimize and the actions are ABC primitives (sec. 2.1).

Hosny et al. [14] formulate synthesis as an MDP whose states are vectors of AIG statistics—numbers of primary inputs and outputs, nodes, edges, levels and latches, and the proportions of AND and NOT nodes—whose actions are ABC primitives, and whose reward combines node count and level count.

Zhu et al. [48] keep ABC primitives as actions but encode the whole AIG with a graph convolutional network, alongside a small vector of statistics and recent actions, and reward the relative reduction in node count. Episodes there have a fixed horizon and no early stopping, so the induced problem is a search over flows of fixed length. This is the formulation we adopt, horizon included, and we state it in full in section 4. Both Hosny et al. [14] and Zhu et al. [48] train with policy gradient methods [39, 44, 27, 36]. We are not aware of a value-based [43, 26] treatment, even though AIG editing is deterministic. These methods report minimization performances beyond the ABC heuristics, but they are not designed to generalize: a policy is trained to reduce one AIG, so the training cost is paid again for every new circuit. Search-based methods lift that restriction. AlphaSyn [32] and AlphaChip [22] plan online and therefore apply to any circuits: every AIG edit choice requires a lookahead, and every lookahead step requires network forward passes. However we argue that the cost of retraining a model is cheap compared to the cost of producing unnecessarily big chips at scale. ABC-RL [3] sits in between: a policy pre-trained on other circuits guides the tree search, and its influence is scaled down when the circuit at hand is far from anything in the training set. Two further formulations widen the setting rather than the state: ESE [34] adds technology mapping operations to the action space and trains with PPO [36], and CB-EVO [20] drops the sequential state altogether and treats the choice of primitive as a contextual bandit whose context is a set of circuit features.

2.4 Graph reinforcement learning for other combinatorial optimization

AIG reduction is an instance of graph structure optimization in the taxonomy of Darvari et al. [8], who survey reinforcement learning applied to combinatorial problems on graphs and report that a graph neural network encoder is the common choice of state representation. Within chip design the same combination is used for transistor sizing [42] and for macro placement [22]; in both cases the encoder is motivated as the component that enables transfer to new circuits. Next, we formulate AIG minimization as a Markov decision problem.

3 Background material




Figure 1: A trajectory in a generic MDP for AIG reduction, on AIGs of the Boolean function $f(x_1, x_2, x_3) = (\bar{x}_1 \wedge x_2, x_2 \wedge x_3)$. Every method surveyed in section 2 acts at this granularity: each action is one ABC primitive applied to the whole graph, and the primitives of section 2.1 preserve functional equivalence by construction, so every state reachable from $\mathcal{G}_0$ still computes f .

3.1 And-inverter graphs minimization

Given an arbitrary Boolean function $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$, the objective is to find an and-inverter graph that encodes f with as few nodes as possible.

Section 3.2.1 from Stoll et al. [38] states that an and-inverter graph $\mathcal{G} := (V, E)$ is a directed acyclic graph of in-degree (fanin) at most two. The node set is partitioned into input nodes of in-degree 0, $V^{in} := \{v_1^{in}, \dots, v_n^{in}\}$, AND nodes of in-degree two, $V^{AND} := \{v_1^{AND}, \dots, v_k^{AND}\}$, and output nodes of in-degree one, $V^{out} := \{v_1^{out}, \dots, v_m^{out}\}$; AIGs are therefore heterogeneous graphs [37]. The edge set is $E \subseteq V \times V \times \{0, 1\}$, with 0 indicating direct transmission and 1 indicating input negation (NOT). For an input $x \in \{0, 1\}^n$, values are assigned to input nodes, propagated through gate nodes (applying inversion where specified), and collected at output nodes

121 to yield $\mathcal{G}(x) \in \{0, 1\}^m$. Because the combination of AND and NOT is functionally complete, any
 122 Boolean function can be represented using only these two operations.

123 We write $\mathcal{G}_f := \{\mathcal{G} : \mathcal{G}(x) = f(x) \forall x \in \{0, 1\}^n\}$ for the set of AIGs functionally equivalent to f .
 124 AIGs are non-canonical representations of Boolean functions [25]—two different AIGs can represent
 125 the same function—so $|\mathcal{G}_f| > 1$ in general: e.g. the graphs of figure 1 are functionally equivalent.
 126 Given a Boolean function $f : \{0, 1\}^n \rightarrow \{0, 1\}^m$, we want to find $\mathcal{G}^* \subseteq \arg \min_{\mathcal{G} \in \mathcal{G}_f} |V|$, the AIGs
 127 functionally equivalent to f with as few nodes as possible. The hardness of this problem is not known:
 128 it is an instance of the Minimum Circuit Size Problem [15], a well-studied problem in NP that is not
 129 known to be NP-hard¹.

130 3.2 Markov decision process

131 AIG minimization can be formulated as a sequential decision making task in which the environment is
 132 the current AIG, the actions are edits of that AIG, and the rewards are shaped to favor edits that remove
 133 nodes. Formally, this is the problem of finding an optimal policy for a Markov decision process
 134 (MDP) [4, 33]. An MDP is a tuple $\mathcal{M} = \langle S, A, R, T, T_0 \rangle$. S is a finite set of states representing all
 135 possible configurations of the environment (e.g. AIGs, or AIG statistics). A is a finite set of actions
 136 available to the agent (e.g. AIG edits). $R : S \times A \rightarrow \mathbb{R}$ is a deterministic reward function that assigns
 137 a real-valued reward to each state-action pair (e.g. number of deleted nodes). $T : S \times A \rightarrow \Delta(S)$ is
 138 the transition function that maps state-action pairs to probability distributions over next states $\Delta(S)$
 139 (e.g. how graph edits change the AIG; here the transitions are deterministic). $T_0 \in \Delta(S)$ is the initial
 140 distribution over states (e.g. a set of AIGs to reduce).

141 Given an MDP $\mathcal{M} \equiv \langle S, A, R, T, T_0 \rangle$, the goal of reinforcement learning is to find a
 142 policy $\pi : S \rightarrow A$ that maximizes the expected discounted sum of rewards $J(\pi) =$
 143 $\mathbb{E} [\sum_{t=0}^{\infty} \gamma^t R(s_t, \pi(s_t)) \mid s_0 \sim T_0, s_{t+1} \sim T(s_t, \pi(s_t))]$ where $0 < \gamma \leq 1$ is the discount factor that
 144 controls the trade-off between immediate and future rewards.

145 We write $V^*(s) = \mathbb{E} [\sum_{t=0}^{\infty} \gamma^t R(s_t, \pi(s_t)) \mid s_0 \sim s, s_{t+1} \sim T(s_t, \pi(s_t))]$ for the value of a state
 146 under an optimal policy, i.e. the discounted sum of rewards collected from s by acting optimally.
 147 V^* is the quantity a critic is trained to approximate in actor-critic methods, and the quantity a state
 148 representation must be able to distinguish states by; section 7 uses it to measure what a representation
 149 can express, independently of any training procedure.

150 3.3 Message passing neural networks

151 A message passing neural network (MPNN) [10] attaches a vector $h_v^{(0)}$ to each node v , initialized from
 152 that node’s features, and refines it over k rounds: $h_v^{(t+1)} = \phi^{(t)}(h_v^{(t)}, \bigoplus_{u \in \mathcal{N}(v)} \psi^{(t)}(h_v^{(t)}, h_u^{(t)}, e_{uv}))$,
 153 where $\mathcal{N}(v)$ are the neighbours of v , e_{uv} is an optional label on the edge between u and v , $\bigoplus$ is a
 154 permutation-invariant aggregator, and $\phi^{(t)}, \psi^{(t)}$ are learned. A graph-level vector is then obtained
 155 by pooling $\{h_v^{(k)}\}_{v \in V}$ with a second permutation-invariant readout. Architectures in this family
 156 differ only in the choice of ψ , $\bigoplus$ and ϕ : GCN [17], GIN [45], GAT [41] and GraphSAGE [13] are
 157 instances, and so are the AIG-specific encoders of appendix F. They also share a limitation. After
 158 k rounds, two nodes that k iterations of the 1-dimensional Weisfeiler-Leman refinement assign the
 159 same color carry the same embedding [45, 28, 1], so no network in the family can tell apart two AIGs
 160 that 1-WL cannot. Section 7.2 turns this into a lower bound on the error of every such encoder.

161 Next, we present our methodology for studying the effect of MPNNs when using RL to train policies
 162 for AIG minimization formulated as an MDP.

163 4 Methodology

164 We use the same methodology as Zhu et al. [48] who first combined graph convolutional networks and
 165 (deep) reinforcement learning for AIG minimization. We use a similar MDP to their’s: the actions are
 166 the five ABC primitives {balance, rewrite, rewrite -z, refactor, refactor -z}, transitions
 167 are deterministic and every primitive preserves functional equivalence, so every reachable state stays

¹<https://mcsp.work/index.html>




Figure 2: PPO on the ten MLCAD benchmarks with five observation encoders, each at its own best hyper-parameters. (a) AND count averaged over the ten benchmarks; (b) change in final AND count against the no-GCN policy, per benchmark and pooled over the ten (*all 10*), the grey band being the no-GCN policy’s own spread over its five seeds; (c) the pooled change against the parameters the encoder adds to the policy. All intervals are 95% bootstrap confidence intervals over five seeds.

in $\mathcal{G}_f$, and an episode applies exactly $H = 20$ of them to the AIG $\mathcal{G}_0$ to reduce, which makes the induced optimization a search over flows of length 20 from a five-letter alphabet. The reward differs slightly: writing n_t for the number of AND nodes after t actions, $R(s_t, a_t) = 1 - n_{t+1}/n_0$ is issued at every step, so with $\gamma = 1$ we optimize node count alone—the objective of section 3.1—and not the multi-objective reward of Hosny et al. [14]. Unlike Zhu et al. [48], we use PPO [36] to train policies instead of REINFORCE [44] since the former is the better more modern learner.

The policies we train always read a features vector $x_G \in \mathbb{R}^{|A|+5}$ holding the histogram of the actions taken so far, the AND and level counts of the current and previous AIG relative to $\mathcal{G}_0$, and the normalized time step: this is the same as in Hosny et al. [14], Zhu et al. [48]. This features vector carries no AIG structural information, since two AIGs with the same size, depth and history are indistinguishable to it. The key novelty of Zhu et al. [48] is to feed the policy a graph convolutional network [17] reading the AIG and pooling it into a graph-level vector concatenated with the features vector x_G . This GCN addition has since then been built upon (cf section 2.3) but never ablated against e.g. Hosny et al. [14]. Ablating GCN, which is the focus of the following sections, is important because while they might increase performances, they definitely add memory and time overheads.

5 Graphs reinforcement learning: reproducing Zhu et al. [48]

5.1 Setup

We minimize the same AIGs as Zhu et al. [48]: apex1, bc0, C1355, C5315, C6288, C7552, dalu, i10, k2 and mainpla. They range from 504 to 6359 AND gates and encode diverse Boolean functions. For each AIG we run PPO with five policies: no GCN, and a small, medium, large and very large GCN. Every (AIG, policy) pair is tuned over the same grid — three learning rates by three entropy coefficients, five seeds each — and we report the cell with the lowest mean final AND count over its five seeds, discarding cells in which a seed did not complete. Each policy therefore receives the same tuning budget and is shown at its own optimum. We periodically save and evaluate the greedy PPO policy: we use it to minimize an AIG and report the AND count after applying $H = 20$ ABC primitives (cf. section 4). All hyperparameters and implementation details are given in appendix A.1.

6 Results

Figure 2(a) shows that a tuned PPO learns to minimize an AIG independently of the policy architecture, reaching a median performance 6% below resyn2 [31]. Figure 7 in appendix E breaks the same runs down by benchmark and the observation holds. Pooled over the ten benchmarks, last row of

figure 2(b), the GCN policies do end between 0.74% and 0.96% below the multi-layer perceptron (MLP) policy with confidence intervals excluding zero, and the best GCN policies produces the smaller circuits on eight to nine benchmarks out of ten (see appendix table 2). The effect is nonetheless marginal: it is barely larger than what re-running the baseline with different seeds produces (grey band), only 6 of the 40 encoder-benchmark comparisons have a confidence interval entirely below zero, and in absolute terms the best GCN saves a median of 11 AND gates per benchmark (see appendix table 2), from none at all on C6288 to 57 gates on bc0. Most importantly, figure 2(c) shows the gain does not increase with encoder size: 2 496 added parameters improve performances as much as 107 968. We repeated the experiment on the 100 AIGs (106 to 46 977 AND gates) of the 2026 IWLS programming contest². The picture there is the same in sign and magnitude, 0.3% to 0.7% below the MLP (appendix B).

Next, we ask why the grains from GCN policies are so marginal despite being a representation specialized for graphs compared to MLPs reading graphs statistics.

7 Why is graphs representation learning improving so little over MLPs?

The previous section compares encoders inside one algorithm, so a null result there could be a property of that algorithm rather than of the representations. We therefore ask a question that does not involve a training algorithm at all: how well can the optimal value V^* of a state (cf section 3.2) be predicted from what a given class of models is able to see? This empirical analyses of graphs representation, in particular of MPNNs (cf. section 3.3), has been studied for graph-level regression tasks other than value prediction in Akbiyik et al. [1].

7.1 Building a dataset

Computing V^* exactly is out of reach: the tree of flows over the five primitives of section 4 has 5^H leaves, and every edge of it costs one ABC call on the full circuit. We therefore estimate it by sampling both the states and the continuations from them. A state is the AIG obtained by applying to the benchmark $\mathcal{G}_0$ a uniformly random flow of length $L \sim \mathcal{U}\{2, \dots, 10\}$; we draw 1,000 such states per benchmark and store each one both as an .aig file and as the statistics $x_{\mathcal{G}}$ of section 4, so that the graph models and the MLP of section 7.2 are evaluated on exactly the same states and the same targets. From each state s we then run $M = 100$ independent rollouts of 8 further uniformly random primitives and keep the best AND count reached, $\hat{V}(s) = \min_{j \leq M} n^{(j)}(s)$, an upper bound on the minimum over the 5^8 flows of length eight that approaches it from above as M grows. Two differences to V^* should be kept in mind. $\hat{V}$ counts AND nodes rather than returns, so it is ordered the other way round from the value of section 3.2—smaller is better—which leaves the comparison between model classes unchanged (appendix A.2). And it truncates the horizon at eight steps instead of the $H = 20$ of the reinforcement learning experiments, so our targets approximate the value of an eight-step-to-go problem, and the bounds of section 7.2 are lower bounds on the error of predicting that quantity. The procedure is repeated with ten seeds per benchmark on the same ten MLCAD circuits as in section 5, and the figures of this section report over those ten repetitions. The sampler is degenerate on two of them, reaching only two distinct values of $\hat{V}$ on C6288 and six on C1355: we exclude C6288 and report over the remaining nine benchmarks, flagging C1355 wherever it appears.

7.2 Theoretical lower bounds on the prediction error

A model that cannot distinguish two states must assign them the same prediction, so a class of models partitions the state space and its best achievable squared error is that of the predictor returning, for each part, the mean target over that part. No model in the class can beat that error, regardless of its size, its training procedure or its optimization. This is the protocol of GraphTester [1], which measures the theoretical boundary of MPNNs (cf. section 3.3) on a given dataset rather than the performance of one trained instance; we reimplement it for the target of section 7.1 and for four representations, ordered by what they can see: the number of nodes $|V_{\mathcal{G}}|$ alone, which is what a 0-layer message passing network reduces to; the pair $(|V_{\mathcal{G}}|, d_{\mathcal{G}})$, with $d_{\mathcal{G}}$ the logic depth reported by ABC; the engineered statistics $x_{\mathcal{G}}$ of section 4 in full, the action histogram included, which is exactly what the MLP policy from section 5 reads; and the 1-WL coloring of the AIG, which upper

²<https://github.com/alanminko/iwls2026-ls-contest/>




Figure 3: Best error (a) and best ranking (b) achievable by each model class on $\widehat{V}$, over nine benchmarks and ten dataset seeds. Each class is replaced by the optimal predictor for the information it can distinguish, so the value shown cannot be beaten by any model in that class. *C1355 has only six distinct targets.

249 bounds the separating power of every architecture of section 3.3. Comparing the last two is the
 250 question of this section: what a learned encoder could express, against what the statistics already
 251 express. They are incomparable rather than nested—only the current size and depth entries of x_G
 252 are functions of the current AIG, the previous step’s size and depth, the normalized time step and
 253 the action histogram being episode history that no encoder of the current graph can recover—so the
 254 x_G bound may fall below the 1-WL bound without contradicting it, and a policy that reads both, as
 255 Algorithm 1 does, is bounded by neither alone. Besides the squared error, which we normalize by the
 256 variance of the target, we report how well each class can *order* states, with Spearman’s ρ , Kendall’s
 257 τ and the weighted τ , since a critic that ranks successors correctly is useful even when its absolute
 258 errors are large. The bounds are computed in sample, so a partition fine enough to isolate every state
 259 would drive the error to zero regardless of whether the representation carries any signal about $\widehat{V}$; we
 260 control for this by recomputing every bound with the targets randomly permuted across states, which
 261 leaves the partition intact and destroys the association. Every bound we report sits 11 to 474 times
 262 below its shuffled-label counterpart, depending on the benchmark, and the two partitions we compare
 263 are of nearly equal granularity, at 865 parts for x_G and 860 for 1-WL out of 1,000 states on average,
 264 so neither class is merely memorizing the targets nor given more degrees of freedom than the other.
 265 Appendix C details how the partitions are computed.

266 7.3 Results

267 A k -layer MPNN separates graphs at most as finely as k iterations of 1-WL, so grouping states by
 268 their 1-WL color and predicting each group’s mean $\widehat{V}$ gives an error no MPNN can beat; the same
 269 construction bounds a 0-layer network, a (size, depth) model, and a model seeing the MLP’s features
 270 x_G . From figure 3, we observe that message passing is worth a great deal over global descriptors:
 271 the bound falls from 0.02–0.64 of the target variance for node count alone, to 1.1×10^{-3} –0.24 once
 272 depth is added, and to 3×10^{-4} – 1.2×10^{-2} for 1-WL. It is worth nothing over x_G . On eight of the
 273 nine benchmarks the x_G bound is the *lower* of the two, at 0.73 to 0.99 times the MPNN bound; only
 274 C1355 goes the other way, where message passing is better by $1.93\times$. The ordering is stable within a
 275 dataset: paired by seed, x_G is lower on all ten seeds of six benchmarks and on seven and eight of ten
 276 for dalu and C7552. For ranking the two classes are indistinguishable — weighted Kendall $\tau \geq 0.97$
 277 for both on every benchmark, with x_G ahead by at most 0.014 — while size and depth alone reach
 278 only 0.60–0.99. Depth is irrelevant — the bound moves by at most 1.1×10^{-3} between $k = 1$ and
 279 $k = 50$, and edge direction and inverter bits change it by less than 10^{-6} (Appendix D). C6288 is
 280 excluded: its target takes only two distinct values.

Limitations of the bounds. Four restrictions should be read with the numbers above. First, they hold over the state distribution of section 7.1—AIGs reached by uniformly random flows of length two to ten—and not over the states a trained policy visits, which are fewer and more correlated; a representation could be uninformative on the former and useful on the latter. Second, each dataset descends from a single benchmark, so what is bounded is the ability to tell apart states *of one circuit*, whereas the argument for learned encoders in section 4 is transfer *across* circuits; our experiment does not test that claim, and a cross-circuit dataset could behave differently. Third, $\hat{V}$ is a Monte-Carlo estimate, so part of its variance is sampling noise that no representation can predict. That noise raises every bound by roughly the same amount and therefore compresses the ratios between classes towards one, which works in favor of the negative conclusion we draw; the 1-WL and x_G bounds being close is evidence that message passing adds little, but not proof that the noise floor is not what they are both close to. Fourth, the 1-WL argument covers message passing networks whose input is the AIG with node-type features, which is the setting of section 4 and of Zhu et al. [48]. It does not cover higher-order architectures, models given node identifiers or positional encodings, nor encoders whose node features are not a function of the graph alone—the simulation-derived features used by some AIG-specific models are an example, and for those the bound of figure 3 is not binding.

8 Discussion

In section 5, we observe that training graphs representations in the form of a GCN policy did not improve RL-based AIG minimization compared to using only an MLP reading graphs statistics and last few actions. In section 7.2, we approximated an upper bound for the performances of MPNNs predicting the optimal states values in the AIG minimization MDP of section 4. The bounds give a candidate explanation for a gap that small: for predicting $\hat{V}$, the statistics x_G the MLP reads are as expressive as any message passing network on the states of section 7.1. On eight of the nine benchmarks the error achievable from x_G is the lower of the two, and for ranking states the two classes are indistinguishable, at weighted Kendall $\tau \geq 0.97$ for both. Nothing a GCN could extract from the graph would then improve the value estimate the policy is trained against, and the reduction it buys would stay of the order we measure.

The bounds do show that message passing separates states far better than size and depth alone, so the result is about the specific comparison with x_G , not about message passing being uninformative.

The practical consequence is that a graph encoder should not be assumed to pay for its parameters here: in this pipeline it buys under 1% of AND count, and the statistics baseline should be run before it is adopted. This is not a statement about graph representation learning for logic synthesis in general. Our evidence covers one policy gradient algorithm, five ABC primitives, a fixed horizon, and value datasets each built from a single circuit, so the transfer across circuits that motivates learned encoders is not tested by our experiments. Appendix F reports a preliminary attempt to train graph models on these datasets; the models do not fit their training set, so we draw no conclusion from it.

9 Future work

Our results are restricted to the setting used by past work: a policy gradient algorithm, five ABC primitives as actions, and the fixed horizon of section 4. Two of those choices—the algorithm and the action space—bear directly on how much a learned representation of the circuit could contribute, and relaxing them is where we would look next.

Other reinforcement learning algorithms. AIG editing is deterministic and its exploration problem is hard, a combination for which value-based algorithms [43, 26] are usually competitive, yet the existing work on AIG reduction surveyed in section 2 is entirely policy gradient-based. That distinction matters here rather than only for sample efficiency: a value-based agent acts by comparing the predicted values of successor states, so its behavior rests entirely on the quantity section 7 measures, whereas in an actor-critic method the value estimate only shapes the advantage. If the representation is the bottleneck anywhere, it should be there, and our experiments do not answer whether a graph encoder helps under such an algorithm.

The full ABC action space. Five primitives give the policy little to decide, and the states it can reach are the images of a handful of short sequences, which may be why the statistics of section 4 suffice to tell them apart. ABC exposes many more primitives, and our environment already implements that larger action space (Section 4) even though the experiments above do not use it. With more primitives, reachable states would differ from one another in more ways, and a representation that sees the circuit rather than its summary would have correspondingly more to distinguish. Rerunning both the ablation of section 5 and the bounds of section 7.2 over that action space would say whether our negative result is a property of AIG reduction itself or of the small action space it is usually given.

References

- [1] Eren Akbiyik, Florian Grötschla, Béni Egressy, and Roger Wattenhofer. Graphtester: Exploring Theoretical Boundaries of GNNs on Graph Datasets. In *Data-centric Machine Learning Research (DMLR) Workshop at ICML 2023, Honolulu, Hawaii*, July 2023.
- [2] Eric Allender and Bireswar Das. Zero knowledge and circuit minimization. *Information and Computation*, 256:2–8, 2017. ISSN 0890-5401. doi: <https://doi.org/10.1016/j.ic.2017.04.004>. URL <https://www.sciencedirect.com/science/article/pii/S0890540117300512>.
- [3] Animesh Basak Chowdhury, Marco Romanelli, Benjamin Tan, Ramesh Karri, and Siddharth Garg. Retrieval-guided reinforcement learning for boolean circuit minimization. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun, editors, *International Conference on Learning Representations*, volume 2024, pages 35039–35060, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/file/96bbdd0ed2a9e7cd2fb7caf2fae15f3d-Paper-Conference.pdf.
- [4] Richard Bellman. *Dynamic Programming*. 1957.
- [5] Robert K. Brayton and Alan Mishchenko. Abc: An academic industrial-strength verification tool. In *International Conference on Computer Aided Verification*, 2010. URL <https://api.semanticscholar.org/CorpusID:1251520>.
- [6] Alba Carballo-Castro, Manuel Madeira, Yiming QIN, Dorina Thanou, and Pascal Frossard. Generating directed graphs with dual attention and asymmetric encoding. In *The Fourteenth International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=s2s5xGQCKM>.
- [7] Andrea Costamagna, Alan Mishchenko, Satrajit Chatterjee, and Giovanni De Micheli. An enhanced resubstitution algorithm for area-oriented logic optimization. In *2024 IEEE International Symposium on Circuits and Systems (ISCAS)*, pages 1–5, 2024. doi: 10.1109/ISCAS58744.2024.10558264.
- [8] Victor-Alexandru Darvariu, Stephen Hailes, and Mirco Musolesi. Graph reinforcement learning for combinatorial optimization: A survey and unifying perspective. *Transactions on Machine Learning Research*, 2024. ISSN 2835-8856. URL <https://openreview.net/forum?id=HduK51xNtS>. Survey Certification.
- [9] Matthias Fey and Jan Eric Lenssen. Fast graph representation learning with pytorch geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*, 2019.
- [10] Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1263–1272. PMLR, 2017.
- [11] Antoine Grosnit, Cedric Malherbe, Rasul Tutunov, Xingchen Wan, Jun Wang, and Haitham Bou Ammar. Boils: Bayesian optimisation for logic synthesis. In *Design, Automation, Test in Europe Conference, 2022*, pages 1193–1196, 2022. doi: 10.23919/DATE54114.2022.9774632.
- [12] Aric A. Hagberg, Daniel A. Schult, and Pieter J. Swart. Exploring network structure, dynamics, and function using networkx. In *Proceedings of the 7th Python in Science Conference*, pages 11–15, 2008.

- [13] William L. Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems*, volume 30, 2017.
- [14] Abdelrahman Hosny, Soheil Hashemi, Mohamed Shalan, and Sherief Reda. Drills: Deep reinforcement learning for logic synthesis. In *2020 25th Asia and South Pacific Design Automation Conference (ASP-DAC)*, pages 581–586, 2020. doi: 10.1109/ASP-DAC47756.2020.9045559.
- [15] Valentine Kabanets and Jin-Yi Cai. Circuit minimization problem. In *Proceedings of the thirty-second annual ACM symposium on Theory of computing*, pages 73–79, 2000.
- [16] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.
- [17] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *International Conference on Learning Representations*, 2017.
- [18] Min Li, Sadaf Khan, Zhengyuan Shi, Naixing Wang, Huang Yu, and Qiang Xu. Deepgate: Learning neural representations of logic gates. In *Proceedings of the 59th ACM/IEEE Design Automation Conference*, pages 667–672, 2022.
- [19] Mufei Li, Viraj Shitole, Eli Chien, Changhai Man, Zhaodong Wang, Srinivas, Ying Zhang, Tushar Krishna, and Pan Li. LayerDAG: A layerwise autoregressive diffusion model of directed acyclic graphs for system. In *Machine Learning for Computer Architecture and Systems 2024*, 2024. URL <https://openreview.net/forum?id=IsarrieQA>.
- [20] Fangzhou Liu, Wuqian Tang, Zehua Pei, Ziyang Yu, Haisheng Zheng, Zhuolun He, Mengjia Dai, Tinghuan Chen, and Bei Yu. Cb-evo: Contextual bandit tuning with evolutionary search for logic synthesis. *ACM Trans. Des. Autom. Electron. Syst.*, 31(6), June 2026. ISSN 1084-4309. doi: 10.1145/3779431. URL <https://doi.org/10.1145/3779431>.
- [21] Jiawei Liu, Jianwang Zhai, Mingyu Zhao, Zhe Lin, Bei Yu, and Chuan Shi. Polargate: Breaking the functionality representation bottleneck of and-inverter graph neural network. In *Proceedings of the 43rd IEEE/ACM International Conference on Computer-Aided Design*, 2024.
- [22] Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Wenjie Jiang, Ebrahim M. Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Azade Nazi, Jiwoo Pak, Andy Tong, Kavya Srinivasa, Will Hang, Emre Tuncer, Quoc V. Le, James Laudon, Richard Ho, Roger Carpenter, and Jeff Dean. A graph placement methodology for fast chip design. *Nature*, 594: 207 – 212, 2021. URL <https://api.semanticscholar.org/CorpusID:235395490>.
- [23] A. Mishchenko, S. Chatterjee, and R. Brayton. Dag-aware aig rewriting: a fresh look at combinational logic synthesis. In *2006 43rd ACM/IEEE Design Automation Conference*, pages 532–535, 2006. doi: 10.1145/1146909.1147048.
- [24] Alan Mishchenko and Robert K. Brayton. Scalable logic synthesis using a simple circuit structure. 2006. URL <https://api.semanticscholar.org/CorpusID:8597391>.
- [25] Alan Mishchenko, Satrajit Chatterjee, Roland Jiang, and Robert K. Brayton. Fraigs: A unifying representation for logic synthesis and verification, 2005. URL <https://api.semanticscholar.org/CorpusID:9209313>.
- [26] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.
- [27] Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In Maria Florina Balcan and Kilian Q. Weinberger, editors, *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pages 1928–1937, New York, New York, USA, 20–22 Jun 2016. PMLR. URL <https://proceedings.mlr.press/v48/mniha16.html>.

- [28] Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 4602–4609, 2019.
- [29] Walter Lau Neto, Yingjie Li, Pierre-Emmanuel Gaillardon, and Cunxi Yu. Flowtune: End-to-end automatic logic optimization exploration via domain-specific multiarmed bandit. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, 42(6):1912–1925, 2023. doi: 10.1109/TCAD.2022.3213611.
- [30] Suhua Ou, Qingshan Yang, and Jian Liu. The global production pattern of the semiconductor industry: an empirical research based on trade network. *Humanities and Social Sciences Communications*, 11(1):1–13, 2024.
- [31] Rajendran Panda and Farid N. Najm. Post-mapping transformations for low-power synthesis. *VLSI Design*, 7:289–301, 1998. URL <https://api.semanticscholar.org/CorpusID:6811282>.
- [32] Zehua Pei, Fangzhou Liu, Zhuolun He, Guojin Chen, Haisheng Zheng, Keren Zhu, and Bei Yu. Alphasyn: Logic synthesis optimization with efficient monte carlo tree search. In *2023 IEEE/ACM International Conference on Computer Aided Design (ICCAD)*, pages 1–9, 2023. doi: 10.1109/ICCAD57390.2023.10323856.
- [33] Martin L. Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. John Wiley & Sons, 1994.
- [34] Yu Qian, Xuegong Zhou, Hao Zhou, and Lingli Wang. An efficient reinforcement learning based framework for exploring logic synthesis. *ACM Trans. Des. Autom. Electron. Syst.*, 29(2), January 2024. ISSN 1084-4309. doi: 10.1145/3632174. URL <https://doi.org/10.1145/3632174>.
- [35] Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268):1–8, 2021.
- [36] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- [37] Chuan Shi, Yitong Li, Jiawei Zhang, Yizhou Sun, and Philip S Yu. A survey of heterogeneous information network analysis. *IEEE Transactions on Knowledge and Data Engineering*, 29(1):17–37, 2016.
- [38] Timo Stoll, Chendi Qian, Ben Finkelshtein, Ali Parviz, Darius Weber, Fabrizio Frasca, Hadar Shavit, Antoine Siraudin, Arman Mielke, Marie Anastacio, Erik Müller, Maya Bechler-Speicher, Michael Bronstein, Mikhail Galkin, Holger Hoos, Mathias Niepert, Bryan Perozzi, Jan Tönshoff, and Christopher Morris. Graphbench: Next-generation graph learning benchmarking, 2026. URL <https://arxiv.org/abs/2512.04475>.
- [39] Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In S. Solla, T. Leen, and K. Müller, editors, *Advances in Neural Information Processing Systems*, volume 12. MIT Press, 1999. URL https://proceedings.neurips.cc/paper_files/paper/1999/file/464d828b85b0bed98e80ade0a5c43b0f-Paper.pdf.
- [40] Gerald Tesauro. Temporal difference learning and td-gammon. *Commun. ACM*, 38(3):58–68, March 1995. ISSN 0001-0782. doi: 10.1145/203330.203343. URL <https://doi.org/10.1145/203330.203343>.
- [41] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *International Conference on Learning Representations*, 2018.

- 473 [42] Hanrui Wang, Kuan Wang, Jiacheng Yang, Linxiao Shen, Nan Sun, Hae-Seung Lee, and Song
474 Han. Gcn-rl circuit designer: Transferable transistor sizing with graph neural networks and
475 reinforcement learning. In *2020 57th ACM/IEEE Design Automation Conference (DAC)*, pages
476 1–6, 2020. doi: 10.1109/DAC18072.2020.9218757.
- 477 [43] Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine learning*, 8(3):279–292, 1992.
- 478 [44] Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist re-
479 inforcement learning. *Mach. Learn.*, 8(3–4):229–256, May 1992. ISSN 0885-6125. doi:
480 10.1007/BF00992696. URL <https://doi.org/10.1007/BF00992696>.
- 481 [45] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural
482 networks? In *International Conference on Learning Representations*, 2019.
- 483 [46] Qiyun Zhao. Funcgnn: Learning functional semantics of logic circuits with graph neural
484 networks, 2025.
- 485 [47] Ziyang Zheng, Shan Huang, Jianyuan Zhong, Zhengyuan Shi, Guohao Dai, Ningyi Xu, and
486 Qiang Xu. Deepgate4: Efficient and effective representation learning for circuit design at
487 scale. In *The Thirteenth International Conference on Learning Representations*, 2025. URL
488 <https://openreview.net/forum?id=b101RabU9W>.
- 489 [48] Keren Zhu, Mingjie Liu, Hao Chen, Zheng Zhao, and David Z. Pan. Exploring logic optimiza-
490 tions with reinforcement learning and graph convolutional network. In *2020 ACM/IEEE*
491 *2nd Workshop on Machine Learning for CAD (MLCAD)*, pages 145–150, 2020. doi:
492 10.1145/3380446.3430622.

A Hyper-parameters

A.1 Graph encoders and reinforcement learning

The environment. The MDP of section 4 instantiates the MDP of section 3.2 with the five ABC primitives as actions, where `-z` enables zero-cost replacements. Episodes start from $\mathcal{G}_0$ and last exactly $H = 20$ actions with no early stopping. Because every primitive preserves functional equivalence, the problem of section 3.1 is never violated, only under-solved. The reward is a level rather than a difference, so the return is maximized by an agent that keeps the AIG small throughout the episode and not merely at the end. Our environment also implements a seven-action variant adding `resub` and `resub -z`, and the full ABC action space, neither of which is used in our experiments.

The observation. Writing n_t and ℓ_t for the number of AND nodes and of levels after t actions, the vector part of the observation is

$$x_{\mathcal{G}} = \left[\underbrace{\frac{1}{q} \sum_{j=1}^q \mathbf{1}[a_{t-j} = a]}_{a \in A}, \frac{n_t}{n_0}, \frac{\ell_t}{\ell_0}, \frac{n_{t-1}}{n_0}, \frac{\ell_{t-1}}{\ell_0}, \frac{t}{H} \right].$$

The first $|A| = 5$ entries are a normalized histogram of the last q actions, with $q = 3$ like in Zhu et al. [48]; the next four are the AND and level counts of the current and of the previous AIG, each divided by its value in $\mathcal{G}_0$ so that the vector is scale-free across benchmarks of very different sizes; the last is the normalized time step, which makes the finite-horizon problem Markov in the observation. It is computed in a single pass over the graph and adds no parameters of its own. The graph part of the observation is the AIG itself, as in Zhu et al. [48]: nodes carry a one-hot encoding of their type among the six types `abc_py` exposes, a directed edge runs from each fanin to the node it feeds, and edges carry no label.

The encoders. Table 1 lists the four graph encoders of section 4: three at depth three with widths from 12 to 128, and one at depth five, so that depth and width are not confounded. Each runs the message passing rounds of section 3.3 over the AIG and pools the node embeddings into a graph-level vector concatenated with $x_{\mathcal{G}}$ before the policy and value heads. The baseline uses no encoder at all and reads $x_{\mathcal{G}}$ alone through a multi-layer perceptron.

Table 1: The four graph encoders. Depth is the number of message passing rounds, width the hidden dimension, and output the dimension of the pooled vector concatenated with $x_{\mathcal{G}}$.

encoder	depth	width	output
<code>small</code>	3	12	4
<code>medium</code>	3	64	32
<code>large</code>	3	128	64
<code>v. large</code>	5	128	64

Training. Policies are trained with the PPO implementation of `stable-baselines3` [35] with $\gamma = 1$, the horizon being finite and fixed, and the encoder is trained end to end with the policy and value heads rather than pre-trained or frozen. Eight environments run in parallel and each contributes 20 steps per update, so an update is computed from 160 transitions and a single episode spans five updates; 8,000 environment steps therefore amount to $N = 50$ updates. After every update we evaluate the greedy policy for one episode, which is the quantity the learning curves report. The policy and value heads are each two hidden layers of 256 units and share the encoder of line 7 of Algorithm 1. Algorithm 1 states the resulting procedure, which we call GRAPHPPPO: it is ordinary PPO with the encoder made explicit, the encoding of the current AIG being the only place where the five configurations we compare differ.

The grid of section 5 crosses three learning rates (10^{-4} , 10^{-5} , 10^{-6}), three entropy coefficients (0, 0.01, 0.1) and five seeds, which with five encoders and ten benchmarks gives the 2,250 runs reported there. Twenty-six of those runs (eighteen `small`, eight `v. large`) stopped before the fiftieth update; we drop them rather than pad them, and requiring all five encoders to have completed a given (benchmark, learning rate, entropy, seed) cell leaves 424 of the 450 cells.

Algorithm 1 GRAPHPPPO. The encoder f_θ is the only component that varies across the runs we compare; everything else is held fixed.

Require: AIG $\mathcal{G}_0$ to reduce with n_0 AND nodes, encoder f_θ , policy head π_θ , value head V_θ , action set A of five ABC primitives, fixed horizon $H = 20$, iterations N , epochs K , clipping ϵ , entropy weight β , value weight c , step size η

- 1: $n^* \leftarrow n_0$
- 2: **for** $i = 1, \dots, N$ **do**
- 3: $\mathcal{D} \leftarrow \emptyset$
- 4: **for** each parallel environment **do**
- 5: $\mathcal{G} \leftarrow \mathcal{G}_0$
- 6: **for** $t = 0, \dots, H - 1$ **do**
- 7: $s_t \leftarrow (f_\theta(\mathcal{G}), x_{\mathcal{G}})$ $\triangleright f_\theta$ is a GCN, or is absent for the baseline
- 8: $a_t \sim \pi_\theta(\cdot | s_t), \quad a_t \in A$
- 9: $\mathcal{G} \leftarrow \text{ABC}(\mathcal{G}, a_t)$ $\triangleright$ deterministic, preserves functional equivalence
- 10: $r_t \leftarrow 1 - |V^{AND}(\mathcal{G})| / n_0$ $\triangleright$ relative size, issued at every step
- 11: $\mathcal{D} \leftarrow \mathcal{D} \cup \{(s_t, a_t, r_t, \log \pi_\theta(a_t | s_t), V_\theta(s_t))\}$
- 12: $n^* \leftarrow \min(n^*, |V^{AND}(\mathcal{G})|)$
- 13: **end for**
- 14: **end for**
- 15: compute returns $\hat{R}_t$ and advantages $\hat{A}_t$ from $\mathcal{D}$
- 16: $\theta_{\text{old}} \leftarrow \theta$
- 17: **for** K epochs over minibatches of $\mathcal{D}$ **do**
- 18: $\rho_t(\theta) \leftarrow \pi_\theta(a_t | s_t) / \pi_{\theta_{\text{old}}}(a_t | s_t)$
- 19: $L(\theta) \leftarrow \mathbb{E}_t[\min(\rho_t \hat{A}_t, \text{clip}(\rho_t, 1 - \epsilon, 1 + \epsilon) \hat{A}_t) - c(V_\theta(s_t) - \hat{R}_t)^2 + \beta \mathcal{H}[\pi_\theta(\cdot | s_t)]]$
- 20: $\theta \leftarrow \theta + \eta \nabla_\theta L(\theta)$ $\triangleright$ gradients flow through f_θ
- 21: **end for**
- 22: **end for**
- 23: **return** n^* , the smallest AND count visited

benchmark	input	no GCN (MLP)	GCN small	GCN medium	GCN large	GCN v. large	resyn2
C1355	504	389 $\pm$ 3	387 $\pm$ 1	387 $\pm$ 0	387 $\pm$ 1	387 $\pm$ 0	390
dalv	1740	1008 $\pm$ 9	1006 $\pm$ 6	1001 $\pm$ 3	1006 $\pm$ 6	1005 $\pm$ 2	1052
C5315	1773	1303 $\pm$ 43	1287 $\pm$ 8	1283 $\pm$ 2	1282 $\pm$ 6	1283 $\pm$ 5	1309
C7552	2074	1371 $\pm$ 12	1372 $\pm$ 10	1367 $\pm$ 11	1369 $\pm$ 5	1369 $\pm$ 10	1455
apex1	2124	1066 $\pm$ 7	1064 $\pm$ 11	1074 $\pm$ 4	1070 $\pm$ 4	1063 $\pm$ 14	1179
k2	2190	1049 $\pm$ 26	1015 $\pm$ 32	1019 $\pm$ 27	1027 $\pm$ 21	1030 $\pm$ 36	1194
C6288	2337	1870 $\pm$ 0	1870 $\pm$ 0	1870 $\pm$ 0	1870 $\pm$ 0	1870 $\pm$ 0	1870
i10	2675	1715 $\pm$ 13	1700 $\pm$ 3	1705 $\pm$ 9	1702 $\pm$ 3	1702 $\pm$ 6	1829
bc0	3501	1512 $\pm$ 46	1485 $\pm$ 59	1481 $\pm$ 31	1484 $\pm$ 28	1455 $\pm$ 13	1713
mainpla	6359	2318 $\pm$ 37	2306 $\pm$ 14	2298 $\pm$ 11	2305 $\pm$ 23	2307 $\pm$ 14	2476

Table 2: Mean AND count after $H = 20$ ABC primitives over the five seeds of each configuration’s best hyper-parameter cell, $\pm$ one standard deviation across those seeds; best per benchmark in bold. resyn2 is deterministic. The closing row normalises by the input AND counts.

530 A.2 Value prediction

531 **The datasets.** The states of section 7.1 are drawn by sampling L primitives independently and
532 uniformly from the five-element action set and running them in order; the graph models read the
533 stored .aig file and the MLP reads the statistics $x_{\mathcal{G}}$ recorded at that point of the flow. The state is
534 reloaded between the M rollouts. Producing one dataset costs $1,000 \times (L + M \times 8) \approx 8 \times 10^5$ ABC
535 primitive calls per benchmark and per seed, which is why M is lowered to 10 on C6288, by far the
536 most expensive circuit of the suite to rewrite. Each of the ten seeds (0 to 9) draws its own 1,000 states
537 and its own rollouts, and each resulting dataset is split at random into training, validation and test
538 sets. That the target is expressed in AND nodes rather than in returns does not affect the comparison
539 between model classes: the map $n \mapsto 1 - n/n_0$ from AND count to the reward of section 4 is affine
540 and order-reversing, all the errors we report are ratios to the variance of the target and are therefore
541 free of its units, and the rank correlations we report are unchanged up to sign.

542 **Training.** The models of appendix F are trained in mini-batches of 16 unless the batch size is
543 itself searched over. Each architecture’s grid of 36 configurations crosses three learning rates (10^{-3} ,
544 5×10^{-4} , 10^{-4}) with a width and a depth, or with the number of attention heads for GAT and the
545 polarity weight for PolarGate. DeepGate is the exception, with 12 configurations: its pretrained
546 encoder is frozen, so only the two-layer head is tuned.

547 B The ex200–ex299 suite

548 We repeat the comparison of section 5 on ex200–ex299, a suite spanning 106 to 46,977 input AND
 549 gates and therefore both larger and more varied than the ten MLCAD circuits. Each encoder ran at its
 550 own baseline hyper-parameters here instead of over the matched grid. The three GCNs reduce the
 551 final AND count by 0.33–0.71% against a reseed standard deviation of 0.54% (Figure 4), and the
 552 difference is flat across two and a half orders of magnitude of circuit size (Figure 5), so the conclusion
 553 of section 5 appears to hold here as well. The MLP runs were executed on CPU and did not finish on
 554 the largest circuits, which is why 20 of the 100 benchmarks are excluded; the comparison is therefore
 555 made on the smaller eighty, and we cannot rule out that the largest circuits behave differently.




Figure 4: The comparison of figure 2 on ex200–ex299, where each encoder ran at its own baseline hyper-parameters instead of the matched grid. Restricted to the 390 of 500 (benchmark, seed) cells all four encoders completed, covering 80 benchmarks.




Figure 5: Reduction against the MLP as a function of input circuit size on ex200–ex299. Line: mean over size quartiles.

556 C Computing the bounds

557 For the size and the size-and-depth classes of section 7.2 the partition is by exact equality of the
 558 descriptors. For x_G , the full feature vector is snapped to a grid of spacing 10^{-8} and states are grouped
 559 by equality of the snapped vector, so the model we bound and the MLP of section 4 see the same thing.
 560 For message passing, we group states by their 1-WL graph hash, computed with `networkx`’s [12]
 561 `weisfeiler_lehman_graph_hash` at every number of iterations $k = 1, \dots, 50$, with each node
 562 labeled by its type.³ We bound four views of the AIG, which is what the four message passing curves
 563 of figure 3 report: the undirected graph $\mathcal{G}$, the directed graph $\mathcal{G}^{\rightarrow}$ in which refinement follows the
 564 fanin relation, and the two variants $\mathcal{G}^e, \mathcal{G}^{\rightarrow e}$ that additionally label each edge with its complement
 565 bit, so that inversion is visible to the refinement rather than only through node types. Errors are
 566 divided by $\max(1, \text{Var } \hat{V})$; in AND-node units the variance is orders of magnitude above one on
 567 every benchmark, so the clamp never binds and the reported quantity is the plain normalized error.
 568 Rank correlations are computed at $k = 50$ refinement iterations. The permutation control uses 25
 569 permutations per dataset, 8 on `mainpla` and `C6288`, and is applied to the rank correlations as well,
 570 where the null is the correlation between $\hat{V}$ and a random permutation of itself.

³The hash is a 16-byte `blake2b` digest. A collision would merge two groups that 1-WL separates and can only raise the reported value, so the bound would become conservative rather than optimistic; at 1,000 graphs per dataset the probability of one is negligible.

571 D The message passing bound against depth

572 Figure 6 plots the message passing bound of section 7.2 against the number of refinement iterations k ,
 573 for the four views of the AIG bounded there. The bound moves by at most 1.1×10^{-3} between $k = 1$
 574 and $k = 50$, and labeling edges with direction or with the complement bit changes it by less than
 575 10^{-6} , so neither deeper refinement nor a richer view of the graph brings a message passing network
 576 closer to $\hat{V}$.




Figure 6: The MPNN bound as a function of depth k .

577 E Per-benchmark learning curves

578 Figure 7 resolves the aggregate of figure 2(a) into one learning curve per benchmark.




Figure 7: Per-benchmark learning curves for the runs aggregated in figure 2(a). Dashed line: resyn2.

579 F Preliminary results: training models to predict $\hat{V}$

580 The bounds of section 7.2 say what a representation *could* express. This appendix reports what
581 models actually trained on the same datasets achieve. We report it as preliminary: the graph models
582 do not fit their training set, and we have not established whether this comes from the models, from
583 our training protocol, or from the task itself, so none of the claims of the paper rest on it.

584 **Setup.** We train eight regressors on the datasets of section 7.1. Four are generic message
585 passing networks—GCN [17], GIN [45], GAT [41] and GraphSAGE [13]—taken from PyTorch
586 Geometric [9]. Three are AIG-specific: DeepGate [18], PolarGate [21] and FuncGNN [46], each
587 run from its authors’ implementation. The eighth is the MLP of section 4, which reads x_G and no
588 graph at all, and is the baseline the graph models have to beat. All eight share the same head so
589 that only the encoder differs: node embeddings are mean-pooled into one vector per AIG, which
590 a two-layer ReLU network maps to a scalar. GCN, GIN and GraphSAGE consume the six-way
591 one-hot node type of section 4; GAT, PolarGate and FuncGNN consume the three-way type (input,
592 AND, inverter) of the DeepGate reader, with the inverter bit exposed as a signed edge feature, so that
593 the models that were designed to use complementation receive it. DeepGate is the one exception
594 to end-to-end training: we load the pretrained encoder, freeze it, and train only the head on its
595 mean-pooled functional embeddings, which is how it is meant to be used as a general-purpose circuit
596 encoder.

597 Targets are $\hat{V}$ divided by the AND count of the benchmark’s initial AIG, so they lie in $(0, 1]$ and are
598 comparable across circuits. Each dataset of 1,000 states is split 80/10/10 into training, validation
599 and test sets by a permutation seeded by the run seed. Models are trained for 1,000 epochs with
600 Adam [16] on the mean squared error. Each architecture is given its own grid of 36 configurations, and
601 12 for DeepGate, whose frozen encoder leaves only the head to tune; the grids are in appendix A.2.
602 The grid is run at seed 0, the configuration with the lowest final validation error is selected, and that
603 configuration alone is then rerun on the ten seeds we report; the seed selects the dataset, the split
604 and the initialization together, so the ten repetitions are independent in all three. We report test error
605 normalized by the variance of the test targets, so that 1.0 is the error of predicting the mean.

606 **Results.** All seven graph models land between 0.90 and 1.74 times the target variance—at or above
607 the constant predictor—while the MLP reaches 0.47 at the median. Their training error is also ≈ 1 ,
608 so this is a failure to fit rather than to generalize, and it leaves them two to three orders of magnitude
609 above the bound of figure 3 that their own architecture class admits. The per-dataset validation curves
610 of figure 9 show the graph models settling at the level of the constant predictor early in training and
611 staying there. A gap of that size between what the class can express and what training reaches is what
612 makes us treat these runs as preliminary rather than as a result about the architectures.




Figure 8: Test error of eight trained models, normalized by the variance of the target so that 1.0 is the error of predicting the mean. Violet ticks: the 1-WL bound of figure 3.




Figure 9: Validation error over training for the configurations of figure 8, one panel per benchmark.