

UNIX

In order to understand the popularity of Linux, we need to travel back in time, about 30 years ago...

Imagine computers as big as houses, even stadiums. While the sizes of those computers posed substantial problems, there was one thing that made this even worse: every computer had a different operating system. Software was always customized to serve a specific purpose, and software for one given system didn't run on another system. Being able to work with one system didn't automatically mean that you could work with another. It was difficult, both for the users and the system administrators.

Computers were extremely expensive then, and sacrifices had to be made even after the original purchase just to get the users to understand how they worked. The total cost per unit of computing power was enormous.

Technologically the world was not quite that advanced, so they had to live with the size for another decade. In 1969, a team of developers in the Bell Labs laboratories started working on a solution for the software problem, to address these compatibility issues. They developed a new operating system, which was

- 1. Simple and elegant.
- 2. Written in the C programming language instead of in assembly code.
- 3. Able to recycle code.

The Bell Labs developers named their project "UNIX."

The code recycling features were very important. Until then, all commercially available computer systems were written in a code specifically developed for one system. UNIX on the other hand needed only a small piece of that special code, which is now commonly named the kernel. This kernel is the only piece of code that needs to be adapted for every specific system and forms the base of the UNIX system. The operating system and all other functions were built around this kernel and written in a higher programming language C.





Introduction to Linux

Linux is an open-source Unix-like operating system-based family on the Linux kernel, and the OS kernel was first published on 17 September 1991 by Linus Torvalds. Typically, Linux is packaged as the Linux distribution, which contains the supporting libraries and system software and kernel, several of which are offered by the GNU Project. Several Linux distributions use the term "Linux" in the title, but the Free Software Foundation uses the "GNU/Linux" title to focus on the necessity of GNU software, causing a few controversies.

Famous Linux distributions are Ubuntu, Fedora Linux, and Debian, the latter of which is composed of several different modifications and distributions, including Xubuntu and Lubuntu. Commercial distributions are SUSE Linux Enterprise and Red Hat Enterprise Linux. Desktop distributions of Linux are windowing systems like Wayland or X11 and desktop environments like KDE Plasma and GNOME.

Originally, Linux was designed for personal computers that were Intel x86 architecture-based, but it have since been moved to more environments than other operating systems.

Including Android, Linux has the biggest installed base of every general-purpose operating system because of the control of the Linux-based Android over smart phones as of May 2022.

However, Linux is used by just around 2.6% of desktop computers as of November 2022.

Linux is one of the most outstanding examples of open-source and free software collaboration. The source code may be distributed, modified, and used non-commercially or commercially by everyone under the conditions of its respective licenses, like the GNU GPL (General Public License). For example, the Linux kernel is licensed upon the GPLv2.

Uses of Linux OS

- Web servers
- Laptops and desktops
- Mobiles devices
- Film production
- Government uses









Linux is an open-source operating system like Windows and MacOS. It is not just limited to the operating system, but nowadays, it is also used as a platform to run desktops, servers, and embedded systems. It provides various distributions and variations as it is open source and has a modular design. The kernel is a core part of the Linux system.

Linux system is used to manage various services such as process scheduling, application scheduling, basic peripheral devices, file system, and more. Linux provides various advantages over other operating systems such as Windows and macOS. So, it is used in almost every field, from cars to home appliances and smartphones to servers (supercomputers).

Following are top 20 advantages of the Linux operating system:

1. Open Source

As it is open-source, its source code is easily available. Anyone having programming knowledge can customize the operating system. One can contribute, modify, distribute, and enhance the code for any purpose.

2. Security

The Linux security feature is the main reason that it is the most favorable option for developers. It is not completely safe, but it is less vulnerable than others. Each application needs to authorize by the admin user. The virus is not executed until the administrator provides the access password. Linux systems do not require any antivirus program.

3. Free

Certainly, the biggest advantage of the Linux system is that it is free to use. We can easily download it, and there is no need to buy the license for it. It is distributed under GNU GPL (General Public License). Comparatively, we have to pay a huge amount for the license of the other operating systems.





Linux is lightweight. The requirements for running Linux are much less than other operating systems. In Linux, the memory footprint and disk space are also lower. Generally, most of the Linux distributions required as little as 128MB of RAM around the same amount for disk space.

5. Stability

Linux is more stable than other operating systems. Linux does not require to reboot the system to maintain performance levels. It rarely hangs up or slow down. It has big up-times.

6. Performance

Linux system provides high performance over different networks. It is capable of handling a large number of users simultaneously.

7. Flexibility

Linux operating system is very flexible. It can be used for desktop applications, embedded systems, and server applications too. It also provides various restriction options for specific computers. We can install only necessary components for a system.

8. Software Updates

In Linux, the software updates are in user control. We can select the required updates. There a large number of system updates are available. These updates are much faster than other operating systems. So, the system updates can be installed easily without facing any issue.

9. Distributions/ Distros

There are many Linux distributions available in the market. It provides various options and flavors of Linux to the users. We can choose any distros according to our needs. Some popular distros are Ubuntu, Fedora, Debian, Linux Mint, Arch Linux, and many more.





For the beginners, Ubuntu and Linux Mint would be useful and, Debian and Fedora would be good choices for proficient programmers.

10. Live CD/USB

Almost all Linux distributions have a Live CD/USB option. It allows us to try or run the Linux operating system without installing it.

11. Graphical User Interface

Linux is a command-line based OS but, it provides an interactive user interface like Windows.

12. Suitable for programmers

It almost all of the most used programming such supports languages as C/C++, Java, Python, Ruby, and more. Further, it offers a vast range of useful applications for development. The programmers prefer the Linux terminal over the Windows command line. The package manager on Linux system helps programmers to understand how things are done. Bash scripting is also a functional feature for the programmers. It also provides support for SSH, which helps in managing the servers quickly.

13. Community Support

Linux provides large community support. We can find support from various sources. There are many forums available on the web to assist users. Further, developers from the various open source communities are ready to help us.

14. Privacy

Linux always takes care of user privacy as it never takes much private data from the user. Comparatively, other operating systems ask for the user's private data.

15. Networking

Linux facilitates with powerful support for networking.









The client-server systems can be easily set to a Linux system. It provides various command-line tools such as ssh, ip, mail, telnet, and more for connectivity with the other systems and servers. Tasks such as network backup are much faster than others.

16. Compatibility

Linux is compatible with a large number of file formats as it supports almost all file formats.

17. Installation

Linux installation process takes less time than other operating systems such as Windows. Further, its installation process is much easy as it requires less user input. It does not require much more system configuration even it can be easily installed on old machines having less configuration.

18. Multiple Desktop Supports

Linux system provides multiple desktop environment support for its enhanced use. The desktop environment option can be selected during installation. We can select any desktop environment such as GNOME (GNU Network Object Model Environment) or KDE (K Desktop Environment) as both have their specific environment.

19. Multitasking

It is a multitasking operating system as it can run multiple tasks simultaneously without affecting the system speed.

20. Heavily documented for beginners

There are many command-line options that provide documentation on commands, libraries, standards such as manual pages and info pages. Also, there are plenty of documents available on the internet in different formats, such as Linux tutorials, Linux documentation project, Server fault, and more.







CLOUD COMPUTING

Cloud computing is a technology that allows individuals and organizations to access and use computing resources (such as servers, storage, databases, networking, software, and more) over the internet on a pay-as-you-go basis. Instead of owning and maintaining physical hardware and data centers, users can leverage the cloud to quickly provision and scale resources as needed.

There are several key characteristics of cloud computing:

- 1. On-Demand Self-Service: Users can provision and manage computing resources as needed without requiring human intervention from service providers.
- 2. Broad Network Access: Cloud services are accessible over the internet from a variety of devices, such as laptops, smartphones, and tablets.
- 3. Resource Pooling: Cloud providers use multi-tenant models, where resources are shared among multiple customers. This allows for cost efficiencies and resource optimization.
- 4. Rapid Elasticity: Cloud resources can be quickly scaled up or down to meet changing workloads and demands. This scalability ensures that you only pay for the resources you use.
- 5. Measured Service: Cloud usage is metered and billed based on actual consumption. This pay-as-you-go model provides cost control and flexibility.

Cloud computing can be categorized into three main service models:

- 1. Infrastructure as a Service (IaaS): IaaS provides virtualized computing resources over the internet. Users can rent virtual machines, storage, and networking components, which they can configure and manage. Examples of IaaS providers include Amazon Web Services (AWS), Microsoft Azure, and Google Cloud Platform (GCP).
- 2. Platform as a Service (PaaS): PaaS offers a platform and environment for developers to build, deploy, and manage applications without the need to worry about underlying infrastructure. PaaS providers include Heroku, Google App Engine, and Microsoft Azure App Service.







3. Software as a Service (SaaS): SaaS delivers software applications over the internet on a subscription basis. Users can access these applications via web browsers without the need to install or maintain software locally. Examples of SaaS offerings include Google Workspace, Microsoft 365, and Salesforce.

Cloud computing is a fundamental technology that has transformed the way businesses and individuals manage and utilize IT resources. It provides cost-efficiency, scalability, flexibility, and accessibility, making it a crucial enabler of digital transformation and innovation.

AWS – AMAZON WEB SERVICES

Amazon Web Services (AWS) is a subsidiary of Amazon providing on-demand cloud computing platforms and APIs (Application Programming Interfaces) to individuals, companies, and governments, on a metered pay-as-you-go basis. AWS offers a wide range of cloud services, including computing power, storage, databases, machine learning, analytics, content delivery, and more. These services enable organizations to scale and deploy applications and infrastructure without the need to invest in and maintain their own physical servers and data centers.

AWS is one of the leading cloud service providers globally and has a vast global network of data centers, allowing customers to host their applications and data in various regions around the world. This global infrastructure, along with a wide array of services and tools, has made AWS a popular choice for businesses looking to leverage the cloud for their computing and storage needs.

Some of the most well-known AWS services include Amazon EC2 (Elastic Compute Cloud) for scalable virtual servers, Amazon S3 (Simple Storage Service) for object storage, Amazon RDS (Relational Database Service) for managed databases, Amazon Lambda for serverless computing, and Amazon SNS (Simple Notification Service) for messaging and notifications, among many others.





AWS provides both infrastructure as a service (IaaS) and platform as a service (PaaS) solutions, allowing users to choose the level of control and flexibility they require for their specific applications and workloads. It has become a cornerstone of the cloud computing industry and is widely used by startups, enterprises, and governments for a variety of purposes, including hosting websites, running machine learning models, storing and analyzing data, and more.

AWS Account Creation (Free tier account)

Creating an AWS Free Tier account is a straightforward process, and it allows you to access a range of AWS services with certain usage limits for free during the first 12 months of your account.

Here are the steps to create an AWS Free Tier account:

- 1. Visit the AWS Free Tier Signup Page: Go to the AWS Free Tier signup page by following this link: https://aws.amazon.com/free/.
- 2. Click "Create an AWS Account": On the AWS Free Tier page, click the "Create an AWS Account" button.
- 3. Sign In or Create a New AWS Account:

If you already have an Amazon.com account, you can sign in with those credentials. If you don't have an Amazon.com account, you'll need to create one. Follow the on-screen instructions to sign in or create an account.

- 4. Provide Account Information:
 - Fill in the required information for your AWS account, including your email address, password, and AWS account name. You'll also need to read and accept the AWS Customer Agreement, the AWS Service Terms, and the AWS Privacy Notice.
- 5. Contact Information: Enter your contact information, including your name, address, and phone number.







- 6. Payment Information: To verify your identity, you'll need to provide valid credit card information. AWS uses this information to ensure that you are a real person and to prevent misuse of the Free Tier. Your credit card will not be charged unless you exceed the Free Tier usage limits or choose to use paid services.
- 7. Identity Verification: You'll need to provide a phone number where you can receive a call from AWS. Follow the instructions to receive a verification code via phone call/sms. Enter the code to complete the identity verification process.
- 8. Choose a Support Plan: AWS offers a free Basic Support plan, for the Free Tier, the Basic Support plan is sufficient.
- 9. Complete the Signup: Review the information you've provided and click "Create Account and Continue" to complete the signup process.
- 10. Welcome to AWS: Your AWS Free Tier account is now created. You can access the AWS Management Console and start using the free services within the Free Tier limits.

Remember to monitor your usage and stay within the Free Tier limits to avoid unexpected charges. AWS Free Tier offers a variety of services at no cost for the first 12 months, but some services may have usage limits. Always check the AWS Free Tier documentation for the most up-to-date information on available services and usage limits.

Amazon Elastic Compute Cloud (Amazon EC2)

Amazon Elastic Compute Cloud (Amazon EC2) is a web service offered by Amazon Web Services (AWS) that provides resizable compute capacity in the cloud. With Amazon EC2, you can launch virtual servers known as "instances" to run applications, host websites, and handle various workloads. Here are some key points and features related to EC2 instances:

1. **Instance Types:** EC2 instances come in various types, each optimized for specific use cases. These types range from general-purpose instances to compute-optimized, memoryoptimized, storage-optimized, and GPU-accelerated instances. You can choose the instance type that best suits your workload's requirements.







- 2. Operating Systems: EC2 supports a wide range of operating systems, including Linux, Windows, and various BSD variants. You can select the operating system that suits your application needs.
- 3. **Instance Lifecycle:** EC2 instances can be launched, terminated, and stopped as needed. You are only billed for the compute capacity you use while the instance is running.
- 4. Amazon Machine Images (AMIs): AMIs are pre-configured templates that define the software, settings, and operating system for your EC2 instances. You can choose from a variety of AMIs provided by AWS or create custom AMIs.
- 5. Key pair: Key pairs are an essential security feature in AWS that helps protect your instances and data from unauthorized access. Always make sure to generate and manage your key pairs carefully and follow security best practices to ensure the safety of your AWS resources
- 6. **Security:** EC2 instances can be launched within Virtual Private Clouds (VPCs), and you can apply security groups and network access control lists to control inbound and outbound traffic to your instances. Additionally, you can use Identity and Access Management (IAM) for fine-grained access control.
- 7. **Storage Options:** EC2 instances can be attached to various types of storage, including Amazon Elastic Block Store (EBS) for block storage and instance store (also known as ephemeral storage) for temporary storage. EBS volumes are network-attached, allowing data to persist even if the instance is terminated.
- 8. Instance Metadata: EC2 instances have access to instance metadata, which includes information about the instance, such as instance type, IP address, and security group settings. This metadata can be used by applications running on the instance.

EC2 instances are a fundamental building block of AWS infrastructure, providing the flexibility and scalability needed to deploy a wide range of applications and workloads in the cloud. The choice of instance type, storage, and configuration depends on your specific use case and performance requirements.





Launching EC2 instances on Amazon Web Services (AWS) can be done through the AWS Management Console, AWS Command Line Interface (CLI), or AWS SDKs. Below, I'll provide step-by-step instructions for launching an EC2 instance using the AWS Management Console:

Step 1: Sign In to Your AWS Account

If you don't already have an AWS account, you'll need to create one. Once you have an account, sign in to the AWS Management Console at https://aws.amazon.com/console/.

Step 2: Navigate to the EC2 Dashboard

In the AWS Management Console, locate and click on the "Services" dropdown in the top left corner, then select "EC2" under the "Compute" section. This will take you to the EC2 Dashboard.

Step 3: Choose an Amazon Machine Image (AMI)

- On the EC2 Dashboard, click the "Launch Instance" button to start the instance creation process.
- Give the name of your server
- In the "Choose an Amazon Machine Image (AMI)" step:
 - Select an AMI from the provided list. You can choose from AWS's preconfigured AMIs .Click on AMAZON LINUX AMI

Step 4: Create or Select a Key Pair

You'll be prompted to create a new key pair or use an existing one. Click on create new key pair, give key pair name and create key pair. After creating a new key pair, make sure to download the private key file and keep it secure folder for further use.

Step 5: Choose an Instance Type

In the "Choose an Instance Type" step: Select the instance type that meets your computing needs. EC2 offers a variety of instance types optimized for different workloads. Click on t2.micro which is free tier eligible







Step 6: Configure Instance Details

- In the "Configure Instance Details" step, you can:
 - Choose the number of instances to launch.

Step 7: Configure Security Group

- In the "Configure Security Group" step, you can:
 - Choose an existing security group or create a new one.
 - Configure inbound and outbound rules to control network traffic to your instance.
 - Click on edit option on network settings and add security rules
 - Allow all traffic and allow anyip4 address

Step 8: Review and Launch

• In the "Review" step, review the configuration settings for your instance. Make sure everything is set up correctly.

Step 9: Launch the Instance

• After reviewing the instance details, click the "Launch" button.

Step 10: View Your Instances

You'll see a confirmation message indicating that your instances are launching. You can
track the status of your instances by going back to the EC2 Dashboard and clicking on
"Instances" in the left-hand navigation pane.

That's it! You've successfully launched EC2 instances on AWS. You can now connect to your instances using SSH (for Linux instances) and start using them for your specific workloads. Make sure to manage your instances, monitor their performance, and follow best security practices for AWS resources.







Connecting ec2 instances to Git bash

To connect to an Amazon EC2 instance using Git Bash (a Bash shell for Windows), you can use SSH (Secure Shell) if you're connecting to a Linux-based EC2 instance. Here are the steps to connect your EC2 instance to Git Bash:

Prerequisites:

- 1. Make sure you have already launched an EC2 instance in your AWS account.
- 2. You should have downloaded the private key file (e.g., your-key.pem) when launching the instance.

Step 1: Locate Your Private Key

Ensure that the private key file (your-key.pem) is stored in a directory on your local machine. For security reasons, it's a good practice to keep your private key in a secure location.

Step 2: Open Git Bash

- Create a newfolder on desktop and copy paste the keypair.pem file in this folder
- Now right click the mouse and open gitbash here

Step 3:Login to console and launch instances

> click on created instances and connect

Step 4: Set Appropriate Permissions for Your Private Key

SSH requires that the private key file is not publicly accessible, so you should change the permissions on the key file to make it more secure. Use the following command:

chmod 400 your-key.pem

And copy in git bash terminal









Step 5: Connect to Your EC2 Instance

- Use the **ssh** command to connect to your EC2 instance.
 - ssh -i your-key.pem ec2-user@YourInstancePublicIP (ssh -i "awskeypair.pem" ec2-user@ec2-3-87-128-182.compute-1.amazonaws.com)
- If you're connecting to an Ubuntu instance, replace ec2-user with ubuntu.

Step 6: Confirm the Connection

- When prompted, confirm the SSH connection by typing "yes" and pressing Enter.
- You should now be connected to your EC2 instance via SSH in Git Bash.

You can now use Git Bash to interact with your EC2 instance, execute commands, and manage your files on the server. Make sure to disconnect from the instance when you're done by typing **exit** and pressing Enter.Stop/terminate the instances after practice.

Remember to keep your private key secure and never share it with others. Additionally, ensure that the security group associated with your EC2 instance allows SSH traffic (port 22) from your local IP address.





LINUX COMMANDS

File commands		
sudo su -	Switching ec2 user to root user	
touch filename	Create the files	
mkdir dirname	Create the directories	
ls	Directory / files listing	
11	Long listing the files/directories	
ls -la	Formatted listing with hidden files	
ls -lt	Sorting the Formatted listing by time modification	
ls -lrth	Sorting the Formatted listing by time modification in reverse order	
cd	Changing directory to home directory	
cd /	Changing directory to root	
cd /opt	Navigating into Optional directory to create the files/directories	
cd dirname	Change directory to dirname	
cd	Coming out of current directory	
cd//	Coming out of two directories	
cd -	To go to the previous directory	
cd ~	Changing directory directly to user home directory	
pwd	Show current working directory	
mkdir dir1 dir2 dir3	Creating a multiple directories	
mkdir –p d1/d2/d3/d4	Creating nested directories	
cat filename	View data in the file	
more filename	Output the contents of the file	
head filename	Output the first 10 lines of the file	
tail filename	Output the last 10 lines of the file	
tail -n filename	Output display only last 10 lines	
touch file1 file 2 file3	Creating multiple files	
rm file	Deleting the file	
rm -r dir	Deleting the directory	
rm -f file	Force to remove the file	
rm -rf dir	Force to remove the directory dir	
cp file1 file2	Copy the contents of file1 to file2	
cp -r dir1 dir2	Copy dir1 to dir2;create dir2 if not present	
mv file1 file2	Rename or move file1 to file2, if file2 is an existing directory	





yum install tree	installing tree package
tree	To display the files and directories in tree structure
echo data >fname	To enter data directly to the fname

System info commands	
date	Show the current date and time
cal	Show this month's calendar
uptime	Show current uptime
w	Display who is on line
whoami	Who you are logged in as
Sleep <time></time>	To hold the terminal by the specified amount of time
uname -a	Show kernel information
cat /proc/cpuinfo	Cpu information
cat proc/meminfo	Memory information
man command	Show the manual data for command
df -h	Show the disk usage
df -Th	Show the disk usage and limit listing to file systems of type TYPE
du	Show directory/file space usage
du -sh	shows folder size and print sizes in human readable format
du -h	shows file size and print sizes in human readable format
free	Show memory and swap usage
who -r	displays run level
	init 0/1/2/3/4/5/6
	0 = stop/hang
	1 = singleuser
	2 = multiuser







CIRCUIT	3 = multiuser + n/w
	4 = reserved
	5 = cli +gui
	6 = reboot
whereis appname	Show possible locations of app
which appname	Show which applications will be run by default
yum install packagename	To install package
yum remove packagename	To remove installed pacakage
hostname	Displays the server name
hostname -I	Displays IP-address of server
hostnamectl set-hostname <name></name>	To set hostname
cat /etc/passwd	To view the user configuration

User commands		
sudo su -	switch to root user	
su - username	Switching user to another user	
id	To display the user ID	
useradd username	To add a user on a Linux server	
passwd password	To create the password for a user	
userdel –r username	To delete a user	
usermod –c "comment" user	Adding comment to the user	

process management commands







URUSII	
kill process id	kill the process for the given process id
kill -9 process id	Kill the process forcibly for the given process id
lscpu	Displays information about cpu
ps	To display the currently working processes
top	Displays all running process

Network commands	
ping google.com	To check connectivity with two nodes
whois domain	Get whois information for domains
dig domain	Get DNS information for domain
wget url	Download file
netstat	Display connection information

Compression commands	
zip –r data.zip filename	Create zip file named data.zip containing filename
unzip data.zip	Extracting .zip files from zip archive
tar -xvf file.tar	Extract the files from file.tar
tar cvf file.tar.gz filename	Change normal file to tar file





File permission commands	
chmod [options] [File_name]	Change the permission of file to octal, which can be found separately for user, group, world by adding, • 4-read(r) • 2-write(w) • 1-execute(x)
Change file permission	chmod <permission> <file name=""> u (Owner) - Permissions used for the owner of the file. g (Group) - Permissions used by members of the group. o (Other) - Permissions used by all other users. r (read) - permit to read the file. w (write) - permit to write the file. x (execute) - permit to execute the file.</file></permission>

Searching commands	
grep pattern file	Search for pattern in file
grep -r pattern dir	Search recursively for pattern in dir
yum install locate	install locate pacakge
updatedb	update db
ocate filename	Find all instances of filename
locate –n 5 filename	locates top 5 locations of given filename
pgrep pattern	Searches for all the named processes, that matches with the pattern and, by default, returns their ID







	Filter commands
cut -d(delimiter) -	To select a specific column of a file. The '-d' option is used as a
f(columnNumber)	delimiter, and it can be a space (' '), a slash (/), a hyphen (-), or
<filename></filename>	anything else. And, the '-f' option is used to specify a column
	number.
comm< fname1>	To compare two files or streams
<fname2></fname2>	
tree	To view files/directories in tree format
wc <fname></fname>	To count the lines, words, and characters in a file
wc -l fname	line count
wc -w fname	word count
wc –c fname	character count
sort <fname></fname>	To sort files in alphabetical order

Shortcuts	
ctrl+c	Halts the current command
ctrl+z	Stops the current command, resume with fg in the foreground or bg in the background
ctrl+d	Logout the current session, similar to exit
ctrl+w	Erases one word in the current line
ctrl+u	Erases the whole line
ctrl+r	Type to bring up a recent command
ctrl+l	clear the entire screen
!!	Repeats the last command
exit	Logout the current session



File system Hierarchy Standard (FHS) for Linux

```
cd /
root --> /

Il
/bin – binary or executable programs - other than root
/etc – system configuration files.
/home – home directory. It is the default current directory.
/opt – optional or third-party software.
/tmp – temporary space, typically cleared on reboot.
/usr – User related programs.
/var – log files.
/sbin – binary executable programs for root.
```

/root -- superuser account in Linux.

```
[root@ip-172-31-44-167 /]#
total 48
                                          2023 bin -> usr/bin
rwxrwxrwx.
                                7 Jan 30
                root root
                root root 16384 Nov
                                       1 22:44
                            3040 Nov
                                         09:24
                root root 16384 Nov
                                         05:19
                                       7
                              61 Nov
                                         04:49
                root root
                                               home
                                               lib -> usr/lib
                                  Jan
                                      30
                                           2023
                root root
                                9
                                 Jan 30
                                               lib64 -> usr/lib64
                root root
                                6
                                 Nov
                                         22:42 local
                root root
                                  Jan 30
                                           2023 media
                                6
                root root
                                  Jan 30
                               6
                                           2023
                root
                     root
              6
                              87
                                 Nov
                                        03:19
                                               opt
                root
                     root
            164
                                         09:24
                                0 Nov
                                                proc
                     root
              8
                root root 16384 Nov
                                         05:17
                                                root
                             800 Nov
                root root
                               8
                                  Jan 30
                                          2023 sbin -> usr/sbin
                root root
                                6 Jan 30
                root root
                root root
                                0 Nov
                                         09:24
                                         09:29
                root root
                             220 Nov
                             144 Nov
                                       1 22:43 usr
                root root
                             266 Nov
```





User stanza

username:userid:usergroup:comment:location:excitation

ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash

VI EDITOR

What is Vi?

The vi editor is elaborated as visual editor. It is installed in every Unix system. In other words, it is available in all Linux distros. It is user-friendly and works same on different distros and platforms. It is a very powerful application. An improved version of vi editor is vim.

The vi editor has two modes:

- Command Mode: In command mode, actions are taken on the file. The vi editor starts in command mode. Here, the typed words will act as commands in vi editor. To pass a command, you need to be in command mode.
- Insert Mode: In insert mode, entered text will be inserted into the file. The Esc key will take you to the command mode from insert mode.

By default, the vi editor starts in command mode. To enter text, you have to be in insert mode, just type 'i' and you'll be in insert mode. Although, after typing i nothing will appear on the screen but you'll be in insert mode. Now you can type anything.

To exit from insert mode press Esc key, you'll be directed to command mode.

Using vi

The vi editor tool is an interactive tool as it displays changes made in the file on the screen while you edit the file.

In vi editor you can insert, edit or remove a word as cursor moves throughout the file.









Commands are specified for each function like to delete it's x or dd.

The vi editor is case-sensitive. For example, p allows you to paste after the current line while P allows you to paste before the current line.

vi syntax: vi <filename>

In the terminal when you'll type vi command with a file name, the terminal will get clear and content of the file will be displayed. If there is no such file, then a new file will be created and once completed file will be saved with the mentioned file name.

Let's understand vi through an example:

To start vi open your terminal and type vi command followed by file name. If your file is in some other directory, you can specify the file path. And if in case, your file doesn't exist, it will create a new file with the specified name at the given location.

Example:

1. vi file

DELL@DESKTOP-TG07D38 MINGW64 ~/Desktop/test

Look at the above snapshot; we are creating a new file file

Command mode

This is what you'll see when you'll press enter after the above command. If you'll start typing, nothing will appear as you are in command mode. By default vi opens in command mode.









Look at the above snapshot; it is blank as it is a new file. To start typing, you have to move to the insert mode. At the end of the terminal window, directory name and file name are displayed.

Insert mode

To move to the insert mode press esc i.

Look at the above snapshot, after pressing i we have entered into insert mode. Now we can write anything. To move to the next line press enter.

Once you have done with your typing, press esc key to return to the command mode.









To save and quit

You can save and quit vi editor from command mode. Before writing save or quit command you have to press colon (:wq) .

exit vi table commands:

Commands	Action
:wq	Save and quit
:w	Save
:q	Quit
:w fname	Save as fname
:wq!	save and quit forcefully
:q!	Quit discarding changes made
:w!	Save (and write to non-writable file)

To exit from vi, first ensure that you are in command mode. Now, type :wq and press enter. It will save and quit vi.

Type:wq to save and exit the file







Look at the above snapshot, command: wq will save and quit the vi editor. When you'll type it in command mode, it will automatically come at bottom left corner.

Vi Commands

Linux vi editor is different from other editors. You have to use different keys to use different functions. Although, it's quite easy and interesting to use vi editor.

The vi editor commands are case sensitive.

Have a look at the vi commands in the following table.

To switch from command to insert mode(esc):

Command	Action
i	Start typing before the current character
I	Start typing at the start of current line
a	Start typing after the current character
A	Start typing at the end of current line
0	Start typing on a new line after the current line
О	Start typing on a new line before the current line







Commands	Action
j	To move down
k	To move up
h	To move left
1	To move right

To jump lines:

Commands	Action
G	Will direct you at the last line of the file
gg	Will direct you to your first position in the file

To delete:

Commands	Action
х	Delete the current character
X	Delete the character before the cursor
r	Replace the current character
xp	Switch two characters
dd	Delete the current line
D	Delete the current line from current character to the end of the line





dG	delete from the current line to the end of the file

To repeat and undo:

Commands	Action
u	Undo the last command
	Repeat the last command

Command to cut, copy and paste:

Commands	Action
dd	Delete a line
уу	(yank yank) copy a line
p	Paste after the current line
Р	Paste before the current line

Command to cut, copy and paste in blocks:

Commands	Action
<n>dd</n>	Delete the specified n number of lines
<n>yy</n>	Copy the specified n number of lines







Commands	Action
θ	Bring at the start of the current line
٨	Bring at the start of the current line
\$	Bring at the end of the current line
dθ	Delete till start of a line
d\$	Delete till end of a line

Joining lines:

Commands	Action
J	Join two lines
уур	Repeat the current line
ddp	Swap two lines

Move forward or backward:

Commands	Action
w	Move one word forward
b	Move one word backward







<n>w</n>	Move specified number of words forward
dw	Delete one word
yw	Copy one word
<n>dw</n>	Delete specified number of words

More commands

:set nu or :set number	to set the numbering in vi editor
:set nonu or :set nonumber	to remove the numbering in vi editor
/ word or character	to search a word or character

awk command

awk command :	awk is a scripting language used for manipulating data and generating
	reports
awk '{print}' fname	To display data
awk '{print \$1,\$4}' fname	Prints 1 st and 4 th column only
awk '/word/{print}' fname	Prints all the line which matches with the 'word'.
awk '{print NR,\$0}' fname	NR prints all the lines along with the line
	number.
awk '{print NR "- " \$1 }' fname	To print the first item along with the row
	number(NR)
	separated with "-" from each line







Linux interview question

- https://qaremote.jobs/blog/linux-interview- $\underline{questions/?gclid=Cj0KCQiAuqKqBhDxARIsAFZELmKZ7M7vGMlBWvfViOhD4}$ AWW9E5FHo6hHfpf3mWS23vjGthc4YblXmYaAjAkEALw_wcB
- > https://www.geeksforgeeks.org/linux-interview-questions/