Preceding material.

II Computational determination of the elements of $\widetilde{N}^{!}_{0,3}$.

1) Determination by h, g, f.

The specification of $u \in \widetilde{M}^{!}_{0,3} | \widetilde{N}^{!}_{0,3}$

Recall that

(21) $\widetilde{N}^{!}_{0,3} | \widetilde{M}^{!}_{0,3}$ = automorphisms of $\widehat{\mathcal{G}}^{+}_{0,3} \simeq \mathrm{Sl}(2,\mathbb{Z})^{\wedge\prime} | \widehat{\mathrm{Sl}(2,\mathbb{Z})^{\prime}}$ that stabilize $\widehat{\Pi}_{0,3}$, induce the identity on $\mathfrak{S}_3 | \mathcal{G}_3 = \widehat{\mathcal{G}}^{+}_{0,3} / \widehat{\Pi}_{0,3}$, and preserve the loop structure (defined by the class of ε_0)

End of opening paragraph.

Preceding material.

II Computational determination of the elements of $\widetilde{N}^{!}_{0,3}$.

1) Determination by h, g, f.

d1

Recall that

(21) $\widetilde{N}^{!}_{0,3}|\widetilde{M}^{!}_{0,3}$ = automorphisms of $\widehat{\mathcal{G}}^{+}_{0,3} \simeq \mathrm{Sl}(2,\mathbb{Z})^{\wedge\prime}|\widehat{\mathrm{Sl}(2,\mathbb{Z})}'$ that stabilize $\widehat{\Pi}_{0,3}$, induce the identity on $\mathfrak{S}_3|\mathcal{G}_3 = \widehat{\mathcal{G}}^{+}_{0,3}/\widehat{\Pi}_{0,3}$, and preserve the loop structure (defined by the class of ε_0)

End of opening paragraph.

Preceding material.

II Computational determination of the elements of $\widetilde{N}^{!}_{0,3}$.

1) Determination by h, g, f.

†

Recall that

(21) $\widetilde{N}^{!}_{0,3}|\widetilde{M}^{!}_{0,3}$ = automorphisms of $\widehat{\mathcal{G}}^{+}_{0,3} \simeq \mathrm{Sl}(2,\mathbb{Z})^{\wedge\prime}|\widehat{\mathrm{Sl}(2,\mathbb{Z})}^{\prime}$ that stabilize $\widehat{\Pi}_{0,3}$, induce the identity on $\mathfrak{S}_3|\mathcal{G}_3 = \widehat{\mathcal{G}}^{+}_{0,3}/\widehat{\Pi}_{0,3}$, and preserve the loop structure (defined by the class of ε_0)

End of opening paragraph.