

Exact signed operator, pulse and covariance bridges

This reader contains the complete three finite calculations. It retains the original coupled-stage system, both physical diffusivities, source chart factors, signed amplitudes, and all displayed residual terms. The companion 102-page coupled-stage reader remains the complete finite growth/return construction.

The reference source is the preserved 165-page supplied manuscript. A later 166-page revision was also checked on the 31 source equations used here: (7.2)–(7.8), (7.22)–(7.42), (9.12)–(9.14). The bounded comparison found no displayed formula change there. This does not certify the whole manuscript or equivalence of its two versions. The source identifiers are:

165 pages: 8c8a94ad9ac824c8b605b9827cadf7beaca48bd10b380de3cfc872a2c37afa81
166 pages: 0e779481c4da40bd28d1e642e1d8ca57447d129610df28dfa5a11e9af8ae228f

Exact page maps and the unchanged raw text of pages 108–110 are documented in `revision_check/REPORT.md`. The coupled Boussinesq source is the work of Levent Alpöge and Tristan Buckmaster.

Contents

I	Axisymmetric operators and reconstruction	3
1	Exact operator bridge to the released Navier–Stokes profiles	3
II	Coupled amplitudes and the full pulse residual	6
2	Scope and source equations	6
3	The coupled physical pair	6
4	Exact local residual map	7
5	Pressure reconstruction and full three-dimensional residual	7
6	Diffusion and energy comparison	8
7	Proven scope	9
III	Physical curl, signed covariance and the retained remainder	10
8	Source objects and the finite calculation	10

9	Physical curl of the actual retained amplitude	10
10	Radial moments, support, and the original chart scales	12
11	The source covariance derivative and its signed right inverse	13
12	Assembly, the actual covariance change, and residual cancellation	13
13	Signs and the exact full-flow reflection	15

Part I

Axisymmetric operators and reconstruction

1 Exact operator bridge to the released Navier–Stokes profiles

This bounded comparison uses the locally saved released Navier–Stokes source (the source pages are 7–15 and 24–27 for the profile, stress and pulse construction). Its stated physical viscosity is denoted by $\nu_{\text{NS}} > 0$. The Boussinesq lane variables and physical viscosity remain d, μ and $\nu = \sqrt{A_0}$; none is identified with ν_{NS} .

Use right-handed cylindrical coordinates (r, ϑ, z) and define

$$y_1 = z, \quad y_2 = \frac{r^2}{2} > 0, \quad v = (u^z, ru^r) = J \nabla_y \Psi, \quad J = \begin{pmatrix} 0 & -1 \\ 1 & 0 \end{pmatrix}.$$

The meridional divergence identity is $\partial_{y_1} v_1 + \partial_{y_2} v_2 = 0$. Define the circulation and meridional vorticity variables

$$\Gamma = ru^\vartheta, \quad \xi = \frac{\omega^\vartheta}{r}, \quad h = \frac{\Gamma}{2y_2} = \frac{u^\vartheta}{r}, \quad Q = \partial_{y_1}^2 + 2y_2 \partial_{y_2}^2, \quad M = Q + 4\partial_{y_2}.$$

The azimuthal momentum and meridional vorticity rows of the cylindrical equations (with arbitrary smooth force components) become, on $y_2 > 0$,

$$D_v \Gamma = \nu_{\text{NS}} Q \Gamma + r f^\vartheta, \quad (1)$$

$$D_v \xi = \nu_{\text{NS}} M \xi + \partial_{y_1} (h^2) + \text{curl}_y (f^z, f^r/r), \quad (2)$$

where $D_v = \partial_t + v \cdot \nabla_y$ and $\text{curl}_y(a, b) = \partial_{y_1} b - \partial_{y_2} a$.

Indeed, $\partial_r = r \partial_{y_2}$ and $\partial_r^2 + r^{-1} \partial_r = 2y_2 \partial_{y_2}^2 + 2\partial_{y_2}$. For Γ , the azimuthal viscous operator is $\partial_r^2 - r^{-1} \partial_r + \partial_z^2 = Q$. For $r\xi = \omega^\vartheta$, the cylindrical operator $(\partial_r^2 + r^{-1} \partial_r - r^{-2} + \partial_z^2)(r\xi)$, divided by r , is $M\xi$; explicitly the radial terms are $2y_2 \xi_{y_2 y_2} + 4\xi_{y_2}$. The centrifugal term is $r^{-2} \partial_z((u^\vartheta)^2) = \partial_{y_1}(\Gamma^2/(4y_2^2)) = \partial_{y_1}(h^2)$. These calculations prove every coefficient in (1)–(2), including the r force conversion.

The velocity–vorticity relation is also retained. Since $u^z = -\Psi_{y_2}$ and $u^r = \Psi_{y_1}/r$,

$$\xi = \frac{\partial_z u^r - \partial_r u^z}{r} = \frac{\Psi_{y_1 y_1}}{2y_2} + \Psi_{y_2 y_2} = \frac{Q\Psi}{2y_2}.$$

Thus the two transport rows do not by themselves replace the elliptic velocity reconstruction. Conversely, on a simply connected meridional domain, a smooth Ψ, Γ satisfying this relation and both transport rows recovers u . Define its momentum residual without pressure as $a = \partial_t u + (u \cdot \nabla)u - \nu_{\text{NS}} \Delta u - f$. The circulation row is $a^\vartheta = 0$, while the vorticity row is $\partial_z a^r - \partial_r a^z = 0$. The one-form $a^r dr + a^z dz$ is therefore closed, and $p = -\int (a^r dr + a^z dz)$ along a path from a fixed base point is path independent. Its derivatives are $p_r = -a^r$, $p_z = -a^z$. This proves the local momentum reconstruction, with pressure unique up to a function of time; boundary data are not removed.

The change from circulation to swirl rate is invertible on the exact retained domain: $\Gamma = 2y_2 h$. Product differentiation gives

$$Q(2y_2 h) = 2y_2 M h, \quad D_v(2y_2 h) = 2y_2 D_v h + 2v_2 h.$$

Therefore (1) is equivalent to

$$D_v h = \nu_{\text{NS}} M h - \frac{v_2}{y_2} h + \frac{f^\vartheta}{r}. \quad (3)$$

The source profile uses precisely this relation: in its similarity variables, E is the azimuthal velocity profile and $H_{\text{src}} = \sqrt{2X}E$ is the scaled circulation profile (source equations (4.3), (4.8)). Since $r = \sqrt{2qX}$ and $u^\vartheta = q^{-A}E$, its physical circulation is $\Gamma = q^{1/2-A}H_{\text{src}} = q^{-h_{\text{src}}}H_{\text{src}}$, where the source exponents satisfy $A = 1/2 + h_{\text{src}}$. Here $q > 0$ is the geometric similarity coordinate and $h_{\text{src}} > 0$ is an exponent; neither is a signed amplitude scale. This is the exact scale dictionary; it does not identify H_{src} with the Boussinesq scalar amplitude.

The sign of the blowout amplitude must be kept separate from that positive geometric coordinate. The axisymmetric equations have the exact involution

$$(u^r, u^\vartheta, u^z, p; f^r, f^\vartheta, f^z) \longmapsto (u^r, -u^\vartheta, u^z, p; f^r, -f^\vartheta, f^z).$$

It sends (Γ, h) to $(-\Gamma, -h)$, leaves ξ and the meridional flow unchanged, and preserves every displayed equation: the only quadratic swirl term is $\partial_{y_1}(h^2)$, while the azimuthal equation is linear in (Γ, f^ϑ) . Consequently a source-selected positive profile $E > 0$ (source pp. 7–9) does not justify assuming that every blowout branch is positive; its reflected branch has $E < 0$, $\Gamma < 0$ and the same blowup magnitude. The exponent $q^{-h_{\text{src}}}$ controls the magnitude in either branch. The source's positive covariance coefficients and viscosity are separate construction choices, not a sign claim about the velocity amplitude.

For comparison with the lane's controlled scalar equation, set $B = h^2$. The globally smooth square equation, including its geometric and viscous terms, is

$$D_v B = \nu_{\text{NS}} M B - 2\nu_{\text{NS}} |\nabla h|_Q^2 - \frac{2v_2}{y_2} B + \frac{2h}{r} f^\vartheta, \quad |\nabla h|_Q^2 = h_{y_1}^2 + 2y_2 h_{y_2}^2. \quad (4)$$

This follows by multiplying (3) by $2h$ and using $M(h^2) = 2hMh + 2|\nabla h|_Q^2$. At zeros of h equation (4) remains smooth; dividing by B is unnecessary and would lose that domain. On a component where $B > 0$, the equivalent expression is $D_v B = \nu_{\text{NS}} M B - \nu_{\text{NS}} |\nabla B|_Q^2 / (2B) - 2v_2 B / y_2 + 2h f^\vartheta / r$.

The exact relation to the Boussinesq lane is consequently an operator correspondence, not a scalar conjugacy. The lane's retained-viscosity scalar row has $D_v \Theta = d\Delta \Theta + f_\Theta$ in Cartesian material coordinates. A direct identification $\Theta = B$ would require, on the same physical domain, both $M = \Delta$ after the nonlinear coordinate pullback and $-2v_2 B / y_2 - 2\nu_{\text{NS}} |\nabla h|_Q^2 + 2h f^\vartheta / r$ to be absorbed into one prescribed force. The first condition fails as an operator identity: $M = \partial_{y_1}^2 + 2y_2 \partial_{y_2}^2 + 4\partial_{y_2}$ has variable metric and drift, whereas the lane's Δ is the Euclidean Cartesian Laplacian. The geometric, gradient and force terms must therefore be retained or calculated in the particular source state. Nonconstant profiles alone would not prove that such terms never cancel. The exact bridge is (1)–(4) with the full residual terms retained. It neither claims that the lane's controls are the source pulses nor changes the source's pressure reconstruction.

For the meridional velocity, the source's pulse construction supplies the following further exact local dictionary (source pp. 11–15 and 74–77). If w is a divergence-free pulse and π its pressure increment, then

$$R(u_B + w, p_B + \pi) = R(u_B, p_B) + L_{u_B}(w, \pi) + \nabla \cdot (w \otimes w),$$

$$L_{u_B}(w, \pi) = \partial_t w + (u_B \cdot \nabla) w + (w \cdot \nabla) u_B - \nu_{\text{NS}} \Delta w + \nabla \pi, \quad \nabla \cdot w = 0.$$

For the moving local phase with wavevector n and transverse amplitude t_m , the source equation is

$$t'_m + \mathcal{K} t_m + m^2 d_N t_m + i k m n \pi_m = -f_m, \quad n \cdot t_m = 0, \quad d_N = \varepsilon k^2 |n|^2,$$

with the source's moving shear matrix $\mathcal{K} = \begin{pmatrix} 0 & -2F & 0 \\ 2F + RF_R & 0 & 0 \\ G_R & 0 & 0 \end{pmatrix}$. The transverse projection uses

$$A_\Phi = -\mathcal{K} + \frac{n(n^T \mathcal{K} - n'^T)}{|n|^2}.$$

These are exact source pulse equations, including viscosity and pressure projection. Their quadratic covariance is chosen to cancel the annular stress; the source explicitly retains curl, cutoff, and correction interactions. The Boussinesq lane's two-dimensional pair and its full profile residuals have an exact algebraic form, but no identification with this three-dimensional pulse equation follows without an additional embedding that supplies the source's cylindrical geometry, moving plane, covariance cone and correction cycle. That embedding is not asserted here.

The current bridge therefore proves a precise morphism of variables, operators, forces and pulse residuals and records the exact obstruction to a direct scalar identification. It establishes the next programme datum while preserving the unproved status of any singular limit or third return.

Part II

Coupled amplitudes and the full pulse residual

2 Scope and source equations

This note records one local, exact comparison. It does not identify the coupled Boussinesq stages with the released Navier–Stokes construction and makes no claim about a global Navier–Stokes solution. The source is the released PDF `openai_navier_stokes.pdf`, SHA-256 `8c8a94ad9ac824c8b605b9827cadf7beaca48bd10b380de3cfc872a2c37afa81`. The source statements used here are Section 7, equations (7.2)–(7.8), (7.12)–(7.22), and Section 9, equations (9.1)–(9.2), on PDF pages 74–75, 77–81, and 101–103. In the source notation, on one lifted pulse rectangle,

$$\Phi = p\theta + p_z Z/\varepsilon + x_0 R - v(pF + p_z G), \quad n = \nabla_* \Phi, \quad (5)$$

with

$$n = (x_0 - v(pF_R + p_z G_R), \quad p/R, \quad p_z - \varepsilon v(pF_Z + p_z G_Z)). \quad (6)$$

For a nonzero integer harmonic m , the exact principal pulse equations are

$$n \cdot t_m = 0, \quad t'_m + K t_m + m^2 d_N t_m + i k m n \pi_m = -f_m, \quad d_N = \varepsilon k^2 |n|^2, \quad (7)$$

where a prime is the pulse-coordinate derivative and

$$K = \begin{pmatrix} 0 & -2F & 0 \\ 2F + R F_R & 0 & 0 \\ G_R & 0 & 0 \end{pmatrix}, \quad A_\Phi = -K + \frac{n(n^T K - (n')^T)}{|n|^2}. \quad (8)$$

The source pressure coefficient is exactly

$$\pi_m = \frac{i}{k m |n|^2} (n \cdot K t_m - (n') \cdot t_m + n \cdot f_m). \quad (9)$$

For $m = 1$, a real homogeneous pulse t_1 has the source energy identity (7.22):

$$\frac{1}{2}(|t_1|^2)' = -g \cdot (t_{1,r}(t_{1,\theta}, t_{1,z})) - \varepsilon k^2 |n|^2 |t_1|^2, \quad (10)$$

where $g = (R F_R, G_R)$ in the tangential coordinates. Thus the source pulse retains both shear transfer and viscous dissipation.

3 The coupled physical pair

For one activated layer of the coupled calculation, put

$$a_c = -\frac{J\zeta \cdot G_{<q}}{K r^2}, \quad b_c = K \zeta_1, \quad \lambda_c^\Theta = \kappa K^2 r^2, \quad \lambda_c^\Omega = \varepsilon_c K^2 r^2. \quad (11)$$

Its exact retained-viscosity pair, including optional scalar and vorticity controls, is

$$\dot{y} = C_c y + c_c, \quad y = \begin{pmatrix} \Theta \\ \Omega \end{pmatrix}, \quad C_c = \begin{pmatrix} -\lambda_c^\Theta & a_c \\ b_c & -\lambda_c^\Omega \end{pmatrix}, \quad c_c = \begin{pmatrix} c_\theta \\ c_\omega \end{pmatrix}. \quad (12)$$

Here $G_{<q}$, ζ , and r evolve with the inherited background and phase ODEs; in particular no fixed-background substitution is made. Let v be a source pulse coordinate on an interval and let $q_v = dt/dv$ describe its physical-time parametrization. The forward source parametrization has $q_v > 0$; the algebra below also retains a negative orientation without changing the amplitude sign. Define $y'(v) = q_v(C_c y + c_c)$. Here K, r are the coupled frequency and phase length, not the source carrier k and cylindrical radius R . The original A_0, λ_0, μ and time scale $\nu = \sqrt{A_0}$ are unchanged. The source chart parameter ε is not identified with either physical diffusivity.

4 Exact local residual map

Let $B(v) \in \mathbb{R}^{3 \times 2}$ be a C^1 tangent frame with full column rank and $n(v)^T B(v) = 0$, so its range is exactly $n(v)^\perp$. Let $B_\ell(v)$ be any left inverse, $B_\ell B = I_2$; then $B B_\ell$ acts as the identity on $n^\perp$. Let $L(v) \in \mathbb{R}^{2 \times 2}$ be any C^1 coefficient map and embed the coupled pair into a transverse source amplitude by

$$t(v) = B(v)L(v)y(v). \quad (13)$$

For an embedding with a non-tangent frame the transversality condition would be

$$n(v)^T B(v)L(v)y(v) = 0. \quad (14)$$

For the tangent frame used here, the condition holds for every L, y . Set

$$H(v) = B_\ell(v)(A_\Phi(v)B(v) - B'(v)). \quad (15)$$

Then the exact projected source residual of the embedded coupled pair is

$$\mathcal{E}_{L,c} := B_\ell \text{proj}_{n^\perp} [t' - A_\Phi t + m^2 d_N t + f_m] = [L' + q_v L C_c - H L + m^2 d_N L] y + q_v L c_c \quad (16)$$

$$+ B_\ell \text{proj}_{n^\perp} f_m. \quad (17)$$

In particular, with $L = I$ and no added source, the defect is the explicit matrix expression

$$\mathcal{E}_{I,0} = (q_v C_c - H + m^2 d_N I_2) y. \quad (18)$$

This gives a local residual relation with every actual coefficient retained.

Proof. Differentiate (13): $t' = B' L y + B L' y + B L y'$. Since $y' = q_v(C_c y + c_c)$, differentiate $n^T B = 0$ to obtain $n^T B' = -(n')^T B$. Also $n^T A_\Phi B = -(n')^T B$, directly from (8). Thus $A_\Phi B - B'$ has transverse range and equals BH . Applying B_ℓ to the transverse terms and $B_\ell \text{proj}_{n^\perp}$ to the force proves (17). More explicitly,

$$n^T(t' - A_\Phi t + m^2 d_N t) = 0, \quad n^T(t' - A_\Phi t + m^2 d_N t + f_m) = n^T f_m. \quad (19)$$

The unprojected force need not be transverse. The pressure below removes precisely this remaining normal component. $\square$

5 Pressure reconstruction and full three-dimensional residual

For any embedded transverse t and arbitrary f_m , define

$$\pi_{L,c} = \frac{i}{km|n|^2} (n \cdot K t - (n') \cdot t + n \cdot f_m). \quad (20)$$

Then the full source residual satisfies the exact decomposition

$$\mathcal{R}_{L,c} := t' + \mathbf{K}t + m^2 d_N t + ikmn\pi_{L,c} + f_m \quad (21)$$

$$= \text{proj}_{n^\perp} (t' + \mathbf{K}t + m^2 d_N t + f_m) = B \mathcal{E}_{L,c}, \quad (22)$$

where the last equality uses the definition of H and the transverse condition. Thus the pressure removes precisely the normal component; it does not remove $\mathcal{E}_{L,c}$, the moving-frame, shear, diffusion, or coupled-background mismatch. If one elects to force the source pulse to obey the released equation, then the unique additional transverse forcing is

$$f_{m,\text{corr}} = -B \mathcal{E}_{L,c}, \quad (23)$$

added to the old f_m . The old $\mathcal{E}_{L,c}$ is evaluated before this addition, so the new projected residual is zero. Since $n^T f_{m,\text{corr}} = 0$, pressure is unchanged. This is an exact local forced relation, not an identification of the physical constructions.

6 Diffusion and energy comparison

The source diffusion multiplier is $m^2 d_N = m^2 \varepsilon k^2 |n|^2$ in (7). The coupled pair has the two retained physical losses λ_c^Θ and λ_c^Ω , which are generally unequal to $m^2 d_N$. Their signed discrepancy in (18) is explicitly

$$(m^2 d_N - q_v \lambda_c^\Theta) \Theta, \quad (m^2 d_N - q_v \lambda_c^\Omega) \Omega \quad (24)$$

when $H = 0$ and C_c is expanded entrywise; with general H the exact diagonal entries are those of $q_v C_c - H + m^2 d_N I_2$. No damping is dropped. If one compares nonnegative loss magnitudes instead, the corresponding cost gaps are $|m^2 d_N - q_v \lambda_c^\Theta|$ and $|m^2 d_N - q_v \lambda_c^\Omega|$. The required finite-interval coordinate map can be constructed explicitly. Let $I = [v_0, v_1]$, and let X_c, X_s be the identity-initial-value fundamental matrices for $D_c = q_v C_c$ and $D_s = H - m^2 d_N I_2$, respectively. For either continuous matrix D , define

$$X_D(v) = I_2 + \sum_{j \geq 1} \int_{v_0 \leq w_j \leq \dots \leq w_1 \leq v} D(w_1) \cdots D(w_j) \, dw_j \cdots dw_1.$$

With $M_D = \sup_I \|D\|$ and $T_I = v_1 - v_0$, the j th integral has norm at most $(M_D T_I)^j / j!$. Uniform convergence proves the integral equation $X_D = I_2 + \int_{v_0}^v D X_D$ and hence $X_D' = D X_D$. The same iteration for $Z' = -ZD$, $Z(v_0) = I_2$ gives $Z X_D = I_2$ by differentiation, proving invertibility on I . For a specified invertible L_0 , set

$$L = X_s L_0 X_c^{-1}, \quad L^{-1} = X_c L_0^{-1} X_s^{-1}.$$

This has norm at most $\|L_0\| e^{(M_c + M_s) T_I}$; its inverse has the same bound with L_0^{-1} . Differentiation proves

$$L' = H L - q_v L C_c - m^2 d_N L, \quad (25)$$

so the homogeneous embedded pair has zero projected residual. This proves an actual finite-interval conjugacy along the retained coefficient path. It does not make the source phase, pressure, cutoff, or nonlinear covariance equal to the coupled Boussinesq fields. For general controls c_c , the forced term is $q_v L c_c$ in (17).

For an arbitrary embedded field (possibly complex), the exact energy balance retains its full defect:

$$\begin{aligned} \frac{1}{2}(|t|^2)' = & -\operatorname{Re}(\bar{t}^T \mathbf{K} t) - m^2 d_N |t|^2 - \operatorname{Re}(\bar{t}^T f_m) \\ & + \operatorname{Re}(\bar{t}^T B \mathcal{E}_{L,c}). \end{aligned} \quad (26)$$

This follows by taking the real Hermitian product of (22) with t . Its pressure term vanishes because n is real and $n^T t = 0$. The $2F$ part of $\mathbf{K}$ is skew-symmetric, hence its real work is zero; the shear work equals $\operatorname{Re}(\bar{t}_r(g_\theta t_\theta + g_z t_z))$. Only for a zero residual, zero force, $m = 1$, and real t does this reduce to (10). The real coupled pair has

$$\frac{1}{2} \frac{d}{dt} |y|^2 = -\lambda_c^\Theta \Theta^2 - \lambda_c^\Omega \Omega^2 + (a_c + b_c) \Theta \Omega + c_\theta \Theta + c_\omega \Omega, \quad (27)$$

which is a two-component physical energy identity. Equations (17) and (27) exhibit exactly where the source's three-dimensional shear flux and the coupled pair's two-dimensional exchange differ.

7 Proven scope

The source uses a cylindrical, localized, divergence-free curl construction (Section 7.4 and Section 9, PDF pages 85–87 and 102–103); the displayed principal pulse equation is only one component of that construction. The comparison above proves an exact local map and its full pressure-projected residual for every finite interval on which the denominators and frame left inverse exist. It preserves source viscosity, moving phase normal, pressure, rotation/shear matrix, and all coupled physical diffusion coefficients. It does not prove that the coupled third-growth or steering stages produce the source's pulse phase Φ , covariance, cutoff tails, or smooth terminal force. Those remain separate bridge problems.

The sign conventions in this comparison are also explicit. The quantities $q_v > 0$, $\varepsilon > 0$, and $d_N = \varepsilon k^2 |n|^2 > 0$ record the chosen orientation of physical time and the positive viscous coefficient; they are not assumptions on the sign of a pulse or blowout amplitude. The equations (7)–(9) are linear in (t_m, f_m) , so the simultaneous replacement $(t_m, f_m, \pi_m) \mapsto (-t_m, -f_m, -\pi_m)$ is an exact reflected branch. Likewise, the local map (13) is sign-equivariant under $y \mapsto -y$ and $c_c \mapsto -c_c$, with the coefficients fixed at the actual path. This is a statement about the retained linear equations, not a sign symmetry of the entire coupled nonlinear system. The source covariance is quadratic, so reversing a wave leaves that covariance unchanged. Reversing the full Navier–Stokes velocity need not reverse its force, since $(u \cdot \nabla)u$ is even in u . The full-flow map that reverses axisymmetric swirl is a spatial reflection; its complete formula is proved in the accompanying covariance bridge. No sign of a blowout or endpoint is inferred from positive geometric scales.

Part III

Physical curl, signed covariance and the retained remainder

8 Source objects and the finite calculation

This calculation uses the preserved 165-page supplied manuscript *Finite Time Blowup for Navier–Stokes*, source equations (7.23)–(7.42), (9.12)–(9.14). Its PDF SHA-256 is

8c8a94ad9ac824c8b605b9827cadf7beaca48bd10b380de3cfc872a2c37afa81.

The source pulse fields, auxiliary rectangles, phases, and leading covariance columns are the given objects; their global construction is source input. Every finite map asserted below is proved here. The existing coupled-stage proofs remain in the complete 102-page reader. The companion pulse note proves the exact frame residual and a constructed finite-interval intertwiner along its evolving coefficients. The source uses positive $q(z, t)$, band scales $Q_\beta = 2^{-\ell_\beta}$, $\varepsilon_\beta = Q_\beta^h$, $A = 1/2 + h$; none is set to one here or identified with the original coupled $A_0, \lambda_0, \mu, \nu = \sqrt{A_0}$ or its physical diffusivities.

All operations in this note are on a compact set inside $q > 0$ and the source active annulus. There are finitely many relevant bands and locally finite source labels. Supports of newly prescribed inputs are strictly inside the annulus, so no lower bound on a leading amplitude at a vanishing shell edge is assumed. Endpoint and shell-edge estimates are not inferred from compact-interior estimates.

9 Physical curl of the actual retained amplitude

Let $y = (\Theta, \Omega)^T$ be the actual smooth retained coupled solution, $y' = q_v(C_c y + c_c)$, with the coefficients of the companion pulse note. Use the smooth actual coefficients on the chosen slow/auxiliary patch; all harmonic coefficients and cutoffs are independent of θ in cylindrical components, and each carrier has nonzero integer angular frequency. For its source tangent frame B , smooth coefficient map L , and a fixed smooth real compact cutoff χ of this type, put

$$t_m = \chi B L y, \quad \mathcal{E}_\chi = \chi \{ [L' + q_v L C_c - H L + m^2 d_N L] y + q_v L c_c \} + \chi' L y, \quad H = B_\ell (A_\Phi B - B').$$

Here prime differentiates along the pulse coordinate; the other slow and auxiliary derivatives remain in the spatial formulas below. Smooth parameter dependence of the companion's constructed L follows directly from its integral equations on a fixed interval: for a nonzero parameter multi-index I ,

$$\partial^I X(v) = \int_{v_0}^v \left[D \partial^I X + \sum_{0 < J \leq I} \binom{I}{J} (\partial^J D) \partial^{I-J} X \right] dw.$$

The initial parameter derivatives vanish for identity initial data. Inductively the known forcing is smooth and bounded on the compact patch; the same convergent ordered-integral iteration solves this equation. This proves every finite mixed derivative of X, X^{-1}, L . Since $n^T B = 0$, $n^T t_m = 0$. Differentiation proves $t'_m - A_\Phi t_m + m^2 d_N t_m = B \mathcal{E}_\chi$. Thus even the pulse-cutoff term is explicit.

A physical version of the exact curl construction makes the intermediate map to momentum residual unambiguous. For each chosen harmonic let $\phi(x, t) = k_\beta m \Phi_\beta(x, t, Y(x, t))$ be its real evaluated phase, let $\xi = \nabla_x \phi \neq 0$, and let $a(x, t) = Q_\beta^{-A} t_m$ be the physical transverse amplitude.

The source coordinate change is $r = \sqrt{Q_\beta}R$, $z = Q_\beta^D Z$, $1 - t = Q_\beta T$, with $D = 1/2 - h$ and normalized axial derivative $D_z = \varepsilon_\beta \partial_Z$. It gives $\xi = (k_\beta m / \sqrt{Q_\beta}) n_\Phi$; all auxiliary chain derivatives are included in n_Φ . Hence $\xi \cdot a = 0$. Define in Cartesian components

$$C = \frac{i \xi \times a}{|\xi|^2}, \quad \mathcal{A} = C e^{i\phi}, \quad \nabla \times \mathcal{A} = (a + r_a) e^{i\phi}, \quad r_a = \nabla \times C. \quad (28)$$

The vector triple-product identity gives $i \xi \times C = a$, proving the last equality. It also shows that the physical potential has exactly the source factor $Q_\beta^{1/2-A}$ relative to its chart coefficient $i n_\Phi \times t_m / (k_\beta m |n_\Phi|^2)$. Cartesian differentiation of C includes derivatives of the cylindrical basis; the same terms are the R^{-1} terms of source (7.37)–(7.38). Take real parts and sum the finite retained harmonics. This constructs a smooth compact velocity w_y with $\nabla \cdot w_y = 0$.

Retain a finite smooth source state (u_*, p_*) , including its background, actual leading waves and their curl corrections, and the real physical pressure increments obtained from the companion pulse pressure formula with $f_m = 0$:

$$\pi_{\chi, m} = \frac{i}{k_\beta m |n|^2} (n^T \mathbf{K} t_m - (n')^T t_m), \quad \pi_y = \sum_{\beta, m} \text{Re}(Q_\beta^{-2A} \pi_{\chi, m} e^{i\phi_{\beta, m}}).$$

These are smooth and compact wherever t_m is. This definition fixes the pressure map without assuming the pulse residual vanishes. Define the actual candidate residual

$$R_y = R_{\nu_{\text{NS}}}(u_* + w_y, p_* + \pi_y), \\ R_{\nu_{\text{NS}}}(u, p) := \partial_t u + (u \cdot \nabla) u - \nu_{\text{NS}} \Delta u + \nabla p. \quad (29)$$

This is a definition by explicit differentiated fields, not an assumed source term. Its exact expansion is

$$R_y = R_{\nu_{\text{NS}}}(u_*, p_*) + \partial_t w_y + (u_* \cdot \nabla) w_y + (w_y \cdot \nabla) u_* - \nu_{\text{NS}} \Delta w_y + \nabla \pi_y + (w_y \cdot \nabla) w_y.$$

Every cutoff, parent, phase, and curl derivative occurs in this formula. Physical ν_{NS} is retained and is distinct from every source time-scaling convention. Define $\Delta R_y = R_y - R_{\nu_{\text{NS}}}(u_*, p_*)$. We correct the new compact increment; this difference has compact support since every added term does. The baseline residual remains explicitly.

The averaging needed next is the source extended-field operation, not a spatial average of the evaluated field. Evaluate derivatives on the extended coefficients first by the complete chain rule. In a fixed chart set $\mathcal{D}_i = \partial_{x_i} + \sum_\alpha (\partial_{x_i} Y_\alpha) \partial_{Y_\alpha}$ and similarly $\mathcal{D}_t$. These are the pullbacks of commuting physical derivatives, so $[\mathcal{D}_i, \mathcal{D}_j] = 0$ on their lifted domain. For smooth periodic coefficients their auxiliary derivative terms have zero Haar average. In cylindrical components angular differentiation also differentiates the basis. This defines an extended residual $\tilde{R}_y$ whose evaluation is exactly (29). Average the tangential components of the increment at fixed slow variables:

$$F_2 = \langle \Delta \tilde{R}_{y, \theta} \rangle, \quad F_1 = \langle \Delta \tilde{R}_{y, z} \rangle, \quad \langle g \rangle = \int_{\mathbb{T}^2} \frac{1}{2\pi} \int_0^{2\pi} g \, d\theta \, dY. \quad (30)$$

These F_e are smooth and compact in the chosen physical annulus. Equations (28)–(30) are the explicit intermediate map from the retained coupled pair to a signed momentum residual. They do not identify it with the original two-dimensional Boussinesq force.

10 Radial moments, support, and the original chart scales

For each fixed (z, t) , choose $0 < r_- < r_+$ containing the compact supports of both F_e and the chosen bumps in the active annulus. The source bump is

$$b_e(r, z, t) = q^{-(e+1)/2} \widehat{b}_e(r/\sqrt{q}), \quad \int_0^\infty x^e \widehat{b}_e(x) dx = 1, \quad e = 1, 2,$$

with interior support. The change $r = \sqrt{q}x$ proves $\int r^e b_e dr = 1$ exactly. Define

$$M_e = \int_0^\infty r^e F_e(r) dr, \quad \sigma_e(r) = -r^{-e} \int_0^r s^e (F_e(s) - b_e(s) M_e) ds. \quad (31)$$

Then

$$(\partial_r + e/r)\sigma_e = -F_e + b_e M_e, \quad \int_0^\infty r^e (F_e - b_e M_e) dr = 0. \quad (32)$$

Differentiate $r^e \sigma_e$ to prove the first identity; integrate and use the bump normalization for the second. The integral is zero below r_- and above r_+ , so σ_e has compact smooth support in the same enclosing interval. A homogeneous solution is cr^{-e} , and a compact homogeneous solution has $c = 0$; thus the primitive is unique among compact solutions of its displayed equation. Moreover a compact solution of $(\partial_r + e/r)\sigma = -F_e$ exists if and only if $M_e = 0$: necessity follows by integrating the weighted derivative, and sufficiency follows from (31). The two moments are therefore the exact surviving finite-dimensional terms.

For $C_e = \int_{r_-}^{r_+} s^e ds$, $|M_e| \leq C_e \|F_e\|_\infty$ and

$$\|\sigma_e\|_\infty \leq r_-^{-e} C_e (\|F_e\|_\infty + \|b_e\|_\infty |M_e|).$$

If $G_e = F_e - b_e M_e$, successive radial derivatives obey the exact recurrence

$$\partial_r^{j+1} \sigma_e = -\partial_r^j G_e - e \sum_{i=0}^j \binom{j}{i} (-1)^i i! r^{-i-1} \partial_r^{j-i} \sigma_e.$$

This proves every finite radial derivative bound inductively. Parameter derivatives follow by differentiating the compact integral; all derivatives of q, b_e and the moving physical data are retained. On the present compact set q is bounded away from zero. No terminal uniform estimate is implied.

The source (9.12)–(9.14) uses physical $F_e = Q^{-2A-1/2} E_e^*$, where $E_2^* = \langle E_\theta \rangle_Y$ and $E_1^* = \langle E_z \rangle_Y$. For our fields define $E_e^* = Q^{2A+1/2} F_e$ in that same convention. With $r = \sqrt{Q}R$ and Q fixed in a chart, the exact conversions are

$$M_e = Q^{e/2-2A} M_e^*, \quad M_e^* = \int R^e E_e^* dR, \quad b_e^*(R) = Q^{(e+1)/2} b_e(\sqrt{Q}R), \\ \Sigma_e(R) = Q^{2A} \sigma_e(\sqrt{Q}R), \quad (\partial_R + e/R) \Sigma_e = -E_e^* + b_e^* M_e^*. \quad (33)$$

Substitute $r = \sqrt{Q}R$ including its measure in the moment, and differentiate Σ_e to prove each factor. The input F_e is already auxiliary independent. Taking only an averaged moment of an unaveraged $F(R, Y)$ would not suffice: $F = b_e(R) \cos(2\pi Y_1)$ has zero averaged moment but a nonzero exterior primitive at each generic Y .

11 The source covariance derivative and its signed right inverse

At each slow point let $w_{\text{tan}} = (w_\theta, w_z)$ and define

$$\mathcal{C}(w) = \langle w_r w_{\text{tan}} \rangle, \quad \mathcal{B}(w, v) = \langle w_r v_{\text{tan}} + v_r w_{\text{tan}} \rangle.$$

Direct expansion proves $\mathcal{C}(w + v) = \mathcal{C}(w) + \mathcal{B}(w, v) + \mathcal{C}(v)$ and $D\mathcal{C}(w)[v] = \mathcal{B}(w, v)$.

Use the exact source real pulses $b_\sigma = \chi_g(\xi_g)\psi(v)t_\sigma^h \cos(k\Phi_\sigma)$, $\sigma \in \{+, -\}$. They exclude the slow cutoff η_β and scalar amplitudes; χ_g is an auxiliary transverse cutoff. The two signs have disjoint auxiliary supports. Put $H_{\text{cov}} = [\mathcal{C}(b_+) \mid \mathcal{C}(b_-)]$. For slow scalar coefficients independent of both averages,

$$\mathcal{C}(a_+ b_+ + a_- b_-) = H_{\text{cov}}(a_+^2, a_-^2)^T.$$

All cross products vanish by disjointness. The factor $1/2$ from $\langle \cos^2(k\Phi_\sigma) \rangle_\theta$ is already inside the columns.

On the source interior cone the fixed primary amplitudes satisfy $a_\sigma = \sqrt{(H_{\text{cov}}^{-1} T_{0,*})_\sigma} > 0$, $T_{0,*} = (Q/q)^{A+1/2} T_0$, and $W_0 = \sqrt{\varepsilon} \sum_\sigma a_\sigma b_\sigma$. For any signed slow real vector Σ , define

$$d_\Sigma = H_{\text{cov}}^{-1} \Sigma / \varepsilon, \quad \delta a_\sigma = (d_\Sigma)_\sigma / (2a_\sigma), \quad L_\Sigma = \sqrt{\varepsilon} \sum_\sigma \delta a_\sigma b_\sigma. \quad (34)$$

It follows exactly that

$$\mathcal{B}(W_0, L_\Sigma) = \varepsilon H_{\text{cov}}(2a \odot \delta a) = \Sigma, \quad (35)$$

$$\mathcal{C}(W_0 + L_\Sigma) = \varepsilon T_{0,*} + \Sigma + \varepsilon H_{\text{cov}}(\delta a_+^2, \delta a_-^2)^T. \quad (36)$$

This proves a linear right inverse of the derivative. It is not an exact inverse of the quadratic covariance map. There is no sign or size restriction on Σ in these identities; no square root of $H_{\text{cov}}^{-1}(T_{0,*} + \Sigma/\varepsilon)$ is taken.

With Euclidean and induced operator norms and $a_{\min} = \min_\sigma |a_\sigma| > 0$, they give the explicit bound

$$\|\mathcal{C}(L_\Sigma)\| \leq \frac{\|H_{\text{cov}}\| \|H_{\text{cov}}^{-1}\|^2}{4\varepsilon a_{\min}^2} \|\Sigma\|^2. \quad (37)$$

Indeed $\|\delta a\| \leq \|H_{\text{cov}}^{-1}\| \|\Sigma\| / (2\varepsilon a_{\min})$ and $\|(\delta a_\sigma^2)_\sigma\|_2 \leq \|\delta a\|_2^2$. All higher derivative costs are explicit from Leibniz and

$$\partial^I H_{\text{cov}}^{-1} = -H_{\text{cov}}^{-1} \sum_{0 < J \leq I} \binom{I}{J} (\partial^J H_{\text{cov}}) \partial^{I-J} H_{\text{cov}}^{-1},$$

and, for any nonzero scalar a , $\partial^I(a^{-1}) = -a^{-1} \sum_{0 < J \leq I} \binom{I}{J} (\partial^J a) \partial^{I-J}(a^{-1})$. Together with (34) these recurrences give finite bounds for each order without assuming constant amplitudes or constant columns.

12 Assembly, the actual covariance change, and residual cancellation

For the physical target $\sigma = (\sigma_2, \sigma_1)$ from (31), use the source squared slow partition $\sum_\beta \eta_\beta^2 = 1$ on its support. Set

$$\begin{aligned} W_{0,\text{phys}} &= \sum_\beta Q_\beta^{-A} \eta_\beta W_{0,\beta}, \\ v_{\text{pr}} &= \sum_\beta Q_\beta^{-A} \eta_\beta L_\beta (Q_\beta^{2A} \sigma). \end{aligned} \quad (38)$$

Overlapping slow labels have disjoint auxiliary supports. Taking cross covariance and using (35) gives

$$\mathcal{B}(W_{0,\text{phys}}, v_{\text{pr}}) = \sum_{\beta} Q_{\beta}^{-2A} \eta_{\beta}^2 Q_{\beta}^{2A} \sigma = \sigma.$$

Every band scale remains distinct. Likewise the leading physical factor is $Q^{-2A} \varepsilon(Q/q)^{A+1/2} = Q^{-A+h+1/2} q^{-A-1/2} = q^{-A-1/2}$ because $A = 1/2 + h$.

Apply the exact curl (28) to each coefficient of v_{pr} , including the slow cutoffs before curling. Write the resulting divergence-free increment as $v_s = v_{\text{pr}} + r_s$. Let $t_{s,m}$ denote the chart transverse harmonic coefficients of $\eta_{\beta} L_{\beta}(Q_{\beta}^{2A} \sigma)$, before multiplication by Q_{β}^{-A} . For each such coefficient choose $\pi_{s,m} = i(n^T K t_{s,m} - (n')^T t_{s,m}) / (k_{\beta} m |n|^2)$ and sum $\text{Re}(Q_{\beta}^{-2A} \pi_{s,m} e^{i\phi_{\beta,m}})$ to define the smooth compact π_s . Its full gradients remain below. Let the actual old wave w consist of the wave part of u_* plus the candidate w_y , including all existing curl corrections, and write $w = W_{0,\text{phys}} + e_w$. Define tensor covariance $\mathcal{T}(w) = \langle w \otimes w \rangle$ and $\mathcal{B}_T(u, v) = \langle u \otimes v + v \otimes u \rangle$. Expansion, with $e_w = w - W_{0,\text{phys}}$, proves

$$\Delta \mathcal{T} = \mathcal{B}_T(W_{0,\text{phys}}, v_{\text{pr}}) + \mathcal{B}_T(e_w, v_{\text{pr}}) + \mathcal{B}_T(w, r_s) + \mathcal{T}(v_s). \quad (39)$$

Its first radial–tangential pair is σ . All other entries and the remaining three tensors are retained. For example their radial–tangential pair has bound

$$2\|e_w\|_{L_{\theta,Y}^2} \|v_{\text{pr}}\|_{L_{\theta,Y}^2} + 2\|w\|_{L_{\theta,Y}^2} \|r_s\|_{L_{\theta,Y}^2} + \|v_s\|_{L_{\theta,Y}^2}^2,$$

by Cauchy–Schwarz. The compact-set estimates above and the explicit curl differentiate to bound all these terms at each finite order.

For clarity the complete residual after adding v_s and its selected pressure π_s is, without any averaging,

$$\begin{aligned} R_{\nu_{\text{NS}}}(u + v_s, p + \pi_s) &= R_{\nu_{\text{NS}}}(u, p) + \partial_t v_s + (u \cdot \nabla) v_s + (v_s \cdot \nabla) u \\ &\quad - \nu_{\text{NS}} \Delta v_s + \nabla \pi_s + (v_s \cdot \nabla) v_s. \end{aligned} \quad (40)$$

This follows by expanding the product and retains viscosity and every pressure term. For a symmetric tensor S the averaged tangential divergence in physical cylindrical coordinates is

$$(\langle \nabla \cdot S \rangle)_{\theta} = (\partial_r + 2/r) \langle S_{r\theta} \rangle + \partial_z \langle S_{z\theta} \rangle, \quad (\langle \nabla \cdot S \rangle)_z = (\partial_r + 1/r) \langle S_{rz} \rangle + \partial_z \langle S_{zz} \rangle.$$

To verify, write the Cartesian divergence in the orthonormal cylindrical basis, using $\partial_{\theta} e_r = e_{\theta}$, $\partial_{\theta} e_{\theta} = -e_r$; periodic angular derivatives average to zero and the two basis terms give $2/r$ and $1/r$ respectively. The auxiliary chain terms average to zero by periodicity, but the physical slow derivatives remain.

Let $U = u_* + w_y$, $P_y = p_* + \pi_y$, and set

$$\mathcal{L} = \partial_t v_s + (U \cdot \nabla) v_s + (v_s \cdot \nabla) U - \nu_{\text{NS}} \Delta v_s + \nabla \pi_s.$$

For a fully explicit averaged remainder, write $U = u_{\text{mean}} + w$, where u_{mean} is its angular mean, and put $\mathcal{V} = \mathcal{L} - (w \cdot \nabla) v_s - (v_s \cdot \nabla) w$. Then the average of (40) is $\langle R_y \rangle + \langle \mathcal{V} \rangle + \nabla \cdot \Delta \mathcal{T}$. Let $S_0 = \mathcal{B}_T(W_{0,\text{phys}}, v_{\text{pr}})$ and $S_{\text{rem}} = \mathcal{B}_T(e_w, v_{\text{pr}}) + \mathcal{B}_T(w, r_s) + \mathcal{T}(v_s)$. Consequently the radial divergence of the first pair in (39) changes the prescribed averaged residual F_e into $b_e M_e$ by (32).

The axial tensor divergences, the other three tensors, the exact linear terms and the pressure terms of (40) remain in the new residual. Equivalently the new averaged tangential residual is exactly

$$\begin{aligned}\langle R_{\text{new}} \rangle_{\text{tan}} &= \langle R_{\nu_{\text{NS}}}(u_*, p_*) \rangle_{\text{tan}} + (b_2 M_2, b_1 M_1) + \langle \mathcal{V} \rangle_{\text{tan}} \\ &\quad + \partial_z((S_0)_{z\theta}, (S_0)_{zz}) + (\nabla \cdot S_{\text{rem}})_{\text{tan}}.\end{aligned}$$

Every term here is defined by the displayed differentiated fields and tensors. None is assumed to vanish. The map from y through (30), (31), (34), and (38) is now an actual composite construction. It retains the signed residual produced by the coupled candidate and the source's original physical and chart units.

13 Signs and the exact full-flow reflection

The maps $F_e \mapsto M_e \mapsto \sigma_e \mapsto L_\Sigma$ are linear and reverse sign with their inputs; $\mathcal{C}(L_\Sigma)$ is even. The two primary amplitudes may also be replaced independently by $s_\sigma a_\sigma$, $s_\sigma \in \{-1, 1\}$, provided the same fixed choice is used in each denominator: the cross identity is unchanged. This does not negate the nonlinear Navier–Stokes equation.

Here is the exact full-flow map. In Cartesian coordinates let $O = \text{diag}(1, -1, 1)$ and define

$$u^\sharp(x, t) = Ou(Ox, t), \quad p^\sharp(x, t) = p(Ox, t), \quad f^\sharp(x, t) = Of(Ox, t).$$

The chain rule gives $\nabla u^\sharp = O(\nabla u)(Ox, t)O$, $\Delta u^\sharp = O(\Delta u)(Ox, t)$, and $(u^\sharp \cdot \nabla)u^\sharp = O((u \cdot \nabla)u)(Ox, t)$. Thus $\nabla \cdot u^\sharp = 0$ and $R_{\nu_{\text{NS}}}(u^\sharp, p^\sharp) = OR_{\nu_{\text{NS}}}(u, p)(Ox, t)$ with the same positive viscosity. In cylindrical components this is

$$(u_r^\sharp, u_\theta^\sharp, u_z^\sharp)(r, \theta, z, t) = (u_r, -u_\theta, u_z)(r, -\theta, z, t),$$

and the force transforms identically. Pressure reflects in its argument. For an axisymmetric field this reverses exactly its swirl; meridional components remain fixed. The entire momentum tensor is mapped to OTO^T , so its radial–tangential pair transforms by $(T_{r\theta}, T_{rz}) \mapsto (-T_{r\theta}, T_{rz})$ after angular averaging. Vorticity transforms as $\omega^\sharp(x, t) = \det(O)O\omega(Ox, t)$, obtained by applying the same derivative identities to the Levi-Civita formula for curl. The map is an involution, preserves the kinetic-energy integral (by $|\det O| = 1$), compact support, smoothness, and blowup magnitude along the reflected path. It preserves zero initial data when present. It proves transport of any established axisymmetric signed swirl divergence to the opposite sign; it does not itself prove an endpoint.

The source five-moment correction, auxiliary mean inverse, and infinite summation are subsequent source operations. Their full estimates are not re-proved here. The earlier draft formulas for them are withdrawn: in particular the fifth moment row is $\int (2RG\gamma_d - RV\Delta v) dR = -J_z$, without an extra outer R , and its reserved profile in a Q chart includes $(Q/q)^A$. The finite map proved above retains the two moments and all other residual terms, so it establishes neither a third shooting return nor an infinite modified viscous sequence.