EHF Katalogbekreftelse ver 1.0

Message Guideline

Element	Name	Req.	Card.	Description	Rule	Example
ApplicationResponse	EHF Catalogue Response	M		Format for Catalogue Response based on CEN BII		
-cbc:UBLVersionID	UBL Version ID	Ο	0 1	Identifies the UBL version on which the transaction instance is based	NOGOV-T58-R002	2.1
—cbc:CustomizationID	Customization identifier	Ο	0 1	Identifies the specification of content and rules that apply to the transaction.	BII2-T58-R002	urn:www.cenbii.eu: transaction:biitrns058:ver2.0 #urn:www.difi.no:ehf: katalogbekreftelse:ver1.0
cbc:ProfileID	Profile identifier	Ο	0 1	Identifies the BII profile or business process context in which the transaction appears.	BII2-T58-R001, EHFPROFILE-T58-R001	urn:www.cenbii.eu:profile: bii01:ver2.0
—cbc:ID	Response identifier	M	1 1	An transaction instance must contain an identifier. The identifier enables positive referencing the document instance for various purposes including referencing between transactions that are part of the same process.	BII2-T58-R004	1
-cbc:IssueDate	Response issue date	M	1 1	The date on which the transaction instance was issued.	BII2-T58-R003	2013-05-10
—cbc:IssueTime	Response issue data	0	0 1	The time at which the transaction instance was issued.		
cbc:Note	Response textual notes	Ο	0 unbour ed	d Used to make any comments or instructions relevant to the response, including the date that the reported decision becomes effective.		
@ languageID		optional				
cac:SenderParty	SenderParty	M	1 1	Information about message sender	BII2-T58-R005	
cbc;EndpointID	Electronic address	Ο	0 1	A response may contain the party electronic address. The address can be of any format and the format should be identified in the message.	NOGOV-T58-R006, NOGOV-T58-R003	
@ schemeID		optional			NOGOV-T58-R005, EUGEN-T58-R001	
cac:PartyIdentification	Party identifier Party Identification	Ο	0 1	It should be possible to specify the identifier or identifiers for the party. Information about Party ID	BII2-T58-R008	923654321
cbc:ID	Party identifier	M	1 1	It should be possible to specify the identifier or identifiers for the party.	BII2-T58-R008	923654321
@ schemeID		optional			EUGEN-T58-R002	
	Party name Party Name	Ō	0 1	The name of the party sending the response. Information about Party Name	BII2-T58-R008	Buyer
cbc:Name	Party name	М	1 1	The name of the party sending the response.	BII2-T58-R008	Buyer
cac:ReceiverParty	ReceiverParty	M	1 1	Information about message receiver	BII2-T58-R006	

Req: M=Mandatory, O=Optional ,R=Recommended

EHF Katalogbekreftelse ver 1.0

Message Guideline

Element	Name	Req.	Card.	Description	Rule	Example
-cbc:EndpointID	Electronic address	0 () 1	A response may contain the party electronic address. The address can be of any format and the format should be identified in the message.	NOGOV-T58-R008, NOGOV-T58-R004	
@ schemeID		optional		-	NOGOV-T58-R007, EUGEN-T58-R001	
—cac:PartyIdentification	Party Identification	0 (1	Information about PartyID		
cbc:ID	Party identifier	M	I 1	It should be possible to specify the identifier or identifiers for the party.	BII2-T58-R007	123456789
@ schemeID		optional			EUGEN-T58-R002	
cac:PartyName	Party name Party Name	0 () 1	The name of the party receiving the response. Information about Party Name	BII2-T58-R007	Supplier
cbc:Name	Party name	M	l 1	The name of the party receiving the response.	BII2-T58-R007	Supplier
-cac:DocumentResponse	DocumentResponse	0 (1	Information about the reason code		
cac:Response	Response	M	I 1	Responseinformation		
-cbc:ResponseCode	Coded decision	0 () 1	A code for the description of the response to the transaction document. AP= Accepted, RE = Rejected, UN/Cefact 4343 Response type code	BII2-T58-R009	AP
@ listID		optional			EUGEN-T58-R003	
cac:DocumentReference	Document Reference	M	1	Document Reference information		
—ebc:ID	Document identifier	M	1	Identifies the document being referred to.		Catalogue-01
-cbc:VersionID	Document version	0 () 1	The version of the document that has been identified with the document identifier.		1

Date: 09/03/2015