UNIT TEST PACKAGE DOCUMENTATION

ABSTRACT. This .pdf file represents a documentation for Unit Tests package in Wolfram Mathematica, which related to the math. research https://arxiv.org/abs/1603.02468.

Contents

Installation and execution	1
Unit test 1	2
Unit test 2	2
Unit test 3	2
Unit test 4	2
Unit test 5	2
Unit test 6	2
Unit test 7	2
Unit test 8	2
Unit test 9	3
Unit test 10	3
Unit test 11	3
Unit test 12	3
Unit test 13	3
Unit test 14	3
Unit test 15	3
Unit test 16	3
Unit test 17	4
Unit test 18	4
Unit test 19	4
Unit test 20	4
Unit test 21	4

Installation and execution

Prior the unit test execution, one has to download the packages main_definitions.m and unit_tests_package.m from https://github.com/kolosovpetro/research_unit_tests. Package unit_tests_package.m is dependent on main_definitions.m. Open these packages in Mathematica and instal by clicking File -> Install..., click Source and choose corresponding file in dropped menu. Perform installation for two packages separately. Then recall the packages main_definitions.m and unit_tests_package.m in Mathematica notebook using the commands

Needs["MainDefinitions"]
Needs["UnitTests"]

Read also http://support.wolfram.com/kb/5648.

Each unit test is inside the package unit_tests_package.m, each unit test to be recalled by a single command without any inputs, for example, unit test 1 to be recalled by the command UnitTest1 to the Mathematica console. Any unit test conditions (iteration limits, etc) to be changed directly inside the package unit_tests_package.m.

Unit test 1

Command UnitTest1 to Mathematica console verifies an identity

$$\mathbf{P}_{a,b}^{m}(n) = \mathbf{P}_{b}^{m}(n) - \mathbf{P}_{a}^{m}(n)$$

Unit test 2

Command UnitTest2 to Mathematica console verifies an identity

$$\mathbf{P}_{a,b}^m(n) = \sum_k \mathbf{X}_k^m(a,b) (-1)^{m-k} n^k$$

Unit test 3

Command UnitTest3 to Mathematica console verifies an identity

$$\mathbf{X}_k^m(a,b) = \mathbf{X}_k^m(b) - \mathbf{X}_k^m(a)$$

Unit test 4

Command UnitTest4 to Mathematica console verifies an identity

$$\mathbf{X}_{t}^{m}(a,b) = (-1)^{m} \sum_{k=1}^{2m-t+1} \mathbf{H}_{m,t}(k)(b^{k} - a^{k})$$

Unit test 5

Command UnitTest5 to Mathematica console verifies an identity

$$\mathbf{P}_{a,b}^{m}(n) = \sum_{k} (-1)^{2m-k} \sum_{\ell=1}^{2m-k+1} \mathbf{H}_{m,k}(\ell) (b^{\ell} - a^{\ell}) n^{k}$$

Unit test 6

Command UnitTest6 to Mathematica console verifies an identity

$$\mathbf{Q}_{a,b}^r(n) = \mathbf{Q}_b^r(n) - \mathbf{Q}_a^r(n)$$

Unit test 7

Command UnitTest7 to Mathematica console verifies an identity

$$(f_t^r * f_t^r)[n] = \mathbf{Q}_{t,n-t+1}^r(n), \quad n \ge 1.$$

Unit test 8

Command UnitTest8 to Mathematica console verifies an identity

$$n^{2m+1} + 1 = \sum_{r \ge 0} \mathbf{A}_{m,r} (f_0^r * f_0^r)[n], \quad n > 0, \quad n \in \mathbb{N}$$

Unit test 9

Command UnitTest9 to Mathematica console verifies an identity

$$n^{2m+1} - 1 = \sum_{r>0} \mathbf{A}_{m,r} (f_1^r * f_1^r)[n], \quad n > 0, \quad n \in \mathbb{N}$$

Unit test 10

Command UnitTest10 to Mathematica console verifies an identity

$$\mathbf{X}_{t}^{m}(a,b) = (-1)^{m} \sum_{j=t}^{m} \mathbf{A}_{m,j} (-1)^{j} {j \choose t} (S_{2j-t}(b) - S_{2j-t}(a))$$

Unit test 11

Command UnitTest11 to Mathematica console verifies an identity

$$\mathbf{P}_{a,b}^{m}(n) = \sum_{k} \sum_{j>k} (-1)^{2m+j-k} \mathbf{A}_{m,j} \binom{j}{k} (S_{2j-k}(b) - S_{2j-k}(a)) n^{k}$$

Unit test 12

Command UnitTest12 to Mathematica console verifies an identity

$$\mathbf{P}_{a+b}^{m}(a+b) \equiv \sum_{k} {2m+1 \choose k} a^{2m+1-k} b^{k}$$

Unit test 13

Command UnitTest13 to Mathematica console verifies an identity

$$n^{2m+1} = \mathbf{P}_n^m(n)$$

Unit test 14

Command UnitTest14 to Mathematica console verifies an identity

$$n^s = n^{[s \text{ is even}]} \mathbf{P}_n^{\lfloor \frac{s-1}{2} \rfloor}(n)$$

Unit test 15

Command UnitTest15 to Mathematica console verifies an identity

$$\mathbf{P}_{t,n-t+1}^{m}(n) = \sum_{r} \mathbf{A}_{m,r} \mathbf{Q}_{t,n-t+1}^{r}(n) \equiv \sum_{r} \mathbf{A}_{m,r} (f_{t}^{r} * f_{t}^{r})[n], \quad n \ge 1.$$

Unit test 16

Command UnitTest16 to Mathematica console verifies an identity

$$\mathbf{P}_n^m(n) - \mathbf{P}_{1,n+1}^m(n) = 1$$

Unit test 17

Command UnitTest17 to Mathematica console verifies an identity

$$(a+b)^s = \sum_k {s \choose k} a^{s-k} b^k \equiv (a+b)^{[s \text{ is even}]} \left(-1 + \mathbf{P}_{a+b+1}^{\lfloor \frac{s-1}{2} \rfloor} (a+b) \right)$$

Unit test 18

Command UnitTest18 to Mathematica console verifies an identity

$$(a+b)^s = \sum_k {s \choose k} a^{s-k} b^k \equiv (a+b)^{[s \text{ is even}]} \left(1 + \mathbf{P}_{1,a+b}^{\lfloor \frac{s-1}{2} \rfloor} (a+b) \right)$$

Unit test 19

Command UnitTest19[a+b] to Mathematica console verifies an identity

$$(a+b)^s = \sum_k \binom{s}{k} a^{s-k} b^k$$

$$= (a+b)^{[s \text{ is even}]} \left(-1 + \sum_k \mathbf{A}_{\lfloor \frac{s-1}{2} \rfloor, k} (f_0^r * f_0^r) [a+b] \right), \quad s \ge 1, \quad a+b \ge 1.$$
Unit test 20

Command UnitTest20[a+b] to Mathematica console verifies an identity

$$(a+b)^s = \sum_k \binom{s}{k} a^{s-k} b^k$$

$$= (a+b)^{[s \text{ is even}]} \left(1 + \sum_k \mathbf{A}_{\lfloor \frac{s-1}{2} \rfloor, k} (f_1^r * f_1^r) [a+b] \right), \quad s \ge 1, \quad a+b \ge 2.$$

Unit test 21

Command UnitTest21 to Mathematica console verifies an identity

$$\mathbf{P}_{n+1}^{m}(n) = \sum_{r=0}^{m} \mathbf{A}_{m,r} \mathbf{C}_{n+1}^{r}(n) \equiv \sum_{r=0}^{m} \mathbf{A}_{m,r} \langle n \rangle^{r} * \langle n \rangle^{r} = n^{2m+1} + 1$$