



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No. 6
Implement a program on 2D array & strings functions.
Date of Performance:
Date of Submission:



Aim: To use 2D arrays and Strings for solving given problem.

Objective: To use 2D array concept and strings in java to solve real world problem

Theory:

- An array is used to store a fixed-size sequential collection of data of the same type.
- An array can be init in two ways:
 1. Initializing at the time of declaration:
`dataType[] myArray = {value0, value1, ..., valuek};`
 2. Dynamic declaration:
`dataType[] myArray = new dataType[arraySize];`
`myArray[index] = value;`
- Two – dimensional array is the simplest form of a multidimensional array. Data of only same data type can be stored in a 2D array. Data in a 2D Array is stored in a tabular manner which can be represented as a matrix.
- A 2D Array can be declared in 2 ways:
 1. Intializing at the time of declaration:
`dataType[][] myArray = { {valueR1C1, valueR1C2...}, {valueR2C1, valueR2C2...},...}`
 2. Dynamic declaration:
`dataType[][] myArray = new dataType[x][y];`
`myArray[row_index][column_index] = value;`

In Java, string is basically an object that represents sequence of char values. An array of characters works same as Java string. **Java String** class provides a lot of methods to perform operations on strings such as `compare()`, `concat()`, `equals()`, `split()`, `length()`, `replace()`, `compareTo()`, `intern()`, `substring()` etc.

1.String literal

To make Java more memory efficient (because no new objects are created if it exists already in the string constant pool).



Example:

```
String demoString = "GeeksforGeeks";
```

2. Using new keyword

- `String s = new String("Welcome");`
- In such a case, JVM will create a new string object in normal (non-pool) heap memory and the literal "Welcome" will be placed in the string constant pool. The variable s will refer to the object in the heap (non-pool)

Example:

```
String demoString = new String ("GeeksforGeeks");
```

Code:

2D array Example

```
public class TwoDimensionalArrayExample {  
    public static void main(String[] args) {  
        // Declare and initialize a 2D array  
        int[][] twoDArray = {  
            {1, 2, 3},  
            {4, 5, 6},  
            {7, 8, 9}  
        };  
  
        // Display the elements of the 2D array  
        System.out.println("Elements of the 2D array:");  
        for (int i = 0; i < twoDArray.length; i++) {  
            for (int j = 0; j < twoDArray[i].length; j++) {  
                System.out.print(twoDArray[i][j] + " ");  
            }  
            System.out.println(); // Move to the next row  
        }  
    }  
}
```



```
}

// Access a specific element
int element = twoDArray[1][2];
System.out.println("Element at row 1, column 2: " + element);
}
}
```

```
C:\KOMAL SAPATALE >java TwoDimensionalArrayExample.java
Elements of the 2D array:
1 2 3
4 5 6
7 8 9
Element at row 1, column 2: 6
```

STRING FUNCTION EXAMPLE

Code:

```
public class Stringoperation
{
public static void main(String args[])
{
String s="JASH MHATRE";
System.out.println(s.toUpperCase());
System.out.println(s.toLowerCase());
System.out.println(s.trim());
System.out.println(s.startsWith("V"));
System.out.println(s.endsWith("a"));
System.out.println(s.charAt(0));
System.out.println(s.charAt(3));
System.out.println(s.length());
}
}
```



```
C:\KOMAL SAPATALE >javac Stringoperation.java  
  
C:\KOMAL SAPATALE >java Stringoperation  
JASH MHATRE  
jash mhatre  
JASH MHATRE  
false  
false  
J  
H  
11
```

Conclusion:

Comment on how you have used the concept of string and 2D array.