```
1    \ProvidesFile{mdoccorr.cfg}[2011/10/13
2                     local typographical corrections with makedoc.sty]
```

... also demonstrates niceverb.sty—see the typeset documentation of the present file in `makedoc.pdf`.

$\boxed{\texttt{\textbackslash SetPatternCodes\{}\langle\textit{commands}\rangle\texttt{\}}}$ redefines `\PatternCodes` to be used in parsing and replacing (some "sanitizing").

```
3    \SetPatternCodes{\MakeOther\\\MakeOther\ }
```

$\boxed{\texttt{\textbackslash StartPrependingChain}}$ initializes setup of a replacement chain:

```
4    \StartPrependingChain
```

$\boxed{\texttt{\textbackslash PrependExpandableAllReplacer\{}\langle\textit{id}\rangle\texttt{\}\{}\langle\textit{find}\rangle\texttt{\}\{}\langle\textit{subst}\rangle\texttt{\}}}$:

```
5    \PrependExpandableAllReplacer{etc}{etc. }{etc.\ }
```

... you can keep inter-sentence space after `etc.` by a code line break.

```
6    \PrependExpandableAllReplacer{Cf}{Cf. }{Cf.\ } %% 2011/01/12
7    \PrependExpandableAllReplacer{cf}{cf. }{cf.\ } %% corr. 2010/03/23
```

... but think of `cf.~`. Don't leave `cf.` at code line end!

```
8    \PrependExpandableAllReplacer{rarr}{->}{$\to$}      %% 2010/11/06
9    \PrependExpandableAllReplacer{larr}{<-}{$\gets$}    %% 2010/11/06
10   % \PrependExpandableAllReplacer{dots}{...}{$\dots$}
```

... 2010/11/24 "symmetric" variant of `\textellipsis`: allow extra space at line end. MD macro 2011/10/13 (final dot separates; TODO provide generally):

```
11   \gdef\MDtwodots{.\kern\fontdimen3\font.\kern\fontdimen3\font}
12   \PrependExpandableAllReplacer{dots}{...}{\MDtwodots.}
```

2011/10/13: original `\dots` correct before punctuation:

```
13   % \PrependExpandableAllReplacer{dots,}{...,}{\dots,}
14   \PrependExpandableAllReplacer{dots:}{...:}{\dots:}
15   \PrependExpandableAllReplacer{dots }{... }{\MDtwodots.\ }
16   \PrependExpandableAllReplacer{TODO}{TODO}{\textcolor{blue}{TODO}}
```

... chain starts here, and here $\boxed{\texttt{\textbackslash MakeDocCorrectHook}}$ (silently) enters through a default variant $\boxed{\texttt{\textbackslash SetCorrectHookJobLast}}$ of $\boxed{\texttt{\textbackslash SetCorrectHookJob\{}\langle\textit{id}\rangle\texttt{\}}}$:

```
17   \SetCorrectHookJobLast
```

$\boxed{\texttt{\textbackslash ResetPatternCodes}}$ resets `\PatternCodes` to their default value (which is `\fdPatternCodes`):

```
18   \ResetPatternCodes
```

... restores fifinddo default.

```
19   \endinput
20
21   HISTORY
22   2009/04/05  with makedoc v0.2
23   2010/03/11  broke some too long code lines
24   2010/03/16  rendered 'mdoccorr.cfg'
25   2010/03/22  try \Prepend...
26   2010/03/23  corrected 'cf'
27   2010/03/29  use \SetPatternCodes etc.
28   2010/11/06  <- and ->
29   2010/11/24  '...' ''symmetric variant" of '\textellipsis';
30               \StartPrependingChain, no more \MakeExpandableAllreplacer
31   2011/01/27  blue "TODO"
32   2011/09/13  \providecommand for dialogues
33   2011/10/13  \MDtwodots, without \PXAR, '...,' '...:'
34
```