PAPER VII

# Quantum Seed and Packet Calculus

## Symmetry, circuits, geometric transport, channels, and finite effective dynamics

Follow the actual declarations from algebra orbits and packet circuits to geometric transport, quantum recovery, and finite resolvent bounds. Each interface keeps its own hypotheses and evidence.

Komorebi P.

Lean and evidence guide • 18 October 2026

**How to use this volume**

**A guide to the actual formal development.** 19 scoped finite items. 323 named theorem declarations. 25 proof modules. The teaching chapters explain the mathematical interfaces and their hypotheses. The complete registers then give exact declarations, source locations, imports, and nine dependency pins.

This edition preserves 67 exact Lean excerpts. Six constructed objects have a separate inherited audit of their proof fields. That additional audit does not enlarge the 323-theorem catalog. Five continuum physics conjectures remain open.

Kernel execution evidence is inherited from the v0.6.0 release dated 6 September 2026. This edition reconciles source bytes, declaration locations, saved axiom records, and current finite computations. No fresh Lean compilation was run.

# Contents


1 Reading a Paper VII Lean theorem 1

2 Navigation through the traditional paper 4

3 Seeds, local orbits, and the packet resolution 10

4 Circuit corners, conserved packets, and leakage 18

5 Moving frames and an actual projected connection 23

6 Finite channels and the full Knill–Laflamme criterion 32

7 Effective resolvents, Euclidean transfer, and finite bounds 42

8 Evidence and reproducible replay 47

9 Complete finite-result map 51

10 All named theorem declarations 56

11 Module dependencies, source identities, and pins 68

12 Exact excerpt register 71

# 1 Reading a Paper VII Lean theorem

## 1.1 Three readings of one construction

The traditional reading begins with a finite state space, its operator algebra and a packet resolution. It derives matrix identities and explains what they mean for dynamics and recovery. The visual reading displays the same objects as corners, address sets, syndrome subspaces and local coordinates. The Lean reading asks a further question: what precise data must be supplied before each conclusion can be constructed?

An endpoint is a theorem whose conclusion expresses the desired result. A supporting lemma may isolate one algebraic or analytic step. A definition constructs an object but is not itself a proof that the object has every advertised property. The formalization deliberately uses several layers: general ring identities, complex matrix specializations, norm estimates, real calculus, spectral constructions and manifold calculus. Reading only a final theorem name loses the distinction between these layers.

The source base is the unchanged v0.6.0 snapshot. Older supplements explain how coverage grew, but their partial descriptions are not the last word on the current source. For example, the fourth block constructed recovery for already orthogonal syndrome data; the fifth block added the spectral reduction and necessity proof for general positive Gram data. The sixth block constructed the range atlas and global manifold curvature. This guide follows the current declarations and retains the older history only where it explains an assumption or correction.

## 1.2 Finite types, matrix types and type classes

Lean's `Matrix d m ℂ` means a function with a row index in `d`, a column index in `m`, and values in the complex numbers. The indices are types, not necessarily integers. A `Fintype d` instance gives the finite enumeration needed for a sum or dimension; a `DecidableEq d` instance lets a definition decide whether two indices agree. `Fin n` is the type of natural numbers smaller than `n`. It supplies a concrete index type without replacing an arbitrary finite type throughout the library.

The notation `Type*` leaves a universe level implicit. Braces in a binder, such as `{n : Type*}`, denote an implicit argument inferred from later data. Round parentheses denote an explicit argument. Square brackets denote a type-class argument: a structure or property that instance search should obtain. These brackets do not make an assumption disappear. A theorem with `[Nonempty n]` is only available when the state index has an inhabitant. A theorem with `[Invertible D]` has an actual invertibility requirement even though no ordinary parameter named `hD` is printed.

The declarations set `autoImplicit false`. Consequently an undeclared symbol is not silently promoted to a fresh theorem variable. A local `variable` command can still supply variables and type classes to subsequent declarations. An excerpt must therefore be read together with its surrounding section, not as an independent file. The chapter contracts explain those surrounding assumptions; the source file and line register permit a direct check.

| Source notation | Mathematical reading |
|---|---|
| `Matrix d m ℂ` | Complex rectangular matrix, also a coefficient array of a bipartite state. |
| `n → ℂ` | Coordinate vector on a finite index type. |
| `→ₗ[ℂ]` | Complex-linear map, with linearity stored in its structure. |

| Source notation | Mathematical reading |
|---|---|
| `→L[ℝ]` | Continuous real-linear map, used for derivatives and parameter-dependent operators. |
| `≃ₗ[ℂ]` | A linear equivalence with inverse and linearity laws. |
| `≃ₜ` | A homeomorphism, including continuity in both directions. |
| `≃L[ℝ]` | Continuous real-linear equivalence. |
| `star`, `conjTranspose` | Involution in an abstract star ring; conjugate transpose for complex matrices. |
| `PosSemidef`, `PosDef` | Positive semidefinite and positive definite matrices, respectively. |
| `IsStarProjection P` | Both idempotence and self-adjointness of the projector. |
| `HasDerivAt f D t` | The actual real derivative of `f` at `t` is `D`. |
| `fderiv ℝ`, `mvfderiv I` | Actual Fréchet derivative; actual derivative of a manifold-to-vector-space map. |
| `IsLeast S r` | Membership of `r` in `S`, together with its lower-bound property. |

### 1.3 Quantifiers and the information a structure stores

A family `P : I → R` is one element of the ring for each packet index. A dependent family `P : (i : F) → J i → Matrix (D i) (D i) ℂ` allows both the local dimension and the local packet-address type to vary with the tensor factor. This is more general than a tensor power of one fixed matrix.

The packet structure stores pairwise multiplication and completeness. Its multiplication law includes the diagonal case, so idempotence is a consequence. It does not store self-adjointness; that is supplied only in the star-ring layer. This distinction lets circuit reconstruction work over any ring while the unitary identities require an adjoint.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 22–25; excerpt `packet_structure`. Hash in Section 12.

```
structure PacketFamily (R I : Type*) [Ring R] [Fintype I] [DecidableEq I] where
  proj : I → R
  mul_proj : ∀ i j, proj i * proj j = if i = j then proj i else 0
  sum_proj : ∑ i, proj i = 1
```

Read `proj : I → R` as the object, `mul_proj` as its orthogonality law and `sum_proj` as its complete resolution of the identity. In a matrix realization the first law is $P_i P_j = \delta_{ij} P_i$. The second is $\sum_i P_i = 1$. No commutative multiplication assumption is present: matrix multiplication remains operator composition.

Structures used later have a different role. `OrthogonalSyndromes` stores an already normalized orthogonal error family, and `KnillLaflamme.Data` stores a general positive Gram matrix. `Data.diagonal` constructs diagonal error data; its active positive directions are then normalized to construct `OrthogonalSyndromes`. The existence of the general Gram data is an assumption of sufficiency; necessity constructs such data from an actual recovery. The final equivalence joins both directions. The correct reading keeps these roles separate rather than interpreting every structure field as a fact proved from scratch.

### 1.4 How to read a proof script

The scripts repeatedly use a small set of proof moves. `rw` replaces an expression using a stated equality. `simp only` performs a controlled reduction with an explicit list of lemmas; `simp` also uses the available simplification database. `ext i j` reduces a matrix equality to equality of each entry. `funext` proves equality of functions by comparing values. `constructor` starts the two obligations of a conjunction or equivalence. `rintro` decomposes quantified and existential data. `obtain` names an existential witness already proved to exist. `refine` fixes the overall shape of a term and leaves specified holes to prove.

The tactic `noncomm_ring` normalizes ring expressions without commuting factors. It is appropriate for identities involving $P_b U P_a$. Ordinary `ring` is used for scalar arithmetic or commutative coefficient expressions. Reading a ring-normalization step as permission to reorder arbitrary matrix factors would give an incorrect mathematical proof.

A line beginning `have` proves or names a local intermediate assertion. The goal remains the same until that assertion is used. A `calc` block presents a chain of equalities or inequalities; each link is a separate obligation. Induction on a list proves all finite circuit depths, including the empty list. A finite example verified by `norm_num` or `fin_cases` proves that concrete example, not a general-dimensional theorem.

For a derivative identity the important move is often `HasDerivAt.unique`: two proven derivatives of the same function at a point must coincide. The script first differentiates a product, then rewrites the product as a constant or as a known function, then invokes uniqueness. Thus the differentiated projector and unitary identities are derived from actual functions and their derivatives, rather than postulated as unrelated first-order data.

### 1.5 Scope is a part of the theorem

The finite-sector results have broad mathematical strength, but several tempting extensions lie outside their conclusions. A statement about the span of an algebra orbit permits every matrix in that algebra; it does not say a physically specified unitary gate set reaches every vector. A finite channel complete-positivity theorem quantifies over every finite reference index; it does not formalize arbitrary infinite reference Hilbert spaces. A derivative computation under supplied smoothness does not prove the existence of a Schrödinger solution for every initial condition.

The projected-connection modules do use arbitrary smooth real parameter manifolds and complete normed model spaces, which is broader than a single finite-dimensional chart. This mathematical parameter-space generality is distinct from the paper's unproved continuum physics conjectures. Neither the word "manifold" nor an abstract C-star-algebra estimate supplies a continuum tower, a physical constraint algebra, a renormalized limit or a Lorentzian emergence theorem.

Read each conclusion under its actual hypotheses and use its source locator to recover the surrounding assumptions. Source identity and excerpt fidelity are current documentation checks. Saved compiler and axiom transcripts are inherited proof evidence. This distinction continues through the replay chapter and full result map.

## 2 Navigation through the traditional paper

The final traditional volume has 154 physical PDF pages. Printed pages are the labels in that volume. PDF pages count the cover and Roman opening pages as well. Every location below was resolved from the actual body page label and checked against the source map. A shared subject does not imply identical formal coverage.

### 2.1 All 19 finite items in the traditional core

| Item | Number | Core statement | Printed | PDF |
|---|---|---|---|---|
| 2.1 | I.2.1 | Orbit dimension of one quantum seed | 5 | 13 |
| 2.2 | I.2.2 | Quantum seed-rank formula | 5 | 13 |
| 2.3 | I.2.3 | Local orbit and Schmidt rank | 6 | 14 |
| 2.4 | I.2.4 | One seed for the computational basis | 6 | 14 |
| 3.1 | I.3.1 | Cyclic quantum projectors | 7 | 15 |
| 3.2 | I.3.2 | Tensor/polyphase refinement | 7 | 15 |
| 4.1 | I.4.1 | Exact circuit path expansion | 8 | 16 |
| 4.2 | I.4.2 | Packetwise unitarity conservation | 9 | 17 |
| 5.1 | I.5.1 | Exact symmetry packets | 10 | 18 |
| 5.2 | I.5.2 | Commutator leakage bound | 11 | 19 |
| 6.1 | I.6.1 | Moving-frame Hamiltonian | 12 | 20 |
| 6.3 | I.6.3 | Canonical packet connection | 13 | 21 |
| 6.4 | I.6.4 | Projected connection | 14 | 22 |
| 7.1 | I.7.1 | Block-diagonal measurement invariance | 16 | 24 |
| 7.2 | I.7.2 | Finite Kraus channel | 17 | 25 |
| 8.1 | I.8.1 | Finite Knill–Laflamme criterion | 18 | 26 |
| 9.1 | I.9.1 | Exact Feshbach resolvent | 20 | 28 |
| 10.1 | I.10.1 | Finite Euclidean transfer | 22 | 30 |
| 11.1 | I.11.1 | Low-mode second-order bound | 25 | 33 |

### 2.2 Strengthened statements and the endpoint boundary

This index includes all 79 proof-bearing named statements in strengthened Part II. A relation identifies shared ingredients or a shared finite result. It does not claim that the whole stronger statement has a dedicated Lean theorem. Entries without a corresponding named endpoint remain written mathematical statements. They do not enlarge the 19-item ledger or the 323-declaration inventory.

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.2.2; 34 | Orbit dimension of one seed | Shared orbit-dimension result; item 2.1. | 42 |
| II.2.3; 34 | Quantum seed rank | Shared sharp seed-count result; item 2.2. | 42 |
| II.2.4; 34 | Local orbit and Schmidt rank | Shared local-orbit and reduced-support result; item 2.3. | 42 |
| II.2.5; 35 | Computational address orbit | Addressed local-X basis construction; item 2.4. | 43 |

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.3.1; 36 | Finite group isotypic projectors | Additional written statement. No corresponding named endpoint in the current 25-module development. | 44 |
| II.3.2; 36 | Representation matrix units | Additional written statement. No corresponding named endpoint in the current 25-module development. | 44 |
| II.3.3; 36 | Cyclic charge projectors | Cyclic specialization is encoded; item 3.1. | 44 |
| II.3.5; 37 | Charge selection rule | Additional written statement. No corresponding named endpoint in the current 25-module development. | 45 |
| II.3.6; 37 | Charge addition | Additional written statement. No corresponding named endpoint in the current 25-module development. | 45 |
| II.3.7; 38 | Tensor charge refinement | Finite tensor grouping is encoded; item 3.2. | 46 |
| II.3.8; 38 | Tensor selection rule | Additional written statement. No corresponding named endpoint in the current 25-module development. | 46 |
| II.4.1; 38 | Exact circuit path expansion | All finite circuit depths are encoded; item 4.1. | 46 |
| II.4.2; 39 | Packet unitarity identities | Both operator unitarity identities; item 4.2. | 47 |
| II.4.3; 39 | Probability conservation from one packet | Operator identity in item 4.2; state-probability corollary is an additional human statement. | 47 |
| II.4.4; 39 | Path interference formula | Additional written statement. No corresponding named endpoint in the current 25-module development. | 47 |
| II.4.5; 40 | Charge pruning of circuit paths | Additional written statement. No corresponding named endpoint in the current 25-module development. | 48 |
| II.5.1; 41 | Exact invariant packets | Fixed-generator exponential packet invariance; item 5.1. | 49 |
| II.5.2; 41 | Off diagonal norm | Additional written statement. No corresponding named endpoint in the current 25-module development. | 49 |
| II.5.3; 41 | Fixed packet leakage | Commutator leakage bound in item 5.2; the off-diagonal norm equality is an additional human statement. | 49 |
| II.5.4; 42 | Leakage probability | Additional written statement. No corresponding named endpoint in the current 25-module development. | 50 |
| II.6.1; 42 | Canonical packet connection | Canonical curve connection identities; item 6.3. | 50 |
| II.6.2; 43 | Exact Kato transport | Additional written statement. No corresponding named endpoint in the current 25-module development. | 51 |
| II.6.3; 43 | Moving frame Hamiltonian | Differentiated moving coordinates; item 6.1. | 51 |
| II.6.4; 44 | Moving packet leakage | Additional written statement. No corresponding named endpoint in the current 25-module development. | 52 |
| II.6.5; 44 | Direct packet rotation | Additional written statement. No corresponding named endpoint in the current 25-module development. | 52 |
| II.6.6; 45 | Convergence of short packet rotations | Additional written statement. No corresponding named endpoint in the current 25-module development. | 53 |

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.6.7; 46 | Nonabelian packet connection | Projected manifold curvature and gauge gluing in item 6.4; local orthonormal-frame formulas are additional human statements. | 54 |
| II.6.8; 47 | Bloch sphere curvature | Additional written statement. No corresponding named endpoint in the current 25-module development. | 55 |
| II.7.2; 47 | Complete operator packet system | Additional written statement. No corresponding named endpoint in the current 25-module development. | 55 |
| II.7.4; 48 | Dephasing as conditional expectation | Additional written statement. No corresponding named endpoint in the current 25-module development. | 56 |
| II.7.5; 49 | Block diagonal measurement invariance | Block-diagonal trace invariance; item 7.1. | 57 |
| II.7.6; 49 | Exact channel block calculus | Additional written statement. No corresponding named endpoint in the current 25-module development. | 57 |
| II.7.8; 50 | Coherence order projectors | Additional written statement. No corresponding named endpoint in the current 25-module development. | 58 |
| II.7.9; 50 | Covariant channels preserve coherence order | Additional written statement. No corresponding named endpoint in the current 25-module development. | 58 |
| II.7.10; 50 | Choi symmetry criterion | Additional written statement. No corresponding named endpoint in the current 25-module development. | 58 |
| II.7.11; 51 | Choi packet decomposition | Additional written statement. No corresponding named endpoint in the current 25-module development. | 59 |
| II.7.14; 52 | Charge preservation by a Lindblad generator | Additional written statement. No corresponding named endpoint in the current 25-module development. | 60 |
| II.7.15; 52 | Independent coherence evolution | Additional written statement. No corresponding named endpoint in the current 25-module development. | 60 |
| II.8.2; 53 | Knill Laflamme as obstruction vanishing | Unnormalized error-family criterion and span recovery in item 8.1; quotient notation is an additional human formulation. | 61 |
| II.8.3; 53 | Orthogonal syndrome construction | General positive Gram spectral reduction; item 8.1. | 61 |
| II.8.4; 54 | Exact recovery on the error span | One total recovery and normalized error-span channels; item 8.1. | 62 |
| II.8.5; 55 | Syndrome measurement preserves logical information | Syndrome cross-error identities support item 8.1; the measurement interpretation is an additional human statement. | 63 |
| II.8.7; 55 | Meaning of the approximate defect | Additional written statement. No corresponding named endpoint in the current 25-module development. | 63 |
| II.9.2; 57 | Exact projected resolvent | Corrected two-invertibility projected resolvent; item 9.1. | 65 |

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.9.3; 57 | Spectral equivalence | Schur/full invertibility equivalence in item 9.1; spectral and eigenvector formulations extend the endpoint. | 65 |
| II.9.4; 57 | Upper half plane sign | Additional written statement. No corresponding named endpoint in the current 25-module development. | 65 |
| II.9.5; 57 | Uniform self energy bounds | Additional written statement. No corresponding named endpoint in the current 25-module development. | 65 |
| II.9.6; 58 | Low energy expansion | Additional written statement. No corresponding named endpoint in the current 25-module development. | 66 |
| II.9.7; 59 | Bare truncation error identity | Additional written statement. No corresponding named endpoint in the current 25-module development. | 67 |
| II.9.8; 59 | Exact retained memory equation | Additional written statement. No corresponding named endpoint in the current 25-module development. | 67 |
| II.9.9; 59 | Positive definite quantum memory | Additional written statement. No corresponding named endpoint in the current 25-module development. | 67 |
| II.9.10; 60 | Finite oscillatory memory expansion | Additional written statement. No corresponding named endpoint in the current 25-module development. | 68 |
| II.9.11; 60 | Exact local closure criterion | Additional written statement. No corresponding named endpoint in the current 25-module development. | 68 |
| II.9.12; 61 | Stability of the self energy | Additional written statement. No corresponding named endpoint in the current 25-module development. | 69 |
| II.9.13; 61 | Uniform Feshbach control | Additional written statement. No corresponding named endpoint in the current 25-module development. | 69 |
| II.10.1; 62 | Finite Euclidean transfer | Actual shifted exponential, positivity and spectrum in item 10.1; read its exact endpoint. | 70 |
| II.10.2; 62 | Hamiltonian reconstruction from transfer | Additional written statement. No corresponding named endpoint in the current 25-module development. | 70 |
| II.10.3; 62 | Finite reflection positivity | Additional written statement. No corresponding named endpoint in the current 25-module development. | 70 |
| II.10.4; 63 | Reflection positive correlators | Additional written statement. No corresponding named endpoint in the current 25-module development. | 71 |
| II.10.5; 63 | Ground packet convergence | Additional written statement. No corresponding named endpoint in the current 25-module development. | 71 |
| II.10.6; 63 | Symmetry resolved transfer | Additional written statement. No corresponding named endpoint in the current 25-module development. | 71 |

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.11.2; 64 | Finite scale limits | Additional written statement. No corresponding named endpoint in the current 25-module development. | 72 |
| II.11.3; 64 | Heat packet decomposition | Additional written statement. No corresponding named endpoint in the current 25-module development. | 72 |
| II.11.4; 65 | Low mode dispersion in dimension d | One-dimensional scalar bound in item 11.1; the d-dimensional summed statement is an additional human result. | 73 |
| II.11.5; 65 | Fixed time heat trace convergence | Additional written statement. No corresponding named endpoint in the current 25-module development. | 73 |
| II.11.7; 66 | Continuum torus small time dimension | Additional written statement. No corresponding named endpoint in the current 25-module development. | 74 |
| II.11.8; 66 | Rigorous intermediate dimension window | Additional written statement. No corresponding named endpoint in the current 25-module development. | 74 |
| II.12.2; 67 | Finite constraint closure criterion | Additional written statement. No corresponding named endpoint in the current 25-module development. | 75 |
| II.12.3; 68 | Physical compression is not a closure test | Finite common-kernel compression audit is encoded in ConstraintAudit. | 76 |
| II.12.4; 68 | Invariance of the physical space | Additional written statement. No corresponding named endpoint in the current 25-module development. | 76 |
| II.12.5; 69 | Exact constraint transport | Additional written statement. No corresponding named endpoint in the current 25-module development. | 77 |
| II.12.6; 69 | Approximate constraint transport | Additional written statement. No corresponding named endpoint in the current 25-module development. | 77 |
| II.13.2; 71 | Bounded Hamiltonian direct limit | Additional written statement. No corresponding named endpoint in the current 25-module development. | 79 |
| II.13.3; 71 | Exact packet direct limit | Additional written statement. No corresponding named endpoint in the current 25-module development. | 79 |
| II.13.4; 72 | Norm summable Hamiltonian tower | Additional written statement. No corresponding named endpoint in the current 25-module development. | 80 |
| II.13.5; 72 | Limit of packet leakage | Additional written statement. No corresponding named endpoint in the current 25-module development. | 80 |
| II.13.6; 72 | Reflection positivity is closed under limits | Additional written statement. No corresponding named endpoint in the current 25-module development. | 80 |
| II.13.7; 73 | Constraint closure under norm convergence | Additional written statement. No corresponding named endpoint in the current 25-module development. | 81 |

| Number; printed | Strengthened statement | Relation to the current formal source | PDF |
|---|---|---|---|
| II.13.8; 73 | Heat trace convergence from trace norm | Additional written statement. No corresponding named endpoint in the current 25-module development. | 81 |

### 2.3 Retained supplements explain the constructed proofs

Part III retains the mathematical portions of all six formal supplements. Read their historical descriptions in order: later constructions strengthen earlier restricted coverage. The source-bound endpoint map records the current result.

| Sections | Retained proof material | Printed | PDF |
|---|---|---|---|
| III.1–III.5 | Packet algebra, symmetry and measurements. Corrected resolvent, spacing condition, and finite constraint audit. | 77–81 | 85–89 |
| III.6–III.10 | Addressed computational seed, tensor refinement, moving coordinates, canonical connection, and Kraus amplification. | 82–85 | 90–93 |
| III.11–III.14 | Actual orbit spaces, sharp seed counts, independently defined Schmidt rank, cyclic characters, and Euclidean exponential. | 86–89 | 94–97 |
| III.15–III.17 | Actual-exponential leakage, chart projected curvature, and total orthogonal-syndrome recovery. | 90–93 | 98–101 |
| III.18–III.23 | General Gram spectral reduction, actual recovery necessity, density/operator bridge, finite references, and error spans. | 94–99 | 102–107 |
| III.24–III.27 | Constructed range local products, smooth transitions, global connection, gauge law, and actual manifold curvature. | 99–101 | 107–109 |

## 3 Seeds, local orbits, and the packet resolution

### 3.1 One seed: identify the actual image before counting it

The starting coefficient array is $C \in \mathrm{Mat}_{d\times m}(\mathbb{C})$. Left multiplication by an arbitrary $d \times d$ matrix changes each row independently within the row space of $C$. This observation is the entire mechanism behind the orbit dimension formula. Lean first defines the row space as the range of the actual right-multiplication linear map; it then defines the orbit as the range of that map acting on all $d$ rows. It does not assume an orbit dimension as an input.

**Contract.** The row and multiplicity index types `d` and `m` have finite enumerations. The orbit is an algebra-action orbit $\{AC : A \in \mathrm{Mat}_{d\times d}(\mathbb{C})\}$, already a linear subspace. Its dimension result has no nonempty-row assumption. The full-orbit equivalence adds `[Nonempty d]` because it cancels the positive row cardinality.

The lemma `mem_orbit_iff_rows` supplies both directions. If $X = AC$, each row of $X$ is a linear combination of rows of $C$. Conversely, choose one coefficient row for each row of $X$, collect them into a matrix $A$, and obtain $AC = X$. The latter choice is an existence argument using classical choice. It is not a numerical algorithm for choosing coefficients.

The explicit linear equivalence below packages that row-by-row correspondence. Its domain is the subspace of reachable coefficient arrays; its codomain is the function space whose value at each row is a member of the row space. Both inverse laws reduce to the underlying functions.

Source: `formalization/SeedOrbit.lean`.

Exact lines 45–52; excerpt `row_equiv`. Hash in Section 12.

```
noncomputable def orbitRowEquiv (C : Matrix d m ℂ) :
    orbitSpace C ≃ₗ[ℂ] (d → rowSpace C) where
  toFun X i := ⟨X.val i, (mem_orbit_iff_rows C X.val).mp X.property i⟩
  invFun f := ⟨fun i => (f i).val, (mem_orbit_iff_rows C _).mpr (fun i => (f i).property)⟩
  left_inv _ := rfl
  right_inv _ := rfl
  map_add' _ _ := rfl
  map_smul' _ _ := rfl
```

**Proof reading.** The `toFun` field extracts the rows and attaches the proved row-space membership. The `invFun` field assembles those rows, using the reverse membership implication. The equalities of functions are definitional, so the inverse and linearity proofs are `rfl`. Taking dimensions of this equivalence gives $|d|\,\mathrm{rank}\,C$. The extra `orbit_span` lemma identifies the subspace with the span of the literal action set.

Source: `formalization/SeedOrbit.lean`.

Exact lines 68–71; excerpt `orbit_dimension`. Hash in Section 12.

```
theorem span_orbit_dimension (C : Matrix d m ℂ) :
    finrank ℂ (Submodule.span ℂ (Set.range fun A : Matrix d d ℂ => A * C)) =
      Fintype.card d * C.rank := by
  rw [orbit_span, orbit_dimension]
```

Source: `formalization/SeedOrbit.lean`.

Exact lines 73–80; excerpt `cyclic_rank`. Hash in Section 12.

```
theorem cyclic_iff_full_rank [Nonempty d] (C : Matrix d m ℂ) :
    orbitSpace C = ⊤ ↔ C.rank = Fintype.card m := by
  rw [Submodule.eq_top_iff_finrank_eq, orbit_dimension]
  have hdim : finrank ℂ (Matrix d m ℂ) = Fintype.card d * Fintype.card m := by
    change finrank ℂ (d → m → ℂ) = _
    simp [Module.finrank_pi_fintype]
  rw [hdim]
  exact Nat.mul_left_cancel_iff (Fintype.card_pos)
```

The nonempty condition deserves attention. If there are no row indices, the ambient coefficient space is zero and every orbit is already full, regardless of the multiplicity index. Cancelling $|d|$ would be invalid. Lean's final cancellation explicitly uses `Fintype.card_pos`; it records precisely why the full-rank test needs an inhabitant. Multiplicity zero is permitted and produces a zero-dimensional target.

### 3.2 Several seeds: stack them and prove a minimum

Continue with a nonempty row index type. For $k$ seeds $C_a$, the allowed generation is

$$X = \sum_{a \in k} A_a C_a,$$

where the algebra element $A_a$ may differ for each seed. This is a linear generating-family problem. The implementation records its universal quantifier over $X$ and its existential family of coefficient matrices.

Source: `formalization/SeedOrbit.lean`.

Exact lines 127–128; excerpt `seed_generate`. Hash in Section 12.

```
def Generates (C : k → Matrix d m ℂ) : Prop :=
  ∀ X : Matrix d m ℂ, ∃ A : k → Matrix d d ℂ, ∑ a, A a * C a = X
```

Source: `formalization/SeedOrbit.lean`.

Exact lines 148–150; excerpt `stack_rank`. Hash in Section 12.

```
theorem generates_iff_rank [Nonempty d] (C : k → Matrix d m ℂ) :
    Generates C ↔ (stackSeeds C).rank = Fintype.card m := by
  rw [generates_iff_rowOrbit, rowOrbit_full]
```

Stacking the seeds gives one matrix with row index $k \times d$. Its row space is the span of all the seed rows. The lemma `stacked_action` proves entrywise that multiplication by the large coefficient matrix is exactly the displayed sum. The rank test therefore says that the stacked seed matrix has full column rank. A rank upper bound gives the necessary inequality $|m| \leq |k||d|$.

The reverse direction is constructive at the matrix level. When the number of columns does not exceed the available row slots, choose an injection of column indices into row indices and place a $1$ at each corresponding coordinate, with zeros elsewhere. The associated multiplication map is injective because its selected output coordinates reproduce the original input coordinates. The rank theorem follows from that injectivity.

Source: `formalization/SeedOrbit.lean`.

Exact lines 158–171; excerpt `full_column`. Hash in Section 12.

```
theorem exists_full_column_rank (h : Fintype.card m ≤ Fintype.card d) :
    ∃ C : Matrix d m ℂ, C.rank = Fintype.card m := by
  classical
  obtain ⟨f⟩ := Function.Embedding.nonempty_of_card_le h
  let C : Matrix d m ℂ := fun i j => if i=f j then 1 else 0
  have hC (x : m → ℂ) (j : m) : (C *ᵥ x) (f j) = x j := by
    simp [C, Matrix.mulVec, dotProduct, f.injective.eq_iff]
  have hi : Function.Injective C.mulVecLin := by
    intro x y hxy
    funext j
    have h := congrFun hxy (f j)
    simpa only [Matrix.mulVecLin_apply, hC] using h
  refine ⟨C, ?_⟩
  rw [Matrix.rank, LinearMap.finrank_range_of_inj hi, Module.finrank_pi]
```

For a finite direct-sum family, `dd mm : I → ℕ` gives the matrix row dimension and multiplicity of each block. A seed now contains one coefficient array in every block. `BlockGenerates` quantifies over simultaneous block targets and permits simultaneous block algebra elements. The equivalence `block_generates_iff` proves that this is exactly the collection of individual generation tests. It does not replace the simultaneous problem by an unproved heuristic.

**Contract.** Every row dimension `dd i` is positive. Multiplicities `mm i` may vanish. The block index `I` is any finite type, including the empty type. The formula is the finite supremum of natural-number ceiling divisions, so an empty block family gives zero.

Define

$$r = \max_{i \in I} \left\lceil \frac{m_i}{d_i} \right\rceil .$$

The source writes this as `Finset.univ.sup` with natural ceiling division. The lemma `seed_formula_le_iff` translates $r \leq s$ into all inequalities $m_i \leq s d_i$. The existence equivalence constructs seeds exactly when those inequalities hold. The final result is `IsLeast`: it proves both that $r$ seeds exist and that every successful seed count is at least $r$.

Source: `formalization/SeedOrbit.lean`.

Exact lines 239–246; excerpt `seed_minimum`. Hash in Section 12.

```
theorem quantum_seed_rank (dd mm : I → ℕ) (hd : ∀ i, 0 < dd i) :
    IsLeast {s : ℕ | ∃ C : Fin s → (i : I) → Matrix (Fin (dd i)) (Fin (mm i)) ℂ,
      BlockGenerates dd mm C} (seedRankFormula dd mm) := by
  constructor
  · exact (exists_block_seeds_iff dd mm hd _).mpr
      ((seed_formula_le_iff dd mm hd _).mp le_rfl)
  · intro s hs
    exact (seed_formula_le_iff dd mm hd s).mpr ((exists_block_seeds_iff dd mm hd s).mp hs)
```

**Proof reading.** The first half of the pair uses `le_rfl` to show the formula satisfies its own inequalities, then applies the proved existence criterion. The second half takes any witness at count $s$, converts its existence to the inequalities, then converts those inequalities back to $r \leq s$. Thus minimality and attainability are both present. The conclusion is stronger than merely displaying a candidate formula.

### 3.3 Schmidt rank is independently defined

For a bipartite vector $\psi : d \times m \to \mathbb{C}$, `coefficientEquiv` identifies $\psi(i, j)$ with the coefficient matrix $C_{ij}$. The local action $A \otimes 1$ becomes $AC$ in those standard product coordinates. This identity is proved by expanding the Kronecker product and summing over the product index.

Source: `formalization/SeedOrbit.lean`.

Exact lines 261–265; excerpt `local_action`. Hash in Section 12.

```
theorem local_tensor_action [DecidableEq m] (A : Matrix d d ℂ) (psi : d × m → ℂ) :
    coefficientEquiv ((A ⊗ₖ (1 : Matrix m m ℂ)) *ᵥ psi) = A * coefficientEquiv psi := by
  ext i j
  simp [coefficientEquiv, Matrix.mulVec, dotProduct,
    Fintype.sum_prod_type, Matrix.one_apply, Matrix.mul_apply]
```

The source does not define Schmidt rank to mean matrix rank and then use that name in a tautology. `HasProductDecomposition C s` means an actual representation

$$C_{ij} = \sum_{a<s} u_a(i) v_a(j).$$

Such a representation factors $C$ through an $s$-dimensional coordinate space, so $\operatorname{rank} C \le s$. Conversely, choose a basis of the row space and express each row in that basis. The row-basis vectors and their coordinate functions give a product decomposition of length exactly $\operatorname{rank} C$. These two directions prove that matrix rank is the least possible product length.

Source: `formalization/SeedOrbit.lean`.

Exact lines 298–300; excerpt `schmidt_minimum`. Hash in Section 12.

```
theorem product_length_minimum (C : Matrix d m ℂ) :
    IsLeast {s : ℕ | HasProductDecomposition C s} C.rank := by
  exact ⟨product_decomposition_at_rank C, fun _ h => product_decomposition_rank_bound C h⟩
```

Source: `formalization/SeedOrbit.lean`.

Exact lines 303–306; excerpt `schmidt_definition`. Hash in Section 12.

```
noncomputable def schmidtRank (psi : d × m → ℂ) : ℕ := by
  classical
  exact Nat.find (show ∃ s, HasProductDecomposition (coefficientEquiv psi) s from
    ⟨_, product_decomposition_at_rank _⟩)
```

`Nat.find` takes the least natural number for which a product decomposition exists. The existence needed by `Nat.find` has already been proved at the rank. The equality `schmidt_rank_eq_matrix_rank` then uses the upper witness and the rank lower bound in opposite directions. It is an equality between independently introduced objects.

The reduced $B$ matrix is also constructed explicitly:

$$(\rho_B)_{j\ell} = \sum_i \psi(i, j) \overline{\psi(i, \ell)}.$$

In the chosen convention it is $C^T(C^T)^*$. Its positivity follows from this Gram representation. Its rank agrees with the matrix rank of $C$, hence with Schmidt rank. Full support is expressed as surjectivity of its multiplication linear map. Combining this with the local orbit dimension gives the endpoint below.

Source: `formalization/SeedOrbit.lean`.

Exact lines 364–366; excerpt `reduced_support`. Hash in Section 12.

```
theorem local_orbit_reduced_support [Nonempty d] (psi : d × m → ℂ) :
    localOrbit psi = ⊤ ↔ LinearMap.range (reducedB psi).mulVecLin = ⊤ := by
  rw [local_orbit_full_iff, reduced_full_support_iff]
```

**Contract.** The full local-orbit/support equivalence assumes `[Nonempty d]`. The dimension equality itself includes zero vectors and empty index types. No normalization of $\psi$ is required for these algebraic rank statements. The action uses every matrix $A$, so the result concerns the linear span under the local operator algebra. It does not assert reachability under an arbitrary restricted family of unitary controls.

### 3.4 Addressed bit flips give a computational basis

`Address n` is `Fin n → ZMod 2`; it is the finite set of bit strings. `State n` is the complex vector space of functions on that address set. The seed is the coordinate vector at the zero address. The linear operator `translation a` evaluates a vector at $x - a$. On a ket it gives $|b\rangle \mapsto |a + b\rangle$.

Each `localX j` translates by the bit vector supported at coordinate $j$. The operator named `controlledX a j` in this module is selected by the classical address bit $a_j$: it is identity when that bit is zero, and the local $X$ otherwise. This definition is an address-dependent selection of a gate; its name should not be read as a separately formalized two-qubit controlled-NOT gate.

The address circuit is the product of this finite gate list. Translation products add their addresses, and the sum of the local address contributions equals $a$. Therefore the circuit translates by $a$ and sends the zero seed to the coordinate basis vector at $a$.

Source: `formalization/ComputationalSeed.lean`.

Exact lines 72–77; excerpt `seed_translation`. Hash in Section 12.

```
theorem circuit_eq_translation {n : ℕ} (a : Address n) :
    addressCircuit a = translation a := by
  unfold addressCircuit
  simp_rw [controlledX_eq_translation]
  simpa only [List.map_ofFn, Function.comp_def, List.sum_ofFn, sum_local_addresses] using
    translation_list_product (List.ofFn (fun j : Fin n => Pi.single j (a j)))
```

Source: `formalization/ComputationalSeed.lean`.

Exact lines 80–82; excerpt `seed_basis`. Hash in Section 12.

```
theorem circuit_seed_basis {n : ℕ} (a : Address n) :
    addressCircuit a (seed n) = Pi.basisFun ℂ (Address n) a := by
  rw [circuit_seed, Pi.basisFun_apply, ket]
```

The basis theorem then supplies linear independence and full span. The cardinality theorem gives $2^n$. When $n = 0$, the bit-string type has exactly one empty address, the gate list is empty, and its product is identity. The source covers this case without a separate positive-qubit assumption.

### 3.5 Cyclic projectors from actual finite-order powers

Let $N > 0$ and $S^N = 1$. The source uses `ZMod N` as the residue type and the standard primitive additive character $\chi$. It defines

$$P_j = \frac{1}{N} \sum_{r \in \mathbb{Z}/N} \chi(-rj) S^{r.\mathrm{val}}.$$

The representation `cyclicPowers S` is constructed from the actual powers of $S$. The proof of its addition law uses $S^N = 1$ to reduce an exponent modulo $N$. The root of unity is identified with $\exp(2\pi i/N)$, and the coefficient lemma recovers the familiar inverse power $\omega^{-rj}$.

Source: `formalization/CyclicProjectors.lean`.

Exact lines 22–26; excerpt `cyclic_character`. Hash in Section 12.

```
theorem character_sum (t : ZMod N) :
    ∑ r : ZMod N, stdAddChar (t*r) = if t=0 then (N : ℂ) else 0 := by
  split_ifs with h
  · simp [h]
  · exact sum_eq_zero_of_ne_one (isPrimitive_stdAddChar N h)
```

The character-sum lemma is the cancellation mechanism. When its argument is zero the sum is $N$; when it is nonzero, primitivity makes the sum vanish. To prove multiplication of packets, first show that left multiplication by the representation acts on a packet by its character. Substitute that eigenaction into the packet product and collapse the remaining character sum.

Source: `formalization/CyclicProjectors.lean`.

Exact lines 44–58; excerpt `cyclic_mul`. Hash in Section 12.

```
theorem packet_mul (rho : ZMod N → A)
    (hadd : ∀ a b, rho (a+b) = rho a * rho b) (j k : ZMod N) :
    packet rho j * packet rho k = if j=k then packet rho j else 0 := by
  conv_lhs => lhs; unfold packet
  rw [Algebra.smul_mul_assoc, Finset.sum_mul]
  simp only [Algebra.smul_mul_assoc, packet_eigen rho hadd, smul_smul,
    ← map_add_eq_mul]
  have hf (r : ZMod N) : -(r*j) + r*k = (k-j)*r := by ring
  simp only [hf]
  rw [← Finset.sum_smul, character_sum]
  by_cases h : j=k
  · subst k
    simp [NeZero.ne N]
  · have hk : k-j ≠ 0 := sub_ne_zero.mpr (Ne.symm h)
    simp [hk, h]
```

Completeness follows from exchanging the two finite sums and applying the same orthogonality in the other index. Adjointness is a separate star-ring argument: conjugate the character, replace $r$ by $-r$, and use the adjoint law for unitary powers. A finite-order element gives the idempotent decomposition; unitarity supplies the Hermitian condition in the complex-matrix endpoint.

Source: `formalization/CyclicProjectors.lean`.

Exact lines 157–170; excerpt `cyclic_matrix`. Hash in Section 12.

```
theorem finite_cyclic_projectors {n : Type*} [Fintype n] [DecidableEq n]
    (S : Matrix n n ℂ) (hS : S^N=1) (hU : S ∈ unitary (Matrix n n ℂ)) :
    (∀ j k : ZMod N, packet (cyclicPowers S) j * packet (cyclicPowers S) k =
      if j=k then packet (cyclicPowers S) j else 0) ∧
    (∑ j : ZMod N, packet (cyclicPowers S) j) = 1 ∧
    (∀ j : ZMod N, S * packet (cyclicPowers S) j =
      omega (N := N)^j.val • packet (cyclicPowers S) j) ∧
    ∀ j : ZMod N, (packet (cyclicPowers S) j).IsHermitian := by
  obtain ⟨hp, hs, he⟩ := cyclic_quantum_projectors S hS
  refine ⟨hp, hs, ?_, ?_⟩
  · intro j
    simpa only [character_as_power] using he j
  · intro j
    exact cyclic_packet_selfAdjoint S hS hU j
```

**Contract.** The ambient general construction is a complex algebra over a ring. The concrete endpoint has a finite matrix state index and decidable equality. `[NeZero N]` excludes zero modulus, includes $N = 1$, and justifies division by $N$. The theorem does not require every packet to have nonzero rank.

### 3.6 Tensor factors and regrouping by residue

The tensor implementation uses a finite factor index `F`, with a potentially different state index `D i` in every factor. A tensor matrix is defined by the product of its local entries. Multiplication expands into a sum over dependent tuples of intermediate indices. The finite product-of-sums identity converts that sum back into the product of local matrix multiplications.

Source: `formalization/TensorRefinement.lean`.

Exact lines 20–27; excerpt `tensor_mul`. Hash in Section 12.

```
theorem tensor_mul (A B : (i : F) → Matrix (D i) (D i) ℂ) :
    tensor (fun i => A i * B i) = tensor A * tensor B := by
  ext x y
  simp only [tensor, Matrix.mul_apply]
  rw [Fintype.prod_sum]
  apply Finset.sum_congr rfl
  intro z _
  exact Finset.prod_mul_distrib
```

The product formula, identity formula, adjoint formula and sum formula then prove that the fine packets indexed by tuples are mutually orthogonal, complete and Hermitian. The coarse construction sums fine packets with the same address. Its generic ring-level proof shows that grouping an orthogonal resolution by any finite address map remains an orthogonal resolution. For polyphase grouping, the address is the sum of the factor residues in `ZMod N`.

Source: `formalization/TensorRefinement.lean`.

Exact lines 139–154; excerpt `tensor_refinement`. Hash in Section 12.

```
theorem tensor_polyphase_refinement {F : Type*} [Fintype F] [DecidableEq F] {D : F → Type*}
    [∀ i, Fintype (D i)] [∀ i, DecidableEq (D i)]
    (N : ℕ) [NeZero N] (P : (i : F) → ZMod N → Matrix (D i) (D i) ℂ)
    (hmul : ∀ i j k, P i j * P i k = if j = k then P i j else 0)
    (hsum : ∀ i, ∑ j, P i j = 1)
    (hstar : ∀ i j, (P i j).conjTranspose = P i j) :
    let Q := fun a : F → ZMod N => tensor (fun i => P i (a i))
    let C := coarse Q (fun a => ∑ i, a i)
    (∀ r s, C r * C s = if r = s then C r else 0) ∧
      (∑ r, C r) = 1 ∧ (∀ r, (C r).conjTranspose = C r) := by
  classical
  dsimp only
  refine ⟨?_, ?_, ?_⟩
  · exact coarse_mul _ _ (fine_mul P hmul)
  · exact coarse_complete _ _ (fine_complete P hsum)
  · exact coarse_selfAdjoint _ _ (fine_selfAdjoint P hstar)
```

**Proof reading.** The two `let` bindings expose the fine family $Q_a$ and the coarse family $C_r$ inside the statement. After `dsimp only`, each conclusion is a direct application of the generic coarse theorem to a previously proved fine-family theorem. The code therefore separates tensor construction from finite grouping, which makes the proof reusable.

The input here is a packet resolution in each tensor factor. The source does not rederive those local packets from each factor's cyclic symmetry inside this theorem; the cyclic-projector endpoint is the preceding construction that can supply them. Together the two constructions implement the traditional passage from cyclic local packets to a tensor refinement and total-residue packets.

# 4 Circuit corners, conserved packets, and leakage

## 4.1 The order of the indices is part of the definition

For a packet resolution $P$, the corner of an operator is

$$U_{ba} = P_b U P_a.$$

The target index $b$ comes first, and the source index $a$ comes second. Matrix factors act from the right on a vector. The gate list in `QuantumPacketCore` is written latest to earliest, $[U_m, \dots, U_1]$, so its product is $U_m \cdots U_1$. Both conventions are explicit source comments and definitions; they determine the orientation of every path.

**Contract.** The basic corner identities require an arbitrary ring `R` and a finite packet index with decidable equality. They require the packet multiplication and completeness laws, but neither an adjoint nor a norm. The coefficients are generally noncommutative.

Inserting $\sum_c P_c = 1$ between two operators gives

$$(UV)_{ba} = \sum_c U_{bc} V_{ca}.$$

The code first rewrites an individual product of corners. The adjacent $P_c P_c$ collapses by idempotence, while all other factors keep their order. Only then does it combine the finite sum and use completeness.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 41–50; excerpt `compose_blocks`. Hash in Section 12.

```
theorem compose_blocks (U V : R) (b a : I) :
    P.block (U * V) b a = ∑ c, P.block U b c * P.block V c a := by
  have term (c : I) : P.block U b c * P.block V c a =
      P.proj b * U * P.proj c * V * P.proj a := by
    unfold block
    calc
      _ = P.proj b * U * (P.proj c * P.proj c) * V * P.proj a := by noncomm_ring
      _ = _ := by rw [P.idempotent]
  simp_rw [term]
  simp only [← Finset.sum_mul, ← Finset.mul_sum, P.sum_proj, block, mul_assoc, one_mul]
```

This is the local mechanism for the whole path expansion. `pathSum` is an explicit recursively nested finite sum. For no gates, its value is $P_b P_a$, preserving the boundary packet. For a gate $U$ followed by a shorter circuit, it sums $U_{bc}$ times the shorter path from $a$ to $c$.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 63–68; excerpt `circuit_path`. Hash in Section 12.

```
theorem circuit_path_expansion (Us : List R) (b a : I) :
    P.block (circuit Us) b a = P.pathSum Us b a := by
  induction Us generalizing b a with
  | nil => simp [circuit, pathSum, block]
  | cons U Us ih =>
      simp only [circuit, pathSum, P.compose_blocks, ih]
```

**Proof reading.** The induction generalizes both boundary indices, which makes the induction hypothesis available at every intermediate $c$. The empty case reduces the identity corner. In the nonempty case, the composition-of-corners lemma creates the exact finite sum needed by the recursive definition; the induction hypothesis replaces each shorter corner. This proves all finite depths rather than checking a two-gate illustration.

Summing the resulting path values over source and target reconstructs the complete circuit operator. It retains coherent complex amplitudes and operator products. No step converts the path sum into a stochastic transition law or assumes that different paths are mutually incoherent.

### 4.2 The two unitarity identities use different hypotheses

To take adjoints, supply a star-ring structure and self-adjoint packet elements. The adjoint swaps source and target:

$$U^*_{ba} = (U^*)_{ab}.$$

For the column identity, the source needs only $U^*U = 1$:

$$\sum_b U^*_{ba} U_{bc} = \delta_{ac} P_a.$$

For the row identity, it needs $UU^* = 1$:

$$\sum_a U_{ba} U^*_{da} = \delta_{bd} P_b.$$

The source states these separately rather than hiding both inside a single unitary predicate. The distinction matters in abstract star rings where a one-sided inverse need not be two-sided.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 119–131; excerpt `unitarity_columns`. Hash in Section 12.

```
theorem unitarity_columns (U : R) (hU : star U * U = 1) (a c : I) :
    (∑ b, star (P.block U b a) * P.block U b c) =
      if a = c then P.proj a else 0 := by
  have term (b : I) : star (P.block U b a) * P.block U b c =
      P.proj a * star U * P.proj b * U * P.proj c := by
    rw [P.adjoint_block hstar]
    unfold block
    calc
      _ = P.proj a * star U * (P.proj b * P.proj b) * U * P.proj c := by noncomm_ring
      _ = _ := by rw [P.idempotent]
  simp_rw [term]
  rw [← Finset.sum_mul, ← Finset.sum_mul, ← Finset.mul_sum, P.sum_proj, mul_one]
  rw [mul_assoc (P.proj a), hU, mul_one, P.mul_proj]
```

**Proof reading.** The local term is reorganized to $P_a U^* P_b U P_c$, using self-adjointness and $P_b^2 = P_b$. Summing over $b$ replaces the middle resolution by the identity. The given equation $U^*U = 1$ removes the operator factors. The final packet multiplication gives the conditional expression in the conclusion. The concrete matrix wrappers merely specialize this already proved identity.

For an actual state, this identity can be combined with the Hilbert-space inner product to interpret conservation of total packet probability. The formal statement displayed here is the operator identity.

A chosen vector, state normalization and the appropriate inner-product interpretation are additional data in such an application.

### 4.3 Exact commutation propagates to the actual exponential

If $H$ commutes with each $P_a$, its cross-packet corners vanish and the diagonal corners reconstruct $H$. The dynamics layer uses a normed complex algebra and the actual power-series exponential. A `Commute` proof for $H$ and $P_a$ propagates through complex scalar multiplication and the exponential. Thus $e^{zH}$ is diagonal in the same packet resolution for every complex scalar $z$.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 168–171; excerpt `symmetry_exp`. Hash in Section 12.

```
theorem symmetry_exponential_no_transfer (H : R)
    (hH : ∀ i, H * P.proj i = P.proj i * H) (z : ℂ)
    (b a : I) (hba : b ≠ a) : P.block (NormedSpace.exp (z • H)) b a = 0 :=
  P.symmetry_no_transfer _ (P.symmetry_exponential_commutes H hH z) b a hba
```

For real-time evolution set $z = -it$. The conclusion is exact zero transfer between distinct packets. The commutation hypothesis is still required. It can be proved from a chosen symmetry or supplied as data; the theorem does not infer it merely from the existence of a packet resolution.

### 4.4 Leakage begins with a differentiated conjugation

The quantitative result works first in an abstract complex C-star algebra. Its matrix specialization activates the Hilbert-space operator norm through `Matrix.Norms.L2Operator`. This scope is essential: the displayed bound is not an arbitrary entrywise matrix norm estimate.

Let $G^* = -G$ and set $V(t) = e^{tG}Pe^{-tG}$. The source constructs this function and differentiates the actual exponential product:

$$V'(t) = e^{tG}(GP - PG)e^{-tG}.$$

It proves that the exponentials are unitary. Left and right multiplication by unitary elements preserve the C-star norm, so $\|V'(t)\| = \|GP - PG\|$.

Source: `formalization/LeakageBound.lean`.

Exact lines 31–38; excerpt `transport_derivative`. Hash in Section 12.

```
theorem transported_derivative (G P : A) (t : ℝ) :
    HasDerivAt (transported G P)
      (exp (t • G) * (G * P - P * G) * exp (t • (-G))) t := by
  have hd := ((hasDerivAt_exp_smul_const G t).mul_const P).mul
    (hasDerivAt_exp_smul_const' (-G) t)
  convert hd using 1
  · rfl
  · noncomm_ring
```

Source: `formalization/LeakageBound.lean`.

Exact lines 46–54; excerpt `transport_lipschitz`. Hash in Section 12.

```
theorem transported_lipschitz (G P : A) (hG : star G = -G) (t s : ℝ) :
    ‖transported G P t - transported G P s‖ ≤
      |t-s| * ‖G*P-P*G‖ := by
  have hh := Convex.norm_image_sub_le_of_norm_deriv_le
    (f := transported G P) (s := Set.univ)
    (fun x _ => (transported_derivative G P x).differentiableAt)
    (fun x _ => (transported_derivative_norm G P hG x).le)
    convex_univ (Set.mem_univ s) (Set.mem_univ t)
  simpa [Real.norm_eq_abs, mul_comm] using hh
```

**Proof reading.** The Lipschitz proof applies a mean-value norm inequality on the convex set of all real times. Its derivative-existence argument comes from `transported_derivative`, and its uniform derivative bound comes from `transported_derivative_norm`. Both are proved for the actual function. Taking one time to be zero gives a bound for $V(t) - P$; multiplying by $e^{tG}$ converts it into a bound for $e^{tG}P - Pe^{tG}$.

For an orthogonal projection,

$$(1 - P)UP = (1 - P)(UP - PU)P.$$

The two projection norms are at most one. Hence the leakage corner is bounded by the exponential commutator. Substitute $G = -iH$ for self-adjoint $H$; its commutator norm equals the norm of $HP-PH$. This gives the concrete endpoint.

Source: `formalization/LeakageBound.lean`.

Exact lines 167–171; excerpt `leakage_matrix`. Hash in Section 12.

```
theorem matrix_commutator_leakage_bound {n : Type*} [Fintype n] [DecidableEq n]
    (H P : Matrix n n ℂ) (hH : H.IsHermitian) (hP : P.IsHermitian)
    (hPP : P*P=P) (t : ℝ) :
    ‖(1-P) * exp ((-(t : ℂ)*Complex.I) • H) * P‖ ≤ |t| * ‖H*P-P*H‖ := by
  exact commutator_leakage_bound H P hH.isSelfAdjoint ⟨hPP, hP.isSelfAdjoint⟩ t
```

**Contract.** The matrix index may be empty. $H$ must be Hermitian and $P$ must be both Hermitian and idempotent. Time is every real $t$, including zero and negative times. The proof does not divide by projector rank, dimension or time, so it includes $P = 0$ and $P = 1$. The estimate concerns a fixed generator $H$ and its exponential, rather than a general time-dependent propagator.

The same file proves a cap at one, giving $\min(1, |t|\|[H, P]\|)$, and exact zero leakage when the commutator is zero. If $H = H_0 + V$ with $[H_0, P] = 0$ and both terms self-adjoint, only $V$ contributes to the commutator. The elementary estimate $\|[V, P]\| \leq 2\|V\|$ gives the perturbation corollary.

Source: `formalization/LeakageBound.lean`.

Exact lines 151–164; excerpt `leakage_perturbation`. Hash in Section 12.

```
theorem perturbation_leakage_bound (H₀ V P : A)
    (hH₀ : IsSelfAdjoint H₀) (hV : IsSelfAdjoint V)
    (hP : IsStarProjection P) (hcomm : H₀*P=P*H₀) (t : ℝ) :
    ‖(1-P)*exp ((-(t : ℂ)*Complex.I) • (H₀+V))*P‖ ≤ 2*|t| *‖V‖ := by
  have hc : (H₀+V)*P-P*(H₀+V) = V*P-P*V := by
    rw [add_mul, mul_add, hcomm]
    noncomm_ring
  have hh := commutator_leakage_bound (H₀+V) P (hH₀.add hV) hP t
  rw [hc] at hh
  calc
    _ ≤ |t| *‖V*P-P*V‖ := hh
    _ ≤ |t| *(2*‖V‖) := mul_le_mul_of_nonneg_left
      (projection_commutator_norm_le V P hP) (abs_nonneg t)
    _ = _ := by ring
```

### 4.5 Dephasing and a precisely restricted measurement invariance

The dephasing map is $\Delta(\rho) = \sum_a P_a \rho P_a$. It removes off-diagonal corners and is idempotent. The finite complex-matrix proof of trace duality says

$$\mathrm{tr}(\Delta(E)\rho) = \mathrm{tr}(E\Delta(\rho)).$$

It follows by expanding the finite sum and cyclically rotating matrix factors inside each trace. The subsequent measurement theorem supplies the condition $\Delta(E) = E$, exactly the block-diagonal-observable condition.

Source: `formalization/QuantumPacketCore.lean`.

Exact lines 208–211; excerpt `measurement`. Hash in Section 12.

```
theorem measurement_invariance (E rho : Matrix n n ℂ) (hE : P.dephase E = E) :
    Matrix.trace (E * rho) = Matrix.trace (E * P.dephase rho) := by
  rw [← hE] at ⊢
  simpa only [P.dephase_idempotent] using dephase_trace_duality P (P.dephase E) rho
```

No positivity or trace-one condition on $\rho$ is needed for this algebraic identity. Calling it a probability equality requires an appropriate state and effect in the application. Taking $E = 1$ proves trace preservation, since completeness and idempotence give $\Delta(1) = 1$. General observables with off-diagonal packet components need not satisfy the invariance premise; dephasing may change their expectation values.

This chapter explains why the finite core begins with a resolution in a ring and only adds hypotheses when a later operation needs them. The exact circuit formula, adjoint conservation, actual exponential and operator-norm leakage are related constructions with distinct theorem contracts.

# 5 Moving frames and an actual projected connection

## 5.1 Differentiate the coordinates before rewriting the equation

Let $U(t)$ be a finite complex-matrix unitary frame and $\psi(t)$ an actual differentiable vector. With $y(t) = U(t)^*\psi(t)$, the effective Hamiltonian is

$$H_{\text{eff}} = U^*HU - iU^*\dot{U}.$$

The source uses real time derivatives of complex-valued entries. The variables `dU` and `dpsi` are candidate derivative values, and the hypotheses `HasDerivAt` assert that they are the actual derivatives at the specified time.

Source: `formalization/MovingFrames.lean`.

Exact lines 23–29; excerpt `frame_product`. Hash in Section 12.

```
theorem matrix_vector_derivative (A : ℝ → Matrix n n ℂ) (y : ℝ → n → ℂ)
    (dA : Matrix n n ℂ) (dy : n → ℂ) (t : ℝ)
    (ha : ∀ i j, HasDerivAt (fun s => A s i j) (dA i j) t)
    (hy : ∀ i, HasDerivAt (fun s => y s i) (dy i) t) (i : n) :
    HasDerivAt (fun s => (A s *ᵥ y s) i) ((dA *ᵥ y t + A t *ᵥ dy) i) t := by
  simpa only [Matrix.mulVec, dotProduct, Pi.add_apply, Pi.mul_apply, Finset.sum_add_distrib] using
    HasDerivAt.fun_sum (u := Finset.univ) (fun j _ => (ha i j).mul (hy j))
```

**Proof reading.** The proof applies the scalar product rule to each summand of the matrix-vector product, then differentiates the finite sum. It produces the two expected terms without assuming differentiability of the transformed coordinates in advance. The adjoint-derivative lemma conjugates the derivative of the transposed entry, using that conjugation is real-linear.

Differentiating $U^*U = 1$ gives $\dot{U}^*U + U^*\dot{U} = 0$, so $U^*\dot{U}$ is skew-adjoint and $-iU^*\dot{U}$ is Hermitian. The conjugated term $U^*HU$ is Hermitian when $H$ is Hermitian. That last premise is explicitly present in the final source; unitarity of $U$ by itself does not establish Hermiticity of an arbitrary $H$.

Source: `formalization/MovingFrames.lean`.

Exact lines 110–132; excerpt `moving_coordinates`. Hash in Section 12.

```
theorem moving_frame_coordinates [DecidableEq n]
    (U : ℝ → Matrix n n ℂ) (psi : ℝ → n → ℂ)
    (H dU : Matrix n n ℂ) (dpsi : n → ℂ) (t : ℝ)
    (hu : ∀ i j, HasDerivAt (fun s => U s i j) (dU i j) t)
    (hp : ∀ i, HasDerivAt (fun s => psi s i) (dpsi i) t)
    (hleft : ∀ s, (U s).conjTranspose * U s = 1)
    (hright : ∀ s, U s * (U s).conjTranspose = 1)
    (hsch : Complex.I • dpsi = H *ᵥ psi t)
    (hH : H.conjTranspose = H) :
    let y := fun s => (U s).conjTranspose *ᵥ psi s
    let dy := dU.conjTranspose *ᵥ psi t + (U t).conjTranspose *ᵥ dpsi
    (∀ i, HasDerivAt (fun s => y s i) (dy i) t) ∧
      Complex.I • dy = effectiveHamiltonian (U t) H dU *ᵥ y t ∧
      (effectiveHamiltonian (U t) H dU).conjTranspose =
        effectiveHamiltonian (U t) H dU := by
```

```
  dsimp only
  have hy := matrix_vector_derivative (fun s => (U s).conjTranspose) psi
    dU.conjTranspose dpsi t (adjoint_derivative U dU t hu) hp
  refine ⟨hy, ?_, effective_hamiltonian_hermitian U H dU t hu hleft hH⟩
  apply moving_frame_equation U psi (fun s => (U s).conjTranspose *ᵥ psi s)
    H dU dpsi _ t hu hp hy (hleft t) _ hsch
  intro s
  rw [Matrix.mulVec_mulVec, hright, Matrix.one_mulVec]
```

**Contract.** The matrix index is finite with decidable equality. Entrywise derivative hypotheses are at one real time $t$. Both unitary identities hold for every time, permitting construction of the inverse coordinates. The original Schrödinger equation $i\dot{\psi} = H\psi(t)$ is a premise, and $H^* = H$ is the premise for the Hermiticity conclusion. The theorem constructs $y$, constructs its derivative and proves its equation; it is not an initial-value existence theorem.

**Proof reading.** After unfolding the two `let` expressions, the proof obtains the actual derivative of $U^*\psi$ from the product rule. It gives that derivative proof to `moving_frame_equation`. The right-unitarity identity reconstructs $\psi = Uy$, while left-unitarity removes $U^*U$ when the differentiated equation is multiplied by $U^*$. The separate Hermiticity lemma uses the differentiated unitary identity and the supplied Hermiticity of $H$.

### 5.2 The canonical connection derives its first-order identities

For a differentiable complete orthogonal family $P_a(t)$, write $D_a = \dot{P}_a(t)$. Differentiating multiplication gives

$$D_a P_b + P_a D_b = \delta_{ab} D_a.$$

Differentiating completeness gives $\sum_a D_a = 0$. Differentiating self-adjointness gives $D_a^* = D_a$. These are consequences of actual derivatives of the original functions.

Source: `formalization/CanonicalConnection.lean`.

Exact lines 78–95; excerpt `connection_jet`. Hash in Section 12.

```
theorem differentiated_orthogonality
    (hd : ∀ a, HasDerivAt (P a) (D a) t)
    (hmul : ∀ s a b, P a s * P b s = if a = b then P a s else 0)
    (a b : I) : D a * P b t + P a t * D b = if a = b then D a else 0 := by
  have h := (hd a).mul (hd b)
  change HasDerivAt (fun s => P a s * P b s) (D a * P b t + P a t * D b) t at h
  by_cases hab : a = b
  · subst b
    have heq : (fun s => P a s * P a s) = P a := by
      funext s
      simpa only [ite_true] using hmul s a a
    rw [heq] at h
    simpa only [ite_true] using h.unique (hd a)
  · have heq : (fun s => P a s * P b s) = fun _ => (0 : R) := by
      funext s
      simpa only [hab, ite_false] using hmul s a b
    rw [heq] at h
    simpa only [hab, ite_false] using h.unique (hasDerivAt_const t (0 : R))
```

The general algebraic part of the file can take these jet identities as hypotheses. The endpoint below proves those hypotheses from the derivative data before applying that algebraic part. It constructs

$$C = \sum_a D_a P_a = \frac{1}{2} \sum_a [D_a, P_a]$$

and establishes $C^* = -C$ and $[C, P_b] = D_b$.

Source: `formalization/CanonicalConnection.lean`.

Exact lines 113–131; excerpt `canonical_connection`. Hash in Section 12.

```
theorem canonical_connection_of_hasDerivAt
    (hd : ∀ a, HasDerivAt (P a) (D a) t)
    (hmul : ∀ s a b, P a s * P b s = if a = b then P a s else 0)
    (hsum : ∀ s, ∑ a, P a s = 1)
    (hstar : ∀ s a, star (P a s) = P a s) :
    let C := canonical (fun a => P a t) D
    star C = -C ∧
      (∀ b, C * P b t - P b t * C = D b) ∧
      (1 / 2 : ℝ) • (∑ a, (D a * P a t - P a t * D a)) = C := by
  dsimp only
  have hj := differentiated_orthogonality P D t hd hmul
  have hdiag (a : I) : D a * P a t + P a t * D a = D a := by
    simpa only [ite_true] using hj a a
  have hz := differentiated_completeness P D t hd hsum
  refine ⟨?_, ?_, ?_⟩
  · exact canonical_skewAdjoint _ _ (hstar t)
      (differentiated_selfAdjoint P D t hd hstar) hz hdiag
  · exact canonical_commutator _ _ (hmul t) (hsum t) hj
  · exact canonical_half_commutator _ _ hz hdiag
```

**Contract.** The actual-derivative endpoint is in a normed real algebra with a star-ring structure, compatible real scalar action and continuous involution. The finite packet index has decidable equality. The projector multiplication, completeness and adjoint identities hold for all real times. This endpoint treats a curve of projectors; it has no manifold curvature conclusion.

The skew-adjointness calculation sums $D_a P_a + P_a D_a = D_a$. Their sum vanishes, giving $C + C^* = 0$. The commutator calculation first isolates $C P_b = D_b P_b$, then obtains $D_b + P_b C = D_b P_b$ from the differentiated multiplication identities and completeness. Subtracting gives the desired commutator. The factor one-half uses the real scalar structure and the same zero sum.

### 5.3 The crucial off-diagonal derivative block is proved

For a parameter-dependent idempotent $P$, differentiating $P^2 = P$ in direction $v$ gives

$$D_v P \, P + P \, D_v P = D_v P.$$

Multiplying this equation by $P$ and cancelling an identical summand gives $P(D_v P)P = 0$. This is a derived fact, not a curvature-specific assumption.

Source: `formalization/ProjectedCurvature.lean`.

Exact lines 22–26; excerpt `sandwich_zero`. Hash in Section 12.

```
theorem jet_sandwich_zero (P D : R) (hP : P*P=P)
    (hD : D*P+P*D=D) : P*D*P=0 := by
  have hh := congrArg (fun z => P*z) hD
  simp only [mul_add, ← mul_assoc, hP] at hh
  exact add_eq_right.mp hh
```

For a range section $s$ with $Ps = s$, differentiating the range condition gives

$$D_v s = (D_v P)s + P(D_v s).$$

The chart connection is $\nabla_X s = P(D_X s)$. Its curvature is the actual commutator

$$R(X,Y)s = \nabla_X \nabla_Y s - \nabla_Y \nabla_X s - \nabla_{[X,Y]} s.$$

The bracket term is essential: it cancels the change in the vector fields in the second directional derivatives. The proof uses Mathlib's actual Fréchet derivative and actual Lie bracket, not independently supplied second-order coefficients.

Source: `formalization/LocalProjectedCurvature.lean`.

Exact lines 79–94; excerpt `local_curvature`. Hash in Section 12.

```
theorem projected_connection_curvature (P : E → F →L[ℝ] F)
    (X Y : E → E) (s : E → F) (x : E)
    (hP : DifferentiableAt ℝ P x) (hPP : ∀ x, P x * P x = P x)
    (hX : DifferentiableAt ℝ X x) (hY : DifferentiableAt ℝ Y x)
    (hs : ContDiffAt ℝ 2 s x) (hPs : ∀ x, P x (s x)=s x) :
    curvature P X Y s x = curvatureForm P x (X x) (Y x) (s x) := by
  have hs1 : DifferentiableAt ℝ s x := hs.differentiableAt (by norm_num)
  have hz (v : E) (z : F) : P x (fderiv ℝ P x v (P x z)) = 0 := by
    have hh := congrArg (fun L : F →L[ℝ] F => L z)
      (projector_differential_sandwich P x hP hPP v)
    simpa [mul_apply_eq_comp] using hh
  rw [curvature_expansion P X Y s x hP hPP hX hY hs]
  conv_lhs => rw [section_jet P s x hP hs1 hPs (Y x),
    section_jet P s x hP hs1 hPs (X x)]
  simp only [map_add, hz, add_zero]
  simp [curvatureForm, hPs, map_sub]
```

**Contract.** The local theorem has real normed model and fiber spaces. $P$, $X$ and $Y$ are differentiable at the specified point; $s$ is twice continuously differentiable there. The idempotent and range-section equations hold as functions. The global chart-level file supplies an earlier variant with global differentiability; the local variant supports use inside arbitrary chart neighborhoods.

**Proof reading.** Expand the derivative of the projected directional derivative by the product rule. The actual Lie-bracket derivative identity cancels the second derivatives of $s$ and the derivatives of $X, Y$. Substitute the differentiated range-section identity into the two remaining first-derivative terms. The components $P(D_v P)P(D_w s)$ vanish by the sandwich lemma. The surviving term is $P[(D_X P), (D_Y P)]s$, and $Ps = s$ puts the final right-hand $P$ into the curvature form.

### 5.4 Build the range atlas from the projector

The global development begins with an actual operator-valued map $P : M \to \mathcal{L}_{\mathbb{R}}(F, F)$. Its fiber is the fixed subspace $\{v : P(x)v = v\}$ with the subspace topology. The total space is the subtype of $M \times F$ consisting of such fixed pairs. The atlas is constructed from $P$ rather than supplied as a hypothesis.

For idempotents $p, q$, define

$$T(p, q) = pq + (1 - p)(1 - q).$$

This is identity at $p = q$, and it intertwines the two projectors. Near a base point $a$, the map $T(P(x), P(a))$ is invertible because invertibility is open in the complete operator algebra and it is identity at $x = a$.

Source: `formalization/GlobalRangeBundle.lean`.

Exact lines 43–43; excerpt `range_transport`. Hash in Section 12.

```
def transport (p q : F →L[ℝ] F) : F →L[ℝ] F := p*q+(1-p)*(1-q)
```

Source: `formalization/GlobalRangeBundle.lean`.

Exact lines 49–54; excerpt `range_intertwines`. Hash in Section 12.

```
theorem transport_intertwines (p q : F →L[ℝ] F) (hp : p*p=p) (hq : q*q=q) :
    p*transport p q=transport p q*q := by
  unfold transport
  have ha : p*(p*q)=p*q := by rw [← mul_assoc,hp]
  have hb : p*(q*q)=p*q := by rw [hq]
  noncomm_ring [hp,hq,ha,hb]
```

Let $U_a = \{x : T(P(x), P(a)) \text{ is invertible}\}$. Reconstruction transports the fixed fiber at $a$ into the ambient space at $x$. Coordinates apply the inverse transport and project to the fixed fiber at $a$. The intertwiners show that both maps land in the correct fibers. On $U_a$, the two inverse identities follow from genuine inverse cancellation.

Source: `formalization/GlobalRangeBundle.lean`.

Exact lines 180–209; excerpt `range_product`. Hash in Section 12.

```
def localProduct (P : M → F →L[ℝ] F) (hPP : ∀ x, P x*P x=P x)
    (hP : ContMDiff I 𝓘(ℝ, F →L[ℝ] F) ∞ P) (a : M) :
    LocalTotal P a ≃ₜ (domain P a × fiber (P a)) where
  toFun z := ((z.val.val.1,z.property),toCoord P hPP a z.val.val.1 z.val.val.2)
  invFun y := ⟨⟨(y.1.val,fromCoord P a y.1.val y.2),
    fromCoord_range P hPP a y.1.val y.2),y.1.property⟩
  left_inv := by
    intro z
    apply Subtype.ext
    apply Subtype.ext
    apply Prod.ext
    · rfl
    · exact fromCoord_toCoord P hPP a _ z.property _ z.val.property
  right_inv := by
```

```
    intro y
    apply Prod.ext
    · rfl
    · exact toCoord_fromCoord P hPP a _ y.1.property y.2
  continuous_toFun := by
    have hx : Continuous (fun z : LocalTotal P a => z.val.val.1) := by fun_prop
    have hv : Continuous (fun z : LocalTotal P a => z.val.val.2) := by fun_prop
    have hc : Continuous (fun z : LocalTotal P a => toCoord P hPP a z.val.val.1) :=
      (smooth_toCoord P hPP hP a).continuousOn.comp_continuous hx (fun z => z.property)
    exact (hx.subtype_mk _).prodMk (hc.clm_apply hv)
  continuous_invFun := by
    have hx : Continuous (fun y : domain P a × fiber (P a) => y.1.val) := by fun_prop
    have hv : Continuous (fun y : domain P a × fiber (P a) => y.2) := by fun_prop
    have hc : Continuous (fun y : domain P a × fiber (P a) => fromCoord P a y.1.val) :=
      (smooth_fromCoord P hP a).continuous.comp hx
    exact ((hx.prodMk (hc.clm_apply hv)).subtype_mk _).subtype_mk _
```

This declaration is a homeomorphism from the restricted actual total space to $U_a \times \mathrm{fiber}(P(a))$. In addition to inverse laws, it proves continuity in both directions using the smooth coordinate and reconstruction maps. Transitions are composed from these actual maps. They are continuous linear maps in each fiber, smooth in the base, and satisfy the cocycle law by cancelling the middle reconstruction-coordinate pair.

Source: `formalization/GlobalRangeBundle.lean`.

Exact lines 241–252; excerpt `range_atlas`. Hash in Section 12.

```
theorem smooth_range_bundle_atlas (P : M → F →L[ℝ] F) (hPP : ∀ x, P x*P x=P x)
    (hP : ContMDiff I 𝓘(ℝ, F →L[ℝ] F) ∞ P) :
    (∀ a, IsOpen (domain P a) ∧ a ∈ domain P a) ∧
    (∀ a, Nonempty (LocalTotal P a ≃ₜ (domain P a × fiber (P a)))) ∧
    (∀ a b, ContMDiffOn I 𝓘(ℝ, fiber (P a) →L[ℝ] fiber (P b)) ∞
      (transition P hPP a b) (domain P a ∩ domain P b)) ∧
    (∀ a x, x ∈ domain P a → transition P hPP a a x=1) ∧
    (∀ a b c x, x ∈ domain P a ∩ domain P b ∩ domain P c →
      (transition P hPP b c x).comp (transition P hPP a b x)=transition P hPP a c x) := by
  exact ⟨fun a => ⟨isOpen_domain P hP.continuous a,mem_domain P hPP a⟩,
    fun a => ⟨localProduct P hPP hP a),smooth_transition P hPP hP,
    transition_self P hPP,fun a b c x hx => transition_cocycle P hPP a b c x hx.1.2⟩
```

**Contract.** The range-atlas construction uses a smooth real projector map on a charted parameter space and a complete real normed fiber space. Idempotence is required; self-adjointness is not needed for this bundle construction. The explicit atlas theorem does not demand a global chart. Local linear fiber equivalences prove local constancy of finite rank whenever finite rank is being interpreted. The underlying fiber equivalence is the stronger structural statement.

The implementation uses this explicit smooth atlas directly. It does not package it as a Mathlib `ContMDiffVectorBundle` instance. This is a boundary of representation, not an assumed atlas hidden in the proof: the total space, open domains, local product homeomorphisms, transitions and their identities are all constructed and proved.

### 5.5 The global derivative and gauge gluing

On the manifold, the global connection is defined using `mvfderiv`, the actual derivative of a manifold-to-vector-space map. A tangent vector at $x$ has type `TangentSpace I x`, so a vector field is a dependent function giving one such vector at every point.

Source: `formalization/GlobalProjectedConnection.lean`.

Exact lines 29–30; excerpt `global_nabla`. Hash in Section 12.

```
def nabla (P : M → F →L[ℝ] F) (X : ∀ x : M, TangentSpace I x) (s : M → F) (x : M) : F :=
  P x (mvfderiv I s x (X x))
```

Source: `formalization/GlobalProjectedConnection.lean`.

Exact lines 59–63; excerpt `global_leibniz`. Hash in Section 12.

```
theorem nabla_leibniz (P : M → F →L[ℝ] F) (X : ∀ x : M, TangentSpace I x)
    (s : M → F) (c : M → ℝ) (x : M) (hs : MDifferentiableAt I 𝓘(ℝ,F) s x)
    (hc : MDifferentiableAt I 𝓘(ℝ,ℝ) c x) (hPs : P x (s x)=s x) :
    nabla I P X (c • s) x = (mvfderiv I c x (X x)) • s x + c x • nabla I P X s x := by
  simp [nabla,mvfderiv_smul hc hs,hPs,add_comm]
```

The global range property follows immediately from idempotence. Additivity in sections uses actual differentiability premises. The Leibniz rule needs the range condition for $s(x)$ because the scalar derivative term initially contains $P(x)s(x)$. Linearity in the vector field uses linearity of the derivative. A germ lemma says that locally equal functions have the same covariant derivative at the point.

Local coordinate connections reconstruct a range section, differentiate it globally and then take coordinates. On an open domain, local reconstruction equals the original section in a neighborhood. The germ lemma therefore identifies the local and global connection. On an overlap, coordinate transitions carry one representation into the other.

Source: `formalization/GlobalProjectedConnection.lean`.

Exact lines 115–124; excerpt `global_glue`. Hash in Section 12.

```
theorem local_connections_glue (P : M → F →L[ℝ] F) (hPP : ∀ x, P x*P x=P x)
    (hP : ContMDiff I 𝓘(ℝ,F →L[ℝ] F) ∞ P) (a b : M)
    (X : ∀ x : M, TangentSpace I x) (s : M → F) (hPs : ∀ x, P x (s x)=s x)
    (x : M) (hx : x ∈ domain P a ∩ domain P b) :
    transition P hPP a b x (localNabla I P hPP a X (fun y => toCoord P hPP a y (s y)) x) =
      localNabla I P hPP b X (fun y => toCoord P hPP b y (s y)) x := by
  rw [localNabla_represents_global I P hPP hP a X s hPs x hx.1,
    localNabla_represents_global I P hPP hP b X s hPs x hx.2]
  change toCoord P hPP b x (fromCoord P a x (toCoord P hPP a x (nabla I P X s x))) = _
  rw [fromCoord_toCoord P hPP a x hx.1 _ (nabla_in_range I P hPP X s x)]
```

Source: `formalization/ProjectedBundleCompletion.lean`.

Exact lines 40–53; excerpt `smooth_section`. Hash in Section 12.

```
theorem smooth_section_iff (P : M → F →L[ℝ] F) (hPP : ∀ x, P x*P x=P x)
    (hP : ContMDiff I 𝓘(ℝ,F →L[ℝ] F) ∞ P) (a x : M) (hx : x ∈ domain P a)
    (s : M → F) (hPs : ∀ᶠ y in 𝓝 x, P y (s y)=s y) :
    ContMDiffAt I 𝓘(ℝ,F) ∞ s x ↔
      ContMDiffAt I 𝓘(ℝ,fiber (P a)) ∞ (fun y => toCoord P hPP a y (s y)) x := by
  constructor
  · intro hs
    exact ((smooth_toCoord P hPP hP a x hx).contMDiffAt
      ((isOpen_domain P hP.continuous a).mem_nhds hx)).clm_apply hs
  · intro hs
    have hr := (smooth_fromCoord P hP a x).clm_apply hs
    apply hr.congr_of_eventuallyEq
    filter_upwards [hPs,(isOpen_domain P hP.continuous a).mem_nhds hx] with y hy hya
    exact (fromCoord_toCoord P hPP a y hya (s y) hy).symm
```

Source: `formalization/ProjectedBundleCompletion.lean`.

Exact lines 57–70; excerpt `gauge_law`. Hash in Section 12.

```
theorem local_connections_gauge (P : M → F →L[ℝ] F) (hPP : ∀ x, P x*P x=P x)
    (hP : ContMDiff I 𝓘(ℝ,F →L[ℝ] F) ∞ P) (a b x : M)
    (hx : x ∈ domain P a ∩ domain P b) (X : ∀ y : M, TangentSpace I y)
    (u : M → fiber (P a)) :
    localNabla I P hPP b X (fun y => transition P hPP a b y (u y)) x =
      transition P hPP a b x (localNabla I P hPP a X u x) := by
  have hs : ∀ y, P y (fromCoord P a y (u y))=fromCoord P a y (u y) :=
    fun y => fromCoord_range P hPP a y (u y)
  change localNabla I P hPP b X (fun y => toCoord P hPP b y (fromCoord P a y (u y))) x = _
  rw [localNabla_represents_global I P hPP hP b X (fun y => fromCoord P a y (u y)) hs x hx.2]
  change toCoord P hPP b x (nabla I P X (fun y => fromCoord P a y (u y)) x) =
    toCoord P hPP b x (fromCoord P a x
      (toCoord P hPP a x (nabla I P X (fun y => fromCoord P a y (u y)) x)))
  rw [fromCoord_toCoord P hPP a x hx.1 _ (nabla_in_range I P hPP X _ x)]
```

The smooth-section equivalence needs only an eventual range condition near the point, not an unproved globally extended section. The gauge law in the completion file applies to arbitrary local coordinate functions and compares their reconstructed connection values on an overlap. It is not restricted to a prechosen global frame.

### 5.6 Manifold curvature and its endpoint

The final curvature theorem uses a smooth real boundaryless manifold modeled on a complete real normed space $E$. The model is $\mathcal{J}(\mathbb{R}, E)$; the manifold has `ChartedSpace E M` and a smooth `IsManifold` instance for that model. The source pulls vector fields into a chart centered at the point, identifies the manifold derivative and bracket with their chart versions, and then proves the cancellation using actual manifold operations.

Source: `formalization/ManifoldProjectedCurvature.lean`.

Exact lines 214–232; excerpt `manifold_curvature`. Hash in Section 12.

```
theorem projected_connection_curvature (P : M → F →L[ℝ] F)
    (X Y : ∀ x : M, TangentSpace 𝓘(ℝ,E) x) (s : M → F) (x : M)
    (hP : ContMDiff 𝓘(ℝ,E) 𝓘(ℝ,F →L[ℝ] F) ∞ P) (hPP : ∀ x, P x*P x=P x)
    (hX : ContMDiff 𝓘(ℝ,E) 𝓘(ℝ,E).tangent ∞
      (fun x => (X x : TangentBundle 𝓘(ℝ,E) M)))
    (hY : ContMDiff 𝓘(ℝ,E) 𝓘(ℝ,E).tangent ∞
      (fun x => (Y x : TangentBundle 𝓘(ℝ,E) M)))
    (hs : ContMDiff 𝓘(ℝ,E) 𝓘(ℝ,F) ∞ s) (hPs : ∀ x, P x (s x)=s x) :
    curvature 𝓘(ℝ,E) P X Y s x = curvatureForm 𝓘(ℝ,E) P x (X x) (Y x) (s x) := by
  have hP1 := hP.mdifferentiableAt (x := x) (by simp)
  have hs1 := hs.mdifferentiableAt (x := x) (by simp)
  have hz (v : TangentSpace 𝓘(ℝ,E) x) (z : F) : P x (mvfderiv 𝓘(ℝ,E) P x v (P x z))=0 := by
    have hh := congrArg (fun L : F →L[ℝ] F => L z)
      (projector_differential_sandwich P x hP1 hPP v)
    simpa [mul_apply_eq_comp] using hh
  rw [curvature_expansion P X Y s x hP hPP hX hY hs]
  conv_lhs => rw [section_jet P s x hP1 hs1 hPs (Y x),section_jet P s x hP1 hs1 hPs (X x)]
  simp only [map_add,hz,add_zero]
  simp [curvatureForm,hPs,map_sub]
```

**Contract.** Here $P$, the two vector fields and the ambient range section are smooth. The equations $P(x)^2 = P(x)$ and $P(x)s(x) = s(x)$ are given globally. The conclusion is $R(X,Y)s = P(dP \wedge dP)P\,s$ at an arbitrary point. The final manifold curvature endpoint assumes no global chart, no supplied curvature identity and no supplied range atlas. The atlas portion separately requires completeness of the fiber space. Finite complex quantum spaces fit by restriction to their underlying real spaces.

The next theorem proves tensoriality: replacing the two fields and the section by smooth extensions with the same values at the point leaves curvature unchanged. The completion file makes the curvature form alternating and real-linear, proves it maps into the actual fiber, and defines the resulting continuous linear fiber endomorphism. Constant projector maps, including zero and identity, have zero curvature form.

This chain explains the division among the six projected-geometry files. `ProjectedCurvature` establishes the parameter-space algebra and calculus; `LocalProjectedCurvature` localizes the hypotheses; `GlobalRangeBundle` constructs the atlas; `GlobalProjectedConnection` defines and glues the connection; `ManifoldProjectedCurvature` proves the actual global curvature formula; `ProjectedBundleCompletion` supplies intrinsic section, gauge and fiber-form compatibility. Treating only the earliest chart file as current coverage would miss the later global constructions.

# 6 Finite channels and the full Knill–Laflamme criterion

## 6.1 Complete positivity has an actual amplification map

The Kraus channel is the finite complex-matrix map

$$\Phi(\rho) = \sum_a K_a \rho K_a^*.$$

Its additivity and complex homogeneity construct an actual linear map. Each summand preserves positive semidefiniteness by a matrix congruence, so the finite sum is positive. Trace preservation is a separate theorem under $\sum_a K_a^* K_a = 1$, proved by cyclic trace rotation and completeness of that Kraus sum.

To prove complete positivity the source does not merely restate positivity. It defines blockwise amplification on matrices indexed by $J \times n$ and identifies it entrywise with the actual Kraus family $1_J \otimes K_a$.

Source: `formalization/KrausChannels.lean`.

Exact lines 48–56; excerpt `kraus_amplify`. Hash in Section 12.

```
theorem amplification_eq_kraus {J : Type*} [Fintype J] [DecidableEq J]
    (K : A → Matrix n n ℂ) (rho : Matrix (J × n) (J × n) ℂ) :
    amplify (channel K) rho =
      channel (fun a => (1 : Matrix J J ℂ) ⊗ₖ K a) rho := by
  ext ⟨i, u⟩ ⟨j, v⟩
  simp_rw [amplify, channel, Matrix.sum_apply, Matrix.mul_apply,
    Matrix.conjTranspose_apply, Matrix.kroneckerMap_apply]
  simp [Fintype.sum_prod_type, Matrix.one_apply, apply_ite]
  rfl
```

Source: `formalization/KrausChannels.lean`.

Exact lines 58–62; excerpt `kraus_cp`. Hash in Section 12.

```
theorem channel_completely_positive {J : Type*} [Fintype J] [DecidableEq J]
    (K : A → Matrix n n ℂ) {rho : Matrix (J × n) (J × n) ℂ}
    (hrho : rho.PosSemidef) : (amplify (channel K) rho).PosSemidef := by
  rw [amplification_eq_kraus]
  exact channel_positive _ hrho
```

**Contract.** The system and Kraus index types are finite. The reference type `J` is arbitrary finite with decidable equality. Complete positivity itself does not require Kraus normalization; normalization is needed for trace preservation and preservation of density matrices. Every finite reference dimension is quantified in the theorem, rather than sampled in an example. Infinite reference systems are not encoded by these finite matrix declarations.

**Proof reading.** The amplification identity expands entries of a Kronecker product, uses the identity matrix to force equality of the reference indices, and collapses the corresponding sums. Once amplification is literally a Kraus map, the earlier positivity theorem applies without a new positivity hypothesis about the amplified channel.

### 6.2 Orthogonal syndromes are the recovery stage

The recovery construction begins with a code projection $P$ and an orthogonal normalized family $E_a$ satisfying

$$E_a P = E_a, \qquad E_a^* E_b = \delta_{ab} P.$$

Their output packets $Q_a = E_a E_a^*$ are orthogonal star projections. Their sum $Q$ is a star projection and $Q^\perp = 1 - Q$ is its complement.

Source: `formalization/SyndromeRecovery.lean`.

Exact lines 21–27; excerpt `syndrome_structure`. Hash in Section 12.

```
structure OrthogonalSyndromes (R I : Type*) [Ring R] [StarRing R]
    [Fintype I] [DecidableEq I] where
  code : R
  code_projection : IsStarProjection code
  error : I → R
  restricted : ∀ a, error a * code = error a
  gram : ∀ a b, star (error a) * error b = if a=b then code else 0
```

The decoder is

$$\mathcal{R}(\sigma) = \sum_a E_a^* \sigma E_a + Q^\perp \sigma Q^\perp.$$

The complement term is important. Without it the decoder would generally lose trace on input outside the sum of syndrome output spaces. The implementation uses `Option I` as the total recovery-Kraus index: `some a` denotes $E_a^*$, and `none` denotes $Q^\perp$. Thus the extra branch is encoded in the actual finite family.

Source: `formalization/SyndromeRecovery.lean`.

Exact lines 84–90; excerpt `syndrome_complete`. Hash in Section 12.

```
theorem recoveryKraus_complete :
    (∑ a, star (S.recoveryKraus a)*S.recoveryKraus a) = 1 := by
  rw [Fintype.sum_option]
  simp only [recoveryKraus, star_star, S.complement_projection.isSelfAdjoint.star_eq,
    S.complement_projection.isIdempotentElem.eq]
  change S.complement + S.total = 1
  simp [complement]
```

**Proof reading.** The sum over `Option I` splits into the complement branch and the syndrome branches. Self-adjointness and idempotence turn the complement contribution into $Q^\perp$; the syndrome contribution is $Q$. Their sum is the identity. This proves trace preservation on the entire ambient matrix space, not merely on noisy code states.

For an arbitrary code-supported operator $P\rho P = \rho$, the decoder of a cross error is

$$\mathcal{R}(E_a \rho E_b^*) = \delta_{ab} \rho.$$

The orthogonal Gram law kills every nonmatching syndrome contribution, and the complement annihilates each error output.

Source: `formalization/SyndromeRecovery.lean`.

Exact lines 103–124; excerpt `syndrome_cross`. Hash in Section 12.

```
theorem decoder_cross_error (rho : R) (hrho : S.code*rho*S.code=rho) (a b : I) :
    S.decoder (S.error a*rho*star (S.error b)) = if a=b then rho else 0 := by
  have hc (c : I) :
      star (S.error c)*(S.error a*rho*star (S.error b))*S.error c =
        if c=a then (if a=b then rho else 0) else 0 := by
    have heq : star (S.error c)*(S.error a*rho*star (S.error b))*S.error c =
        (star (S.error c)*S.error a)*rho*(star (S.error b)*S.error c) := by
      noncomm_ring
    rw [heq, S.gram, S.gram]
    by_cases hca : c=a
    · subst c
      by_cases hab : a=b
      · subst b; simp [hrho]
      · simp [hab, Ne.symm hab]
    · simp [hca]
  have hq : S.complement*(S.error a*rho*star (S.error b))*S.complement=0 := by
    calc
      _ = (S.complement*S.error a)*rho*(star (S.error b)*S.complement) := by
        noncomm_ring
      _ = 0 := by rw [S.complement_error, zero_mul, zero_mul]
  simp only [decoder, hc, hq, add_zero]
  simp
```

At the abstract star-ring level, this is an algebraic correction identity. The concrete complex-matrix layer additionally proves positivity, trace preservation, complete positivity at every finite reference dimension and preservation of density matrices. A weighted normalized mixture and a coherent error superposition are then handled by linearity and the cross-error formula.

This file alone would prove recovery for supplied orthogonal syndrome data. It would not prove that arbitrary Knill–Laflamme Gram data can be put into that form, and it would not prove necessity of the Gram condition. The current source has separate modules for those obligations.

### 6.3 General Gram data are not assumed diagonal

The finite Knill–Laflamme data consist of a star projection $P$, errors $E_a$, and a positive semidefinite coefficient matrix $C$ with

$$PE_a^* E_b P = C_{ab} P.$$

No invertibility of $C$ is required. The matrix can be singular and can have off-diagonal coefficients.

Source: `formalization/KnillLaflammeSufficiency.lean`.

Exact lines 187–193; excerpt `kl_data`. Hash in Section 12.

```
structure Data (n I : Type*) [Fintype n] [DecidableEq n] [Fintype I] [DecidableEq I] where
  code : Matrix n n ℂ
  code_projection : IsStarProjection code
  error : I → Matrix n n ℂ
  gramMatrix : Matrix I I ℂ
```

```
  gram_positive : gramMatrix.PosSemidef
  gram : ∀ a b, code * star (error a) * error b * code = gramMatrix a b • code
```

First restrict each error to the code by replacing $E_a$ with $E_a P$. This changes neither the noisy output of a supported operator nor its compressed Gram data. The source's `mix E U r` uses the columns of $U$ as the new error coordinates. It proves that mixing transforms the Gram matrix to $U^* C U$ and that unitary mixing leaves the Kraus noise map unchanged.

The actual Hermitian spectral theorem supplies `eigenvectorUnitary` and real eigenvalues. Positive semidefiniteness proves those eigenvalues are nonnegative. The declaration below constructs the diagonal error data directly from that spectral information.

Source: `formalization/KnillLaflammeSufficiency.lean`.

Exact lines 204–214; excerpt `kl_diagonal`. Hash in Section 12.

```
noncomputable def diagonal : DiagonalErrors n I where
  code := K.code
  code_projection := K.code_projection
  error := mix (fun a => K.error a*K.code)
    (K.gram_positive.isHermitian.eigenvectorUnitary : Matrix I I ℂ)
  restricted := mix_restricted K.code (fun a => K.error a*K.code)
    (fun a => by rw [mul_assoc, K.code_projection.isIdempotentElem.eq]) _
  weight := K.gram_positive.isHermitian.eigenvalues
  nonnegative := K.gram_positive.eigenvalues_nonneg
  gram := diagonalized_gram K.code (fun a => K.error a*K.code) K.gramMatrix
    K.gram_positive K.restricted_error_gram
```

**Proof reading.** The `error` field mixes the code-restricted errors by the spectral unitary. The `weight` field uses the actual eigenvalues. The `gram` field applies the proved diagonalization identity. The `restricted` field uses idempotence of the code projector, and the `nonnegative` field comes from positivity of the input Gram matrix. The result is built, not supplied as a new input.

### 6.4 Singular directions are eliminated without division by zero

If a diagonal weight is zero, the corresponding restricted error satisfies $E^* E = 0$. For finite complex matrices this forces $E = 0$. Therefore the construction does not normalize a zero spectral direction.

Source: `formalization/KnillLaflammeSufficiency.lean`.

Exact lines 107–110; excerpt `kl_null`. Hash in Section 12.

```
theorem zero_weight_error (a : I) (ha : D.weight a = 0) : D.error a = 0 := by
  have hh : star (D.error a) * D.error a = 0 := by
    simpa only [ite_true, ha, Complex.ofReal_zero, zero_smul] using D.gram a a
  exact Matrix.conjTranspose_mul_self_eq_zero.mp hh
```

The active index is the subtype `{a : I // 0 < D.weight a}`. For an active error define $F_a = \lambda_a^{-1/2} E_a$. The source proves the square root is nonzero and its square equals the weight before using its inverse. The normalized errors satisfy $F_a^* F_b = \delta_{ab} P$, so the preceding syndrome construction applies.

For an unnormalized original error family, the decoder corrects the noise to the exact scale

$$\mathcal{R}\left(\sum_a E_a \rho E_a^*\right) = \mathrm{tr}(C)\rho.$$

Unitary mixing preserves the noise, the restricted noise agrees on the code, and the spectral eigenvalue sum is the trace of $C$. If the original errors form a normalized channel and $P \neq 0$, compressing the Kraus completeness relation gives $\mathrm{tr}(C)P = P$, so the scale is one. If $P = 0$, every supported operator is zero and the correction assertion follows directly.

Source: `formalization/KnillLaflammeSufficiency.lean`.

Exact lines 252–259; excerpt `kl_corrects`. Hash in Section 12.

```
theorem recovery_corrects (hcomplete : (∑ a, star (K.error a)*K.error a) = 1)
    (rho : Matrix n n ℂ) (hrho : K.code*rho*K.code=rho) :
    K.diagonal.syndromes.decoder (noise K.error rho) = rho := by
  rw [K.recovery_noise_scaled rho hrho]
  by_cases hp : K.code = 0
  · have hr : rho=0 := by simpa [hp] using hrho.symm
    simp [hr]
  · rw [K.gram_trace_one hp hcomplete, one_smul]
```

**Contract.** This sufficiency statement assumes finite complex matrices, a star code projection, a positive Gram matrix and its compressed Gram relation, together with global Kraus normalization for exact unit-scale channel correction. The correction conclusion covers all code-supported operators, not only positive ones. The decoder is an actual finite CPTP extension on the whole space. Its spectral construction is mathematical and noncomputable; no numerical eigenvalue routine or executable decoder-performance claim is supplied.

### 6.5 Necessity starts from actual recovery

The reverse implication takes a finite recovery family $R_r$ with $\sum_r R_r^* R_r = 1$, and assumes its actual composite Kraus map fixes every code-supported operator. It must derive the Gram condition rather than take it as a premise.

The key rigidity lemma says that if $A^*A$ is the rank-one Gram matrix of a vector $p$, then every row of $A$ is a scalar multiple of $p$. If $p = 0$, positivity gives $A = 0$. Otherwise choose a nonzero coordinate $p_t$. A vector supported in two coordinates and orthogonal to $p$ is in the kernel of $A^*A$, hence of $A$. The resulting two-coordinate equation yields the row proportionality.

Source: `formalization/KnillLaflammeNecessity.lean`.

Exact lines 19–45; excerpt `kl_rigidity`. Hash in Section 12.

```
theorem rank_one_gram_rigidity {q J : Type*} [Fintype q] [DecidableEq q]
    [Fintype J] [DecidableEq J] (A : Matrix J q ℂ) (p : q → ℂ)
    (hgram : A.conjTranspose*A = Matrix.vecMulVec (star p) p) :
    ∃ z : J → ℂ, ∀ j t, A j t = z j*p t := by
  by_cases hp : p=0
  · have hA : A=0 := Matrix.conjTranspose_mul_self_eq_zero.mp (by simpa [hp] using hgram)
```

```
    exact ⟨fun _ => 0, by simp [hA]⟩
  · obtain ⟨t,ht⟩ : ∃ t, p t ≠ 0 := Function.ne_iff.mp hp
    refine ⟨fun j => A j t / p t, ?_⟩
    intro j s
    let v : q → ℂ := Pi.single s (p t) - Pi.single t (p s)
    have hpv : p ▪ᵥ v = 0 := by
      simp [v, dotProduct_sub, dotProduct_single, mul_comm]
    have hav : A *ᵥ v=0 := by
      apply (Matrix.conjTranspose_mul_self_mulVec_eq_zero A v).mp
      rw [hgram]
      ext u
      change (∑ x, star (p u) * p x * v x) = 0
      simp_rw [mul_assoc]
      rw [← Finset.mul_sum]
      change star (p u) * (p ▪ᵥ v) = 0
      rw [hpv, mul_zero]
    have heq : A j s*p t - A j t*p s=0 := by
      simpa [v, Matrix.mulVec_sub, Matrix.mulVec_single, mul_comm] using congrFun hav j
    change A j s = (A j t / p t) * p s
    field_simp [ht]
    linear_combination heq
```

To apply this to Kraus operators, flatten each operator's entries into a row indexed by a pair of matrix coordinates. Evaluate the asserted map equality on matrix units. This yields the rank-one Gram equality for the flattened matrix. Each composite recovery operator $R_r E_a P$ must therefore be $z_{ra} P$.

Now insert the recovery completeness relation into $P E_a^* E_b P$. It becomes the sum of adjoint products of those composite operators. Their scalar form gives a positive Gram matrix $C = Z^* Z$ with the required coefficients.

Source: `formalization/KnillLaflammeNecessity.lean`.

Exact lines 86–105; excerpt `kl_necessity`. Hash in Section 12.

```
theorem gram_of_recovery (P : Matrix n n ℂ) (hP : IsStarProjection P)
    (E : I → Matrix n n ℂ) (R : J → Matrix n n ℂ)
    (hR : (∑ r, star (R r)*R r)=1)
    (hcorrect : ∀ rho, P*rho*P=rho → noise R (noise E rho)=rho) :
    ∃ C : Matrix I I ℂ, C.PosSemidef ∧
      ∀ a b, P*star (E a)*E b*P=C a b • P := by
  obtain ⟨z,hz⟩ := corrected_kraus_family P hP E R hcorrect
  let Z : Matrix J I ℂ := fun r a => z (r,a)
  refine ⟨Z.conjTranspose*Z, Matrix.posSemidef_conjTranspose_mul_self Z, ?_⟩
  intro a b
  have heq : P*star (E a)*E b*P = ∑ r, star (R r*E a*P)*(R r*E b*P) := by
    calc
      _ = P*star (E a)*(∑ r, star (R r)*R r)*E b*P := by rw [hR, mul_one]
      _ = _ := by
        simp only [Finset.mul_sum, Finset.sum_mul, star_mul,
          hP.isSelfAdjoint.star_eq, mul_assoc]
  rw [heq]
  simp_rw [hz, star_smul, hP.isSelfAdjoint.star_eq, smul_mul_assoc,
    mul_smul_comm, smul_smul, hP.isIdempotentElem.eq]
  simp only [Matrix.mul_apply, Matrix.conjTranspose_apply, Finset.sum_smul, Z]
```

**Proof reading.** The witness $Z^*Z$ is positive by an existing matrix theorem. The intermediate `heq` is obtained by inserting $\sum_r R_r^* R_r = 1$ without reordering the error factors. After rewriting every $R_r E_a P$ as a scalar times $P$, self-adjointness and idempotence reduce the sum to the entries of $Z^*Z$ times $P$. Thus positivity is proved from the recovery, not imposed on an unknown matrix.

### 6.6 The state formulation is bridged to all code operators

A physical criterion is usually stated for density matrices: positive semidefinite, trace one and supported on the code. The necessity argument above uses all code-supported operators. The source supplies the missing bridge.

First, a nonzero positive matrix has positive nonzero trace. Scaling by the inverse real trace produces a density matrix; linearity then removes that normalization. Zero positive matrices are handled separately. Next, the complex polarization identity expresses an arbitrary outer product $xy^*$ as a linear combination of pure positive matrices. Finally, matrix units span all matrices. Agreement of two complex-linear maps on pure states therefore forces agreement on every operator.

Source: `formalization/QuantumStateBridge.lean`.

Exact lines 119–129; excerpt `density_bridge`. Hash in Section 12.

```
theorem density_corrects_iff_operators {I J : Type*} [Fintype I] [Fintype J]
    (P : Matrix n n ℂ) (hP : IsStarProjection P)
    (E : I → Matrix n n ℂ) (R : J → Matrix n n ℂ) :
    (∀ rho : Matrix n n ℂ, rho.PosSemidef → Matrix.trace rho=1 → P*rho*P=rho →
      noise R (noise E rho)=rho) ↔
    (∀ rho : Matrix n n ℂ, P*rho*P=rho → noise R (noise E rho)=rho) := by
  constructor
  · intro hh rho hs
    exact fixes_operators_of_density P hP ((noiseLinear R).comp (noiseLinear E)) hh rho hs
  · intro hh rho _ _ hs
    exact hh rho hs
```

The predicate `StateCorrectable P E` existentially quantifies a natural number and a recovery family on `Fin m`. Its recovery is normalized and fixes all normalized code density matrices. The final endpoint combines the density bridge with the already proved operator-space equivalence.

Source: `formalization/QuantumStateBridge.lean`.

Exact lines 139–151; excerpt `kl_criterion`. Hash in Section 12.

```
theorem state_correctable_iff_gram {I : Type*} [Fintype I] [DecidableEq I]
    (P : Matrix n n ℂ) (hP : IsStarProjection P) (E : I → Matrix n n ℂ)
    (hE : (∑ a, star (E a)*E a)=1) :
    StateCorrectable P E ↔ ∃ C : Matrix I I ℂ, C.PosSemidef ∧
      ∀ a b, P*star (E a)*E b*P=C a b • P := by
  rw [← correctable_iff_gram P hP E hE]
  constructor
  · rintro ⟨m,R,hR,hcorrect⟩
    exact ⟨m,R,hR,(density_corrects_iff_operators P hP E R).mp hcorrect⟩
  · rintro ⟨m,R,hR,hcorrect⟩
    exact ⟨m,R,hR,(density_corrects_iff_operators P hP E R).mpr hcorrect⟩

open scoped Kronecker
```

**Contract.** The code is a star projection. The error family is finite and normalized by $\sum_a E_a^* E_a = 1$. The existential Gram matrix must be positive semidefinite and satisfy every compressed cross relation. The theorem permits the zero code; then no nonzero normalized code density matrix exists, and the operator bridge remains valid because the supported operator space is zero.

### 6.7 Reference systems and error spans

The finite-reference theorem identifies each reference block of $1 \otimes \mathcal{R}$ and $1 \otimes \mathcal{E}$ with the corresponding system noise map. The supported reference matrix condition implies each system block is code-supported, so the operator correction theorem applies block by block.

Source: `formalization/QuantumStateBridge.lean`.

Exact lines 164–182; excerpt `kl_reference`. Hash in Section 12.

```
theorem recovery_with_reference {I J A : Type*} [Fintype I] [Fintype J] [Fintype A] [DecidableEq
 ↪  A]
    (P : Matrix n n ℂ) (E : I → Matrix n n ℂ) (R : J → Matrix n n ℂ)
    (hcorrect : ∀ rho, P*rho*P=rho → noise R (noise E rho)=rho)
    (rho : Matrix (A × n) (A × n) ℂ)
    (hs : ((1 : Matrix A A ℂ) ⊗ₖ P)*rho*((1 : Matrix A A ℂ) ⊗ₖ P)=rho) :
    amplifiedNoise R (amplifiedNoise E rho)=rho := by
  have hblock (i j : A) :
      P*(Matrix.of fun a b => rho (i,a) (j,b))*P=(Matrix.of fun a b => rho (i,a) (j,b)) := by
    ext u v
    have hh := congrArg (fun M : Matrix (A × n) (A × n) ℂ => M (i,u) (j,v)) hs
    simpa [Matrix.mul_apply, Matrix.kroneckerMap_apply, Fintype.sum_prod_type, Matrix.one_apply]
     ↪  using hh
  ext ⟨i,u⟩ ⟨j,v⟩
  rw [amplifiedNoise_block]
  have hin : (fun a b => amplifiedNoise E rho (i,a) (j,b)) =
      noise E (fun a b => rho (i,a) (j,b)) := by
    ext a b
    exact amplifiedNoise_block E rho i j a b
  rw [hin]
  exact congrArg (fun M : Matrix n n ℂ => M u v) (hcorrect _ (hblock i j))
```

It follows that the same correction identity holds for entangled states with any finite reference system. Positivity and trace-one are not required for the displayed algebraic identity; they can be supplied to interpret the matrix as a density state. This is stronger than checking only product states and does not rely on assuming separability.

The error-span module keeps track of cross coefficients. With the source's Gram orientation,

$$\mathcal{R}(E_a \rho E_b^*) = C_{ba} \rho.$$

The reversed indices are deliberate. Expanding a coherent combination produces the scalar $\sum_{a,b} c_a \overline{c_b} C_{ba}$. Summing such expressions over a new Kraus family $F_j$ in the old error span gives a common scalar multiplier. If the new family is normalized, trace preservation forces that multiplier to one on a nonzero code. The zero-code case again has only the zero supported operator.

Source: `formalization/ErrorSpanRecovery.lean`.

Exact lines 138–165; excerpt `kl_span`. Hash in Section 12.

```
theorem recovery_span_channel (F : J → Matrix n n ℂ) (c : J → I → ℂ)
    (hc : ∀ j, F j=∑ a, c j a • K.error a)
    (hF : (∑ j, star (F j)*F j)=1)
    (rho : Matrix n n ℂ) (hrho : K.code*rho*K.code=rho) :
    K.diagonal.syndromes.decoder (noise F rho)=rho := by
  let q : ℂ := ∑ j, ∑ a, ∑ b, c j a*star (c j b)*K.gramMatrix b a
  have hscaled (rho : Matrix n n ℂ) (hs : K.code*rho*K.code=rho) :
      K.diagonal.syndromes.decoder (noise F rho)=q • rho := by
    change K.diagonal.syndromes.decoderLinear (∑ j, F j*rho*star (F j)) = _
    rw [map_sum]
    change (∑ j, K.diagonal.syndromes.decoder (F j*rho*star (F j))) = _
    simp_rw [hc, K.recovery_error_superposition rho hs]
    rw [← Finset.sum_smul]
  rw [hscaled rho hrho]
  by_cases hp : K.code=0
  · have hz : rho=0 := by simpa [hp] using hrho.symm
    simp [hz]
  · have hpos : K.code.PosSemidef := by
      have hx := Matrix.posSemidef_conjTranspose_mul_self K.code
      change (star K.code*K.code).PosSemidef at hx
      rw [K.code_projection.isSelfAdjoint.star_eq, K.code_projection.isIdempotentElem.eq] at hx
      exact hx
    have ht : Matrix.trace K.code ≠ 0 := (hpos.trace_eq_zero_iff).not.mpr hp
    have hs : K.code*K.code*K.code=K.code := by simp only [K.code_projection.isIdempotentElem.eq]
    have hh := congrArg Matrix.trace (hscaled K.code hs)
    rw [K.recovery_preserves_trace, noise_preserves_trace F hF, Matrix.trace_smul] at hh
    have hq : q=1 := mul_right_cancel₀ ht (by simpa using hh.symm)
    rw [hq, one_smul]
```

This is one fixed recovery correcting every normalized channel in the error span, with the coefficients explicitly witnessing span membership. It does not claim unit-scale correction for an arbitrary unnormalized linear combination. For unnormalized error families, the separate criterion requires a nonnegative scale $t$ independent of the supported input operator and proves equivalence with the Gram relation.

Source: `formalization/ErrorSpanRecovery.lean`.

Exact lines 188–209; excerpt `kl_family`. Hash in Section 12.

```
theorem error_family_correctable_iff_gram (P : Matrix n n ℂ) (hP : IsStarProjection P)
    (E : I → Matrix n n ℂ) :
    ErrorFamilyCorrectable P E ↔ ∃ C : Matrix I I ℂ, C.PosSemidef ∧
      ∀ a b, P*star (E a)*E b*P=C a b • P := by
  constructor
  · rintro ⟨m,R,hR,t,ht,hcorrect⟩
    exact gram_of_scaled_recovery P hP E R hR t ht hcorrect
  · rintro ⟨C,hC,hgram⟩
    let K : Data n I := ⟨P,hP,E,C,hC,hgram⟩
    let e := Fintype.equivFin (Option K.diagonal.Active)
```

```
    let R := K.diagonal.syndromes.recoveryKraus
    refine (Fintype.card (Option K.diagonal.Active), fun r => R (e.symm r), ?_,
      (Matrix.trace C).re, (RCLike.nonneg_iff.mp hC.trace_nonneg).1, ?_)
    · exact (e.symm.sum_comp (fun a => star (R a)*R a)).trans K.recovery_complete
    · intro rho hrho
      change (∑ r, R (e.symm r)*noise E rho*star (R (e.symm r))) = _
      rw [e.symm.sum_comp (fun a => R a*noise E rho*star (R a))]
      have hreal : ((Matrix.trace C).re : ℂ)=Matrix.trace C := by
        exact Complex.ext rfl (by simpa using (RCLike.nonneg_iff.mp hC.trace_nonneg).2.symm)
      rw [hreal]
      exact (K.diagonal.syndromes.decoder_eq_kraus (noise E rho)).symm.trans
        (K.recovery_noise_scaled rho hrho)
```

The example module checks illustrative finite cases, including singular and non-diagonal Gram behavior. Those examples help expose conventions, but the general theorem rests on spectral reduction, normalized syndrome recovery, rank-one necessity and the density-operator bridge. The current scope is the full finite complex-matrix criterion under its stated hypotheses; the earlier orthogonal-syndrome block alone was only a stage of that proof.

# 7 Effective resolvents, Euclidean transfer, and finite bounds

## 7.1 A resolvent identity needs two invertibility hypotheses

Split the state index into a retained type $P$ and an eliminated type $Q$. Let the full operator have blocks $A_{pp}, A_{pq}, A_{qp}, A_{qq}$. The eliminated resolvent block is $D = z1_Q - A_{qq}$, and the Schur complement is

$$S(z) = z1_P - A_{pp} - A_{pq}D^{-1}A_{qp}.$$

The theorem identifies the retained corner of the full inverse with $S(z)^{-1}$. Its two bracketed type-class assumptions assert invertibility of $D$ and invertibility of the full resolvent matrix.

Source: `formalization/SchurFeshbach.lean`.

Exact lines 27–44; excerpt `feshbach`. Hash in Section 12.

```
theorem projected_resolvent (App : Matrix P P ℂ) (Apq : Matrix P Q ℂ)
    (Aqp : Matrix Q P ℂ) (Aqq : Matrix Q Q ℂ) (z : ℂ)
    [Invertible (Matrix.scalar Q z-Aqq)]
    [Invertible (Matrix.scalar (P ⊕ Q) z-Matrix.fromBlocks App Apq Aqp Aqq)] :
    ((Matrix.scalar (P ⊕ Q) z-Matrix.fromBlocks App Apq Aqp Aqq)⁻¹).submatrix
      Sum.inl Sum.inl = (schur App Apq Aqp Aqq z)⁻¹ := by
  let D := Matrix.scalar Q z-Aqq
  let A := Matrix.scalar P z-App
  have he := resolvent_blocks App Apq Aqp Aqq z
  let : Invertible (Matrix.fromBlocks A (-Apq) (-Aqp) D) := Invertible.copy ‹_› _ he.symm
  let : Invertible (A-(-Apq)*⅟D*(-Aqp)) := Matrix.invertibleOfFromBlocks₂₂Invertible A (-Apq)
  ↪ (-Aqp) D
  have hinv := Matrix.invOf_fromBlocks₂₂_eq A (-Apq) (-Aqp) D
  have hs : A-(-Apq)*⅟D*(-Aqp)=schur App Apq Aqp Aqq z := by
    simp only [Matrix.neg_mul,Matrix.mul_neg,neg_neg,Matrix.invOf_eq_nonsing_inv,schur,D,A]
  rw [he,← Matrix.invOf_eq_nonsing_inv,hinv]
  change ⅟(A-(-Apq)*⅟D*(-Aqp))=(schur App Apq Aqp Aqq z)⁻¹
  rw [Matrix.invOf_eq_nonsing_inv]
  congr 1
```

**Contract.** Both finite state-index types have decidable equality. The eliminated block and the full resolvent matrix are invertible. Lean's matrix inverse notation is a total operation, but that notation alone does not supply genuine invertibility at a singular matrix. The theorem uses the invertibility assumptions to justify the actual inverse identities.

**Proof reading.** First rewrite $z1-A$ as the displayed block matrix, retaining the negative signs on the two off-diagonal blocks. Copy the given full invertibility instance to that rewritten matrix. A Mathlib block-inverse theorem supplies invertibility of its Schur complement and the full inverse formula. Rewrite the inverse-of-invertible notation to the nonsingular matrix inverse, then select the retained submatrix. The two negative off-diagonal factors multiply to the sign already encoded in the definition of `schur`.

The source retains a concrete counterexample to dropping full invertibility: at $z = 0$ with $H = \mathrm{diag}(0, -1)$, the eliminated resolvent block is $1$, while the full matrix $z1 - H = \mathrm{diag}(0, 1)$ is singular.

Source: `formalization/SchurFeshbach.lean`.

Exact lines 59–64; excerpt `feshbach_counterexample`. Hash in Section 12.

```
theorem eliminated_invertible_full_singular :
    IsUnit (1 : ℂ) ∧ ¬ IsUnit (!![0, 0; 0, 1] : Matrix (Fin 2) (Fin 2) ℂ) := by
  constructor
  · exact isUnit_one
  · rw [Matrix.isUnit_iff_isUnit_det]
    norm_num [Matrix.det_fin_two]
```

The companion `schur_invertible` theorem says that, under eliminated-block invertibility, full invertibility is equivalent to Schur-complement invertibility. This locates the remaining pole rather than assuming it absent. The corrected assumption is part of the checked interpretation of the traditional result. The retained Paper VI proof is reused in this source; the present edition does not rerun the earlier paper.

### 7.2 Euclidean transfer is the power-series exponential

The transfer is

$$T_e(t) = \exp(-t(H - e1)).$$

The definition uses the actual matrix exponential. For Hermitian $H$, a continuous-functional-calculus theorem identifies it with the scalar function $x \mapsto e^{-t(x-e)}$ applied to $H$.

Source: `formalization/EuclideanTransfer.lean`.

Exact lines 39–47; excerpt `euclidean_cfc`. Hash in Section 12.

```
theorem transfer_cfc (H : Matrix n n ℂ) (hH : H.IsHermitian) (e t : ℝ) :
    transfer H e t = cfc (fun x : ℝ => Real.exp ((-t)*(x-e))) H := by
  rw [cfc_comp' Real.exp (fun x : ℝ => (-t)*(x-e)) H]
  have hlin : cfc (fun x : ℝ => (-t)*(x-e)) H = (-t) • (H - e • (1 : Matrix n n ℂ)) := by
    rw [cfc_const_mul (-t) (fun x : ℝ => x-e) H,
      cfc_sub (fun x : ℝ => x) (fun _ : ℝ => e) H, cfc_id' ℝ H hH.isSelfAdjoint, cfc_const e H
      ↪ hH.isSelfAdjoint]
    simp only [Algebra.algebraMap_eq_smul_one]
  rw [hlin, CFC.real_exp_eq_normedSpace_exp (shifted_hermitian H hH e t).isSelfAdjoint]
  rfl
```

**Proof reading.** The proof composes the functional calculus for the exponential with the affine scalar function $-t(x - e)$. It evaluates that affine function through the calculus as $-t(H - e1)$. A theorem relating real continuous functional calculus to the normed-space exponential identifies the final object with the original power series. The spectral conclusions therefore apply to the actual transfer, not an independently postulated spectral surrogate.

The shift $e_0$ is the minimum of the actual Hermitian eigenvalues. It is defined only when the finite state index is nonempty, because an empty spectrum has no minimum element. The source proves both membership of $e_0$ in the spectrum and the lower-bound property. Positive definiteness of $T_e(t)$ follows from strict positivity of the scalar exponential for every real $t$. Semigroup composition follows because the two scaled generators commute.

Source: `formalization/EuclideanTransfer.lean`.

Exact lines 89–96; excerpt `euclidean_endpoint`. Hash in Section 12.

```
theorem finite_euclidean_transfer [Nonempty n] (H : Matrix n n ℂ)
    (hH : H.IsHermitian) (t s : ℝ) (ht : 0 ≤ t) :
    (transfer H (groundEnergy hH) t).PosDef ∧
    transfer H (groundEnergy hH) (t+s) =
      transfer H (groundEnergy hH) t * transfer H (groundEnergy hH) s ∧
    spectrum ℝ (transfer H (groundEnergy hH) t) ⊆ Set.Ioc 0 1 := by
  exact ⟨transfer_posDef H hH _ _, transfer_add H _ _ _,
    transfer_spectrum_interval H hH _ _ ht (ground_energy_le hH)⟩
```

**Contract.** The endpoint assumes a nonempty finite state index, Hermitian $H$ and nonnegative $t$. It includes $t = 0$. The other time $s$ is arbitrary real in the semigroup identity. Spectral containment in $(0, 1]$ uses $t \geq 0$ and the ground-energy shift. A separate endpoint states containment for the complex spectrum as the real interval's complex image. No infinite-dimensional transfer or continuum limit is concluded.

### 7.3 The low-mode bound keeps its exact constant

The finite-circle dispersion expression is $\lambda_h(w) = 4h^{-2}\sin^2(wh/2)$. The source first proves

$$0 \leq x^2 - \sin^2 x \leq \frac{x^4}{3}$$

for every real $x$, using the quadratic upper bound for sine squared, the cubic error bound for $x - \sin x$ and the estimate $|x + \sin x| \leq 2|x|$. Substituting $x = wh/2$ yields

$$0 \leq w^2 - \lambda_h(w) \leq \frac{w^4}{12}h^2.$$

Source: `formalization/LowModeConvergence.lean`.

Exact lines 32–45; excerpt `low_mode`. Hash in Section 12.

```
theorem low_mode_error (w h : ℝ) (hh : h≠0) :
    0 ≤ w^2-eigenvalue w h ∧ w^2-eigenvalue w h ≤ w^4/12*h^2 := by
  have hs := sine_square_error (w*h/2)
  have hpos : 0 ≤ 4/h^2 := by positivity
  have he : w^2-eigenvalue w h=4/h^2*((w*h/2)^2-Real.sin (w*h/2)^2) := by
    unfold eigenvalue
    field_simp
    ring
  rw [he]
  constructor
  · exact mul_nonneg hpos hs.1
  · calc
      _ ≤ 4/h^2*((w*h/2)^4/3) := mul_le_mul_of_nonneg_left hs.2 hpos
      _ = w^4/12*h^2 := by field_simp; ring
```

**Proof reading.** The proof scales the sine inequality by the nonnegative quantity $4/h^2$. A field calculation identifies the scaled error with $w^2 - \lambda_h(w)$. The final algebra simplifies its upper bound to the coefficient $1/12$. The nonzero-spacing hypothesis justifies division; the conclusion has no small-frequency premise and holds for every real $w$.

For a fixed frequency, the right-hand side tends to zero quadratically as $h$ tends to zero through nonzero values. A growing frequency range needs control of $w^4h^2$. The theorem by itself does not prove convergence of an entire spectrum, a spectral-dimension plateau, a dynamics limit or a spacetime reconstruction. Those applications require their own quantified range and analytic arguments.

### 7.4 A compressed anomaly can vanish for purely algebraic reasons

The constraint audit sits beside the 19 finite ledger items. If every constraint right-annihilates $P$, then every product term in the proposed anomaly also right-annihilates $P$, so $P\mathcal{A}P = 0$ for arbitrary structure coefficients. The source needs no projector axioms for this observation.

Source: `formalization/ConstraintAudit.lean`.

Exact lines 31–34; excerpt `constraint_kernel`. Hash in Section 12.

```
theorem compressed_anomaly_zero (C : I → R) (f : I → R)
    (P : R) (hP : ∀ c, C c * P = 0) (a b : I) :
    P * anomaly C f a b * P = 0 := by
  rw [mul_assoc, anomaly_annihilates_common_kernel C f P hP, mul_zero]
```

It also constructs a nonzero physical projector and two rational $3 \times 3$ constraints that act on its complement. Their commutator is nonzero, yet its physical compression is zero.

Source: `formalization/ConstraintAudit.lean`.

Exact lines 56–60; excerpt `constraint_nonclosure`. Hash in Section 12.

```
theorem commutator_nonzero : constraintX * constraintZ - constraintZ * constraintX ≠ 0 := by
  intro h
  have h12 := congrArg (fun A : Matrix (Fin 3) (Fin 3) ℚ => A 1 2) h
  norm_num [constraintX, constraintZ, Matrix.mul_apply, Fin.sum_univ_succ] at h12
  norm_num [Matrix.cons_val_two] at h12
```

This supplies a concrete scope warning: exact common-kernel compression cannot by itself certify operator closure on the whole space. It does not prove that an intended continuum constraint algebra exists or that every refinement has the same behavior. The hypotheses of the finite audit must be checked before applying it to a proposed physical construction.

### 7.5 The broader manuscript and the five open targets

The preserved original paper and the strengthened traditional edition discuss memory, geometry, diagnostics and physical interpretation beyond the named finite endpoints. A traditional proof can be more explanatory than a formal theorem statement, and a strengthened mathematical statement can go beyond the selected formal endpoint. Coverage is assigned by the full result map, not by similarity of wording or proximity on a page.

The original manuscript's five explicitly named continuum conjectures are anomaly-free refinement, uniform Feshbach control, Lorentzian reconstruction, an Einstein infrared limit and a massless spin-two sector. None is a theorem target in the 19-item ledger. Finite path reconstruction, finite recovery, a projected connection, a resolvent identity and a dispersion error bound do not jointly prove those existence and limiting claims. The formal source provides rigorous finite ingredients and, in the geometric case, broad parameter-manifold calculus under its stated assumptions.

The complete theorem catalog includes seven constraint-audit declarations, four Schur–Feshbach declarations and the other supporting lemmas. The count 323 therefore means named declarations in the current finite development, not 323 independently stated claims in the traditional paper, and not 323 continuum results.

# 8 Evidence and reproducible replay

## 8.1 What the saved compiler record establishes

The inherited run is `verification/final_finite_release_run/SUMMARY.json` in the unchanged v0.6.0 snapshot. It began on 6 September 2026 at 15:30:24 UTC and was updated at 15:32:49.641452 UTC. It records successful compilation of all 25 current modules, all 323 named theorem axiom audits, and two deliberate rejected controls. Current static reconciliation checks the source hashes and saved log hashes against those records.

The allowed axiom set is `propext`, `Classical.choice`, and `Quot.sound`. Every reported theorem dependency set is a subset of it. One reported theorem is axiom-free. These are foundational dependencies accepted in the recorded Lean environment. They do not remove manuscript hypotheses such as full-resolvent invertibility or Kraus normalization. Axiom auditing and hypothesis reading answer different questions.

The separate inherited `CONSTRUCTED_OBJECTS_AUDIT.json`, in the same release-run directory, records six constructed objects: the fiber, projection to the fiber, local product homeomorphism, local continuous linear fiber equivalence, fiber-valued covariant derivative, and fiber curvature. Definitions can contain proofs of inverse, linearity or continuity fields, so a theorem-name inventory alone would miss part of this evidence. The six-object audit remains separate from the 323-theorem count. The current computation report checks 12 bindings between the inherited audit, source, inventory, runner, transcript and cumulative summary. It adds no theorem declarations and executes no Lean compiler.

The source archive omits the compiled public and private interfaces, the portable compiler kit and the Mathlib cache. The saved success record is inherited compilation evidence. It is not a fresh compilation on this host or an independent recheck of all imported Mathlib proofs. The recorded release reused its pinned library environment and did not rebuild earlier papers.

## 8.2 Source and document checks in this edition

The guide resolves nested namespaces in active source and derives 323 distinct theorem declarations across 25 modules. That set matches the saved theorem inventory and every saved theorem axiom report. All 19 finite ledger entries resolve, including `GlobalConnection.covariant` among the geometric supporting endpoints. Where a ledger entry gives only a module, the guide adds explicitly identified source pointers. It preserves the original ledger.

All 67 selected excerpts are exact contiguous source blocks and remain byte-identical to the retrieved guide's raw UTF-8 selections. Their line ranges, original module hashes and excerpt hashes accompany this document. Rendered code uses explicit font fallback for the mathematical script letters and small-square dot-product symbol absent from the monospaced font. The raw source is unchanged. The PDF checks cover every theorem name, excerpt, reference, missing glyph and text bound.

The local `static_check.py` checks saved source and log identities, transitive local import hashes, declarations, dependency pins, inherited rejection records and the six-object audit. It also compares every delimited mathematical span and every contract and proof-walk paragraph in the six teaching chapters with the retrieved edition. These are editorial and source-consistency checks. They do not compile Lean or validate a new proof.

### 8.3 The actual current finite computations

The current report is `verification/monograph_checks/COMPUTATIONAL_REVIEW.json`, dated 9 October 2026. Its six bounded execution records retain actual commands, environment versions, caps, inputs, outputs and hashes. The original and corrected numerical gates use Python 3.12.14, NumPy 2.3.5 and SciPy 1.17.0. The symbolic gate uses SymPy 1.14.0. The earlier dependency-unavailability statements in retained October 6 reports describe that older host and are superseded for this edition.

The original companion passes 22 actual pytest cases. A second entry point calls those same 22 functions directly, so this is not 44 independent tests. The verifier software passes 16 regression methods: nine positive methods and seven malformed-input or tamper controls. These Python controls differ from the two inherited deliberate Lean rejections. No fresh kernel or compiler-control run was available because `lean`, `lake` and `elan` are absent.

All 1,048 stored result leaves, including 1,045 numerical fields, exactly match the original experiment replay. The recorded comparison bounds are absolute $10^{-10}$ and relative $10^{-8}$, although equality made those allowances unnecessary in this run. The unchanged strengthened suite passes 18,049 checks in 15 groups. Its separately corrected copy passes 17,699 checks in the same 15 groups, with 87 exact mode-index assertions for $N = 4, \ldots, 32$. The two lower endpoints change from `-N//2` to `-(N//2)`. For odd `N`, Python floor division otherwise adds a repeated residue representative. The 350-check difference reflects corrected bookkeeping. The raw source remains intact, and the two overlapping suite totals are not added.

The independent exact rational witnesses contain 269 assertions in total, including three explicit negative controls and a separate singular-inverse rejection benchmark. The original visual-example gate runs 180 SymPy assertions, including nine rejected controls, hence 171 positive assertions. The extended gate runs 373 positive exact assertions and 12 rejected controls over rational and Gaussian-rational finite examples. All 38 vector plate sources regenerate byte-identically: 26 original plates and 12 extended plates. Plate regeneration checks presentation consistency rather than adding mathematical proof coverage.

A separate audit, `verification/monograph_checks/TRADITIONAL_EXACT_MODELS_REVIEW.json`, checks the three new traditional illustrations. It passes 30 positive exact assertions and rejects six deliberately false assertions. The model JSON and three generated PDFs reproduce byte-identically. These are fixed examples of seed support, block inversion and channel scaling. They add no formal targets or general recovery conclusion.

The manifest records retain the actual finite ranges, conventions and tolerances. Original numerical checks typically use bounds from $10^{-12}$ to $10^{-10}$, with a $10^{-6}$ moving-frame certificate. The strengthened base tolerance is $2 \times 10^{-9}$, with individual bounds through $2 \times 10^{-7}$. Exact arithmetic gates have no numerical tolerance. These executions overlap and use different count units. Their totals are neither summed as independent evidence nor interpreted as universal theorems. They do not settle any of the five physical continuum targets.

| Evidence | Time or source | Meaning |
|---|---|---|
| 25 module compiler exits | Saved 6 September release | Inherited compilation under the locked toolchain. |
| 323 theorem axiom records | Saved release, currently reconciled | Current source declarations agree with the stored audited set. |

| Evidence | Time or source | Meaning |
|---|---|---|
| Six constructed-object audits | Separate saved release record | Proof fields in definitions are audited separately. |
| Source, excerpt and document checks | Current 9 October edition | Exact source correspondence and readable navigation. |
| 22 pytest cases, 16 verifier methods | Current Python execution | Software checks at the recorded inputs and conditions. |
| Numerical and exact witness gates | Current bounded executions | Case-bound computations with explicit arithmetic and assumptions. |
| 38 vector source regenerations | Current presentation replay | Deterministic plate sources, with no added theorem coverage. |

### 8.4 Rebuild only this guide

The guide directory contains the authored TeX, frozen navigation, rendered code, raw excerpts, styles and bundled fonts. `build.py` copies the complete source tree to an isolated temporary directory and performs four XeLaTeX passes. It compiles the authored document without regenerating prose, source data, figures or mathematical evidence. It does not invoke Lean.

```
python editable/lean_guide/build.py
python editable/lean_guide/build.py --output-directory /path/to/pdf_rebuild
python editable/lean_guide/build.py --check-only
```

Run these commands from the package root, or supply an absolute path to the script. Python 3, XeLaTeX and the TeX packages named in the preamble are required. Fonts resolve through the relative `fonts/` directory. The optional `--output-directory` keeps delivered products unchanged, and `--check-only` writes no delivered products.

Source-table regeneration additionally needs FontTools and the preserved snapshot:

```
python editable/lean_guide/assemble.py
python editable/lean_guide/static_check.py
python editable/lean_guide/build.py
python editable/lean_guide/verify_pdf.py
```

Both source scripts accept `--source PATH` for a relocated snapshot. Assembly stops if counts, inventory, saved axiom sets or source identities disagree. A new source edition requires a deliberate revision of the expected counts and endpoint selection together with its own evidence. These scripts reconcile documentation. They are not proof checkers.

### 8.5 Replay the formal development with the pinned kit

With the separately supplied pinned portable kit, set the working directory to `source/complete/Paper_VII_Complete_v0.6.0_With_Visual_Appendix/original_snapshot`, relative to the package root. Choose a new output directory to preserve the inherited evidence.

```
python scripts/verify.py --kit /path/to/kit \
  --out verification/my_run --timeout 240
python scripts/audit_constructions.py --kit /path/to/kit \
  --run verification/my_run
python scripts/test_verifier.py
```

The verifier checks runtime version and Mathlib revision, then compiles local modules in dependency order with one worker and strict warnings. It compares emitted axiom audits with the exact inventory and checks both deliberate invalid controls. The construction audit uses the fresh run's actual build interfaces. It rejects stale source or interface identities.

For short execution windows, the retained checkpoint mechanism can pause after a few checks:

```
python scripts/verify.py --kit /path/to/kit \
  --out verification/my_run --timeout 240 \
  --max-checks 3 --resume
```

Repeat until the verifier reports complete success. Exit code 2 means paused or incomplete. Resume checks the verifier, runner, inventory, source dependencies and both public and private interfaces before trusting a cached module. An interrupted build remains incomplete even when earlier modules passed.

The `check_low_memory.py` launcher uses ordinary Lean with one worker. Its name does not promise an enforced memory cap. The snapshot is not a delivered Lake project with a current `lakefile`. Its provenance manifest supplies the portable kit's locked dependencies. A bare `lake build` would not reproduce the retained procedure.

### 8.6 The retained complete-bundle wrapper

Set the working directory to `source/complete/Paper_VII_Complete_v0.6.0_With_Visual_Appendix`. Its wrapper exposes distinct actions:

```
python Run-PaperVII.py verify
python Run-PaperVII.py examples --output-dir /path/to/example_replay
python Run-PaperVII.py original --output-dir /path/to/original_replay
```

The integrity action verifies the manifest and checksums. The example action runs the original visual-appendix example suite with its declared dependencies. The original action runs the original numerical, figure, TeX and verifier-software workflow. Its own documentation identifies that action as a companion replay rather than Lean execution. The current report records its separate actual gates. It does not claim that the original all-in-one PowerShell chain, figure-generation chain or historical manuscript rebuild ran as a single workflow.

All nine dependency revisions and the compiler commit appear in the dependency appendix. Source and transcript hashes bind this reading to its inherited artifacts. Document construction, current finite computation and kernel replay each have a distinct purpose and separately reportable outcome.

## 9 Complete finite-result map

The following map preserves all 19 ledger scopes and resolves their current formal endpoints. Their recorded completion is inherited from the source release under the stated hypotheses. It does not assert that every sentence in the traditional paper is separately formalized. Source pointers added where the ledger gives only a module are identified explicitly.

### 9.1 2.1 / Orbit dimension of one quantum seed

**Preserved ledger scope.** Actual matrix multiplication orbit, explicit equivalence with independently chosen rows, d times rank(C), and full-rank cyclicity when d is nonempty. No orbit-dimension hypothesis is assumed.

**Formal endpoints.**

- `KomorebiPaperVII.SeedOrbit.span_orbit_dimension`; `SeedOrbit.lean`, line 68.

### 9.2 2.2 / Quantum seed-rank formula

**Preserved ledger scope.** Actual sums of k matrix actions, full-column-rank seed construction, simultaneous finite direct-sum generation, and an IsLeast proof for max_i ceil(m_i/d_i). Every d_i is positive. Empty block families use supremum 0.

**Formal endpoints.**

- `KomorebiPaperVII.SeedOrbit.quantum_seed_rank`; `SeedOrbit.lean`, line 239.

### 9.3 2.3 / Local orbit and Schmidt rank

**Preserved ledger scope.** Actual Kronecker local action in standard product coordinates. Schmidt rank is independently defined as minimum product-vector decomposition length, with its equality to matrix rank proved. Derives local orbit dimension and equivalence with full support of the actual B-reduced matrix; the full-orbit equivalence assumes a nonempty A index.

**Formal endpoints.**

- `KomorebiPaperVII.SeedOrbit.local_orbit_reduced_support`; `SeedOrbit.lean`, line 364.

### 9.4 2.4 / One seed for the computational basis

**Preserved ledger scope.** Explicit local Pauli X addressing for every n, including n=0. The constructed gate word sends the zero seed to the standard coordinate basis, with linear independence, span and cardinality 2^n.

**Formal endpoints.**

- `KomorebiPaperVII.ComputationalSeed.circuit_seed_basis`; `ComputationalSeed.lean`, line 80.

### 9.5 3.1 / Cyclic quantum projectors

**Preserved ledger scope.** Constructs the primitive complex character and rho(r)=S^val(r) from S^N=1 for every N>0, including N=1. Proves exact exponential-root coefficient formula, character orthogonality, multiplication, completeness, eigenaction, and self-adjointness for unitary S. Includes a concrete complex-matrix theorem.

**Formal endpoints.**

- `KomorebiPaperVII.CyclicProjectors.finite_cyclic_projectors`; `CyclicProjectors.lean`, line 157.

### 9.6 3.2 / Tensor/polyphase refinement

**Preserved ledger scope.** Arbitrary finite tensor factors and dimensions. Proves tensor product multiplication, identity, adjoint and sum laws, then orthogonality, completeness and self-adjointness after grouping by total residue for N>0.

**Formal endpoints.**

- `KomorebiPaperVII.TensorRefinement.tensor_polyphase_refinement`; `TensorRefinement.lean`, line 139.

### 9.7 4.1 / Exact circuit path expansion

**Preserved ledger scope.** Arbitrary finite gate list, corner expansion and complete reconstruction.

**Source pointers added by the guide.**

- `KomorebiPaperVII.PacketFamily.circuit_path_expansion`; `QuantumPacketCore.lean`, line 63.
- `KomorebiPaperVII.PacketFamily.circuit_reconstruction`; `QuantumPacketCore.lean`, line 70.

### 9.8 4.2 / Packetwise unitarity conservation

**Preserved ledger scope.** Both identities in a star ring, plus concrete complex-matrix specializations.

**Source pointers added by the guide.**

- `KomorebiPaperVII.PacketFamily.unitarity_columns`; `QuantumPacketCore.lean`, line 119.
- `KomorebiPaperVII.PacketFamily.unitarity_rows`; `QuantumPacketCore.lean`, line 134.
- `KomorebiPaperVII.matrix_unitarity_columns`; `QuantumPacketCore.lean`, line 181.
- `KomorebiPaperVII.matrix_unitarity_rows`; `QuantumPacketCore.lean`, line 188.

### 9.9 5.1 / Exact symmetry packets

**Preserved ledger scope.** Generator blocks and actual exponential; zero cross-packet transfer.

**Source pointers added by the guide.**

- `KomorebiPaperVII.PacketFamily.symmetry_exponential_no_transfer`; `QuantumPacketCore.lean`, line 168.
- `KomorebiPaperVII.PacketFamily.symmetry_exponential_diagonal`; `QuantumPacketCore.lean`, line 163.

### 9.10 5.2 / Commutator leakage bound

**Preserved ledger scope.** Actual exponential with self-adjoint H and orthogonal P. Proves the Hilbert operator-norm bound for all real times, without nonzero-rank or nonempty-matrix assumptions. Also proves observable-conjugation Lipschitz continuity, the cap at one, and a symmetry-breaking perturbation estimate.

**Formal endpoints.**

- `KomorebiPaperVII.Leakage.matrix_commutator_leakage_bound`; `LeakageBound.lean`, line 167.

### 9.11 6.1 / Moving-frame Hamiltonian

**Preserved ledger scope.** Entrywise actual real derivatives of finite complex matrices and vectors. Constructs y=U*psi and its derivative, verifies the transformed Schrodinger equation and Hermiticity. The effective-Hamiltonian Hermiticity conclusion explicitly assumes H*=H.

**Formal endpoints.**

- `KomorebiPaperVII.MovingFrames.moving_frame_coordinates`; `MovingFrames.lean`, line 110.

### 9.12 6.3 / Canonical packet connection

**Preserved ledger scope.** Actual derivatives in a normed real star algebra with continuous star. Differentiates projector multiplication, completeness and self-adjointness to prove both formulas for C, skew-adjointness and [C,P_b]=dot(P_b). Does not include manifold curvature.

**Formal endpoints.**

- `KomorebiPaperVII.Connection.canonical_connection_of_hasDerivAt`; `CanonicalConnection.lean`, line 113.

### 9.13 6.4 / Projected connection

**Preserved ledger scope.** Smooth real boundaryless parameter manifolds modeled on a complete normed space; complete real normed fibers, including finite quantum spaces through underlying real calculus. Constructs the actual range total space, open local product homeomorphisms, smooth fiber-linear transitions, inverse and cocycle laws, and locally constant rank. Proves local smooth-section equivalence, the actual global covariant derivative, connection laws and gauge gluing. Derives curvature using actual manifold derivatives and the actual Lie bracket, and proves tensoriality. Uses an explicit smooth atlas rather than a packaged Mathlib ContMDiffVectorBundle instance. No global chart, pre-existing range-bundle atlas or curvature identity is assumed.

**Formal endpoints.**

- `KomorebiPaperVII.ManifoldCurvature.projected_connection_curvature`; `ManifoldProjectedCurvature.lean`, line 214.
- `KomorebiPaperVII.RangeBundle.smooth_range_bundle_atlas`; `GlobalRangeBundle.lean`, line 241.
- `KomorebiPaperVII.BundleCompletion.localProduct_overlap`; `ProjectedBundleCompletion.lean`, line 31.
- `KomorebiPaperVII.BundleCompletion.smooth_section_iff`; `ProjectedBundleCompletion.lean`, line 40.

- `KomorebiPaperVII.GlobalConnection.covariant`; `GlobalProjectedConnection.lean`, line 44.
- `KomorebiPaperVII.GlobalConnection.local_connections_glue`; `GlobalProjectedConnection.lean`, line 115.
- `KomorebiPaperVII.BundleCompletion.local_connections_gauge`; `ProjectedBundleCompletion.lean`, line 57.

### 9.14 7.1 / Block-diagonal measurement invariance

**Preserved ledger scope.** Trace duality, measurement invariance and trace preservation for finite complex matrices.

**Source pointers added by the guide.**

- `KomorebiPaperVII.measurement_invariance`; `QuantumPacketCore.lean`, line 208.
- `KomorebiPaperVII.dephase_trace_preserving`; `QuantumPacketCore.lean`, line 213.

### 9.15 7.2 / Finite Kraus channel

**Preserved ledger scope.** Finite complex matrix Kraus map: linearity, positivity, trace preservation under sum(K* K)=I, identity-tensor amplification at every finite auxiliary dimension, complete positivity and density-matrix preservation.

**Formal endpoints.**

- `KomorebiPaperVII.Kraus.channel_completely_positive`; `KrausChannels.lean`, line 58.

### 9.16 8.1 / Finite Knill-Laflamme criterion

**Preserved ledger scope.** Full finite complex-matrix Knill-Laflamme criterion. Constructs a total completely positive trace-preserving recovery from general positive semidefinite Gram data using actual spectral diagonalization, positive-eigenvalue support and proof that null errors vanish. Derives necessity from actual recovery via rank-one Kraus rigidity. Proves equivalence for normalized code density matrices, preservation with arbitrary finite references, the unnormalized error-family criterion with an explicit nonnegative scale, and correction of every normalized channel in the same error span by the same recovery. Zero code is handled separately. This is a mathematical, noncomputable spectral construction, not a numerical decoder implementation.

**Formal endpoints.**

- `KomorebiPaperVII.KnillLaflamme.state_correctable_iff_gram`; `QuantumStateBridge.lean`, line 139.
- `KomorebiPaperVII.KnillLaflamme.error_family_correctable_iff_gram`; `ErrorSpanRecovery.lean`, line 188.
- `KomorebiPaperVII.KnillLaflamme.Data.recovery_span_channel`; `ErrorSpanRecovery.lean`, line 138.
- `KomorebiPaperVII.KnillLaflamme.recovery_with_reference`; `QuantumStateBridge.lean`, line 164.

### 9.17 9.1 / Exact Feshbach resolvent

**Preserved ledger scope.** Corrected: eliminated block AND full resolvent matrix invertible. Paper VI proof reused.

**Source pointers added by the guide.**

- `KomorebiPaperVII.SchurFeshbach.projected_resolvent`; `SchurFeshbach.lean`, line 27.
- `KomorebiPaperVII.SchurFeshbach.schur_invertible`; `SchurFeshbach.lean`, line 46.

### 9.18 10.1 / Finite Euclidean transfer

**Preserved ledger scope.** Actual power-series matrix exponential, identified with continuous functional calculus. Constructs the minimum eigenvalue on a nonempty finite state space, proves positive definiteness, semigroup composition, and real and complex spectrum containment in (0,1] for nonnegative time.

**Formal endpoints.**

- `KomorebiPaperVII.EuclideanTransfer.finite_euclidean_transfer`; `EuclideanTransfer.lean`, line 89.

### 9.19 11.1 / Low-mode second-order bound

**Preserved ledger scope.** Explicit h != 0; stronger all-real-frequency bound with constant 1/12. Paper VI proof reused.

**Source pointers added by the guide.**

- `KomorebiPaperVII.LowModeConvergence.low_mode_error`; `LowModeConvergence.lean`, line 32.

## 10 All named theorem declarations

The following catalog is derived from active declarations in the 25 current source modules, with nested namespaces resolved. It is reconciled against the saved theorem inventory and all 323 saved axiom reports. It includes supporting lemmas, the finite constraint audit, and strengthened endpoints; it is not a list of 323 manuscript theorems. The source line is the declaration line. "Core" means an endpoint in the finite-result map; "support" means a declaration used in the formal development or its scope audit. All saved axiom sets lie within `propext`, `Classical.choice`, and `Quot.sound`; the full source-bound sets accompany the guide.

### 10.1 CanonicalConnection: 9 theorem declarations

Source: `formalization/CanonicalConnection.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Connection.canonical_right` | 18; support |
| `KomorebiPaperVII.Connection.canonical_left_relation` | 23; support |
| `KomorebiPaperVII.Connection.canonical_commutator` | 39; support |
| `KomorebiPaperVII.Connection.canonical_skewAdjoint` | 48; support |
| `KomorebiPaperVII.Connection.canonical_half_commutator` | 59; support |
| `KomorebiPaperVII.Connection.differentiated_orthogonality` | 78; support |
| `KomorebiPaperVII.Connection.differentiated_completeness` | 98; support |
| `KomorebiPaperVII.Connection.differentiated_selfAdjoint` | 106; support |
| `KomorebiPaperVII.Connection.canonical_connection_of_hasDerivAt` | 113; Core 6.3 |

### 10.2 ComputationalSeed: 14 theorem declarations

Source: `formalization/ComputationalSeed.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.ComputationalSeed.translation_zero` | 24; support |
| `KomorebiPaperVII.ComputationalSeed.translation_add` | 27; support |
| `KomorebiPaperVII.ComputationalSeed.translation_ket` | 31; support |
| `KomorebiPaperVII.ComputationalSeed.translation_involution` | 35; support |
| `KomorebiPaperVII.ComputationalSeed.localX_on_ket` | 40; support |
| `KomorebiPaperVII.ComputationalSeed.controlledX_eq_translation` | 51; support |
| `KomorebiPaperVII.ComputationalSeed.translation_list_product` | 63; support |
| `KomorebiPaperVII.ComputationalSeed.sum_local_addresses` | 68; support |
| `KomorebiPaperVII.ComputationalSeed.circuit_eq_translation` | 72; support |
| `KomorebiPaperVII.ComputationalSeed.circuit_seed` | 78; support |
| `KomorebiPaperVII.ComputationalSeed.circuit_seed_basis` | 80; Core 2.4 |
| `KomorebiPaperVII.ComputationalSeed.addressed_seed_linearIndependent` | 83; support |
| `KomorebiPaperVII.ComputationalSeed.addressed_seed_spans` | 87; support |
| `KomorebiPaperVII.ComputationalSeed.number_of_addresses` | 91; support |

### 10.3 ConstraintAudit: 7 theorem declarations

Source: `formalization/ConstraintAudit.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.ConstraintAudit.anomaly_annihilates_common_kernel` | 26; support |
| `KomorebiPaperVII.ConstraintAudit.compressed_anomaly_zero` | 31; support |
| `KomorebiPaperVII.ConstraintAudit.physical_idempotent` | 43; support |
| `KomorebiPaperVII.ConstraintAudit.physical_nonzero` | 46; support |
| `KomorebiPaperVII.ConstraintAudit.constraints_annihilate_physical` | 51; support |
| `KomorebiPaperVII.ConstraintAudit.commutator_nonzero` | 56; support |
| `KomorebiPaperVII.ConstraintAudit.physical_commutator_zero` | 62; support |

### 10.4 CyclicProjectors: 18 theorem declarations

Source: `formalization/CyclicProjectors.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.CyclicProjectors.character_sum` | 22; support |
| `KomorebiPaperVII.CyclicProjectors.packet_eigen` | 28; support |
| `KomorebiPaperVII.CyclicProjectors.packet_mul` | 44; support |
| `KomorebiPaperVII.CyclicProjectors.packet_idempotent` | 60; support |
| `KomorebiPaperVII.CyclicProjectors.packet_complete` | 65; support |
| `KomorebiPaperVII.CyclicProjectors.powers_zero` | 76; support |
| `KomorebiPaperVII.CyclicProjectors.powers_add` | 79; support |
| `KomorebiPaperVII.CyclicProjectors.powers_one` | 84; support |
| `KomorebiPaperVII.CyclicProjectors.cyclic_quantum_projectors` | 87; support |
| `KomorebiPaperVII.CyclicProjectors.star_character` | 97; support |
| `KomorebiPaperVII.CyclicProjectors.packet_selfAdjoint` | 104; support |
| `KomorebiPaperVII.CyclicProjectors.powers_star` | 116; support |
| `KomorebiPaperVII.CyclicProjectors.cyclic_packet_selfAdjoint` | 127; support |
| `KomorebiPaperVII.CyclicProjectors.omega_exponential` | 136; support |
| `KomorebiPaperVII.CyclicProjectors.character_as_power` | 140; support |
| `KomorebiPaperVII.CyclicProjectors.packet_coefficient` | 143; support |
| `KomorebiPaperVII.CyclicProjectors.cyclic_projector_formula` | 151; support |
| `KomorebiPaperVII.CyclicProjectors.finite_cyclic_projectors` | 157; Core 3.1 |

### 10.5 ErrorSpanRecovery: 9 theorem declarations

Source: `formalization/ErrorSpanRecovery.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.scaled_corrected_kraus_family` | 23; support |

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.compressed_gram_from_scalar` | 48; support |
| `KomorebiPaperVII.KnillLaflamme.noise_preserves_trace` | 65; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_scalar_composites` | 79; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_cross_error` | 94; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_error_superposition` | 112; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_span_channel` | 138; Core 8.1 |
| `KomorebiPaperVII.KnillLaflamme.gram_of_scaled_recovery` | 175; support |
| `KomorebiPaperVII.KnillLaflamme.error_family_correctable_iff_gram` | 188; Core 8.1 |

### 10.6 EuclideanTransfer: 12 theorem declarations

Source: `formalization/EuclideanTransfer.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.EuclideanTransfer.shifted_hermitian` | 23; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_hermitian` | 27; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_zero` | 30; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_add` | 33; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_cfc` | 39; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_spectrum` | 49; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_posDef` | 54; support |
| `KomorebiPaperVII.EuclideanTransfer.transfer_spectrum_interval` | 65; support |
| `KomorebiPaperVII.EuclideanTransfer.ground_energy_le` | 77; support |
| `KomorebiPaperVII.EuclideanTransfer.ground_energy_mem` | 83; support |
| `KomorebiPaperVII.EuclideanTransfer.finite_euclidean_transfer` | 89; Core 10.1 |
| `KomorebiPaperVII.EuclideanTransfer.transfer_complex_spectrum` | 99; support |

### 10.7 GlobalProjectedConnection: 10 theorem declarations

Source: `formalization/GlobalProjectedConnection.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.GlobalConnection.nabla_in_range` | 48; support |
| `KomorebiPaperVII.GlobalConnection.nabla_add_sections` | 53; support |
| `KomorebiPaperVII.GlobalConnection.nabla_leibniz` | 59; support |
| `KomorebiPaperVII.GlobalConnection.nabla_add_vectors` | 65; support |
| `KomorebiPaperVII.GlobalConnection.nabla_smul_vector` | 69; support |
| `KomorebiPaperVII.GlobalConnection.nabla_germ` | 73; support |
| `KomorebiPaperVII.GlobalConnection.smooth_directional` | 81; support |
| `KomorebiPaperVII.GlobalConnection.smooth_nabla` | 88; support |
| `KomorebiPaperVII.GlobalConnection.localNabla_represents_global` | 102; support |
| `KomorebiPaperVII.GlobalConnection.local_connections_glue` | 115; Core 6.4 |

### 10.8 GlobalRangeBundle: 22 theorem declarations

Source: `formalization/GlobalRangeBundle.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.RangeBundle.mem_fiber` | 30; support |
| `KomorebiPaperVII.RangeBundle.project_coe` | 36; support |
| `KomorebiPaperVII.RangeBundle.project_fiber` | 39; support |
| `KomorebiPaperVII.RangeBundle.transport_self` | 45; support |
| `KomorebiPaperVII.RangeBundle.transport_intertwines` | 49; support |
| `KomorebiPaperVII.RangeBundle.transport_inverse_intertwines` | 56; support |
| `KomorebiPaperVII.RangeBundle.mem_domain` | 73; support |
| `KomorebiPaperVII.RangeBundle.isOpen_domain` | 76; support |
| `KomorebiPaperVII.RangeBundle.fromCoord_range` | 90; support |
| `KomorebiPaperVII.RangeBundle.toCoord_fromCoord` | 97; support |
| `KomorebiPaperVII.RangeBundle.fromCoord_toCoord` | 105; support |
| `KomorebiPaperVII.RangeBundle.transition_self` | 121; support |
| `KomorebiPaperVII.RangeBundle.transition_cocycle` | 127; support |
| `KomorebiPaperVII.RangeBundle.smooth_transport` | 139; support |
| `KomorebiPaperVII.RangeBundle.smooth_inverse_transport` | 144; support |
| `KomorebiPaperVII.RangeBundle.smooth_toCoord` | 154; support |
| `KomorebiPaperVII.RangeBundle.smooth_fromCoord` | 159; support |
| `KomorebiPaperVII.RangeBundle.smooth_transition` | 164; support |
| `KomorebiPaperVII.RangeBundle.localProduct_base` | 212; support |
| `KomorebiPaperVII.RangeBundle.localProduct_transition` | 217; support |
| `KomorebiPaperVII.RangeBundle.fiber_rank_locally_constant` | 234; support |
| `KomorebiPaperVII.RangeBundle.smooth_range_bundle_atlas` | 241; Core 6.4 |

### 10.9 KnillLaflammeExamples: 8 theorem declarations

Source: `formalization/KnillLaflammeExamples.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.Examples.redundant_complete` | 25; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.redundant_gram_positive` | 32; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.redundant_gram_singular` | 36; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.redundant_gram_off_diagonal` | 41; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.redundant_correctable` | 45; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.dephasing_complete` | 57; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.dephasing_not_correctable` | 64; support |
| `KomorebiPaperVII.KnillLaflamme.Examples.zero_code_correctable` | 74; support |

### 10.10 KnillLaflammeNecessity: 7 theorem declarations

Source: `formalization/KnillLaflammeNecessity.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.rank_one_gram_rigidity` | 19; support |
| `KomorebiPaperVII.KnillLaflamme.kraus_rank_one_rigidity` | 52; support |
| `KomorebiPaperVII.KnillLaflamme.corrected_kraus_family` | 68; support |
| `KomorebiPaperVII.KnillLaflamme.gram_of_recovery` | 86; support |
| `KomorebiPaperVII.KnillLaflamme.correctable_iff_gram` | 115; support |
| `KomorebiPaperVII.KnillLaflamme.not_correctable_of_nonscalar` | 133; support |
| `KomorebiPaperVII.KnillLaflamme.recovery_cross_from_scalar` | 142; support |

### 10.11 KnillLaflammeSufficiency: 22 theorem declarations

Source: `formalization/KnillLaflammeSufficiency.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.mix_restricted` | 28; support |
| `KomorebiPaperVII.KnillLaflamme.mix_gram` | 33; support |
| `KomorebiPaperVII.KnillLaflamme.mix_noise` | 45; support |
| `KomorebiPaperVII.KnillLaflamme.diagonalized_gram` | 74; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.zero_weight_error` | 107; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.sqrt_weight_ne_zero` | 118; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.sqrt_weight_sq` | 121; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.normalized_restricted` | 125; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.normalized_gram` | 128; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.error_eq_sqrt_normalized` | 152; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.decode_diagonal_error` | 156; support |
| `KomorebiPaperVII.KnillLaflamme.DiagonalErrors.decode_noise` | 175; support |
| `KomorebiPaperVII.KnillLaflamme.Data.restricted_error_gram` | 198; support |
| `KomorebiPaperVII.KnillLaflamme.Data.restricted_noise` | 216; support |
| `KomorebiPaperVII.KnillLaflamme.Data.diagonal_noise` | 227; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_noise_scaled` | 232; support |
| `KomorebiPaperVII.KnillLaflamme.Data.gram_trace_one` | 238; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_corrects` | 252; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_complete` | 262; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_preserves_trace` | 267; support |
| `KomorebiPaperVII.KnillLaflamme.Data.recovery_completely_positive` | 271; support |
| `KomorebiPaperVII.KnillLaflamme.Data.exists_recovery` | 278; support |

### 10.12 KrausChannels: 7 theorem declarations

Source: `formalization/KrausChannels.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Kraus.channel_add` | 16; support |
| `KomorebiPaperVII.Kraus.channel_smul` | 20; support |
| `KomorebiPaperVII.Kraus.channel_positive` | 29; support |
| `KomorebiPaperVII.Kraus.channel_trace_preserving` | 33; support |
| `KomorebiPaperVII.Kraus.amplification_eq_kraus` | 48; support |
| `KomorebiPaperVII.Kraus.channel_completely_positive` | 58; Core 7.2 |
| `KomorebiPaperVII.Kraus.channel_density_matrix` | 64; support |

### 10.13 LeakageBound: 17 theorem declarations

Source: `formalization/LeakageBound.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Leakage.exp_unitary` | 25; support |
| `KomorebiPaperVII.Leakage.transported_derivative` | 31; support |
| `KomorebiPaperVII.Leakage.transported_derivative_norm` | 40; support |
| `KomorebiPaperVII.Leakage.transported_lipschitz` | 46; support |
| `KomorebiPaperVII.Leakage.exponential_commutator_bound` | 56; support |
| `KomorebiPaperVII.Leakage.leakage_corner` | 67; support |
| `KomorebiPaperVII.Leakage.leakage_corner_norm` | 75; support |
| `KomorebiPaperVII.Leakage.skew_generator_leakage_bound` | 88; support |
| `KomorebiPaperVII.Leakage.generator_skew` | 96; support |
| `KomorebiPaperVII.Leakage.generator_commutator_norm` | 100; support |
| `KomorebiPaperVII.Leakage.commutator_leakage_bound` | 106; support |
| `KomorebiPaperVII.Leakage.exact_symmetry_zero_leakage` | 114; support |
| `KomorebiPaperVII.Leakage.unitary_corner_norm` | 122; support |
| `KomorebiPaperVII.Leakage.capped_commutator_leakage_bound` | 133; support |
| `KomorebiPaperVII.Leakage.projection_commutator_norm_le` | 141; support |
| `KomorebiPaperVII.Leakage.perturbation_leakage_bound` | 151; support |
| `KomorebiPaperVII.Leakage.matrix_commutator_leakage_bound` | 167; Core 5.2 |

### 10.14 LocalProjectedCurvature: 6 theorem declarations

Source: `formalization/LocalProjectedCurvature.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.LocalCurvature.projector_jet` | 25; support |
| `KomorebiPaperVII.LocalCurvature.projector_differential_sandwich` | 33; support |

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.LocalCurvature.section_jet` | 38; support |
| `KomorebiPaperVII.LocalCurvature.nabla_derivative` | 47; support |
| `KomorebiPaperVII.LocalCurvature.curvature_expansion` | 60; support |
| `KomorebiPaperVII.LocalCurvature.projected_connection_curvature` | 79; support |

### 10.15 LowModeConvergence: 2 theorem declarations

Source: `formalization/LowModeConvergence.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.LowModeConvergence.sine_square_error` | 15; support |
| `KomorebiPaperVII.LowModeConvergence.low_mode_error` | 32; Core 11.1 |

### 10.16 ManifoldProjectedCurvature: 17 theorem declarations

Source: `formalization/ManifoldProjectedCurvature.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.ManifoldCurvature.derivative_in_chart` | 28; support |
| `KomorebiPaperVII.ManifoldCurvature.differentiable_in_chart` | 34; support |
| `KomorebiPaperVII.ManifoldCurvature.smooth_in_chart` | 39; support |
| `KomorebiPaperVII.ManifoldCurvature.derivative_clm_apply` | 49; support |
| `KomorebiPaperVII.ManifoldCurvature.chartField_self` | 65; support |
| `KomorebiPaperVII.ManifoldCurvature.chartField_differentiable` | 74; support |
| `KomorebiPaperVII.ManifoldCurvature.bracket_in_chart` | 80; support |
| `KomorebiPaperVII.ManifoldCurvature.directional_chart_pullback` | 91; support |
| `KomorebiPaperVII.ManifoldCurvature.second_directional_in_chart` | 115; support |
| `KomorebiPaperVII.ManifoldCurvature.derivative_lieBracket` | 132; support |
| `KomorebiPaperVII.ManifoldCurvature.projector_jet` | 150; support |
| `KomorebiPaperVII.ManifoldCurvature.projector_differential_sandwich` | 161; support |
| `KomorebiPaperVII.ManifoldCurvature.section_jet` | 167; support |
| `KomorebiPaperVII.ManifoldCurvature.nabla_derivative` | 178; support |
| `KomorebiPaperVII.ManifoldCurvature.curvature_expansion` | 191; support |
| `KomorebiPaperVII.ManifoldCurvature.projected_connection_curvature` | 214; Core 6.4 |
| `KomorebiPaperVII.ManifoldCurvature.curvature_is_tensorial` | 236; support |

### 10.17 MovingFrames: 9 theorem declarations

Source: `formalization/MovingFrames.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.MovingFrames.matrix_product_derivative` | 15; support |
| `KomorebiPaperVII.MovingFrames.matrix_vector_derivative` | 23; support |
| `KomorebiPaperVII.MovingFrames.adjoint_derivative` | 32; support |
| `KomorebiPaperVII.MovingFrames.differentiated_unitarity` | 37; support |
| `KomorebiPaperVII.MovingFrames.frame_velocity_skew` | 52; support |
| `KomorebiPaperVII.MovingFrames.connection_hermitian` | 60; support |
| `KomorebiPaperVII.MovingFrames.effective_hamiltonian_hermitian` | 72; support |
| `KomorebiPaperVII.MovingFrames.moving_frame_equation` | 83; support |
| `KomorebiPaperVII.MovingFrames.moving_frame_coordinates` | 110; Core 6.1 |

### 10.18 ProjectedBundleCompletion: 12 theorem declarations

Source: `formalization/ProjectedBundleCompletion.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.BundleCompletion.total_domain_open` | 25; support |
| `KomorebiPaperVII.BundleCompletion.localProduct_overlap` | 31; Core 6.4 |
| `KomorebiPaperVII.BundleCompletion.smooth_section_iff` | 40; Core 6.4 |
| `KomorebiPaperVII.BundleCompletion.local_connections_gauge` | 57; Core 6.4 |
| `KomorebiPaperVII.BundleCompletion.curvatureForm_self` | 73; support |
| `KomorebiPaperVII.BundleCompletion.curvatureForm_swap` | 76; support |
| `KomorebiPaperVII.BundleCompletion.curvatureForm_add_left` | 81; support |
| `KomorebiPaperVII.BundleCompletion.curvatureForm_smul_left` | 86; support |
| `KomorebiPaperVII.BundleCompletion.curvatureForm_in_range` | 90; support |
| `KomorebiPaperVII.BundleCompletion.fiberCurvature_coe` | 103; support |
| `KomorebiPaperVII.BundleCompletion.constant_projector_flat` | 108; support |
| `KomorebiPaperVII.BundleCompletion.smooth_section_chart_independent` | 112; support |

### 10.19 ProjectedCurvature: 20 theorem declarations

Source: `formalization/ProjectedCurvature.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Curvature.jet_sandwich_zero` | 22; support |
| `KomorebiPaperVII.Curvature.nabla_in_range` | 47; support |
| `KomorebiPaperVII.Curvature.projector_jet` | 52; support |
| `KomorebiPaperVII.Curvature.projector_differential_sandwich` | 60; support |
| `KomorebiPaperVII.Curvature.section_jet` | 65; support |

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Curvature.nabla_derivative` | 74; support |
| `KomorebiPaperVII.Curvature.curvature_expansion` | 87; support |
| `KomorebiPaperVII.Curvature.projected_connection_curvature` | 106; support |
| `KomorebiPaperVII.Curvature.curvatureForm_alternating` | 123; support |
| `KomorebiPaperVII.Curvature.curvatureForm_antisymmetric` | 126; support |
| `KomorebiPaperVII.Curvature.curvatureForm_left_range` | 131; support |
| `KomorebiPaperVII.Curvature.curvatureForm_right_range` | 136; support |
| `KomorebiPaperVII.Curvature.curvatureForm_pullback` | 142; support |
| `KomorebiPaperVII.Curvature.nabla_scalar_leibniz` | 149; support |
| `KomorebiPaperVII.Curvature.nabla_add_vectorfields` | 157; support |
| `KomorebiPaperVII.Curvature.nabla_smul_vectorfield` | 162; support |
| `KomorebiPaperVII.Curvature.curvatureForm_add_left` | 167; support |
| `KomorebiPaperVII.Curvature.curvatureForm_add_right` | 172; support |
| `KomorebiPaperVII.Curvature.curvatureForm_smul_left` | 177; support |
| `KomorebiPaperVII.Curvature.curvatureForm_smul_right` | 181; support |

### 10.20 QuantumPacketCore: 19 theorem declarations

Source: `formalization/QuantumPacketCore.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.PacketFamily.idempotent` | 32; support |
| `KomorebiPaperVII.PacketFamily.reconstruct` | 38; support |
| `KomorebiPaperVII.PacketFamily.compose_blocks` | 41; support |
| `KomorebiPaperVII.PacketFamily.circuit_path_expansion` | 63; Core 4.1 |
| `KomorebiPaperVII.PacketFamily.circuit_reconstruction` | 70; Core 4.1 |
| `KomorebiPaperVII.PacketFamily.symmetry_no_transfer` | 76; support |
| `KomorebiPaperVII.PacketFamily.symmetry_diagonal` | 80; support |
| `KomorebiPaperVII.PacketFamily.dephase_idempotent` | 90; support |
| `KomorebiPaperVII.PacketFamily.adjoint_block` | 114; support |
| `KomorebiPaperVII.PacketFamily.unitarity_columns` | 119; Core 4.2 |
| `KomorebiPaperVII.PacketFamily.unitarity_rows` | 134; Core 4.2 |
| `KomorebiPaperVII.PacketFamily.symmetry_exponential_commutes` | 156; support |
| `KomorebiPaperVII.PacketFamily.symmetry_exponential_diagonal` | 163; Core 5.1 |
| `KomorebiPaperVII.PacketFamily.symmetry_exponential_no_transfer` | 168; Core 5.1 |
| `KomorebiPaperVII.matrix_unitarity_columns` | 181; Core 4.2 |
| `KomorebiPaperVII.matrix_unitarity_rows` | 188; Core 4.2 |
| `KomorebiPaperVII.dephase_trace_duality` | 195; support |
| `KomorebiPaperVII.measurement_invariance` | 208; Core 7.1 |
| `KomorebiPaperVII.dephase_trace_preserving` | 213; Core 7.1 |

### 10.21 QuantumStateBridge: 9 theorem declarations

Source: `formalization/QuantumStateBridge.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.KnillLaflamme.outer_polarization` | 21; support |
| `KomorebiPaperVII.KnillLaflamme.linearMap_eq_of_pure` | 30; support |
| `KomorebiPaperVII.KnillLaflamme.sandwich_pure` | 64; support |
| `KomorebiPaperVII.KnillLaflamme.fixes_positive_of_density` | 70; support |
| `KomorebiPaperVII.KnillLaflamme.fixes_operators_of_density` | 100; support |
| `KomorebiPaperVII.KnillLaflamme.density_corrects_iff_operators` | 119; support |
| `KomorebiPaperVII.KnillLaflamme.state_correctable_iff_gram` | 139; Core 8.1 |
| `KomorebiPaperVII.KnillLaflamme.amplifiedNoise_block` | 157; support |
| `KomorebiPaperVII.KnillLaflamme.recovery_with_reference` | 164; Core 8.1 |

### 10.22 SchurFeshbach: 4 theorem declarations

Source: `formalization/SchurFeshbach.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.SchurFeshbach.resolvent_blocks` | 20; support |
| `KomorebiPaperVII.SchurFeshbach.projected_resolvent` | 27; Core 9.1 |
| `KomorebiPaperVII.SchurFeshbach.schur_invertible` | 46; Core 9.1 |
| `KomorebiPaperVII.SchurFeshbach.eliminated_invertible_full_singular` | 59; support |

### 10.23 SeedOrbit: 34 theorem declarations

Source: `formalization/SeedOrbit.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.SeedOrbit.mem_orbit_iff` | 31; support |
| `KomorebiPaperVII.SeedOrbit.mem_orbit_iff_rows` | 35; support |
| `KomorebiPaperVII.SeedOrbit.row_dimension` | 54; support |
| `KomorebiPaperVII.SeedOrbit.orbit_dimension` | 58; support |
| `KomorebiPaperVII.SeedOrbit.orbit_span` | 63; support |
| `KomorebiPaperVII.SeedOrbit.span_orbit_dimension` | 68; Core 2.1 |
| `KomorebiPaperVII.SeedOrbit.cyclic_iff_full_rank` | 73; support |
| `KomorebiPaperVII.SeedOrbit.cyclic_multiplicity_bound` | 82; support |
| `KomorebiPaperVII.SeedOrbit.rowOrbit_mem` | 93; support |
| `KomorebiPaperVII.SeedOrbit.rowOrbit_dimension` | 112; support |
| `KomorebiPaperVII.SeedOrbit.rowOrbit_full` | 117; support |
| `KomorebiPaperVII.SeedOrbit.stacked_action` | 130; support |
| `KomorebiPaperVII.SeedOrbit.generates_iff_rowOrbit` | 135; support |

| Named declaration | Source line |
|---|---|
| KomorebiPaperVII.SeedOrbit.generates_iff_rank | 148; support |
| KomorebiPaperVII.SeedOrbit.seed_count_lower | 152; support |
| KomorebiPaperVII.SeedOrbit.exists_full_column_rank | 158; support |
| KomorebiPaperVII.SeedOrbit.exists_generating_seeds_iff | 173; support |
| KomorebiPaperVII.SeedOrbit.block_generates_iff | 195; support |
| KomorebiPaperVII.SeedOrbit.exists_block_seeds_iff | 210; support |
| KomorebiPaperVII.SeedOrbit.seed_formula_le_iff | 229; support |
| KomorebiPaperVII.SeedOrbit.quantum_seed_rank | 239; Core 2.2 |
| KomorebiPaperVII.SeedOrbit.local_tensor_action | 261; support |
| KomorebiPaperVII.SeedOrbit.product_decomposition_rank_bound | 272; support |
| KomorebiPaperVII.SeedOrbit.product_decomposition_at_rank | 289; support |
| KomorebiPaperVII.SeedOrbit.product_length_minimum | 298; support |
| KomorebiPaperVII.SeedOrbit.schmidt_rank_eq_matrix_rank | 308; support |
| KomorebiPaperVII.SeedOrbit.local_orbit_is_tensor_span | 319; support |
| KomorebiPaperVII.SeedOrbit.local_orbit_schmidt_dimension | 328; support |
| KomorebiPaperVII.SeedOrbit.partial_trace_gram | 336; support |
| KomorebiPaperVII.SeedOrbit.reduced_rank_eq_schmidt | 343; support |
| KomorebiPaperVII.SeedOrbit.reduced_positive | 348; support |
| KomorebiPaperVII.SeedOrbit.reduced_full_support_iff | 352; support |
| KomorebiPaperVII.SeedOrbit.local_orbit_full_iff | 357; support |
| KomorebiPaperVII.SeedOrbit.local_orbit_reduced_support | 364; Core 2.3 |

### 10.24 SyndromeRecovery: 18 theorem declarations

Source: formalization/SyndromeRecovery.lean.

| Named declaration | Source line |
|---|---|
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.packet_selfAdjoint | 37; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.packet_mul | 41; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.total_projection | 53; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.complement_projection | 61; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.total_error | 64; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.complement_error | 68; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.error_adjoint_complement | 71; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.recoveryKraus_complete | 84; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_eq_kraus | 92; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_add | 97; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_cross_error | 103; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_smul | 129; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_weighted_noise | 138; support |
| KomorebiPaperVII.Recovery.OrthogonalSyndromes.decoder_error_superposit ion | 149; support |
| KomorebiPaperVII.Recovery.recovery_positive | 180; support |
| KomorebiPaperVII.Recovery.recovery_trace_preserving | 186; support |

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.Recovery.recovery_complete_positivity` | 197; support |
| `KomorebiPaperVII.Recovery.recovery_density_matrix` | 212; support |

### 10.25 TensorRefinement: 11 theorem declarations

Source: `formalization/TensorRefinement.lean`.

| Named declaration | Source line |
|---|---|
| `KomorebiPaperVII.TensorRefinement.tensor_mul` | 20; support |
| `KomorebiPaperVII.TensorRefinement.tensor_one` | 30; support |
| `KomorebiPaperVII.TensorRefinement.tensor_sum` | 42; support |
| `KomorebiPaperVII.TensorRefinement.tensor_adjoint` | 54; support |
| `KomorebiPaperVII.TensorRefinement.fine_mul` | 67; support |
| `KomorebiPaperVII.TensorRefinement.fine_complete` | 86; support |
| `KomorebiPaperVII.TensorRefinement.fine_selfAdjoint` | 94; support |
| `KomorebiPaperVII.TensorRefinement.coarse_mul` | 108; support |
| `KomorebiPaperVII.TensorRefinement.coarse_complete` | 126; support |
| `KomorebiPaperVII.TensorRefinement.coarse_selfAdjoint` | 133; support |
| `KomorebiPaperVII.TensorRefinement.tensor_polyphase_refinement` | 139; Core 3.2 |

# 11 Module dependencies, source identities, and pins

## 11.1 Current local module graph

The dependencies below are read from both public imports and import-all commands. Duplicate imports count once. Import-all is significant in this Lean module edition because private implementation details can be needed by downstream proofs. A module with no local import still imports the pinned Mathlib files named in its source.

| Module | Direct current local imports |
|---|---|
| `CanonicalConnection` | Mathlib only |
| `ComputationalSeed` | Mathlib only |
| `ConstraintAudit` | Mathlib only |
| `CyclicProjectors` | Mathlib only |
| `ErrorSpanRecovery` | `KnillLaflammeNecessity`; `KnillLaflammeSufficiency`; `QuantumStateBridge`; `SyndromeRecovery` |
| `EuclideanTransfer` | Mathlib only |
| `GlobalProjectedConnection` | `GlobalRangeBundle`; `LocalProjectedCurvature`; `ProjectedCurvature` |
| `GlobalRangeBundle` | Mathlib only |
| `KnillLaflammeExamples` | `ErrorSpanRecovery`; `KnillLaflammeNecessity`; `KnillLaflammeSufficiency`; `QuantumStateBridge` |
| `KnillLaflammeNecessity` | `KnillLaflammeSufficiency` |
| `KnillLaflammeSufficiency` | `SyndromeRecovery` |
| `KrausChannels` | Mathlib only |
| `LeakageBound` | Mathlib only |
| `LocalProjectedCurvature` | `ProjectedCurvature` |
| `LowModeConvergence` | Mathlib only |
| `ManifoldProjectedCurvature` | `GlobalProjectedConnection`; `ProjectedCurvature` |
| `MovingFrames` | Mathlib only |
| `ProjectedBundleCompletion` | `ManifoldProjectedCurvature` |
| `ProjectedCurvature` | Mathlib only |
| `QuantumPacketCore` | Mathlib only |
| `QuantumStateBridge` | `KnillLaflammeNecessity`; `KnillLaflammeSufficiency` |
| `SchurFeshbach` | Mathlib only |
| `SeedOrbit` | Mathlib only |
| `SyndromeRecovery` | Mathlib only |
| `TensorRefinement` | Mathlib only |

## 11.2 Current source SHA-256 identities

### CanonicalConnection

`f2b433bdd432e18c9cb7af45403a1adcdd0426f5e9115d098317744e4b0fc3ed`

### ComputationalSeed

`6b92535db98ff199d4b5fd3307c2c3935d5fe6c769761eae9fe4af71bb64c6c4`

### ConstraintAudit

`e00fe71eb73e8ed8a652839d4f927e282784001d6c454f8cb2fe66f866de0371`

### CyclicProjectors

`f0f88121acd4fc2f270de7e0ad7ca8d9e273945987a869935df670248e5d206b`

### ErrorSpanRecovery

`f8a02ecda26d3a7d55378c06599597ada186b801750af09be0bbb2c3ae9191ed`

### EuclideanTransfer

`5a259e9245571bf84048a3ff2f7d332cff29c8c2c9b3fcac515dceb43f594bad`

### GlobalProjectedConnection

`ec618cd64d17d1bca4dee9ea0fae3c7f943c3347f4b1c8be063f3dd8517e0beb`

### GlobalRangeBundle

`cbd9b611d6160a91a76332cad47d246f89cd82f02d38854089bf7f4eaa988b33`

### KnillLaflammeExamples

`52f6ea5ccfc664ba41150c026015bec8a99d9eeb82880206b26456dee4abae05`

### KnillLaflammeNecessity

`ff7b077fc8d55474c3a3b8ad6ae1017f4082e16dd9282ca07ecc5240f759c65d`

### KnillLaflammeSufficiency

`3b71fbe77e55d8f603580678ada7ce4fd6303e8e1f1f5e028afb68c6bfc2e017`

### KrausChannels

`915ebc9806b5f47ec8f958a72bfafe02723c5dcc47fceccdade1bcd3579e078f`

### LeakageBound

`859f23f52f1274d485c2496828938cf48a8b5bf5a574264a7f04107b5b089887`

### LocalProjectedCurvature

`6f59e61c3b60fca127a7cf9fdce369e26b421e2f20843c263201019cdf2af1c0`

### LowModeConvergence

`7e077b24ccdfb970b349171d55551f39127a4556b2e2d247c47f6a4bc0774595`

### ManifoldProjectedCurvature

`9803d99d975303179ccecbbfae1133bcab47496cee452cf3e130f3c4870a1e12`

### MovingFrames

`8961ac05b66911ad82c84bc49ade3cac6eac2a84728898cc86a8286599f0ddef`

### ProjectedBundleCompletion

`29afe46959d4538fc2833de8e014faf8be2203f811654796847d1b7597868d77`

### ProjectedCurvature

`ad7b8cd20af860c3f455874c0009b3d18f40a5fe937531cd6798007406316686`

### QuantumPacketCore

`92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`

### QuantumStateBridge

`b3a76f530fb11075d5494f45a94d102c9084125e291c2bcd9ffa5210f6e8bdb2`

**SchurFeshbach**

`2ce60c9300b85ff06064d296cdf773f7cf9d2e0eafb7acbda15973fe851bb479`

**SeedOrbit**

`0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`

**SyndromeRecovery**

`23a176970c7adb9e995005d50722eebf953889147802f35ea9024b0081d6af84`

**TensorRefinement**

`b0587b32f55d50125790345695b777786d23e3f46141e7056049d3ef5a11e0f2`

### 11.3 Pinned compiler and dependency revisions

Compiler: `leanprover/lean4:v4.34.0-rc2`. Saved runtime commit: `6a10ac8c22beadecabdbb0919c2b50214762f91d`. The following are the nine manifest packages; replay should use the locked revisions, including inherited dependencies.

| Package | Locked revision |
|---|---|
| mathlib | `aeb72f1e9981b6d35b426b16dca7759be3e7ba06` |
| plausible | `d9598f07b1bc701f1e3aae163d2681c1fd978793` |
| LeanSearchClient | `ba67e212be1197b84c1f1f6299488a10a3002713` |
| importGraph | `d8823026ac7ef130c253089d95685f9877b95323` |
| proofwidgets | `a8acbfd87375ff4abe14ce09db5b7664d383bc7f` |
| aesop | `18889deb9e83ea7420ef51c160d6f88552e744e3` |
| Qq | `507746ab8f4b643ccdacb2ec4cdb5853fa9f8ab3` |
| batteries | `4cac2177c37f5530c4da76aa8e4307f3fc9e4dcb` |
| Cli | `ab3a82db9fea14cf0fd7f5a2de650f4b534640af` |

## 12 Exact excerpt register

Each excerpt is a contiguous block of the unchanged source, retaining its full declaration and proof. The printed code uses explicit font fallback only where the monospaced font lacks a glyph. The corresponding `.lean.txt` file preserves raw UTF-8, without editorial substitutions. The source and excerpt hashes below bind the printed selection to its original context. Module-level assumptions remain in force when an excerpt is read; the teaching chapters state the relevant type classes and hypotheses.

### row_equiv

Source: `formalization/SeedOrbit.lean`.

Lines 45–52; declaration `orbitRowEquiv`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `a4d1d840bdcebbbffc42ae57380b479bc57d2afe07de79b1fe9e34bdda086c28`.

### orbit_dimension

Source: `formalization/SeedOrbit.lean`.

Lines 68–71; declaration `span_orbit_dimension`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `365ce586b2f58c4a3574bdc7af540baa1094dd028e25cd712a1334bb6782eb24`.

### cyclic_rank

Source: `formalization/SeedOrbit.lean`.

Lines 73–80; declaration `cyclic_iff_full_rank`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `f82dfbcc44084af989f282f53c4380f8b99bd21b2ced9722c556a65551ab7fdc`.

### seed_generate

Source: `formalization/SeedOrbit.lean`.

Lines 127–128; declaration `Generates`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `f5f2e4255c8ba1ace030b5315a2b6be0db3fc24fe4beda857449e94a5b41b6de`.

### stack_rank

Source: `formalization/SeedOrbit.lean`.

Lines 148–150; declaration `generates_iff_rank`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `f490fd86582b597c2a514ab1effe39cab73d59a96ca7a6b9923d52eb8c02702c`.

### full_column

Source: `formalization/SeedOrbit.lean`.

Lines 158–171; declaration `exists_full_column_rank`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `63d1eecf433f1ddc3dbfc779101bca490c43fcc6709bfa193f2c7e5ee31ee615`.

### seed_minimum

Source: `formalization/SeedOrbit.lean`.

Lines 239–246; declaration `quantum_seed_rank`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `89ee9cb7e0961e27954fe763e202dd0c3f44282f2b5fa3cc2abbf7bc71b316c5`.

### schmidt_definition

Source: `formalization/SeedOrbit.lean`.

Lines 303–306; declaration `schmidtRank`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `1279ef8ea57e64959c0d7d67193ccbb143617830b9007b93e5aae3a6de863f42`.

### schmidt_minimum

Source: `formalization/SeedOrbit.lean`.

Lines 298–300; declaration `product_length_minimum`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `435e38531c7e19906f0ce32c7a69346a9990726ce7d9e697e8b6443d9f95942c`.

### local_action

Source: `formalization/SeedOrbit.lean`.

Lines 261–265; declaration `local_tensor_action`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `8130668bea5e0e3ab38489f1a45a4a7b7d0593996ab788615ef7bbc36ed52ab8`.

### reduced_support

Source: `formalization/SeedOrbit.lean`.

Lines 364–366; declaration `local_orbit_reduced_support`.

Source SHA-256: `0b1da8c7e74ccc7bbca8e2b7c0c26bce01bc95d4089616ba95c1e4fe2f147773`.

Excerpt SHA-256: `147a14439c7983ad43f62238f014efeebb80b403a15160f3c8a64c23af1bdc6d`.

### seed_basis

Source: `formalization/ComputationalSeed.lean`.

Lines 80–82; declaration `circuit_seed_basis`.

Source SHA-256: `6b92535db98ff199d4b5fd3307c2c3935d5fe6c769761eae9fe4af71bb64c6c4`.

Excerpt SHA-256: `e228b9b252604336965a67975ccbebbe2c014dadc8da35b9e38f9457fad20162`.

### seed_translation

Source: `formalization/ComputationalSeed.lean`.

Lines 72–77; declaration `circuit_eq_translation`.

Source SHA-256: `6b92535db98ff199d4b5fd3307c2c3935d5fe6c769761eae9fe4af71bb64c6c4`.

Excerpt SHA-256: `42c2842952870bb25e00b99c1d316542ccb39edcc35b9bf5282899c130919b8c`.

### cyclic_character

Source: `formalization/CyclicProjectors.lean`.

Lines 22–26; declaration `character_sum`.

Source SHA-256: `f0f88121acd4fc2f270de7e0ad7ca8d9e273945987a869935df670248e5d206b`.

Excerpt SHA-256: `6182ca8cbfb31865af273e0554bd4027e66efedb0195c6e5548ff6041df9fbad`.

### cyclic_mul

Source: `formalization/CyclicProjectors.lean`.

Lines 44–58; declaration `packet_mul`.

Source SHA-256: `f0f88121acd4fc2f270de7e0ad7ca8d9e273945987a869935df670248e5d206b`.

Excerpt SHA-256: `5d5eb96a4f93624594bcc443e22a1fd3b50078f6219ca12787f9492f83e149f5`.

### cyclic_matrix

Source: `formalization/CyclicProjectors.lean`.

Lines 157–170; declaration `finite_cyclic_projectors`.

Source SHA-256: `f0f88121acd4fc2f270de7e0ad7ca8d9e273945987a869935df670248e5d206b`.

Excerpt SHA-256: `314f68975d510c4ac2dbf381e55d004877797f7e011199f51b0743c4231fe886`.

### tensor_mul

Source: `formalization/TensorRefinement.lean`.

Lines 20–27; declaration `tensor_mul`.

Source SHA-256: `b0587b32f55d50125790345695b777786d23e3f46141e7056049d3ef5a11e0f2`.

Excerpt SHA-256: `840d1c4953c639cdfb51054f3e6524dd7e5e58c9f56328e253b43677ef4950d9`.

### tensor_refinement

Source: `formalization/TensorRefinement.lean`.

Lines 139–154; declaration `tensor_polyphase_refinement`.

Source SHA-256: `b0587b32f55d50125790345695b777786d23e3f46141e7056049d3ef5a11e0f2`.

Excerpt SHA-256: `2f58f8936bffee8ed36834f4618bcb5de3ef8454cffcd992cf9bd226fe21bb07`.

### packet_structure

Source: `formalization/QuantumPacketCore.lean`.

Lines 22–25; declaration `PacketFamily`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `94b93d351a97d973bf990a4a8d1fcd4a8d04e12ae60192ab2eaf58fd05722bde`.

### compose_blocks

Source: `formalization/QuantumPacketCore.lean`.

Lines 41–50; declaration `compose_blocks`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `d62cbe9447e98700c0387ade81a7695945d771ac4aad6dc2e445fb925825dec1`.

### circuit_path

Source: `formalization/QuantumPacketCore.lean`.

Lines 63–68; declaration `circuit_path_expansion`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `8a7447d90ccb095429646dbfcb867b148a3807779708cc2e65b183c3691fc338`.

### unitarity_columns

Source: `formalization/QuantumPacketCore.lean`.

Lines 119–131; declaration `unitarity_columns`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `54be9086567756fa2f7a0f2136a49ed2b27eb5289098ad7171c6e4db4ca7b8ba`.

### symmetry_exp

Source: `formalization/QuantumPacketCore.lean`.

Lines 168–171; declaration `symmetry_exponential_no_transfer`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `39905e80eae8288643f906f8bce86131420f979f90a22972af30af14907e2fdb`.

### measurement

Source: `formalization/QuantumPacketCore.lean`.

Lines 208–211; declaration `measurement_invariance`.

Source SHA-256: `92e49bb023877ed1f1c2bb34968aa81ee7724fa3a8e1801a831cfc70f1de3595`.

Excerpt SHA-256: `d98f2c05feb20e8ec9edc53e090c36e404cc45977db5bf30b82abb62d4b2cad2`.

### transport_derivative

Source: `formalization/LeakageBound.lean`.

Lines 31–38; declaration `transported_derivative`.

Source SHA-256: `859f23f52f1274d485c2496828938cf48a8b5bf5a574264a7f04107b5b089887`.

Excerpt SHA-256: `4f6cf06917d31eef4a0cb83ee091863c72390050b998c3ec82f81ed4715b0536`.

### transport_lipschitz

Source: `formalization/LeakageBound.lean`.

Lines 46–54; declaration `transported_lipschitz`.

Source SHA-256: `859f23f52f1274d485c2496828938cf48a8b5bf5a574264a7f04107b5b089887`.

Excerpt SHA-256: `f7a3612f65196115dc1c6dc0b6721a1a057db6f39fedd361e43acbe872a31cf7`.

### leakage_matrix

Source: `formalization/LeakageBound.lean`.

Lines 167–171; declaration `matrix_commutator_leakage_bound`.

Source SHA-256: `859f23f52f1274d485c2496828938cf48a8b5bf5a574264a7f04107b5b089887`.

Excerpt SHA-256: `2da717dabf6f741c4b0d5d435b27898cd4360e6a75bd401e9b9ca08bbea787b1`.

### leakage_perturbation

Source: `formalization/LeakageBound.lean`.

Lines 151–164; declaration `perturbation_leakage_bound`.

Source SHA-256: `859f23f52f1274d485c2496828938cf48a8b5bf5a574264a7f04107b5b089887`.

Excerpt SHA-256: `6c29b54826e1a17a70cc88a993747995a66d98bc4de068407fe606ab14f39e84`.

### frame_product

Source: `formalization/MovingFrames.lean`.

Lines 23–29; declaration `matrix_vector_derivative`.

Source SHA-256: `8961ac05b66911ad82c84bc49ade3cac6eac2a84728898cc86a8286599f0ddef`.

Excerpt SHA-256: `b541e7998198257db7256977da20097d88c1093f7a302793f133b501727fb886`.

### moving_coordinates

Source: `formalization/MovingFrames.lean`.

Lines 110–132; declaration `moving_frame_coordinates`.

Source SHA-256: `8961ac05b66911ad82c84bc49ade3cac6eac2a84728898cc86a8286599f0ddef`.

Excerpt SHA-256: `a54d0ad271dcb2a4a32e0800cb13e680e61dc3f6fa699184ba31ae9c5d81b095`.

### connection_jet

Source: `formalization/CanonicalConnection.lean`.

Lines 78–95; declaration `differentiated_orthogonality`.

Source SHA-256: `f2b433bdd432e18c9cb7af45403a1adcdd0426f5e9115d098317744e4b0fc3ed`.

Excerpt SHA-256: `eb57f9d5f332db8c25c84c3e5a6bb54c1cd10454626ef4f3d200a3c3878d1c2e`.

### canonical_connection

Source: `formalization/CanonicalConnection.lean`.

Lines 113–131; declaration `canonical_connection_of_hasDerivAt`.

Source SHA-256: `f2b433bdd432e18c9cb7af45403a1adcdd0426f5e9115d098317744e4b0fc3ed`.

Excerpt SHA-256: `ee12fd06d9eaa15681457221c5d4aca3d1aaff2b2487d0b6389cedebd82bc40e`.

### sandwich_zero

Source: `formalization/ProjectedCurvature.lean`.

Lines 22–26; declaration `jet_sandwich_zero`.

Source SHA-256: `ad7b8cd20af860c3f455874c0009b3d18f40a5fe937531cd6798007406316686`.

Excerpt SHA-256: `7dc40b766cb348d7f859e22f3264fe7832a0243c2573b3c72b2e0670f962ae77`.

### local_curvature

Source: `formalization/LocalProjectedCurvature.lean`.

Lines 79–94; declaration `projected_connection_curvature`.

Source SHA-256: `6f59e61c3b60fca127a7cf9fdce369e26b421e2f20843c263201019cdf2af1c0`.

Excerpt SHA-256: `536eabe9e44ef8fea3518c58157a34c7e2485e4bd4cd031aecced8c419426013`.

### range_transport

Source: `formalization/GlobalRangeBundle.lean`.

Lines 43–43; declaration `transport`.

Source SHA-256: `cbd9b611d6160a91a76332cad47d246f89cd82f02d38854089bf7f4eaa988b33`.

Excerpt SHA-256: `dfd3703c4861cefd45738415feb43fd6d139ae903e22fcfa54a52f3ae3166b59`.

### range_intertwines

Source: `formalization/GlobalRangeBundle.lean`.

Lines 49–54; declaration `transport_intertwines`.

Source SHA-256: `cbd9b611d6160a91a76332cad47d246f89cd82f02d38854089bf7f4eaa988b33`.

Excerpt SHA-256: `270a82bb94c15f6815e19aacca566c805b4c02366ca5aa7f0af3a21edeff6ea7`.

### range_product

Source: `formalization/GlobalRangeBundle.lean`.

Lines 180–209; declaration `localProduct`.

Source SHA-256: `cbd9b611d6160a91a76332cad47d246f89cd82f02d38854089bf7f4eaa988b33`.

Excerpt SHA-256: `1f6345cfbb46c8c9cfd05c107d4c065ff4203c2f6579ab9ad3f77f677446c0a7`.

### range_atlas

Source: `formalization/GlobalRangeBundle.lean`.

Lines 241–252; declaration `smooth_range_bundle_atlas`.

Source SHA-256: `cbd9b611d6160a91a76332cad47d246f89cd82f02d38854089bf7f4eaa988b33`.

Excerpt SHA-256: `8e70b5873ddcf4e12a7c8f010839e666e3eed7810e9e45ac18fe8694cf61d9fd`.

### global_nabla

Source: `formalization/GlobalProjectedConnection.lean`.

Lines 29–30; declaration `nabla`.

Source SHA-256: `ec618cd64d17d1bca4dee9ea0fae3c7f943c3347f4b1c8be063f3dd8517e0beb`.

Excerpt SHA-256: `21fd6220b421762dd36a043194975b4cb173eb8ecba9904f1e82558148f56361`.

### global_leibniz

Source: `formalization/GlobalProjectedConnection.lean`.

Lines 59–63; declaration `nabla_leibniz`.

Source SHA-256: `ec618cd64d17d1bca4dee9ea0fae3c7f943c3347f4b1c8be063f3dd8517e0beb`.

Excerpt SHA-256: `7c4fed39fa233c060d4c3cb834aec746aa20118fac168fe896e2b97d1b71e20e`.

### global_glue

Source: `formalization/GlobalProjectedConnection.lean`.

Lines 115–124; declaration `local_connections_glue`.

Source SHA-256: `ec618cd64d17d1bca4dee9ea0fae3c7f943c3347f4b1c8be063f3dd8517e0beb`.

Excerpt SHA-256: `44e2c6deb0f447d93e739a761bebd05a7202663add66936ed4ca8b04f8140f56`.

### manifold_curvature

Source: `formalization/ManifoldProjectedCurvature.lean`.

Lines 214–232; declaration `projected_connection_curvature`.

Source SHA-256: `9803d99d975303179ccecbbfae1133bcab47496cee452cf3e130f3c4870a1e12`.

Excerpt SHA-256: `b16a27faaca85a392b119d8a58b11243610f490f85808d3f503f924be9d4b759`.

### smooth_section

Source: `formalization/ProjectedBundleCompletion.lean`.

Lines 40–53; declaration `smooth_section_iff`.

Source SHA-256: `29afe46959d4538fc2833de8e014faf8be2203f811654796847d1b7597868d77`.

Excerpt SHA-256: `4d880ef0afe4f2904521de95d6987431163c41a619192455f0d4963381a109ab`.

### gauge_law

Source: `formalization/ProjectedBundleCompletion.lean`.

Lines 57–70; declaration `local_connections_gauge`.

Source SHA-256: `29afe46959d4538fc2833de8e014faf8be2203f811654796847d1b7597868d77`.

Excerpt SHA-256: `3515991be601fc80774ba245cf2fd97b415f112cf14f1303201a2f488392eca3`.

### kraus_amplify

Source: `formalization/KrausChannels.lean`.

Lines 48–56; declaration `amplification_eq_kraus`.

Source SHA-256: `915ebc9806b5f47ec8f958a72bfafe02723c5dcc47fceccdade1bcd3579e078f`.

Excerpt SHA-256: `1323a35ef1a6247fba9aa829edaebc571ab8045b4e0362a24ca12abd66386fa6`.

### kraus_cp

Source: `formalization/KrausChannels.lean`.

Lines 58–62; declaration `channel_completely_positive`.

Source SHA-256: `915ebc9806b5f47ec8f958a72bfafe02723c5dcc47fceccdade1bcd3579e078f`.

Excerpt SHA-256: `aecdfd6e1b918aac49f394badbf080146717c04ebf3d94a03f06528db544435e`.

### syndrome_structure

Source: `formalization/SyndromeRecovery.lean`.

Lines 21–27; declaration `OrthogonalSyndromes`.

Source SHA-256: `23a176970c7adb9e995005d50722eebf953889147802f35ea9024b0081d6af84`.

Excerpt SHA-256: `73f2e29a5c2b47648bf6729fa98b330f3532a0f288038c89b1388338a3042e0d`.

### syndrome_complete

Source: `formalization/SyndromeRecovery.lean`.

Lines 84–90; declaration `recoveryKraus_complete`.

Source SHA-256: `23a176970c7adb9e995005d50722eebf953889147802f35ea9024b0081d6af84`.

Excerpt SHA-256: `ee0a642c16544ee89b34db86766f682bfc4789777d83f2b7d51b749b359521e7`.

### syndrome_cross

Source: `formalization/SyndromeRecovery.lean`.

Lines 103–124; declaration `decoder_cross_error`.

Source SHA-256: `23a176970c7adb9e995005d50722eebf953889147802f35ea9024b0081d6af84`.

Excerpt SHA-256: `c5524fa7c2b23fb404c2cc2b7c66c4d1be519b0fc2c8189e0b6cd5cbb0aacb15`.

### kl_data

Source: `formalization/KnillLaflammeSufficiency.lean`.

Lines 187–193; declaration `Data`.

Source SHA-256: `3b71fbe77e55d8f603580678ada7ce4fd6303e8e1f1f5e028afb68c6bfc2e017`.

Excerpt SHA-256: `ee0fe883d0c774bf87c6bb168c1419d60e29142fc7711f195c500c9fa12187db`.

### kl_diagonal

Source: `formalization/KnillLaflammeSufficiency.lean`.

Lines 204–214; declaration `diagonal`.

Source SHA-256: `3b71fbe77e55d8f603580678ada7ce4fd6303e8e1f1f5e028afb68c6bfc2e017`.

Excerpt SHA-256: `db1af099e2586af393a0b1574fb59cc0f8464f63a93001e6a52e70d3e62db4a8`.

### kl_null

Source: `formalization/KnillLaflammeSufficiency.lean`.

Lines 107–110; declaration `zero_weight_error`.

Source SHA-256: `3b71fbe77e55d8f603580678ada7ce4fd6303e8e1f1f5e028afb68c6bfc2e017`.

Excerpt SHA-256: `062b1f1c10c1db14ed3d3fa301585f6746b2a816af2a875256e671740ef79ddc`.

### kl_corrects

Source: `formalization/KnillLaflammeSufficiency.lean`.

Lines 252–259; declaration `recovery_corrects`.

Source SHA-256: `3b71fbe77e55d8f603580678ada7ce4fd6303e8e1f1f5e028afb68c6bfc2e017`.

Excerpt SHA-256: `0edf5306e8febc4c8d0dd4bf808c41f3498f9c568687a547926941d315f33bf5`.

### kl_rigidity

Source: `formalization/KnillLaflammeNecessity.lean`.

Lines 19–45; declaration `rank_one_gram_rigidity`.

Source SHA-256: `ff7b077fc8d55474c3a3b8ad6ae1017f4082e16dd9282ca07ecc5240f759c65d`.

Excerpt SHA-256: `c7b1e822236c6453ea334c28938823c2af3318444fef3cf82ee5311d7310c0da`.

### kl_necessity

Source: `formalization/KnillLaflammeNecessity.lean`.

Lines 86–105; declaration `gram_of_recovery`.

Source SHA-256: `ff7b077fc8d55474c3a3b8ad6ae1017f4082e16dd9282ca07ecc5240f759c65d`.

Excerpt SHA-256: `b3955cdc9224b5c2af85de359794d01818749364c809e7ce3d991b9c109ad40f`.

### density_bridge

Source: `formalization/QuantumStateBridge.lean`.

Lines 119–129; declaration `density_corrects_iff_operators`.

Source SHA-256: `b3a76f530fb11075d5494f45a94d102c9084125e291c2bcd9ffa5210f6e8bdb2`.

Excerpt SHA-256: `ae811fac94c396d9ee2052588ea8668a2e69f5d24c3bcdd26560c4567b6fe95f`.

### kl_criterion

Source: `formalization/QuantumStateBridge.lean`.

Lines 139–151; declaration `state_correctable_iff_gram`.

Source SHA-256: `b3a76f530fb11075d5494f45a94d102c9084125e291c2bcd9ffa5210f6e8bdb2`.

Excerpt SHA-256: `3e7dd0d4356f6ce599db17a3d9a4049a86fb612e0bb8254114f6f5e15df70dcb`.

### kl_reference

Source: `formalization/QuantumStateBridge.lean`.

Lines 164–182; declaration `recovery_with_reference`.

Source SHA-256: `b3a76f530fb11075d5494f45a94d102c9084125e291c2bcd9ffa5210f6e8bdb2`.

Excerpt SHA-256: `e6301010a1248fffde60cbd86f25278f5615775f2ef4fc02bb5a57276b510366`.

### kl_span

Source: `formalization/ErrorSpanRecovery.lean`.

Lines 138–165; declaration `recovery_span_channel`.

Source SHA-256: `f8a02ecda26d3a7d55378c06599597ada186b801750af09be0bbb2c3ae9191ed`.

Excerpt SHA-256: `108c56b74be5789d672f77a69cf5d11fac6376476eda291ca96358ad2f9c5aba`.

### kl_family

Source: `formalization/ErrorSpanRecovery.lean`.

Lines 188–209; declaration `error_family_correctable_iff_gram`.

Source SHA-256: `f8a02ecda26d3a7d55378c06599597ada186b801750af09be0bbb2c3ae9191ed`.

Excerpt SHA-256: `5d027f08e3b3e93ee21eda17960f631aadd79cae3e6d0e47df52bdced92e4df7`.

### feshbach

Source: `formalization/SchurFeshbach.lean`.

Lines 27–44; declaration `projected_resolvent`.

Source SHA-256: `2ce60c9300b85ff06064d296cdf773f7cf9d2e0eafb7acbda15973fe851bb479`.

Excerpt SHA-256: `d84ccc733fea567da198271006256848b4afa3112df09490598de9968c00ca70`.

### feshbach_counterexample

Source: `formalization/SchurFeshbach.lean`.

Lines 59–64; declaration `eliminated_invertible_full_singular`.

Source SHA-256: `2ce60c9300b85ff06064d296cdf773f7cf9d2e0eafb7acbda15973fe851bb479`.

Excerpt SHA-256: `377aa16415eeb74cce76d96a5bc1e33ac627d32dbccdcb9465f52bb456552283`.

### euclidean_cfc

Source: `formalization/EuclideanTransfer.lean`.

Lines 39–47; declaration `transfer_cfc`.

Source SHA-256: `5a259e9245571bf84048a3ff2f7d332cff29c8c2c9b3fcac515dceb43f594bad`.

Excerpt SHA-256: `9eb0a3b8ac13e09838ab8074571b5149b2040c810140f3518039b8edb8915e61`.

### euclidean_endpoint

Source: `formalization/EuclideanTransfer.lean`.

Lines 89–96; declaration `finite_euclidean_transfer`.

Source SHA-256: `5a259e9245571bf84048a3ff2f7d332cff29c8c2c9b3fcac515dceb43f594bad`.

Excerpt SHA-256: `ee9c869877cc94941a4308d727f4d422bb8d5c13864aa4c33755d0f5a1ef3d8a`.

### low_mode

Source: `formalization/LowModeConvergence.lean`.

Lines 32–45; declaration `low_mode_error`.

Source SHA-256: `7e077b24ccdfb970b349171d55551f39127a4556b2e2d247c47f6a4bc0774595`.

Excerpt SHA-256: `7de00df6c8e15233a57e9432f25072c725e03efb58d3b6e0cfa6a72d61a0b97c`.

### constraint_kernel

Source: `formalization/ConstraintAudit.lean`.

Lines 31–34; declaration `compressed_anomaly_zero`.

Source SHA-256: `e00fe71eb73e8ed8a652839d4f927e282784001d6c454f8cb2fe66f866de0371`.

Excerpt SHA-256: `121148fa69ae880879db5578d139bcff070684810952dc73d45f9fe7106ce78d`.

### constraint_nonclosure

Source: `formalization/ConstraintAudit.lean`.

Lines 56–60; declaration `commutator_nonzero`.

Source SHA-256: `e00fe71eb73e8ed8a652839d4f927e282784001d6c454f8cb2fe66f866de0371`.

Excerpt SHA-256: `2a18c6988e67ff03d9308f041e90dc1e3713f983dc36f07f9b1f28f91454d3bd`.