



November 19, 2009

Revision 1.0

# PEX 8619 Hardware Design Checklist

## Introduction

This document is intended for systems design engineers incorporating the PEX 8619 PCI Express switch into a system hardware design. It provides a handy list of basic design checks covering schematic and printed-circuit board (PCB) layout designs. Including these checks as part of your design review can help insure that important details are not overlooked when your design is committed to hardware, thereby improving your chances for a successful bring-up. In preparation for your design review, we also recommend that you check our website, [www.plxtech.com](http://www.plxtech.com), and download the most current technical specifications, errata, and related documentation. This document supersedes and replaces previous released revisions.

## 1 Schematic Design Checks

This section includes checks on basic elements of the circuit design, including schematic symbol, power supply, configuration straps, clocks, reset, configuration serial EEPROM, I2C, JTAG, GPIO, and other signals. All power and signal balls on the device are covered.

### 1.1 Schematic Symbol

For designers using ORCAD schematic capture tools, an ORCAD symbol library is available on the PLX website at [www.plxtech.com](http://www.plxtech.com). This library symbol is pre-checked by PLX engineers, and it is also used in the design of the PEX 8619 RDK.

For designers not using the PLX-supplied schematic symbol, we highly recommend double-checking your symbol's signal ball names and numbers for accuracy before using the symbol in your schematic design.

### 1.2 Power Supply

#### 1.2.1 Regulated DC Supply Voltages

The PEX 8619 requires the following regulated DC voltages:

- ☐ VDD10: 1.0 Volts, +/- 5% - Powers digital core logic
- ☐ VDD25: 2.5 Volts, +/- 10% - Powers external I/O signals

These DC supplies can be sequenced on or off in any order. Refer to the data book for specific load current requirements.

#### 1.2.2 Filtered Analog Supply Voltages

From the VDD10 and VDD25 supplies, the following analog supply voltages are derived:

- ☐ VDD10A: 1.0 Volts, filtered from VDD10, powers PCI Express SerDes signals
- ☐ VDD25A: 2.5 Volts, filtered from VDD25, powers internal clock PLL

### 1.2.3 Power, Ground Ball Connections

Signal Name	Ball #	Signal Type	Checked	Recommendations
VDD10	F7, F11, F12, G6, G13, H6, L13, M6, M13, N7, N8, N12	CPWR	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>1.0 V Power for Core Logic (12 Balls)</b>  PEX8619 RDK Decoupling Scheme: 12 Caps 1000 pF 0201 caps at each power ball 4 Caps 0.1 uF near device 2 Caps 1uF near device
VDD10A	C7, C9, C11, G16, H3, J16, K3, L16, T8, T10, T12	APWR	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>1.0 V Power for SerDes Analog Circuits (12 Balls)</b>  Tie to VDD10. PEX8619 RDK Decoupling Scheme: 12 Caps 1000 pF 0201 caps at each power ball 4 Caps 0.1 uF near device 2 Caps 1uF near device
VDD25	F6, F13, N6, N13	I/OPWR	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>2.5V Power for I/O Logic Functions (4 Balls)</b>  PEX8619 RDK Decoupling Scheme: 4 Caps 1000 pF 0201 caps at each power ball. 2 Caps 0.1µF near device 2 Caps 1 µF near device
VDD25A	F9, J13, K6, N10	PLLWR	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>2.5V Power for PLL Circuits (4 Balls)</b>  Tie to VDD25. PEX8619 RDK Decoupling Scheme: 4 Caps 1000 pF 0201 caps at each power ball. 2 Caps 0.1µF near device 2 Caps 1 µF near device
VSS, VSS_THERMAL	A1-3, A6, A12, A18, B1, B6, B12, B18, C1, C6, C8, C10, C12, D6, D12, E6, E12, F5, F10, F14-18, G1-5, G7-12, H7-12, H16, J3, J6-12, K7-13, L3, L7-12, M7-12, M14-18, N1-5, N9, N14, P7, P13, R7, R13, T7, T9, T11, T13, U1, U7, U13, U18, V1-3, V7, V13, V17, V18	GND	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>Ground Connections (104 Balls)</b>

## 1.3 Clocks

### 1.3.1 Clock Source and Line Termination

REFCLK Source	Signal Type	Checked	Requirements
External REFCLK Clock Transmitter	External-CML	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	Frequency Tolerance: $\pm 300$ ppm, max. 33 $\Omega$ series (in-line) and 49 $\Omega$ shunt (to GND) required on each differential signal, near the clock source.

### 1.3.2 Clock Input Balls

Signal Name	Ball #	Signal Type	Checked	Recommendations
PEX_REFCLKn , PEX_REFCLKp	V10, U10	CML Input	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>100 MHz PCI Express Reference Clock input pair.</b> When Dual Clocking is enabled, these are the Spread-Spectrum Clocking (SSC) domain signals. Requires 100nF AC coupling capacitor in series with each differential signal.
PEX_REFCLKCFCn, PEX_REFCLKCFCp	A9, B9	CML Input	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>100 MHz PCI Express Constant-Frequency Clock Input Signal pair.</b> When Dual Clocking is enabled, these are the Constant-Frequency Clocking (CFC) domain signals. Requires 100nF AC coupling capacitor in series with each differential signal.  When Dual Clocking is not used, these signals can be left floating.

## 1.4 Reset

Signal Name	Ball #	Signal Type	Checked	Recommendations
PEX_PERST#	P17	I	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>PCI Express Reset</b> Used to initiate a fundamental reset. This reset is propagated to all downstream ports, except those configured as NT.
PEX_NT_RESET#	P16	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>NT Port Reset</b> Active-Low Output Used to Propagate Reset across an NT Port

## 1.5 Configuration Straps

Signal Name	Ball #	Signal Type	Checked	Recommendations
STRAP_DEBUG_SEL0#	N17	I STRAP	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>Factory Test Only</b> Tie to VDD25.
STRAP_FAST_BRINGUP#	C2	I STRAP	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>Factory Test Only</b> Tie to VDD25.
STRAP_NT_ENABLE#	N18	I STRAP	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>Enable NT Mode</b> Tie to Ground (VSS) to enable NT mode, otherwise, pull or tie to VDD25
STRAP_NT_UPSTRM_PORTSEL[3:0]	P6, R1, P2, P1	I STRAP	<b>YES</b> <input type="checkbox"/> <b>NO</b> <input type="checkbox"/> <b>UNKNOWN</b> <input type="checkbox"/>	<b>Non-Transparent Upstream Port Select Straps (4 Balls)</b> Binary value selects port number. See data book for additional details. L = Tie to Ground; H = Pull or tie to VDD25:  LLLL = Port 0 LLLH = Port 1 LLHL = Port 2 LLHH = Port 3 LHLL = Port 4 LHLH = Port 5 LHHL = Port 6 LHHH = Port 7 HLLL = Port 8 HLLH = Port 9 HLHL = Port 10 HLHH = Port 11 HHLL = Port 12 HHLH = Port 13 HHHL = Port 14 HHHH = Port 15

Signal Name	Ball #	Signal Type	Checked	Recommendations
STRAP_UPSTRM_PORTSEL[3:0]	E1, F2, F3, E2	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Upstream Port Select Straps (4 Balls)</b> Binary value selects port number. See data book for additional details. L = Tie to Ground; H = Pull or tie to VDD25: LLLL = Port 0 LLLH = Port 1 LLHL = Port 2 LLHH = Port 3 LHLL = Port 4 LHLH = Port 5 LHHL = Port 6 LHHH = Port 7 HLLL = Port 8 HLLH = Port 9 HLHL = Port 10 HLHH = Port 11 HHLL = Port 12 HHLH = Port 13 HHHL = Port 14 HHHH = Port 15
STRAP_PLL_BYPASS#	R15	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Tie to VDD25.
STRAP_PROBE_MODE#	T17	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Tie to VDD25.
STRAP_SERDES_MODE_EN#	C4	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Tie to VDD25.
STRAP_PORTCFG[3:0]	C13, B2, A4, A5	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Port Configuration Straps (4 balls)</b> Binary value selects port number. See data book for additional details. L = Tie to Ground; H = Pull or tie to VDD25: LLLL = 16 ports x1 LLLH = x4, 12 ports x1 LLHL = x4, x4, 8 ports x1 LLHH = x4, x4, x4, x1, x1, x1, x1 LHLL = x4, x4, x4, x4 LHLH = x8, 8 ports x1 LHHL = x8, x4, x1, x1, x1, x1 LHHH = x8, x8, x4 HLLL = x8, x8 All other encodings are <i>reserved</i> .
STRAP_SPARE[5,1]#	T5, T4	<b>Reserved</b>	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only (3 balls)</b> Pull to VDD25 for normal operation.

NDA CONFIDENTIAL -- kotlin-novator | vtuz vova

Signal Name	Ball #	Signal Type	Checked	Recommendations
STRAP_SPARE0#	R4	<i>Reserved</i>	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only (3 balls)</b> Do not connect this ball to board electrical paths.
STRAP_UPCFG_TIMER_EN#	U5	ISTRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Enable Up-Config Timer</b> Tie to ground to enable up-config timer.
STRAP_SMBUS_EN#	U4	ISTRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Enable SMBus</b> Tie to ground to enable SMBus, otherwise pull to VDD25
STRAP_NT_P2P_EN#	R5	ISTRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Enable Legacy Mode NT</b> Tie to ground to enable Legacy mode NT. Pull to VDD25 to enable Vista-compliant NT mode
STRAP_SSC_ISO_ENABLE#	U3	ISTRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Enable Spread-Spectrum Clocking</b> Tie to Ground (VSS) to enable spread-spectrum clock isolation, otherwise, pull high to VDD25
STRAP_TESTMODE[3:0]	U17, V16, V15, V14	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only (4 balls)</b> Pull high to VDD25 for normal operation.
STRAP_RESERVED16	D14	I STRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Reserved</b> Connect this ball to Ground (VSS).
STRAP_RESERVED17#	F1	ISTRAP	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Pull high to VDD25 for normal operation.

## 1.6 PCI Express Interface

Signal Name	Ball #	Signal Type	Checked	Recommendations
PEX_LANE_GOOD[15:0]#	T2, T1, P3, R2, E5, E13, A13, B3, E16, D17, D18, B17, U15, U16, T14, U14	I/O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Active-Low PCI Express Lane Linkup Status Indicator Outputs for lanes 15:0 (16 Balls)</b> These signals can directly drive common-anode LED modules (external current-limiting resistors are required).
PEX_PERn[15:0]	M5, L5, J5, H5, D7, D8, D10, D11 G14, H14, K14, L14, R12, R11, R9, R8	CMLRn	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Negative Half of PCI Express Receiver Differential Signal Pairs for lanes 15:0 (16 Balls)</b>

NDA CONFIDENTIAL -- kotlin-novator | vtuz vova

Signal Name	Ball #	Signal Type	Checked	Recommendations
PEX_PERp[15:0]	M4, L4, J4, H4, E7, E8, E10, E11, G15, H15, K15, L15, P12, P11, P9, P8	CMLRp	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Positive Half of PCI Express Receiver Differential Signal Pairs for lanes 15:0</b>
PEX_PETn[15:0]	M2, L2, J2, H2, A7, A8, A10, A11, G17, H17, K17, L17, V12, V11, V9, V8	CMLTn	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Negative Half of PCI Express Transmitter Differential Signal Pairs for lanes 15:0 (16 Balls)</b>  100 nF AC coupling caps required on all PCI Express transmit pairs.
PEX_PETp[15:0]	M1, L1, J1, H1, B7, B8, B10, B11, G18, H18, K18, L18, U12, U11, U9, U8	CMLTp	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Positive Half of PCI Express Transmitter Differential Signal Pairs for lanes 15:0 (16 Balls)</b>  100 nF AC coupling caps required on all PCI Express transmit pairs.

## 1.7 Serial EEPROM

As of this writing, a serial configuration EEPROM is **not required** for the PEX 8619. Use of a serial configuration EEPROM in systems designs is optional. However, we highly recommend including the serial EEPROM circuit as a stuffing option, to allow inclusion of EEPROM-based performance enhancements and/or errata workarounds that may become available in the future.

### 1.7.1 Serial EEPROM Type

Use Atmel part number AT25256A or equivalent for programming the PEX 8619. Be sure to specify the ‘-1.8’ version of the part, which can support operation at VCC voltage of 2.5Volts. Power the device from the VDD25 supply, bypassed with 0.1 uF.

### 1.7.2 Serial EEPROM Interface

Signal Name	Ball #	Signal Type	Checked	Recommendations
EE_CS#	R17	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Serial EEPROM Chip Select Output.</b> Connect to EEPROM CS# input. Can be left floating if not used.
EE_DI	N15	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Serial EEPROM Data Input (Write Data)</b> Connect to EEPROM serial data input, SI. Can be left floating if not used.
EE_DO	N16	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Serial EEPROM Data Output (Read Data)</b> Connect to EEPROM serial data output, SO. Weakly pulled up. Should be externally pulled high to VDD25
EE_SK	R18	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Serial EEPROM Clock Output</b> Connect to EEPROM clock input, SCK. Can be left floating if not used.

### 1.7.3 Additional EEPROM Signals

- ☐ **WP#:** Tie to EEPROM VCC if not used, else jumper to GND to enable write-protect.

☐ **HOLD#:** Tie to EEPROM VCC

## 1.8 JTAG Interface

Signal Name	Ball #	Signal Type	Checked	Recommendations
JTAG_TCK	B15	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>JTAG Test Clock Input</b> Frequency can be from 0 to 10 MHz. This signal is internally pulled up to VDD2.5 through a weak pull-up resistor. If this ball is connected to external board circuits, an external pull-up is also recommended.
JTAG_TDI	E14	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>JTAG Test Data Input</b> This signal is internally pulled up to VDD2.5 through a weak pull-up resistor. If this ball is connected to external board circuits, an external pull-up is also recommended.
JTAG_TDO	C15	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>JTAG Test Data Output</b> Serial output from the JTAG TAP Controller test instructions and data. Can be left open (no connect) if JTAG interface is not used.
JTAG_TMS	C14	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>JTAG Test Mode Select</b> This signal is internally pulled up to VDD2.5 through a weak pull-up resistor. If this ball is connected to external board circuits, an external pull-up is also recommended.
JTAG_TRST#	D15	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>JTAG Test Reset</b> Pull to GROUND (VSS) through 1.5K ohms for normal operation

## 1.9 I<sup>2</sup>C Slave Interface Signals

Signal Name	Ball #	Signal Type	Checked	Recommendations
I2C_ADDR[2:0]	E18, E17, C18	I/PU	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>I<sup>2</sup>C Slave Address Bits 2 through 0 (3 Balls)</b> Used to configure the device address on the I <sup>2</sup> C Bus. If I <sup>2</sup> C or PEX_INTA# output is used, I2C_ADDR[2:0] should be strapped to a unique address, to avoid address conflict with any other I <sup>2</sup> C devices (on the same I <sup>2</sup> C Bus segment) that have the upper four bits of their 7-bit I <sup>2</sup> C Slave address also Set to 1011b. Must be pulled High to VDD2.5 or Low to VSS (GND) through external resistors.
I2C_SCL0	C17	I, OD	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>I<sup>2</sup>C Serial Clock</b> I <sup>2</sup> C Clock source. Requires an external pull-up resistor, the value of which depends on the I2C bus architecture. It must be strong enough to overcome I2C bus capacitance to meet timing, but weak enough that the OD drivers can sink the current. The PEX 8619 RDK uses a 2.2K Pull-up.
I2C_SDA0	A17	I/O OD	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>I<sup>2</sup>C Serial Data</b> Transfers and receives I <sup>2</sup> C data. Requires an external pull-up resistor, the value of which depends on the I2C bus architecture. It must be strong enough to overcome I2C bus capacitance to meet timing, but weak enough that the OD drivers can sink the current. The PEX 8619 RDK uses a 2.2K Pull-up.



## 1.10 Serial Hot-Plug Controller Signals

Signal Name	Ball #	Signal Type	Checked	Recommendations
I2C_SCL1	B16	I, OD	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>I<sup>2</sup>C Serial Clock</b> I <sup>2</sup> C Clock source. Requires an external pull-up resistor, the value of which depends on the I2C bus architecture. It must be strong enough to overcome I2C bus capacitance to meet timing, but weak enough that the OD drivers can sink the current. The PEX 8619 RDK uses a 10 K $\Omega$ Pull-up.
I2C_SDA1	C16	I/O OD	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>I<sup>2</sup>C Serial Data</b> Transfers and receives I <sup>2</sup> C data. Requires an external pull-up resistor, the value of which depends on the I2C bus architecture. It must be strong enough to overcome I2C bus capacitance to meet timing, but weak enough that the OD drivers can sink the current. The PEX 8619 RDK uses a 10 K $\Omega$ Pull-up.
SHPC_INT#	A16	I	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Serial Hot Plug Controller Interrupt</b> Active-Low signal used only by Hot Plug-capable Transparent downstream Ports. Pull high to VDD25 through 3.3K ohms.

## 1.11 Miscellaneous Signals

Signal Name	Ball #	Signal Type	Checked	Recommendations
GPIO[31:0]	D4, D5, B4, B5, C5, C3, B14, E15, D16, T18, P15, R16, R14, T15, T16, P14, V6, V5, V4, R6, U6, U2, P5, P4, R3, T3, F4, D1, D2, E3, D3, E4	I/O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>General-Purpose I/O (32 balls)</b>
THERMAL_DIODEn	A15	<i>Reserved</i>	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Do not connect this ball to board electrical paths.
THERMAL_DIODEp	A14	<i>Reserved</i>	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Factory Test Only</b> Do not connect this ball to board electrical paths.
REXT_A[3:0]	K4, D9, J15, R10		YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	Tie each REXT_An to REXT_Bn through a 1.43K ohms, 1% Resistor.
REXT_B[3:0]	L6, F8, H13, N11		YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	Tie each REXT_Bn to REXT_An through a 1.43K ohms, 1% Resistor.
PEX_INTA#	P18	OD	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Interrupt Output</b> Assertion (Low) indicates that one or more events and/or errors were detected. See data book for details. Pull high to VDD25 through 3.3K ohms.

Signal Name	Ball #	Signal Type	Checked	Recommendations
FATAL_ERR#	B13	O	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>Fatal Error</b> Asserted Low when a Fatal error is detected in the PEX 8619. See data book for details. No pull up required.
NC	E9, J14, J17, J18, K1, K2, K5, P10, T6	No Connect	YES <input type="checkbox"/> NO <input type="checkbox"/> UNKNOWN <input type="checkbox"/>	<b>No Connect (9 Balls)</b> Do not connect these balls to board electrical paths.

## 1.12 Additional Schematic Design Considerations

### 1.12.1 PERST#

The PEX 8619 requires the PERST# signal to be asserted for at least 100ms after the board's power is stable to allow the chip to initialize correctly. Insure that Power On Reset and Power Valid detection circuitry implemented in your design meets this requirement. Refer to the PEX 8619 RDK Hardware Reference Manual for an example schematic.

### 1.12.2 Mid-Bus Probe Points

If your design contains embedded PCI Express links, it can sometimes be useful to add probe pads to your PCB design to allow instrumentation access to PCI Express links on the board. If you are planning to include mid-bus probe footprints in your PCB design, be aware that they may induce jitter and/or reduce signal integrity on the PCI Express lanes it is connected to. Refer to your instrumentation vendor's specifications for specific layout design considerations.

### 1.12.3 Spread Spectrum Clocking (SSC)

The PEX 8619 supports a Spread Spectrum REFCLK source. The SSC clock *must* originate from the PCI Express connector on a slot in the motherboard or through a common clock source that is being distributed to all add-in cards and/or PCI Express devices in the system.

If your REFCLK source is non-SSC, then you may have separate REFCLK sources on different cards or devices as long as their frequency difference is within  $\pm 300\text{ppm}$ . ( $\sim 30\text{ps}$  for a 100MHz Clock source) Refer to the PEX 8619 data book for more information.

## 2 PCB Layout Design Checks

**Note:** The following guidelines were provided for PCI Express 2.5 GT/s (Gen 1) transmission lines. On the Gen 2 PCI Express 5.0 GT/s signaling by increasing the pre-emphasis and increasing receiver sensitivity are supposed to counteract the bandwidth related losses associated with the frequency increase. However, as frequency goes up, other discontinuities become more of a factor not just the simple channel loss. We strongly recommend you simulate and verify your design at the operating frequency. HSPICE models are available on the [PLX website](#).

Since PCI Express links operate at very high speeds, proper PCB routing of each RX and TX pair in each lane is critical for maintaining signal integrity on each PCI Express link. The PCI-SIG provides numerous suggestions about how to correctly design PCB's containing PCI Express links. Several important guidelines for proper layout of PCI Express SerDes signals are listed below. Additional information is available from the PCI-SIG website, [www.pci-sig.com](http://www.pci-sig.com).

#### 1. Recommended Microstrip Trace Impedance:

- Differential Impedance:  $85\ \Omega \pm 20\%$
- Single ended Impedance:  $55\ \Omega \pm 15\%$

#### 2. Recommended Stripline Trace Impedance:

- Differential Impedance:  $85\ \Omega \pm 15\%$
- Single ended Impedance:  $55\ \Omega \pm 15\%$

#### 3. Maintain $\geq 20$ mil trace edge to plane edge gap

4. Match signal trace lengths to within 5 mils. Equalize using a snaked trace near the receive end if needed, but avoid "tight bends"
5. Route signals over continuous, un-broken planes.
6. Use GND-GND stitching vias near signal vias when routing between PCB layers
7. Do not route over plane splits or voids. Allow no more than 1/2 trace width routed over via antipad
8. Match left/right turn bends where possible. No 90-degree bends or "tight" bend structures.
9. The reference clock signal pair should maintain the same reference plane for the entire routed length and should not cross any plane splits (breaks in the reference plane)
10. Reference clock terminating components should be placed as close as possible to their respective driving sources, ideally within 100 mils of the clock/receiver component pin/ball.
11. Match all segment lengths between differential pairs along the entire length of the pair.
12. Maintain constant line impedance along the routing path by keeping the same line width and line separation.
13. Avoid routing differential pairs adjacent to noisy signal lines or high speed switching devices such as clock chips.
14. Recommended reference clock differential pair spacing (clock to clock#)  $\leq 11.25$  mils.
15. Recommended reference clock trace spacing to other traces is  $\geq 20$  mils.
16. Recommended reference clock line width  $\geq 5$  mils.
17. When routing the 100MHz differential clock, do not divide the two halves of the clock pair between layers.
18. Recommended reference clock differential impedance:  $85 \Omega \pm 15\%$
19. Recommended PCI Express reference clock to PCI express reference clock length matching to within 25 mils
20. AC Coupling Capacitors: The same package size and value of capacitor should be used for each signal in a differential pair. Refer to the *PCI Express Base Specification* for permitted values.
21. AC Coupling Capacitors: Locate capacitors for coupled traces in a differential pair at the same location along the differential traces. Place them as close to each other as possible.
22. AC Coupling Capacitors: The "breakout" into and out of the capacitor mounting pads should be symmetrical for both signal lines in a differential pair. In addition, the area under the cap footprint should be voided of metal.
23. Test points and probing structures should not introduce stubs on the differential pairs.
24. Use Low ESR, ceramic caps for lane AC-coupling.