

DBSeeder - Relational Database Data Generator.

build passing release v2.9.0 release date last saturday github repo or version not found

Table of Contents

- 1. Introduction**
 - 1.1 RDBMS Overview**
 - 1.2 RDBMS Directory**
 - 1.3 Performance Example**
- 2. Data**
 - 2.1 Database Schema**
 - 2.2 Construction of the Dummy Data Content**
- 3. Installation**
- 4. Operating Instructions**
 - 4.1 Scripts**
 - 4.2 Execution Variations**
 - 4.3 Control Parameters**
 - 4.4 Statistics**
- 5. RDBMS Specific Technical Details**
- 6. trino**

1. Introduction

DBSeeder allows the generation of large amounts of anonymized random dummy data for selected relational database systems (RDBMS) - useful e.g. for stress testing.

The database schema underlying the data generation can be freely defined. The names of the database, the schema and the user can be freely chosen, unless the respective database management system contains restrictions. If the selected database, schema or user already exist, they are deleted with all including data. **DBSeeder** then creates the selected database, schema or user and generates the desired dummy data. A maximum of 2 147 483 647 rows can be generated per database table. The database schema to be used, that is, the required database tables can be user defined using a JSON file. Details can be found here: [2.1 Database Schema](#).

Currently, depending on the capabilities of the specific RDBMS, the following functionalities and data types are supported:

- constraints
 - foreign (referential) key
 - not null constraint
 - primary key
 - unique (alternate) key
- data types
 - BIGINT - large integer
 - BLOB - large binary object
 - CLOB - large character Object
 - TIMESTAMP - timestamp including date
 - VARCHAR - variable text

The database systems considered meet the following conditions:

1. The database system is freely available in a documented docker image for testing purposes.
2. The database system provides a well documented JDBC interface.
3. A complete documentation of the SQL commands is available.

1.1 RDBMS Overview

RDBMS	Ticker Symbol(s)	RDBMS Versions	Latest JDBC
AgensGraph	agens	v2.1.1 - v2.1.3	1.4.2-c1
Apache Derby	derby, derby_emb	10.15.2.0	10.15.2.0
CockroachDB	cockroach	v20.2.5 - v21.1.2	see PostgreSQL
CrateDB	cratedb	4.1.6 - 4.5.1	2.6.0

RDBMS	Ticker Symbol(s)	RDBMS Versions	Latest JDBC
CUBRID	cubrid	10.2 - 11.0	11.0.1.0286
Exasol	exasol	6.2.8-d1 - 7.0.10	7.0.7
Firebird	firebird	3.0.5 - v4.0.0rc1	4.0.3.java11
H2 Database Engine	h2, h2_emb	1.4.200	1.4.200
HSQLDB	hsqldb, hsqldb_emb	2.5.1 - 2.6.0	2.6.0
IBM Db2 Database	ibmdb2	11.5.1.0 - 11.5.5.1	11.5.5.0
IBM Informix	informix	14.10 FC3DE - 14.10.FC5DE	4.50.4.1
MariaDB Server	mariadb	10.4.13 - 10.6.1	2.7.3
Mimer SQL	mimer	v11.0.3c - v11.0.5a	3.40
MonetDB	monetdb	Jun2020-SP1 - Oct2020-SP5	3.0.jre8
MySQL Database	mysql	8.0.20 - 8.0.25	8.0.25
OmniSciDB	omnisci	5.6.1	5.6.0
Oracle Database	oracle	12c - 19c	21.1.0.0
Percona Server for MySQL	percona	8.0.23-14	see MySQL
PostgreSQL	postgresql	12.3 - 13.3	42.2.20
SQL Server	sqlserver	2019-latest	9.2.1.jre15
SQLite	sqlite	3.32.0 - 3.32.3	3.34.0
trino	mysql_trino,	339 - 358	358
	oracle_trino,		
	postgresql_trino,		
	sqlserver_trino		
VoltDB	voltodb	9.2.1	10.1.1
YugabyteDB	yugabyte	2.2.2.0-b15 - 2.7.1.1-b1	42.2.7-yb-3

1.2 RDBMS Directory

The following database systems are included in the current version of **DBSeeder**:

- [AgensGraph](#)
 - client only version
 - commercial, open source
 - derived from PostgreSQL
 - property graph model and relational model
 - [see technical details here](#)
- [Apache Derby](#)
 - client and embedded version
 - open source
 - relational model
 - [see technical details here](#)
- [CockroachDB](#)
 - client only version
 - commercial, open source
 - compatible with PostgreSQL JDBC
 - relational model
 - [see technical details here](#)
- [CrateDB](#)
 - client only version
 - commercial, open source
 - compatible with PostgreSQL

- relational model
 - [see technical details here](#)
- [CUBRID](#)
 - client only version
 - compatible with MySQL
 - open source
 - relational model
 - [see technical details here](#)
- [Exasol](#)
 - client only version
 - commercial
 - in-memory, column-oriented, relational model
 - [see technical details here](#)
- [Firebird](#)
 - client and embedded (not supported here) version
 - open source
 - relational model
 - [see technical details here](#)
- [H2 Database Engine](#)
 - client and embedded version
 - compatible with HSQLDB, PostgreSQL
 - open source
 - relational model
 - [see technical details here](#)
- [HSQLDB](#)
 - client and embedded version
 - open source
 - relational model
 - [see technical details here](#)
- [IBM Db2 Database](#)
 - client only version
 - commercial
 - relational model
 - [see technical details here](#)
- [IBM Informix](#)
 - client only version
 - commercial
 - relational model
 - [see technical details here](#)
- [MariaDB Server](#)
 - client only version
 - derived from MySQL
 - open source
 - relational model
 - [see technical details here](#)
- [Mimer SQL](#)
 - client only version
 - commercial
 - relational model
 - [see technical details here](#)
- [MonetDB](#)
 - client only version
 - open source
 - column-oriented relational model
 - [see technical details here](#)
- [MySQL Database](#)
 - client only version
 - open source
 - relational model
 - [see technical details here](#)
- [OmniSciDB](#)

- client only version
- commercial, open source
- GPU and CPU version
- relational model
- [see technical details here](#)
- [Oracle Database](#)
 - client only version
 - commercial
 - relational model
 - [see technical details here](#)
- [Percona Server for MySQL](#)
 - client only version
 - commercial, open source
 - derived from MySQL
 - relational model
 - [see technical details here](#)
- [PostgreSQL](#)
 - client only version
 - open source
 - relational model
 - [see technical details here](#)
- [SQL Server](#)
 - client only version
 - commercial
 - derived from Adaptive Server Enterprise
 - relational model
 - [see technical details here](#)
- [SQLite](#)
 - commercial, open source
 - embedded only version
 - relational model
 - [see technical details here](#)
- [trino](#)
 - compatible with Accumulo, Cassandra, Elasticsearch, Hive, Kudu, MongoDB, MySQL, Pinot, PostgreSQL, Redis, Redshift
 - distributed query engine
 - open source
 - [see technical details here](#)

For the RDBMS MySQL, Oracle, PostgreSQL and SQL Server the JDBC driver from trino can optionally be used instead of the original JDBC driver. The prerequisite for this is that trino is either installed locally (Linux) or is available as a Docker container (Linux and Windows). Details can be found here: [6. trino](#).

- [VoltDB](#)
 - client only version
 - commercial, open source
 - derived from H-Store, HSQLDB
 - in-memory relational model
 - [see technical details here](#)
- [YugabyteDB](#)
 - client only version
 - commercial, open source
 - compatible with Cassandra, PostgreSQL, Redis
 - derived from PostgreSQL, RocksDB
 - inspired by Cloud Spanner
 - relational model
 - [see technical details here](#)

1.3 Performance Example

An interesting side effect of working with **DBSeeder** is the ability to compare the performance of data generation (**INSERT**) between the databases (e.g. Version 2.9.0 Windows 10):

ticker symbol	DBMS	db type	runtime in ms	start time	end time	host name	no. cores	operating system
h2_emb	H2 Database Engine	embedded	2503	04.06.2021 10:03	04.06.2021 10:03	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
sqlite	SQLite	embedded	2513	04.06.2021 11:10	04.06.2021 11:10	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
postgresql	PostgreSQL	client	2746	04.06.2021 11:02	04.06.2021 11:02	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
agens	AgensGraph	client	2827	04.06.2021 09:55	04.06.2021 09:55	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
mariadb	MariaDB Server	client	2954	04.06.2021 10:18	04.06.2021 10:18	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
exasol	Exasol	client	3253	04.06.2021 10:00	04.06.2021 10:00	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
cockroach	CockroachDB	client	4049	04.06.2021 09:55	04.06.2021 09:55	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
cratedb	CrateDB	client	4160	04.06.2021 09:56	04.06.2021 09:56	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
mysql	MySQL Database	client	5101	04.06.2021 10:20	04.06.2021 10:21	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
cubrid	CUBRID	client	5341	04.06.2021 09:57	04.06.2021 09:57	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
sqlserver	MS SQL Server	client	5343	04.06.2021 11:11	04.06.2021 11:11	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
percona	Percona Server for MySQL	client	6085	04.06.2021 11:01	04.06.2021 11:01	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
h2	H2 Database Engine	client	6204	04.06.2021 10:03	04.06.2021 10:03	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
mimer	Mimer SQL	client	7492	04.06.2021 10:19	04.06.2021 10:19	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
oracle	Oracle Database	client	11888	04.06.2021 10:41	04.06.2021 10:41	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
yugabyte	YugabyteDB	client	12060	04.06.2021 11:30	04.06.2021 11:31	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
derby	Apache Derby	client	14005	04.06.2021 09:57	04.06.2021 09:58	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
derby_emb	Apache Derby	embedded	15328	04.06.2021 09:58	04.06.2021 09:58	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
hsqldb	HyperSQL Database	client	16652	04.06.2021 10:04	04.06.2021 10:04	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
informix	IBM Informix	client	18105	04.06.2021 10:17	04.06.2021 10:17	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
ibmdb2	IBM Db2 Database	client	23360	04.06.2021 10:13	04.06.2021 10:13	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
monetdb	MonetDB	client	32987	04.06.2021 10:19	04.06.2021 10:19	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
omnisci	OmniSciDB	client	37880	04.06.2021 10:38	04.06.2021 10:39	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
firebird	Firebird	client	92278	04.06.2021 10:01	04.06.2021 10:02	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
hsqldb_emb	HyperSQL Database	embedded	193760	04.06.2021 10:04	04.06.2021 10:08	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
postgresql_trino	PostgreSQL	trino	439684	04.06.2021 11:03	04.06.2021 11:10	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
mysql_trino	MySQL Database	trino	915551	04.06.2021 10:22	04.06.2021 10:37	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
oracle_trino	Oracle Database	trino	971543	04.06.2021 10:44	04.06.2021 11:00	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0
sqlserver_trino	MS SQL Server	trino	1023699	04.06.2021 11:12	04.06.2021 11:29	jfw-w-win-dt-21	32	amd64 / Windows 10 / 10.0

2. Data

2.1 Database Schema

The underlying database schema is defined in a JSON-based parameter file and the associated program code is generated and compiled with the script `scripts/run_db_seeder_generate_schema`. To validate the database schema in the JSON parameter file, the JSON schema file `db_seeder_schema.schema.json` in the directory `src/main/resources` is used.

2.1.1 Structure of the Database Schema Definition File

The definition of a database schema consists of the object `global` with the global parameters and the array `tables`, which contains the definition of the database tables.

2.1.1.1 `globals` - Global Parameters

- `defaultNumberOfRows` - default value for the number of table rows to be generated, if no value is specified in the table definition
- `encodingISO_8859_1` - a string with Western Latin characters is inserted into generated character columns
- `encodingUTF_8` - a string with simplified Chinese characters is inserted into generated character columns specified in the table definition
- `nullFactor` - determines the proportion of NULL values in optional columns and must be between 2 and 99 (inclusive): 2 means 50%, 4 means 25%, 10 means 10%, etc., default value is 4

2.1.1.2 `tables` - Database Table Definitions

- `tableName` - database table name
- `numberOfRows` - number of table rows to be generated
- `columns` - an array of column definitions
 - `columnName` - column name
 - `dataType` - data type, is one of BIGINT, BLOB, CLOB, TIMESTAMP or VARCHAR
 - `size` - for data type VARCHAR the maximum size of the column value
 - `precision` - currently not used
 - `notNull` - is a NULL value allowed ?
 - `primaryKey` - is this the primary key column ?

- **references** - an array of foreign key definitions
 - **referenceTable** - name of the reference database table
 - **referenceColumn** - name of the reference column
- **defaultValueInteger** - default value for integer columns
- **defaultValueString** - default value for alphanumeric columns
- **lowerRangeInteger** - lower limit for an integer column, requires also an upper limit
- **lowerRangeString** - lower limit for an alphanumeric column, requires also an upper limit
- **upperRangeInteger** - upper limit for an integer column
- **upperRangeString** - upper limit for an alphanumeric column
- **validValuesInteger** - valid values for an integer column
- **validValuesString** - valid values for an alphanumeric column
- **tableConstraints** - an array of table constraint definitions
 - **constraintType** - constraint type, is one of FOREIGN, PRIMARY or UNIQUE
 - **columns** - an array with the names of the affected columns
 - **referenceTable** - name of the reference database table, only for foreign keys
 - **referenceColumns** - an array with the names of the affected reference columns, only for foreign keys

Only either a range restriction (**lowerRange...**, **upperRange...**) or a value restriction (**validValues...**) may be specified for each column.

2.1.2 Mapping of Data Types in the JDBC Driver


Data Type	JDBC Method
BIGINT	setLong
BLOB	setBytes
CLOB	setString
TIMESTAMP	setTimestamp
VARCHAR	setNString (Firebird, MariaDB, MS SQL SERVER and Oracle)
	setString (else)

2.1.3 Example File **db_seeder_schema.company.json** in the Directory **resources/json**

This file contains the definition of a simple database schema consisting of the database tables CITY, COMPANY, COUNTRY, COUNTRY_STATE and TIMEZONE.

The abbreviations in the following illustration (created with Toad Data Modeler) mean:

- (AK1) - alternate key (unique key)
- FK - foreign key
- NN - not null
- PK - primary key



2.2 Construction of the Dummy Data Content

The proportion of **NULL** values in optional columns is defined by the global parameter **nullFactor**.

All methods for generating column contents can be overwritten if necessary.

2.2.1 BIGINT

Java method: **getContentBigint**

- If the column parameter **validValuesInteger** is defined in the database schema, a random value is taken from it.
- If the column parameters **lowerRangeInteger** and **upperRangeInteger** are defined in the database schema, a random value is taken from this interval.
- Otherwise the counter for the current row (row number) is used.

2.2.2 BLOB

Java method: **getContentBlob**

- The content of the file `blob.png` from the resource directory (`src/main/resources`) is loaded into these columns. This file contains the company logo of Konnexions GmbH.

2.2.3 CLOB

Java method: `getContentClob`

- The content of the file `clob.md` from the resource directory (`src/main/resources`) is loaded into these columns. This file contains the text of the Konnexions Public License (KX-PL).

2.2.4 TIMESTAMP

Java method: `getContentTimestamp`

- A randomly generated timestamp is assigned to all columns that can contain temporal data.
































2.2.5 VARCHAR

Java method: `getContentVarchar`














- If the column parameter `validValuesString` is defined in the database schema, a random value is taken from it.
- If the column parameters `lowerRangeString` and `upperRangeString` are defined in the database schema, a random value is taken from this interval.
- Otherwise content of the column is constructed depending on the row number and the encoding flags as follows:
 - ASCII (all rows where the index modulo 3 is 0):
 - column name in capital letters
 - underscore `_`
 - current row number left-justified
 - ISO 8859 1 (all rows where the index modulo 3 is 1) :
 - column name in capital letters
 - underscore `_`
 - a string containing specific Western European characters with accent (e.g. French, Portuguese or Spanish)
 - underscore `_`
 - current row number left-justified
 - the ISO 8859 1 version can be prevented by choosing `encodingISO_8859_1 false` in the database schema definition
 - UTF-8 (all rows where the index modulo 3 is 2):
 - column name in capital letters
 - underscore `_`
 - a string containing simplified Chinese characters
 - underscore `_`
 - current row number left-justified
 - the UTF-8 version can be prevented by choosing `encodingUTF_8 false` in the database schema definition
 - If the resulting value exceeds the permissible column size, the value is shortened accordingly from the left

2.2.6 Examples

1. Table CITY

CITY  Enter a SQL expression to filter results (use Ctrl+Space)										
		 PK_CITY_ID 	 FK_COUNTRY_STATE_ID 	 CITY_MAP 	 CREATED 	 MODIFIED 	 NAME 			
<div>Grid</div> <div>Text</div>	1	0	417 	PNG IHDR Ö Ü çOä... [19664]	2020-07-07 21:16:36	2020-07-09 13:58:19	NAME_NAME_0			
	2	1	154 	[NULL]	2020-07-01 15:29:56	2020-07-11 13:22:42	NAME_COMPANÍA_1			
	3	2	307 	PNG IHDR Ö Ü çOä... [19664]	2020-07-03 17:37:20	[NULL]	NAME_名称_2			
	4	3	270 	PNG IHDR Ö Ü çOä... [19664]	2020-07-03 08:17:33	2020-07-03 09:21:59	NAME_NAME_3			
	5	4	201 	PNG IHDR Ö Ü çOä... [19664]	2020-07-09 02:37:50	[NULL]	NAME_COMPANÍA_4			
	6	5	119 	PNG IHDR Ö Ü çOä... [19664]	2020-07-13 23:50:00	2020-07-12 20:48:13	NAME_名称_5			
	7	6	[NULL]	[NULL]	2020-07-20 18:08:54	[NULL]	NAME_NAME_6			
	8	7	[NULL]	PNG IHDR Ö Ü çOä... [19664]	2020-07-10 02:51:42	2020-07-13 22:11:40	NAME_COMPANÍA_7			
	9	8	261 	PNG IHDR Ö Ü çOä... [19664]	2020-07-13 14:53:57	[NULL]	NAME_名称_8			
	10	9	584 	[NULL]	2020-07-13 20:23:48	[NULL]	NAME_NAME_9			
	11	10	[NULL]	PNG IHDR Ö Ü çOä... [19664]	2020-07-04 17:37:34	[NULL]	NAME_COMPANÍA_10			
	12	11	35 	PNG IHDR Ö Ü çOä... [19664]	2020-07-19 01:25:20	2020-06-27 19:33:15	NAME_名称_11			
	13	12	553 	PNG IHDR Ö Ü çOä... [19664]	2020-06-28 16:59:18	[NULL]	NAME_NAME_12			
	14	13	401 	PNG IHDR Ö Ü çOä... [19664]	2020-07-09 15:50:28	2020-07-11 00:37:42	NAME_COMPANÍA_13			
	15	14	127 	PNG IHDR Ö Ü çOä... [19664]	2020-07-15 07:32:40	2020-07-01 18:59:11	NAME_名称_14			
	16	15	296 	PNG IHDR Ö Ü çOä... [19664]	2020-07-10 12:51:31	2020-07-17 11:12:31	NAME_NAME_15			
	17	16	[NULL]	PNG IHDR Ö Ü çOä... [19664]	2020-07-18 19:15:29	2020-07-11 12:23:04	NAME_COMPANÍA_16			
	18	17	523 	PNG IHDR Ö Ü çOä... [19664]	2020-07-08 23:38:14	2020-07-09 19:58:29	NAME_名称_17			
	19	18	230 	PNG IHDR Ö Ü çOä... [19664]	2020-07-01 01:32:05	2020-07-11 15:13:29	NAME_NAME_18			
	20	19	275 	[NULL]	2020-07-02 19:47:10	2020-06-28 15:22:39	NAME_COMPANÍA_19			
	21	20	274 	PNG IHDR Ö Ü çOä... [19664]	2020-07-19 23:43:47	2020-07-04 22:07:54	NAME_名称_20			
	22	21	[NULL]	[NULL]	2020-07-11 22:24:56	[NULL]	NAME_NAME_21			
	23	22	[NULL]	PNG IHDR Ö Ü çOä... [19664]	2020-07-08 03:42:43	2020-07-01 21:37:16	NAME_COMPANÍA_22			
	24	23	[NULL]	PNG IHDR Ö Ü çOä... [19664]	2020-06-27 08:43:04	2020-06-29 23:47:39	NAME_名称_23			
	25	24	158 	PNG IHDR Ö Ü çOä... [19664]	2020-06-28 20:05:01	2020-07-09 22:41:36	NAME_NAME_24			

2. Table COUNTRY

COUNTRY  Enter a SQL expression to filter results (use Ctrl+Space)										
	 PK_COUNTRY_ID 	 COUNTRY_MAP 	 CREATED 	 ISO3166 	 MODIFIED 	 NAME 				
1	0	PNG IHDR Ö Ü çOä... [19664]	2020-06-28 19:36:46	[NULL]	2020-06-30 00:33:11	NAME_NAME_0				
2	1	PNG IHDR Ö Ü çOä... [19664]	2020-07-19 07:16:11	ISO3166_CÓDIGO 3166_1	2020-06-27 23:12:01	NAME_COMPANÍA_1				
3	2	PNG IHDR Ö Ü çOä... [19664]	2020-07-08 22:39:47	ISO3166_ISO 3166标准_2	2020-07-16 18:37:01	NAME_名称_2				
4	3	[NULL]	2020-07-21 14:58:16	ISO3166_ISO3166_3	2020-07-16 01:14:12	NAME_NAME_3				
5	4	PNG IHDR Ö Ü çOä... [19664]	2020-07-01 19:00:23	ISO3166_CÓDIGO 3166_4	2020-06-29 07:27:24	NAME_COMPANÍA_4				
6	5	PNG IHDR Ö Ü çOä... [19664]	2020-07-05 00:54:26	ISO3166_ISO 3166标准_5	2020-07-08 02:20:09	NAME_名称_5				
7	6	PNG IHDR Ö Ü çOä... [19664]	2020-07-06 22:36:40	ISO3166_ISO3166_6	2020-07-04 08:24:18	NAME_NAME_6				
8	7	PNG IHDR Ö Ü çOä... [19664]	2020-07-20 07:33:21	ISO3166_CÓDIGO 3166_7	2020-06-28 06:10:36	NAME_COMPANÍA_7				
9	8	PNG IHDR Ö Ü çOä... [19664]	2020-07-21 14:34:52	ISO3166_ISO 3166标准_8	[NULL]	NAME_名称_8				
10	9	PNG IHDR Ö Ü çOä... [19664]	2020-07-08 08:27:06	ISO3166_ISO3166_9	2020-07-16 00:17:52	NAME_NAME_9				
11	10	[NULL]	2020-06-29 04:43:50	ISO3166_CÓDIGO 3166_10	2020-07-14 19:08:27	NAME_COMPANÍA_10				
12	11	PNG IHDR Ö Ü çOä... [19664]	2020-06-29 11:03:58	ISO3166_ISO 3166标准_11	[NULL]	NAME_名称_11				
13	12	PNG IHDR Ö Ü çOä... [19664]	2020-07-16 15:39:56	ISO3166_ISO3166_12	2020-06-27 16:50:58	NAME_NAME_12				
14	13	PNG IHDR Ö Ü çOä... [19664]	2020-07-12 01:44:07	[NULL]	[NULL]	NAME_COMPANÍA_13				
15	14	PNG IHDR Ö Ü çOä... [19664]	2020-07-12 07:01:06	ISO3166_ISO 3166标准_14	2020-07-18 06:54:10	NAME_名称_14				
16	15	PNG IHDR Ö Ü çOä... [19664]	2020-07-09 15:54:56	[NULL]	[NULL]	NAME_NAME_15				
17	16	PNG IHDR Ö Ü çOä... [19664]	2020-07-16 12:48:24	[NULL]	[NULL]	NAME_COMPANÍA_16				
18	17	PNG IHDR Ö Ü çOä... [19664]	2020-07-06 08:49:55	ISO3166_ISO 3166标准_17	[NULL]	NAME_名称_17				
19	18	[NULL]	2020-07-19 16:21:58	[NULL]	2020-07-02 11:22:09	NAME_NAME_18				
20	19	PNG IHDR Ö Ü çOä... [19664]	2020-07-17 04:08:40	ISO3166_CÓDIGO 3166_19	2020-07-04 04:18:40	NAME_COMPANÍA_19				
21	20	PNG IHDR Ö Ü çOä... [19664]	2020-07-09 16:02:53	[NULL]	2020-07-19 14:04:43	NAME_名称_20				
22	21	PNG IHDR Ö Ü çOä... [19664]	2020-06-29 20:47:52	[NULL]	[NULL]	NAME_NAME_21				
23	22	[NULL]	2020-07-12 01:36:41	[NULL]	2020-07-03 14:32:35	NAME_COMPANÍA_22				
24	23	[NULL]	2020-07-19 09:13:19	ISO3166_ISO 3166标准_23	2020-07-12 17:02:15	NAME_名称_23				
25	24	PNG IHDR Ö Ü çOä... [19664]	2020-07-02 10:15:05	[NULL]	2020-07-06 00:07:07	NAME_NAME_24				

3. Table TIMEZONE

TIMEZONE <small>Enter a SQL expression to filter results (use Ctrl+Space)</small>							
	PK_TIMEZONE_ID	ABBREVIATION	CREATED	MODIFIED	NAME	V_TIME_ZONE	
1	0	ABBREVIATION_ABBREVIATION_0	2020-07-06 02:00:35	[NULL]	NAME_NAME_0	V_TIME_ZONE_V_TIME_ZONE_0	
2	1	ABBREVIATION_ABBREVIATION_1	2020-07-19 23:30:25	2020-07-14 16:15:02	NAME_COMPANÍA_1	V_TIME_ZONE_FUSO_HORÁRIO_1	
3	2	ABBREVIATION_缩写_2	2020-06-27 02:48:13	2020-07-05 15:25:17	NAME_名称_2	V_TIME_ZONE_时区_2	
4	3	ABBREVIATION_ABBREVIATION_3	2020-07-06 20:57:16	2020-06-28 20:43:59	NAME_NAME_3	V_TIME_ZONE_V_TIME_ZONE_3	
5	4	ABBREVIATION_ABBREVIATION_4	2020-07-15 16:05:02	2020-07-02 00:19:52	NAME_COMPANÍA_4	[NULL]	
6	5	ABBREVIATION_缩写_5	2020-07-13 22:57:44	2020-06-27 08:14:01	NAME_名称_5	V_TIME_ZONE_时区_5	
7	6	ABBREVIATION_ABBREVIATION_6	2020-07-19 22:16:01	2020-07-16 10:19:57	NAME_NAME_6	V_TIME_ZONE_V_TIME_ZONE_6	
8	7	ABBREVIATION_ABBREVIATION_7	2020-07-10 03:25:25	2020-06-27 15:57:09	NAME_COMPANÍA_7	V_TIME_ZONE_FUSO_HORÁRIO_7	
9	8	ABBREVIATION_缩写_8	2020-07-03 05:45:30	2020-07-14 01:20:33	NAME_名称_8	V_TIME_ZONE_时区_8	
10	9	ABBREVIATION_ABBREVIATION_9	2020-07-13 23:10:17	2020-07-05 07:34:24	NAME_NAME_9	V_TIME_ZONE_V_TIME_ZONE_9	
11	10	ABBREVIATION_ABBREVIATION_10	2020-07-03 00:11:26	2020-07-11 17:19:21	NAME_COMPANÍA_10	V_TIME_ZONE_FUSO_HORÁRIO_10	

3. Installation

The easiest way is to download a current release of **DBSeeder** from the GitHub repository. You can find the necessary link [here](#). The system requirements are described in the respective release notes.

4. Operating Instructions

4.1 Scripts

4.1.1 Script **run_db_seeder**

Using the **DBSeeder** development and operational Docker image from Docker Hub (see [here](#)) eliminates the need to install the runtime environment.

With the script **run_db_seeder** the complete functionality of the **DBSeeder** application can be used:

- Creating a suitable database
- Generation of any number of dummy data.

All scripts are available in a Windows version (**cmd** / **.bat**) as well as in a Unix version (**bash** / **.sh**). To run the scripts, apart from the prerequisites as release notes (**ReleaseNotes.md**), only the libraries in the **lib** directory and the corresponding script of **run_db_seeder** are required. The creation of the databases also requires a working access to [Docker Hub](#).

All control parameters used in **DBSeeder** (see section 4.2) can be adapted in the scripts to specific needs.


The **run_db_seeder** script is controlled by the following script parameters::

- **DB_SEEDER_DBMS**: the ticker symbol of the desired database management system (default value **sqlite**) or **complete** for all implemented RDBMS.
- **DB_SEEDER_SETUP_DBMS**: should an empty database be created:
 - **yes**: a new database is created based on a suitable Docker image
 - otherwise: no database is created
- **DB_SEEDER_NO_CREATE_RUNS**: Number of dummy data generation runs:
 - 1: one run
 - 2: two runs
 - otherwise: no run

For the run variants **complete_client**, **complete_emb** and **complete_trino**, statistics files with the following data name structure are created in the file directory **resources\statistics** by default:

```
db_seeder_<bash | cmd>_<db_type>_unknown_<DBSeeder release>.tsv
```

An overview of the structure of the scripts used can be taken from the following diagram:



4.1.2 Script `scripts/run_db_seeder_statistics`

This script aggregates the existing statistics files into a single overall file. The file name of this overall file is defined with parameter `db_seeder.file.statistics.summary.name` and the existing statistics files are searched in the file directories according to parameter `db_seeder.file.statistics.summary.source`. The file format `csv` or `tsv` depends on the parameter `db_seeder.file.statistics.delimiter`.

Example content:

```

ticker symbol  RDBMS version  creator db type schema  runtime in ms  start time  end time  host name  no.
cores  operating system  file_name
agens  AgensGraph  v2.6.0  bash  client  unknown  14  2020-10-05 16:09:36.618076382  2020-10-05
16:09:51.570013623  ubuntu 2  amd64 / Linux / 5.4.0-48-generic  db_seeder_bash_client_unknown_2.6.0
cratedb  CrateDB  v2.6.0  bash  client  unknown  24  2020-10-05 16:11:40.160409347  2020-10-05
16:12:04.695790414  ubuntu 2  amd64 / Linux / 5.4.0-48-generic  db_seeder_bash_client_unknown_2.6.0
cubrid  CUBRID  v2.6.0  bash  client  unknown  50  2020-10-05 16:13:22.287362093  2020-10-05
16:14:12.339067275  ubuntu 2  amd64 / Linux / 5.4.0-48-generic  db_seeder_bash_client_unknown_2.6.0

```

4.2 Execution Variations

4.2.1 Ubuntu 20.04 LTS (including VMware)

- **Requirements:**

- Ubuntu 20.04 installed directly or via VMware
- run `sudo apt update`
- run `sudo apt install dos2unix git`
- add the following lines to `.bash_profile`:

```
if [ -f ~/.bashrc ]; then
    source ~/.bashrc
fi
```

- run `git clone https://github.com/KonnexionsGmbH/db_seeder` (cloning the **DBSeeder** repository)
- run `cd db_seeder`
- run `./scripts/run_prep_bash_scripts.sh` (preparing the shell scripts)
- run `./scripts/run_install_4_ubuntu_20.04_vm_wsl2.sh` (setting up the WSL2 environment)
- close the Ubuntu shell and reopen it again
- run `cd db_seeder`
- run `gradle copyJarToLib`
- **Execution:** run `./run_db_seeder.sh`
- **Issues:**
 - trino and SQL Server Connector
 - YugabyteDB and Docker image

4.2.1 Ubuntu 20.04 LTS and **DBSeeder** Image



- **Requirements:**
 - pull the **DBSeeder** image from DockerHub: `docker pull konnexionsgmbh/db_seeder:latest`
 - create an appropriate container: `docker run -it --name db_seeder -v /var/run/docker.sock:/var/run/docker.sock konnexionsgmbh/db_seeder:latest bash`
 - run `git clone https://github.com/KonnexionsGmbH/db_seeder` (cloning the **DBSeeder** repository)
 - run `cd db_seeder`
 - run `./scripts/run_prep_bash_scripts.sh` (preparing the shell scripts)
 - run `gradle copyJarToLib`
- **Execution:** `./run_db_seeder.sh`
- **Issues:**
 - trino and SQL Server Connector

4.2.2 Ubuntu 20.04 LTS and Windows Subsystem Linux 2

- **Requirements:**
 - install Ubuntu 20.04 from Microsoft Marketplace
 - run `sudo apt update`
 - run `sudo apt install dos2unix`
 - add the following lines to `.bash_profile`:

```
if [ -f ~/.bashrc ]; then
    source ~/.bashrc
fi
```

- activate the **WSL INTEGRATION** for Ubuntu 20.04 in Docker



- **Requirements (continued):**

- run `git clone https://github.com/KonnexionsGmbH/db_seeder` (cloning the **DBSeeder** repository)
- run `cd db_seeder`
- run `./scripts/run_prep_bash_scripts.sh` (preparing the shell scripts)
- run `./scripts/run_install_4_ubuntu_20.04_vm_wsl2.sh` (setting up the WSL2 environment)
- close the Ubuntu shell and reopen it again
- run `cd db_seeder`
- run `gradle copyJarToLib`

- **Execution:** run `./run_db_seeder.sh`

- **Issues:**

- trino and SQL Server Connector
- YugabyteDB and Docker image

4.2.3 Windows 10 Pro

- **Requirements:**
 - run `git clone https://github.com/KonnexionsGmbH/db_seeder` (cloning the **DBSeeder** repository)
 - run `cd db_seeder`
- **Execution:** run `run_db_seeder.bat`
- **Issues:**
 - trino and SQL Server Connector
 - YugabyteDB and Docker image

4.3 Control Parameters

4.3.1 Supported Parameters

The flow control parameters for **DBSeeder** are stored in the properties file `src/main/resources/db_seeder.properties` and can all be overridden by the environment variables defined in the scripts. The following control parameters are currently supported:

```
db_seeder.character_set_server=
db_seeder.collation_server=
db_seeder.connection.host=
db_seeder.connection.host.trino=
db_seeder.connection.port=0
db_seeder.connection.port.trino=0
db_seeder.connection.prefix=
db_seeder.connection.service=
db_seeder.connection.suffix=

db_seeder.database.sys=
db_seeder.database=

db_seeder.file.configuration.name=
db_seeder.file.json.name=resources/json/db_seeder_schema.company.json
db_seeder.file.statistics.delimiter=\t
db_seeder.file.statistics.header=ticker symbol;RDBMS;db type;runtime in ms;start time;end time;host name;no.
cores;operating system
db_seeder.file.statistics.name=resources/statistics/db_seeder_local.tsv
db_seeder.file.statistics.summary.name=resources/statistics/db_seeder_summary.tsv
db_seeder.file.statistics.summary.source=resources/statistics;Transfer

db_seeder.password.sys=
db_seeder.password=

db_seeder.schema=

db_seeder.user.sys=
db_seeder.user=
```

4.3.2 Explanation and Cross-reference

Property incl. Default Value [db.seeder.]	Environment Variable [DB_SEEDER_]	Used By	Description
character.set.server=<x...x>	CHARACTER_SET_SERVER	mariadb	default server character set
collation.server=<x...x>	COLLATION_SERVER	mariadb	default server collation
connection.host=<x...x>	CONNECTION_HOST	all client RDBMS	host name or ip address of the database server
connection.host_trino=<x...x>	CONNECTION_HOST_TRINO	trino	host name or ip address of the trino
connection.port=<9...9>	CONNECTION_PORT	all client RDBMS	port number of the database server
connection.port_trino=<9...9>	CONNECTION_PORT_TRINO	trino	port number of the trino

Property incl. Default Value [db.seeder.]	Environment Variable [DB_SEEDER.]	Used By	Description
connection.prefix= <x...x>	CONNECTION_PREFIX	all RDBMS	prefix of the database connection string
connection.service= <x...x>	CONNECTION_SERVICE	oracle	service name of the database connection string
connection.suffix= <x...x>	CONNECTION_SUFFIX	firebird, hsqldb, mysql, percona, voltdb	suffix of the database connection string
database.sys= <x...x>	DATABASE_SYS	agens, cockroach, informix, mariadb, mimer, monetdb, mysql, omnic, percona, postgresql, sqlserver, yugabyte	privileged database name
database= <x...x>	DATABASE	all RDBMS except cratedb, exasol, monetdb, oracle, voltdb	database name
file.configuration.name= <x...x>	FILE_CONFIGURATION_NAME	n/a	directory and file name of the DBSeeder configuration file
file.json.name= <x...x>	FILE_JSON_NAME	scripts/run_db_seeder_generate_schema	directory and file name of the JSON file containing the database schema
file.statistics.delimiter= <x...x>	FILE_STATISTICS_DELIMITER	all RDBMS	separator of the statistics file created in run_db_seeder
file.statistics.header= <x...x>	FILE_STATISTICS_HEADER	all RDBMS	header line of the statistics file created in run_db_seeder
file.statistics.name= <x...x>	FILE_STATISTICS_NAME	all RDBMS	file name of the statistics file created in run_db_seeder
file.statistics.summary.name= <x...x>	FILE_STATISTICS_SUMMARY_NAME	all RDBMS	file name of the summary statistics file created in run_db_seeder_statistics
file.statistics.summary.source= <x...x>	FILE_STATISTICS_SUMMARY_SOURCE	all RDBMS	directory name(s) (separated by semicolon) of the source directories containing statistics files
password.sys= <x...x>	PASSWORD_SYS	agens, exasol, firebird, ibmdb2, informix, mariadb, mimer, monetdb, mysql, omnic,	password of the privileged user
		oracle, percona, postgresql, sqlserver	password of the privileged user
password= <x...x>	PASSWORD	all RDBMS except cockroach, derby, ibmdb2, informix	password of the normal user
schema=kxn_schema	SCHEMA	agens, derby, exasol, h2, hsqldb, ibmdb2, monetdb, postgresql, sqlserver, yugabyte	schema name
user.sys= <x...x>	USER_SYS	all RDBMS except derby, voltdb	name of the privileged user
user=kxn_user	USER	all RDBMS except derby, ibmdb2, informix	name of the normal user

4.4 Statistics

5. RDBMS Specific Technical Details

[DBeaver](#) is a great tool to analyze the database content. Below are also DBeaver based connection parameter examples for each database management system.

[AgensGraph](#) / [Apache Derby](#) / [CockroachDB](#) / [CrateDB](#) / [CUBRID](#) / [Exasol](#) / [Firebird](#) / [H2 Database Engine](#) / [HSQLDB](#) / [IBM Db2 Database](#) / [IBM Informix](#) / [MariaDB Server](#) / [Mimer SQL](#) / [MonetDB](#) / [MySQL Database](#) / [OmniSciDB](#) / [Oracle Database](#) / [Percona Server for MySQL](#) / [PostgreSQL](#) / [SQL Server](#) / [SQLite](#) / [trino](#) / [VoltDB](#) / [YugabyteDB](#)

5.1 AgensGraph

- **data types:**

DBSeeder Type	AgensGraph Database Type
BIGINT	BIGINT
BLOB	BYTEA
CLOB	TEXT
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**

- CREATE DATABASE: see PostgreSQL
- CREATE SCHEMA: see PostgreSQL
- CREATE TABLE: see PostgreSQL
- CREATE USER: see PostgreSQL

- **Docker image (latest):**

- pull command: `docker pull bitnine/agensgraph:v2.1.3`
- [DockerHub](#)

- **encoding:** see PostgreSQL

- **issue tracking:** [GitHub](#)

- **JDBC driver (latest):**

- version 1.4.2-c1
- [Maven repository](#)

- **source code:** [GitHub](#)

5.2 Apache Derby

- **data types:**


DBSeeder Type	Apache Derby Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**


- CREATE DATABASE - n/a
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- CREATE USER - n/a

- **Docker image (latest - only client version`):**
 - pull command: `docker pull konnexionsgmbh/apache_derby:10.15.2.0`
 - [DockerHub](#)
- **encoding:** by using the following JVM parameter: `-Dderby.ui.codeset=UTF8`
- **issue tracking:** [Jira](#)
- **JDBC driver (latest):**
 - version 10.15.2.0
 - client version: [Maven repository](#)
 - embedded version: [Maven repository](#)
- **source code:** [Apache Derby](#)
- **DBeaver database connection settings:**

-- client version:



-- embedded version:



5.3 CockroachDB

- **data types:**

DBSeeder Type	CockroachDB Type
BIGINT	INT
BLOB	BYTES
CLOB	STRING
TIMESTAMP	TIMESTAMP
VARCHAR	STRING

- **DDL syntax:**

- [CREATE DATABASE](#)
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull cockroachdb/cockroach:v21.1.2`
- [DockerHub](#)

- **encoding:** by default `utf8` encoding

- **issue tracking:** [GitHub](#)

- **JDBC driver (latest):**

- same as PostgreSQL

- **privileged database access:** user `root`

- **source code:** [GitHub](#)

- **DBeaver database connection settings:**

Connection "CockroachDB [kxn_user - kxn_db]" configuration

Connection settings
CockroachDB connection settings

Connection settings

- Initialization
- Shell Commands
- Client identification
- Transactions
- General
- Metadata
- Errors and timeouts
- > Data editor
- > SQL Editor

Main CockroachDB Driver properties SSH Proxy SSL

Server

Host: localhost Port: 26257

Database: kxn_db

Authentication

Authentication: Database Native

Username: kxn_user

Password: ☒ Save password locally

Advanced

User role: Local Client:

Information icon You can use variables in connection parameters.

Driver name: CockroachDB [Edit Driver Settings](#)

[Test Connection ...](#) [OK](#) [Cancel](#)

5.3 CrateDB

- **data types:**

DBSeeder Type	CrateDB Type
BIGINT	BIGINT
BLOB	OBJECT
CLOB	TEXT
TIMESTAMP	TIMESTAMP
VARCHAR	TEXT

- **DDL syntax:**

- CREATE DATABASE - n/a
- CREATE SCHEMA - n/a
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull crate:4.5.1`
- [DockerHub](#)


- **encoding:** by default `utf8` encoding

- **issue tracking:** [GitHub](#)

- **JDBC driver (latest):**

- version 2.6.0
- [JFrog Bintray repository](#)

- **privileged database access:** user `crate`
- **restrictions:**
 - no constraints (e.g. foreign keys or unique keys)
 - no transaction concept
 - no triggers
 - only a very proprietary BLOB implementation
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**




5.4 CUBRID

- **data types:**

DBSeeder Type	CUBRID Type
BIGINT	INT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - CREATE DATABASE - n/a
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull cubrid/cubrid:11.0`
 - [DockerHub](#)

- **encoding:** by specifying after the database name when database is created: `kxn_db de_DE.utf8`
- **issue tracking:**
 - [Jira](#)
- **JDBC driver (latest):**
 - version 11.0.1.0286
 - [Maven repository](#)
- **privileged database access:** users `DBA` and `PUBLIC`
- **restrictions:** no full UTF-8 support
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**



5.5 Exasol

- **data types:**

DBSeeder Type	Exasol Type
BIGINT	BIGINT
BLOB	VARCHAR(2000000)
CLOB	VARCHAR(2000000)
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - CREATE DATABASE - n/a
 - [CREATE SCHEMA](#)
 - [CREATE TABLE](#)

- [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull exasol/docker-db:7.0.10`
 - [DockerHub](#)
- **JDBC driver (latest):**
 - version 7.0.7
 - [Maven repository](#)
- **privileged database access:** user `sys` password `exasol`
- **DBeaver database connection settings:**

Connection "Exasol [kxn_user]" configuration

Connection settings
Exasol connection settings

General
Metadata
Errors and timeouts
Data viewer
SQL Editor

Main Driver properties SSH Proxy

Database
Host List: 127.0.0.1
Backup Host List: ☐ Use Backup Host List
Port: 8899
☐ Encrypt Communication

Authentication (Database Native)
Username: kxn_user
Password: ☒ Save password locally

You can use variables in connection parameters.

Driver name: Exasol [Edit Driver Settings](#)

Test Connection ... OK Cancel


5.6 Firebird

- **data types:**

DBSeeder Type	Firebird Type
BIGINT	INTEGER
BLOB	BLOB
CLOB	BLOB SUB_TYPE 1
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - [CREATE DATABASE](#)
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - [CREATE USER](#)

- **Docker image (latest):**
 - pull command: `docker pull jacobalberty/firebird:v4.0.0rc1`
 - [DockerHub](#)
- **encoding:** by using the following JDBC URL parameter: `encoding=UTF8`
- **issue tracking:** [GitHub](#)
- **JDBC driver (latest):**
 - version 4.0.3.java11
 - [Maven repository](#)
- **privileged database access:** user `SYSDBA`
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**




5.7 H2 Database Engine

- **data types:**


DBSeeder Type	H2 Database Engine Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - CREATE DATABASE - n/a
 - [CREATE SCHEMA](#)

- [CREATE TABLE](#)
- [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull konnexionsgmbh/h2_database_engine:1.4.200`
 - [DockerHub](#)
- **encoding:** H2 internally uses Unicode, and supports all character encoding systems and character sets supported by the virtual machine you use.
- **issue tracking:** [GitHub](#)
- **JDBC driver (latest):**
 - version 1.4.200
 - [Maven repository](#)
- **privileged database access:** user `sa`
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**
 - client version:



-- embedded version:



5.8 HSQLDB

- **data types:**

DBSeeder Type	HSQLDB Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**

- CREATE DATABASE - n/a
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull konnexionsgmbh/hypersql_database:2.6.0`
- [DockerHub](#)

- **encoding:** by using the following system property `sqlfile.charset=UTF-8`.

- **issue tracking:** [SourceForge](#)

- **JDBC driver (latest):**


- version 2.6.0
- [Maven repository](#)

- **privileged database access:** user `SA`


- **source code:** [SourceForge](#)

- **DBeaver database connection settings:**

-- client version:



-- embedded version:



5.9 IBM Db2 Database

- **data types:**

DBSeeder Type	IBM Db2 Database Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**

- [CREATE DATABASE](#)
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull ibmcom/db2:11.5.5.1`
- [DockerHub](#)

- **encoding:**

- by using the CCSID clause in the CREATE statements for any of the following objects:
 - Database
 - Table space
 - Table
 - procedure or function


- **JDBC driver (latest):**

- version 11.5.54.0
- [Maven repository](#)

- **privileged database access:** user `db2inst1`

- **restrictions:** the IBM Db2 DBMS only accepts operating system accounts as database users

- **DBeaver database connection settings:**



5.10 IBM Informix

- **data types:**

DBSeeder Type	IBM Informix Database Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	DATETIME YEAR TO FRACTION
VARCHAR	VARCHAR (1-254) / LVARCHAR

- **DDL syntax:**

- [CREATE DATABASE](#)
- CREATE SCHEMA - n/a
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull ibmcom/informix-developer-database:14.10.FC5DE`
- [DockerHub](#)

- **encoding:**

- code-set conversion value is extracted from the DB_LOCALE value specified at the time the connection is made


- **JDBC driver (latest):**

- version 4.50.4.1
- [Maven repository](#)

- **privileged database access:**

- user `informix`

- password `in4mix`
- database / schema `sysmaster`
- INFORMIXSERVER `informix`
- **restrictions:** the IBM Informix DBMS only accepts operating system accounts or users mapped to operating system accounts as database users
- **DBeaver database connection settings:**




5.11 MariaDB Server

- **data types:**

DBSeeder Type	MariaDB Type
BIGINT	BIGINT
BLOB	LONGBLOB
CLOB	LONGTEXT
TIMESTAMP	DATETIME
VARCHAR	VARCHAR

- **DDL syntax:**
 - [CREATE DATABASE](#)
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull mariadb:10.6.1`
 - [DockerHub](#)
- **encoding:**
 - server level: `SET character_set_server = 'latin2';`

- database level: `CHARACTER SET = 'keybcs2'`
- table level: `CHARACTER SET 'utf8'`
- column level: `CHARACTER SET 'greek'`
- **issue tracking:** [Jira](#)
- **JDBC driver (latest):**
 - version 2.7.2
 - [Maven repository](#)
- **privileged database access:**
 - user: `mysql`
 - password: `root`
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**




5.12 Mimer SQL

- **data types:**

DBSeeder Type	MimerSQL Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	NVARCHAR

- **DDL syntax:**
 - [CREATE DATABASE](#)
 - CREATE SCHEMA - n/a

- [CREATE TABLE](#)
- [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull mimersql/mimersql_v11.0.5a`
 - [DockerHub](#)
- **encoding:** NCHAR, NVARCHAR
- **JDBC driver (latest):**
 - version 3.41a
 - [Mimer Website](#)
- **privileged database access:**
 - database: `mimerdb`
 - user: `SYSADM`
- **DBeaver database connection settings:**




5.13 MonetDB

- **data types:**

DBSeeder Type	MonetDB Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - CREATE DATABASE - n/a

- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull monetdb/monetdb:Oct2020-SP5`
 - [DockerHub](#)
- **encoding:** no special configuration should be needed
- **issue tracking:** [GitHub](#)
- **JDBC driver (latest):**
 - version 3.0.jre8
 - [MonetDB Java Download Area](#)
- **privileged database access:**
 - database: `demo`
 - user: `monetdb`
 - password: `monetdb`
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**



5.14 MySQL Database

- **data types:**

DBSeeder Type	MySQL Database Type
BIGINT	BIGINT
BLOB	LONGBLOB
CLOB	LONGTEXT

DBSeeder Type	MySQL Database Type
TIMESTAMP	DATETIME
VARCHAR	VARCHAR

- **DDL syntax:**

- [CREATE DATABASE](#)
- CREATE SCHEMA - n/a
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull mysql:8.0.25`
- [DockerHub](#)

- **encoding:** for applications that store data using the default MySQL character set and collation (utf8mb4, utf8mb4_0900_ai_ci), no special configuration should be needed

- **JDBC driver (latest):**


- version 8.0.25
- [Maven repository](#)

- **privileged database access:**

- database: `sys`
- user: `root`

- **source code:** [GitHub](#)

- **DBeaver database connection settings:**




5.15 OmniSciDB

- **data types:**

DBSeeder Type	OmniSciDB Type
BIGINT	BIGINT
BLOB	TEXT ENCODING NONE
CLOB	TEXT ENCODING NONE
TIMESTAMP	TIMESTAMP(0)
VARCHAR	TEXT ENCODING NONE

- **DDL syntax:**
 - [CREATE DATABASE](#)
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull omnisci/core-os-cpu`
 - [DockerHub](#)
- **encoding:** no special configuration should be needed
- **issue tracking:** [GitHub](#)
- **JDBC driver (latest):**
 - version 5.6.0
 - [Maven repository](#)
- **privileged database access:**
 - database: `omnisci`
 - user: `admin`
- **restrictions:**
 - column and table names case sensitive
 - max. column length 32767 bytes
 - no binary columns
 - no constraints, e.g. unique keys
 - no foreign / referential keys
 - no primary key
 - no triggers
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**



5.16 Oracle Database

- **data types:**

DBSeeder Type	Oracle Database Type
BIGINT	NUMBER
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR2

- **DDL syntax:**

- CREATE DATABASE - n/a
- CREATE SCHEMA - n/a
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image:** [DockerHub](#)

- **encoding:** since Oracle Database 12c Release 2 the default database character set used is the Unicode character set AL32UTF8


- **JDBC driver (latest):**

- version 21.1.0.0
- [Maven repository](#)

- **privileged database access:**

- database: `orclpdb1`
- user: `SYS AS SYSDBA`

- **DBeaver database connection settings:**



5.17 Percona Server for MySQL

- **data types:**

DBSeeder Type	Percona Sercver Type
BIGINT	BIGINT
BLOB	LOB
CLOB	LONGTEXT
TIMESTAMP	DATETIME
VARCHAR	VARCHAR

- **DDL syntax:**

- CREATE DATABASE: see MySQL Database
- CREATE SCHEMA - n/a
- CREATE TABLE: see MySQL Database
- CREATE USER: see MySQL Database

- **Docker image (latest):**

- pull command: `docker pull percona/percona-server:8.0.23-14`
- [DockerHub](#)

- **encoding:** for applications that store data using the default MySQL character set and collation (utf8mb4, utf8mb4_0900_ai_ci), no special configuration should be needed

- **issue tracking:** [Jira](#)

- **JDBC driver (latest):**

- version 8.0.23
- [Maven repository](#)

- **privileged database access:**

- database: `sys`
- user: `root`

- **source code:** [GitHub](#)

5.18 PostgreSQL

- **data types:**

DBSeeder Type	PostgreSQL Type
BIGINT	BIGINT
BLOB	BYTEA
CLOB	TEXT
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**

- [CREATE DATABASE](#)
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull postgres:13.3-alpine`
- [DockerHub](#)

- **encoding:** when creating the database: `CREATE DATABASE testdb WITH ENCODING 'EUC_KR' ...`


- **issue tracking:** [PostgreSQL](#)

- **JDBC driver (latest):**

- version 42.2.19
- [Maven repository](#)

- **source code:** [GitHub](#)

- **DBeaver database connection settings:**



5.19 SQL Server

- **data types:**

DBSeeder Type	SQL Server Type
BIGINT	BIGINT
BLOB	VARBINARY (MAX)
CLOB	VARCHAR (MAX)
TIMESTAMP	DATETIME2
VARCHAR	VARCHAR

- **DDL syntax:**

- [CREATE DATABASE](#)
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- [CREATE USER](#)

- **Docker image (latest):**

- pull command: `docker pull mcr.microsoft.com/mssql/server:2019-latest`
- [DockerHub](#)

- **encoding:** to use the UTF-8 collations that are available in SQL Server 2019 (15.x), you must select UTF-8 encoding-enabled collations (`_UTF8`)


- **JDBC driver (latest):**

- version 9.2.1.jre15
- [Maven repository](#)

- **privileged database access:**

- database: `master`
- user: `sa`

- **restrictions:** no full UTF-8 support in the given Docker images
- **DBeaver database connection settings:**



5.20 SQLite

- **data types:**


DBSeeder Type	SQLite Type
BIGINT	INTEGER
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	DATETIME
VARCHAR	VARCHAR2

- **DDL syntax:**
 - CREATE DATABASE - n/a
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - CREATE USER - n/a
- **encoding:** by using the following parameter: `PRAGMA encoding='UTF-8';`
- **issue tracking:** [SQLite](#)
- **JDBC driver (latest):**
 - version 3.34.0
 - [Maven repository](#)
 - determines also the DBMS version
- **restrictions:**
 - no Docker image necessary, hence not available

- no user management

- **source code:** [SQLite](#)

- **DBeaver database connection settings:**



5.21 trino

- **data types:**

DBSeeder Type	trino Type
BIGINT	BIGINT
BLOB	BLOB
CLOB	CLOB
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**

- CREATE DATABASE - n/a
- [CREATE SCHEMA](#)
- [CREATE TABLE](#)
- CREATE USER - n/a

- **Docker image (latest):**

- pull command: `docker pull trinodb/trino:358`
- [DockerHub](#)

- **encoding:** full support of UTF-8 (see [here](#))

- **issue tracking:** [GitHub](#)

- **JDBC driver (latest):**

- version 358
- [Maven repository](#)

- **source code:** [GitHub](#)

5.22 VoltDB

- **data types:**

DBSeeder Type	VoltDB Type
BIGINT	BIGINT
BLOB	VARBINARY(1048576)
CLOB	VARCHAR(1048576)
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - CREATE DATABASE - n/a
 - CREATE SCHEMA - n/a
 - [CREATE TABLE](#)
 - CREATE USER - n/a
- **Docker image (latest):**
 - pull command: `docker pull voltdb/voltdb-community:9.2.1`
 - [DockerHub](#)
- **issue tracking:** [Jira](#)
- **JDBC driver (latest):**
 - version 10.1.1
 - [Maven repository](#)
- **source code:** [GitHub](#)

5.23 YugabyteDB

- **data types:**

DBSeeder Type	YugabyteDB Database Type
BIGINT	BIGINT
BLOB	BYTEA
CLOB	TEXT
TIMESTAMP	TIMESTAMP
VARCHAR	VARCHAR

- **DDL syntax:**
 - [CREATE DATABASE](#)
 - [CREATE SCHEMA](#)
 - [CREATE TABLE](#)
 - [CREATE USER](#)
- **Docker image (latest):**
 - pull command: `docker pull yugabytedb/yugabyte:2.7.1.1-b1`
 - [DockerHub](#)
- **encoding:** see PostgreSQL
- **issue tracking:** [GitHub](#)

- **JDBC driver (latest):**
 - version 42.2.7-yb-3
 - [Maven repository](#)
- **source code:** [GitHub](#)
- **DBeaver database connection settings:**

Connection "yugabyte [kxn_db - kxn_user]" configuration

Connection settings
YugabyteDB connection settings

YugabyteDB

Main | **YugabyteDB** | Driver properties | SSH | Proxy | SSL

Server

Host: localhost Port: 5433

Database: kxn_db

Authentication

Authentication: Database Native Database native authentication

Username: kxn_user

Password: •••••••• ☒ Save password locally

Advanced

Local Client: PostgreSQL 10

i You can use variables in connection parameters.

Driver name: YugabyteDB [Edit Driver Settings](#)

[Test Connection ...](#) [OK](#) [Cancel](#)

6. trino

[trino](#) can integrate the following DBMS, among others:

- MySQL via the [MySQL Connector](#),
- Oracle via the [Oracle Connector](#), and
- PostgreSQL via the [PostgreSQL Connector](#).
- SQL Server via the [SQL Server Connector](#),

DBSeeder makes it possible to use trino's JDBC driver and the corresponding connectors as an alternative to the JDBC drivers of the DBMS suppliers. To use the trino JDBC driver, a trino server is required. With the script `db_seeder_trino_environment` a trino server can be set up. Since trino does not support the Windows operating system, a suitable Docker image is created for Windows. For Linux, e.g. Ubuntu, the script can alternatively be used to perform a local installation of the trino server.